

# PlotInteraction

March 13, 2017

```
In [ ]: from silx.gui import qt
        %gui qt
```

## 1 simple plot of a 2D image

- using Plot2D

### 1.1 load data from data/lena.hdf5

```
In [1]: # input using .hdf5
import h5py
import numpy
dataPath='data/ascent.h5'
f=h5py.File(dataPath)
from silx.io.utils import h5ls
h5ls(dataPath)
```

```
Out[1]: '<HDF5 dataset "data": shape (512, 512), type "<i8">\n'
```

```
In [2]: image=numpy.array(f['data'], dtype='float32')
```

### 1.2 plot the image


```
In [ ]: from silx.gui.plot import Plot2D
plotImage=Plot2D()
plotImage.addImage(image, origin=(0, 0), legend='sino')
plotImage.show()
```

## 2 display the pixel intensity distribution

### 2.1 create the histogramnd

- using silx.math.histogram.Histogramnd
- <http://www.silx.org/doc/silx/dev/modules/math/histogram.html>

```
In [ ]: from silx.math.histogram import Histogramnd
        histo, w_histo, edges = Histogramnd(image.flatten(),
                                              n_bins=256,
                                              histo_range=[0,256])
```



ascent image


## 2.2 plot the histogram

- using `silx.gui.plot.Plot1d`

```
In [ ]: from silx.gui.plot import Plot1D
        plotHisto = Plot1D()
        plotHisto.addCurve(range(256), histo, legend='intensity')
        plotHisto.show()
```

## 3 create a PlotAction which plot the histogram for the current image

- using `silx.gui.plot.PlotActions.PlotAction`
- doc@ [http://www.silx.org/doc/silx/dev/modules/gui/plot/plotactions\\_examples.html](http://www.silx.org/doc/silx/dev/modules/gui/plot/plotactions_examples.html)



simple-image

```
In [ ]: from silx.gui.plot.PlotActions import PlotAction
        from silx.math.histogram import Histogramnd
        from silx.gui.plot import Plot1D

        class ComputeHistogramAction(PlotAction):
            """Computes the intensity distribution on the current image

            :param plot: :class:`.PlotWidget` instance on which to operate
            :param parent: See :class:`QAction`
            """
```

```

def __init__(self, plot, parent=None):
    PlotAction.__init__(self,
                        plot,
                        icon='shape-circle',
                        text='pixels intensity',
                        tooltip='Compute image intensity distribution',
                        triggered=self.computeIntensityDistribution,
                        parent=parent)
    self.plotHistogram=Plot1D()

def computeIntensityDistribution(self):
    """Get the active image and compute the image
    intensity distribution"""
    # By inheriting from PlotAction, we get access to attribute
    # self.plot
    # which is a reference to the PlotWindow
    activeImage = self.plot.getActiveImage()

    if activeImage is not None:

        histo, w_histo, edges = Histogramnd(activeImage[0].flatten(),
                                             n_bins=256,
                                             histo_range=[0,256])

        self.plotHistogram.addCurve(range(256),
                                     histo,
                                     legend='pixel intensity')

        self.plotHistogram.show()

```

### 3.1 Add this action into the toolBar of the window

```

In [ ]: plotHisto.clear()
        myaction=ComputeHistogramAction(plotImage)
        toolBar=plotImage.toolBar()
        toolBar.addAction(myaction)
        plotImage.show()

```

## 4 show automatically the histogram when the image change

- using `plotImage.sigActiveImageChanged.connect(plotHisto)`

```

In [ ]: from silx.math.histogram import Histogramnd

def computeIntensityDistribution():
    """Get the active image and compute the image
    intensity distribution"""
    # By inheriting from PlotAction, we get access to attribute
    # self.plot

```

```

        # which is a reference to the PlotWindow
        activeImage = plotImage.getActiveImage()

        if activeImage is not None:
            histo, w_histo, edges = Histogramnd(activeImage[0].flatten(),
                                                n_bins=256,
                                                histo_range=[0,256])

            from silx.gui.plot import Plot1D
            plotHistogram = Plot1D()
            plotHistogram.addCurve(range(256),
                                  histo,
                                  legend='pixel intensity')
            plotHistogram.show()

In [ ]: plotImage=Plot2D()
        plotImage.sigActiveImageChanged.connect(computeIntensityDistribution)
        plotImage.addImage(image, origin=(0, 0), legend='lena')

In [ ]: from silx.gui.plot.PlotActions import PlotAction
        from silx.math.histogram import Histogramnd
        from silx.gui.plot import Plot1D

        class ComputeHistogramAction(PlotAction):
            """Computes the intensity distribution on the current image

            :param plot: :class:`.PlotWidget` instance on which to operate
            :param parent: See :class:`QAction`
            """

            def __init__(self, plot, parent=None):
                PlotAction.__init__(self,
                                    plot,
                                    icon='shape-circle',
                                    text='pixels intensity',
                                    tooltip='Compute image intensity distribution',
                                    triggered=self.computeIntensityDistribution,
                                    checkable=True,
                                    parent=parent)
                self.plotHistogram=Plot1D()
                self.plot.sigActiveImageChanged.connect(self.update)

            def update(self):
                # By inheriting from PlotAction, we get access to attribute
                # self.plot
                # which is a reference to the PlotWindow
                activeImage = self.plot.getActiveImage()

                if activeImage is not None:

```

```

        histo, w_histo, edges = Histogramnd(activeImage[0].flatten(),
                                             n_bins=256,
                                             histo_range=[0, 255])

        self.plotHistogram.addCurve(range(256),
                                     histo,
                                     legend='pixel intensity')


    def computeIntensityDistribution(self):
        """Get the active image and compute the image intensity distribution"""
        if self.isChecked():
            self.update()
            self.plotHistogram.show()
        else:
            self.plotHistogram.hide()

In [ ]: plotImage=Plot2D()
        myaction=ComputeHistogramAction(plotImage)
        toolBar=plotImage.toolBar()
        toolBar.addAction(myaction)
        plotImage.addImage(image, origin=(0, 0), legend='ascent')
        plotImage.show()

In [ ]: plotImage.addImage(image/2.0, origin=(0, 0), legend='acent')

```

## 5 For information : the class diagram of the Plot module



plot class diagram