

Data_fitting

March 9, 2017

1 Data fitting

Curve fitting is the process of constructing a curve, or mathematical function, that has the best fit to a series of experimental data points.


1.1 Loading data

```
In [1]: %pylab inline
```

Populating the interactive namespace from numpy and matplotlib

```
In [2]: import silx.io
specfile = silx.io.open("data/31oct98.dat")
xdata = specfile["/22.1/measurement/TZ3"]
ydata = specfile["/22.1/measurement/If4"]
plot(xdata, ydata)
```

```
Out[2]: [<matplotlib.lines.Line2D at 0x7f4e53a948d0>]
```



1.2 Use of a builtin fitting function

The fitting function is a function of the data-point (xdata) and of a set of parameters. Silx offers a set of usual fitting functions in module `silx.math.fit.functions`.


In this example, we will use a gaussian function, `sum_gauss`, whose parameters are *height*, *center* and *fwfm* (full-width at half maximum). The function accepts a multiple number of these 3 base parameters, to fit a sum of multiple gaussian peaks.

```
In [3]: from silx.math.fit.functions import sum_gauss
```

An essential part of the iterative fitting process is the choice of the initial set of parameters `p0`. Our initial estimate is that we have 2 peaks, centered at $x = 29.45$ and at $x = 29.55$, with amplitude 55000 and 60000 and with a full-width at half maximum of 0.03.

```
In [4]: p0 = [55000., 29.45, 0.03,
             60000., 29.55, 0.03]
         plot(xdata, ydata, label="Actual data")
         plot(xdata, sum_gauss(xdata, *p0), label="Initial guess")
         legend()
         title("Before fitting")
```

```
Out[4]: <matplotlib.text.Text at 0x7f4e52e23898>
```



1.3 Fitting using silx

```
In [5]: from silx.math.fit import leastsq
```


```
In [6]: p, cov_matrix = leastsq(model=sum_gauss, xdata=xdata, ydata=ydata, p0=p0)
        print(p)
```

```
[ 5.65660023e+04  2.94595631e+01  3.19836859e-02  5.92015970e+04
 2.95275309e+01  3.54588691e-02]
```

```
In [7]: %timeit p, cov_matrix = leastsq(model=sum_gauss, xdata=xdata, ydata=ydata,
100 loops, best of 3: 6.24 ms per loop
```

```
In [8]: #Display the result of the fit
        #plot(xdata, sum_gauss(xdata, *p0), label="Initial guess")
        plot(xdata, sum_gauss(xdata, *p), label="Fitted curve")
        plot(xdata, ydata, label="Experimental data")
        legend()
        title("Result of the fit")
```

```
Out[8]: <matplotlib.text.Text at 0x7f4e52da97f0>
```



Can we improve this by adding a small third peak at $x = 29.61$ in our estimation?

```


In [9]: # estimate
p0 = [55000., 29.45, 0.03,
      60000., 29.55, 0.03,
      5000., 29.61, 0.05]

# fit
p, cov_matrix = leastsq(model=sum_gauss, xdata=xdata, ydata=ydata, p0=p0)

# plot
plot(xdata, sum_gauss(xdata, *p0), label="Initial guess")
plot(xdata, sum_gauss(xdata, *p), label="Fitted curve")
plot(xdata, ydata, label="Experimental data")
legend()
title("Result of the fit (3 peaks)")

```

Out[9]: <matplotlib.text.Text at 0x7f4e52d930f0>



It turns out that we were wrong regarding the position of our third peak, and about the amplitudes of all 3 peaks. The fit converged towards a much better 3-peak solution:

```


In [10]: print(p)
          plot(xdata, sum_gauss(xdata, *p), label="Fitted curve")
          for i in range(3):
              plot(xdata, sum_gauss(xdata, *p[3*i:3*i+3]), label="Peak %d" % (i+1))
          legend()

```

5.05170978e+04	2.94588874e+01	2.62330656e-02	5.27459196e+04
2.95283488e+01	2.84759182e-02	1.03471962e+04	2.94988854e+01

-1.37750880e-01]

Out[10]: <matplotlib.legend.Legend at 0x7f4e52ca3c18>



2 Conclusion

Fitting curves requires the following steps:

- get the data points `x_data` and `y_data`
- define the fitting function as `y_data = function(x_data, param)`
- choose an initial guess for the set of parameters `p0`
- run the optimizer
- check the result.

3 Fitting data with a background

Beyond simple curve fitting, *silx* offers more builtin fitting tools, to handle initial parameter estimation (including peak detection) and background estimation.

We need to import the `FitManager` class and the module defining builtin fit theories (`silx.math.fit.fittheories`).

3.1 Loading data

Lets load an image, and sum all samples along the horizontal dimension to get a 1D curve.


```
In [11]: # import fabio
         # img = fabio.open("data/medipix.edf").data

         with silx.io.open("data/medipix.edf") as my_file:
             img = my_file["scan_0/instrument/detector_0/data"][0]

         imshow(np.log(img))
```

/users/knobel/.local/lib/python3.4/site-packages/ipykernel/__main__.py:7: RuntimeWarning


Out[11]: <matplotlib.image.AxesImage at 0x7f4e52c27320>



Sum all samples for each row of the image, to get a curve.

```
In [12]: ydata = img.sum(axis=1)
         xdata = numpy.arange(len(img), dtype="float")
         plot(xdata, ydata)
         axis([0, xdata.max(), 0, ydata.max()])
         title("Sum along the horizontal direction")
```

Out[12]: <matplotlib.text.Text at 0x7f4e52be17f0>



3.2 Setting up a FitManager

If we want to fit a single gaussian to this data, we clearly need to remove the constant background signal, at about $y = 12000$.

```
In [13]: from silx.math.fit import FitManager, fittheories, bgtheories
         fitman = FitManager()
         fitman.setdata(x=xdata, y=ydata)
         fitman.loadtheories(fittheories)
         fitman.loadbgtheories(bgtheories)
         fitman.settheory('Gaussians')
         fitman.setbackground("Constant")
```

3.3 Estimating initial parameters

Now that the FitManager is set-up, we need to estimate the initial parameters before running the fit. This is done by simply running the `estimate` method of `fitmanager`. This method uses the estimation function defined in fit theories.

An automatic peak detection algorithm is used for gaussian-like fit theories. We do not need to specify the number of peaks or their position. The fwhm is estimated based on the highest peak (maximum value) in the data.

The results are stored internally in the FitManager instance as attribute `fit_results`. This attribute stores a list of dictionaries, one per parameter to be fitted.

```
In [14]: fitman.estimate()

for param in fitman.fit_results:
    print("Estimated value for param %s: %f" % (param["name"], param["estimated_value"]))

Estimated value for param Constant: 11810.000000
Estimated value for param Height1: 63176.944734
Estimated value for param Position1: 135.955454
Estimated value for param FWHM1: 7.078567
```

The estimation function managed to find 1 peak and correctly estimated its gaussian parameters and the background level.

3.4 Final fit

Running the fit is as simple as running the estimation.


```
In [15]: params, uncertainties, infodict = fitman.runfit()

for param in fitman.fit_results:
    print("Fitted value for param %s: %f" %
          (param["name"], param["fitresult"]))

plot(xdata, ydata, label="Original data")
plot(xdata, params[0] + sum_gauss(xdata, *params[1:]),
      label="Fitted data")

Fitted value for param Constant: 11918.694707
Fitted value for param Height1: 63103.126632
Fitted value for param Position1: 135.955545
Fitted value for param FWHM1: 7.061779
```

```
Out[15]: [<matplotlib.lines.Line2D at 0x7f4e52c6f898>]
```

As you can see, parameters can be accessed as the first value returned by the `runfit` method, a simple list of raw values, or again as attribute `fitman.fit_results`.

3.5 More FitManager features

FitManager offers more features, such as: - setting constraints for parameters - advanced background models, beyond simple constant or linear: strip or snip backgrounds - adding custom fit and background theories, with customised estimation function, customized derivatives...

4 Exercise

```
x = numpy.arange(10).astype(numpy.float64)
y = 0.001 * x**3 + 25.1 * x**2 + 1.2 * x - 25
```

1. Fit degree-2 polynomial to this data
2. Fit a degree-3 polynomial to this data
3. Fit a degree-3 polynomial to this data using FitManager.
4. Print the chi-square value and number of iterations for all previous tasks.

- Tip: For the 3-rd task, to add a model function to FitManager:

```
from silx.math.fit import FitTheory
from silx.math.fit import FitManager

def poly3(x, a, b, c, d):
    return a * x**3 + b * x**2 + c*x + d
```

```

my_poly3_theory = FitTheory(function=poly3, parameters=["a", "b", "c", "d"])

fitman = FitManager()
fitman.addtheory(name="my poly", theory=my_poly3_theory)
...

```

```

In [ ]: # 1. Fill-in the blanks (...)
import numpy
from silx.math.fit import leastsq

# generate synthetic data
x = numpy.arange(10).astype(numpy.float64)
y = 0.001 * x**3 + 25.1 * x**2 + 1.2 * x - 25

# define the model function
def poly2(x,...):
    return ...

# define initial estimated parameters
p0 = ...

# Run the fit
...

# print the results (optimized parameters)
...

```

```

In [ ]: # 2.
import numpy
from silx.math.fit import leastsq

x = numpy.arange(10).astype(numpy.float64)
y = 0.001 * x**3 + 25.1 * x**2 + 1.2 * x - 25

# define the model function
def poly3(...):
    return ...

# define initial estimated parameters
p0 = ...

# Run the fit
...

# print the results (optimized parameters)
...

```

```

In [ ]: # 3.
import numpy

x = numpy.arange(10).astype(numpy.float64)
y = 0.001 * x**3 + 25.1 * x**2 + 1.2 * x - 25

from silx.math.fit import FitTheory
from silx.math.fit import FitManager

def poly3(x, a, b, c, d):
    return a * x**3 + b * x**2 + c*x + d

# define a fit theory for this function and these 4 parameters
my_poly3_theory = FitTheory(...)

fitman = FitManager()
# add the theory to fitma
fitman....
# select the theory
fitman....
# set the data (x, y)
fitman....

# FitManager.estimate() returns an array of initial parameters
p0 = fitman.estimate()
# ... and as we didn't define an estimation function, it will be an array of
print("Estimated parameters: ", p0)

# FitManager.runfit() returns the same data as leastsq(..., full_output=True)
p, cov, info = fitman.runfit()

print("Parameters [a, b, c, d]: " + str(p))

for param in fitman.fit_results:
    print("parameter %s: %f" % (param["name"], param["fitresult"]))

In [ ]: # 4.

p, cov_matrix, info = leastsq(poly2, x, y, p0, ...)

# print the number of iterations and the chisq
print(...)
print(...)

```