



MONASH
University

Are current sortition methods creating representative panels? A framework analysis

Daniel Leo Loza

B.Bus, AMusA

MONASH
BUSINESS
SCHOOL

**Department of
Econometrics &
Business Statistics**

☎ (03) 9905 2478
✉ BusEco-Econometrics@monash.edu

ABN: 12 377 614 012

Report for
Honours Research Proposal, Monash University

8 May 2026



Are current sortition methods creating representative panels? A framework analysis.

Author: Daniel Leo Loza (B.Bus, AMusA)

SID: 33842388

Supervisors: Dr. Jessica Leung, Prof. Dianne Cook

1 Introduction

1.1 Topic

This thesis aims to evaluate whether current sortition methods lead to representative panels in practice. Through simulation and visualisation of algorithm performance, we will examine whether current tools are producing panels that are representative, and offer a way to assess representativeness in practice before deliberation.

1.2 Background and Motivation

In a social landscape where the public is growing progressively disillusioned with its representation in politics (Landemore [2026](#)), it is important to consider ways in which we can foster more inclusive decision-making practices. One way of achieving this, adopted recently by an increasing number of institutions, including the Parisian ("[Paris Creates a Permanent Citizens' Council](#)" [2021](#)), Irish (Walsh & Elkind [2021](#)), and British Columbian (Ward [2008](#)) governments, is using sortition to create panels that are more representative of the population for political discussions and deliberations. As a result, the need for fair and representative methods of building panels is only growing, and progress is being made in improving the structure of selective algorithms. However, there are still many challenges to overcome in order to ensure that these panels consistently achieve the level of representation that they set out to.

Sortition is a method of selection that uses random sampling to create panels that should be descriptively representative of a population. It has been used in various contexts, reaching as far back as ancient Athens (where it was how jurors were selected), and now into modern times for citizens' assemblies, as mentioned prior. The idea is that by randomly selecting individuals from the population, we can create panels that are more representative and inclusive than those selected through traditional methods, like elections or open-ended surveys. Sortition also reduces dominance by elites or highly engaged groups, enabling broader participation across social classes (Giuliani [2025](#)), making it more likely that decisions are in the relevant population's best interest.

One of the main roadblocks in sortition is ensuring that the selection process is transparent and fair, and that the panels are truly representative of the population in terms of demographics and perspectives. But this raises the questions of what it means to be fair, what it means to be representative, and how these look from a systematic perspective.

As a process, sortition can be broken down into four stages: 1) defining the population and traits of interest, 2) requesting expressions of interest from a random subset of the population, 3) feeding respondents into a sortition algorithm, and 4) panel is selected and engaged for deliberation. Notably, there is currently no rigorous evaluation of representation achieved before a process is run. Additionally, each of these steps potentially introduces bias, impacting the representativeness of the panel. As such, it is crucial to measure how the level of representativeness (or *potential* representativeness) flows through each stage, and to understand how different factors may affect it.

Sortition methods have been evolving over time. Prior to algorithmic means, panel selection was carried out through simple self-selection (response to survey/advertising) and proportional sampling to meet panel size requirements. As sortition began to grow more robust, the Legacy (Flanigan et al. 2021) techniques started surfacing—these saw panels put together through simple choosing of respondents who met the most required “category” condition at any given moment, and would continue iterating until the required marginal counts were present in the selected panel. This led to situations of extreme selection likelihoods, if minorities existed—as members were selected indiscriminately of implied likelihood, meaning there were situations where an individual would potentially be selected 0% of the time. To counteract this, the more systematic algorithm “MaxiMin” was implemented (Baharav & Flanigan 2024); seeking not only to meet panel quotas, but to raise the lowest individual’s selection likelihood, to eliminate the 0% selection case, in order to improve representativeness. This, however, now presented the risk of likelihood manipulation, as selection was based more directly on the combination of all category responses given by an individual, rather than pure counts needed for the panel to be filled. As a result, the inverse function “MiniMax” was employed to reduce extreme cases on the other end—eliminating the 100% selection chance case by minimising maximal selection likelihood of any given individual, providing an approach that was more resistant and robust to coercion, but simultaneously reintroducing the potential 0% likelihood problem. Though robustness itself lies beyond the scope of this paper’s aims, it is important to note the existence of MiniMax as an approach to the sortition problem, as it impacted further algorithmic development, and robustness as a goal presents an opportunity for further investigation.

More recently, and of direct relevance to the current study, further iterations of MiniMax and MaxiMin, in the forms of “LexiMin” (Flanigan et al. 2021) and “Goldilocks” (Baharav & Flanigan 2024), were established. These present more generally practical outcomes, with the former being used in industry at

present. LexiMin takes the idea of MaxiMin and repeats it for every individual sequentially, maximising *all* individuals' likelihoods, rather than just those who sit at the absolute bottom. Thus, raising the selection likelihood floor for the participant pool overall. It is, however, like MaxiMin, vulnerable to manipulation (which remains beyond the scope of this paper)—leading into the development of the Goldilocks algorithm solution. Goldilocks aims to simultaneously raise the selection likelihood floor (eliminating the 0% selection chance and improving representativeness), as well as lower the ceiling (eliminating the 100% selection case and making the process more robust against manipulation). A tool for Goldilocks' use is in development at the time of the writing of this paper, and is expected to be made publicly available in the near future. As such, it will not be used for the current study, but may present an opportunity for further research.

However, there is limited literature on the visualisations of the outputs of these algorithms. Additionally, it appears that none of these directly address or validate the presence of any particular intersections within the panels they produce, which presents a risk for insufficient representation.

2 Research Design

This study hopes to develop visual tools to understand the LexiMin algorithm in order to:

1. Demonstrate how it operates
2. Measure the level of representation it achieves
3. Investigate where and how it falls short

There has been limited work done on visualising outputs of the LexiMin algorithm, which limits transparency and interpretability of the process. Additionally, we hope to assess the difference in effectiveness and performance across different sample sizes, population distributions, and extreme cases, as real-world communities can be complex, and optimal sortition should be able to capture this confidently. Within this, we also hope to observe the nature of intersections captured by the algorithm and how these are affected when certain trait groups are particularly small or large, or when response rates differ across groups. With these insights, we will then hope to establish a dashboard that will help guide quota constraint choices and strengthen representativeness.

2.1 Methodology

As the main focus of this paper is visualising algorithmic performance, we will follow a simulation study method to have full control over the data used, following the previously outlined sortition steps used in practice. The study will construct an example “population”, with a set number of traits of interest, for which we will create a set number of observations for each possible response type

(e.g. a number of males, a number of females and a number of non-binary people for the gender trait, and so on for other traits). These will then be shuffled and combined to form the individual observations within the simulated population. From this, a randomly selected subset will be given an opportunity to respond to a survey. This population subset will have response rates (likelihoods) set across their trait variables, which will be run through a random binomial distribution with a set seed, to simulate responses. This respondent “survey sample” will then be fed into the publicly accessible Panelot sortition interface (based on Flanigan et al. (2021) LexiMin) to run selection lottery, where a specific panel will be selected with a set seed for reproducibility, then pulled back for comparison against the distributions at previous steps. The outputs of each step will be visualised with mosaic plots (Jeppson & Hofmann 2023) and UpSet plots (Gehlenborg 2019) to show the distribution of traits and intersections at each stage, as well as pie charts to show the marginal distributions of traits and how these would be superficially compared in practice.

Our specific test cases will be:

- Populations (N) of size 10000, 50000, 100000
- Contact rate (population subset) of 10%, 30% and 50%, to show how the algorithm performs with different levels of data availability, and how this impacts representativeness
- Selected panel sizes (k) of 30 and 50, as these are common in practice
- Traits of interest (m) of 3 and 5, as these are common in practice
- Population distributions of Uniform, Gaussian, and Beta across traits, to show how the algorithm performs with different levels of skew and complexity
- Uniform and variable survey response rates of 1%, 3%, and 5%, to show how the algorithm performs under commonly observed response rates, and when different groups are more or less likely to respond
- Extreme cases where one or more groups are particularly small (e.g. 1% of the population) or large (e.g. 80% of the population), to show how the algorithm performs when certain groups are more or less likely to be represented

After visualising the outputs of the algorithm across these different scenarios, we will then attempt to build a tool designed to allow users to input their population and survey sample data, alongside their Panelot-generated lottery output and a specific seed, then visualise the distribution of traits and intersections in the selected panel against the population, to make it easier to assess representative performance across panel selections.

2.2 Expected Results

As the algorithms are not defined to inspect presence of particular intersections, it is expected that there will be no way to ensure a certain “type” of person (beyond defined marginal categories) will be present within the selected panel. As such, it is expected that there will be some extreme case panel iterations with entirely missing population-observed intersections.

2.3 Small Test Case

To demonstrate the visualisation process and the necessity of this study, we will create a small test case with a population of 1000 individuals, with two traits of interest: age and gender. The age groups will be 18-29, 30-44, 45-64, and 65+, with proportions of 25%, 30%, 25%, and 20% respectively. The gender groups will be 48% male, 48% female, and 4% non-binary. We will follow the methodology outlined above to simulate the population (with an assumed 100% contact rate, to keep the test small), survey sample, and selected panel, with an assumed response rate of 30% across all groups (for simplicity), and a selected panel size of 30. These will then be visualised.

Visualising Population




Figure 1: *Distributions of age groups and genders in the simulated population dataset, shown as pie charts. Colour corresponds to the category, and size of the slice corresponds to the proportion of the population within that category. All marginal groups are represented.*

Demographic Summary (Pie Charts) Industry practitioners often use pie charts and similar graphics to visualise the distribution of traits in the population, as they are simple and easy to understand. However, it is important to note that, by construction, pie charts merely show the margin observations within a dataset. Figure 1 shows the distribution of age groups and genders in the simulated population dataset, respectively, as they would be shown to explain the population to a client or stakeholder.




Figure 2: Relationship between age and gender in the population shown as a mosaic plot. Colour indicates gender. Width of the bars correspond to the count within the category. Every combination contains observations.

Mosaic Plot Figure 2 shows the mosaic plot of the population dataset, which demonstrates the distribution of age groups across gender. The plot shows that the simulated population has more younger men than women, on average. It also shows that 12 intersections exist, connecting all traits from each category.




Figure 3: Relationship between age and gender in the population shown as an UpSet plot. Bar heights indicate the number of observations within each intersection. All intersections are present, with the largest being between the 30-44 age group and the female gender, followed by 30-44 and male.

UpSet Plot Figure 3 shows the UpSet plot of the population dataset, which demonstrates the counts of intersections of age groups across gender. The plot shows that the largest intersection is between the 30-44 age group and the female gender, followed by males for the same age group. A representative panel would contain these intersections.

Visualising Survey Sample




Figure 4: Relationship between age and gender in the survey sample shown as a mosaic plot. Colour indicates gender. Width of the bars correspond to the count within the category. All intersections still present, though the distribution has shifted, with some groups being more or less represented than before.

Mosaic Plot Figure 4 shows the mosaic plot of the survey sample dataset, which demonstrates the distribution of age groups across gender in the simulated survey sample. The plot shows that the distribution has changed from the population dataset, with some groups being more or less represented than before. For example, the genders among ages are now less balanced across all age groups.

UpSet Plot Figure 5 shows the UpSet plot of the survey sample dataset, which demonstrates the counts of intersections of age groups across gender in the simulated survey sample. The plot shows that the largest intersection is still between the 30-44 age group and the female gender.




Figure 5: Relationship between age and gender in the survey sample shown as an UpSet plot. Bar heights indicate the number of observations within each intersection. All intersections are still present, though the distribution has shifted, though the intersections between the 30-44 age group and male and female genders remain among the largest.

Visualising Panel Sample




Figure 6: Relationship between age and gender in the selected panel shown as a mosaic plot. Colour indicates gender. Width of the bars correspond to the count within the category. Seven intersections are now not present, and the distribution has shifted significantly from the population and survey sample datasets.

Mosaic Plot Figure 6 shows the mosaic plot of the selected panel dataset, which demonstrates the distribution of age groups across gender in the simulated selected panel. By the time we reach this

step, we can see that the distribution has changed significantly from the population dataset. In fact, this particular iteration presents an extreme case where all younger panel members are female, all older members are male, and all non-binary members are in the oldest group.




Figure 7: Relationship between age and gender in the selected panel shown as an UpSet plot. Bar heights indicate the number of observations within each intersection. Level of representation has significantly decreased, with a number of intersections, including 30-44 and male, now missing.

UpSet Plot Figure 7 shows the UpSet plot of the selected panel dataset, which demonstrates the counts of intersections of age groups across gender in the simulated selected panel. Echoing the distribution shift shown in the mosaic plot, the UpSet plot shows that a number of intersections are now missing. This was, to some extent, expected for the non-binary group, as only two members of this group were going to be selected regardless, meaning at least two intersections would not be represented. However, the complete absence of all younger male and non-binary members, as well as all older female members is a significant deviation from the population and survey sample datasets, and demonstrates the risk of insufficient representation when intersections are not directly addressed by the selection process.




Figure 8: *Distributions of age groups and genders in the selected panel dataset, shown as pie charts. Colour corresponds to the category, and size of the slice corresponds to the proportion of the population within that category. All marginal groups are represented, and the distribution appears similar to the population pie charts, though this is misleading as it does not show the absence of certain intersections.*

Demographic Summary (Pie Charts) The use of pie charts and other simple graphics, despite their popularity among practitioners and stakeholders due to their simplicity, is misleading in this situation. Figure 8 is notably almost identical to the population pie charts (with difference as result of rounding) in Figure 1, as the marginal distributions of age and gender are the same across the population and selected panel datasets. However, from Figure 6 and Figure 7, younger male and non-binary, and older female individuals are not contained within the selected panel, which means it is not representative of the population.

This example is the crux of why sortition performance must be visually evaluated at the intersectional level, prior to any sort of deliberation or decision-making process, as it can reveal significant representativeness issues that may not be apparent from summary statistics alone, and which may impact the legitimacy and quality of the panel's outcomes. While a panel may fulfil marginal quotas, it may still not be representative of the population. Consequently, it may fail to deliver the core democratic benefits intended by the sortition process. For this reason, we will be investigating ways to benchmark performance through visualisation, to make sure selected panels are representative before they are used for deliberation.

2.4 Research Plan

Month	Goal
June	Establish data cases
	Run simulation
	Begin visualising
July	Consolidate visualisations
	Explore framework/tool options
August	Build tool
	Consider further applications
September	Evaluate tool
	Draft thesis
October	Second draft of thesis
November	Final draft of thesis

References

- Baharav, C & B Flanigan (2024). Fair, Manipulation-Robust, and Transparent Sortition. *Proceedings of the 25th ACM Conference on Economics and Computation*, 756–775. (Visited on 04/15/2026).
- Flanigan, B, P Gözl, A Gupta, B Hennig & AD Procaccia (2021). Fair algorithms for selecting citizens' assemblies. *Nature* **596**, 548–552.
- Gehlenborg, N (2019). *UpSetR: A More Scalable Alternative to Venn and Euler Diagrams for Visualizing Intersecting Sets*. R package version 1.4.0. <https://CRAN.R-project.org/package=UpSetR>.
- Giuliani, A (2025). Sortition in Politics: From History to Contemporary Democracy. *Parliaments, Estates and Representation* **45**(3), 317–335.
- Jeppson, H & H Hofmann (2023). Generalized Mosaic Plots in the Ggplot2 Framework. *The R Journal* **14**(4), 50–78. (Visited on 04/28/2026).
- Landemore, H (2026). Opinion | No Shy Person Left Behind. *The New York Times*. (Visited on 04/20/2026).
- Paris Creates a Permanent Citizens' Council (2021). *Sortition Foundation*. (Visited on 04/14/2026).
- Walsh, CD & JA Elkind (2021). The Dissatisfied and the Engaged: Citizen Support for Citizens' Assemblies and Their Willingness to Participate. *Irish Political Studies* **36**(4), 647–666. (Visited on 04/15/2026).
- Ward, I (2008). An Experiment in Political Communication: The British Columbia Citizens' Assembly on Electoral Reform. *Australian Journal of Political Science* **43**(2), 301–315. (Visited on 04/15/2026).