



Simple | Secure | Trusted



Simplifying Networks, Amplifying Connectivity

PRODUCT	MODEL No.	DESCRIPTION
Stackable Enterprise Switch - Layer 3		
	AP-SG6500E-16F-4XG-R	8 x 100/1000Base-X (SFP) + 4 x GE Combo (RJ45/SFP) + 4 x 10GbE (SFP+) 1 Console, 1 USB, 1 RJ45 management port - AC + 48VDC power supply - Switching capacity 112Gbps - Forwarding rate 83Mpps - VLAN Table 4K - MAC Address 16K - Static & Dynamic Routing
	AP-SG6500E-28F-4XG-R	16 x 100/1000Base-X (SFP) + 8x GE Combo(RJ45/SFP) + 4 x 10GE(SFP+) 1 Console, 1 USB, 1 RJ45 management port - Rack Mount 1U - Dual AC + 48VDC power supply - Switching Capacity 128Gbps - Packet Forwarding 95Mpps - MAC Address 16K - VLAN Table 4K
	AP-SG6500E-52F-4XG-R	48Ports 1*G SFP with 4*10G Uplink Ports + 1 Console Port - Rack Mount 1U - Dual Power AC/DC - Switching Capacity 176Gbps - Packet Forwarding 131Mpps - MAC Address 16K - Static Routing, OSPF v3,BGP4+ - VLAN Table 4K
	AP-SG6500E-28X-4XG	24 x 10/100/1000BaseT + 4 x 10GE(SFP+) 1 Console, 1 USB, 1 reset, 1 RJ45 management port - AC power supply - Switching capacity 128Gbps - Forwarding rate 95Mpps - MAC Address 16K
	AP-SG6500E-52X-4XG	48 x 10/100/1000BaseT + 4 x 10GE(SFP+) 1 Console, 1 USB, 1 reset, 1 RJ45 management port - AC power supply - Switching capacity 176Gbps - Forwarding rate 131Mpps - MAC Address 16K
	AP-SG6500E-26XF2Q	24x10GbE (SFP+) + 2x40GbE(QSFP) 1 Console, 1 USB, 1 reset, 1 RJ45 management port - Dual Power AC + 48VDC - Switching capacity 640Gbps - Forwarding rate 480Mpps - MAC Address 32K - VLAN Table 4K
	AP-SG6500E-8G24XF2Q	8 x 10/100/1000BaseT + 24 x 10GE(SFP+) + 2 x 40GE(QSFP+) - Dual Power AC+DC (48V) 1 Console, 1 USB, 1 RJ45 management port 1 Reset Button - Forwarding performance 488Mpps - Switching capacity 656Gbps - MAC Address 32K
	AP-SG6500E-20X4FX-4XG-R2	20 x 10/100/1000BaseT + 4 x GE Combo (GT/SFP) + 4 x 10GE(SFP+) - Dual Power AC+AC 1 Console, 1 USB, 1 RJ45 management port 1 Reset Button - Forwarding performance 95Mpps - Switching capacity 128Gbps
	AP-SG6500E-52X-4XG-R2	48 x 10/100/1000BaseT + 4 x 10GE(SFP+) - Dual Power AC+AC 1 Console, 1 USB, 1 RJ45 management port 1 Reset Button - Forwarding performance 131Mpps - Switching capacity 176Gbps
	AP-SG6200-24XF2SQ	24x10GE(SFP+) + 2x100GE(QSFP28) 1 modular AC+1 optional modular AC power supply 1 Console, 1 USB, 1 RJ45 management port 1 Reset Button - Forwarding performance 488Mpps - Switching capacity 656Gbps - Auto MDI/MDIX
	S6200-24X6C-HI	24 x 10G SFP+ and 6 x 100G QSFP28 1+1 power supplies (AC), 3+1 fans 1 Console, 1 USB, 1 RJ45 management ports - Forwarding performance: 600Mpps - Switching capacity: 1.68Tbps
	S6200-48X6C-HI	48 x 10G SFP+ and 6 x 100G QSFP28 1+1 power supplies (AC), 3+1 fans 1 console, 1 USB, 1 RJ45 management ports - Forwarding performance: 600Mpps - Switching capacity: 2.16Tbps

PRODUCT	MODEL No.	DESCRIPTION
Stackable Enterprise Switch - Layer 3		
	AP-SG6200-28X4XF-6XG	• 24x1GE + 4x1GE(SFP) + 6x10G(SFP+) • 1 Modular AC+1 optional modular AC power supply • 1 Console, 1 USB, 1 RJ45 management port • 1 Reset Button • Forwarding performance 131Mpps • Switching capacity 176Gbps • Auto MDI/MDIX
	AP-SG6200-28X4XF-P-6XG	• 24x1GE(PoE) + 4x1GE(SFP) + 6x10G(SFP+) • 1 Modular AC+1 optional modular AC power supply • 1 Console, 1 USB, 1 RJ45 management port • 1 Reset Button • Forwarding performance 131Mpps • Switching capacity 176Gbps • PoE+, up to 750W with dual PSU or 375W with 1 PSU • Auto MDI/MDIX
	AP-SG6200-52FX-6XG	• 48x1GE(SFP) + 6x10G(SFP+) • 1 Modular AC+1 optional modular AC power supply • 1 Console, 1 USB, 1 RJ45 management port • 1 Reset Button • Forwarding performance 161Mpps • Switching capacity 216Gbps • Auto MDI/MDIX
	AP-SG6200-48X-6XG	• 48x1GE + 6x10G(SFP+) • Dual Fixed AC power supply • 1 Console, 1 USB, 1 RJ45 management port • 1 Reset Button • Forwarding performance 161Mpps • Switching capacity 216Gbps • Auto MDI/MDIX
	AP-CS6100-24XF2QSF-E1	• 24 x 10GE(SFP+) + 2x100GE(QSFP28) • 1 modular AC+1 optional modular AC power supply • 1 Console, 1 USB, 1 RJ45 management port • 1 Rest Button • Forwarding performance: 488Mpps • Switching capacity: 656Gbps • Auto MDI/MDIX
Data Center Switch		
	AP-DSG7510-48S6Q-HI	• 48 x 10G SFP+ and 6 x 40G QSFP • AC+AC Power Supply • 1 Console, 1 USB, 1 RJ45 management port • Forwarding performance 1071Mpps • Switching capacity 1440Gbps
	AP-DSG7580-48S6CQ	• 48 x 25G/10G SFP28 and 6 x100G QSFP28 • AC+AC Power Supply • 1 Console, 1 USB, 1 RJ45 management port • Forwarding performance 2.6 bpps • Switching capacity 3.6 Tbps
	AP-DSG7580-32CQ	• 32 x 100G QSFP28 • AC+AC Power Supply • 1 x Console, 1 x USB, 1 x 100/1000Base-T MGMT • Forwarding performance 4.7Bpps • Switching capacity 6.4Tbps
Chassis Switch		
	DC-RS-8604E	• 4-Slot Chassis • AC+AC Power Supply • Dimensions (W x D x H) 445mm x 421mm x 266mm (6U) • Backbone Switching Capacity 2120Gbps • Forwarding Rate 1577Mpps
	DC-RS-8610E	• 10-Slot Chassis (2 slot management blades, 8 slot business blade) • AC+AC Power Supply • Dimensions (W x D x H) 436mm x 478mm x 797mm (18U) • Backbone Switching Capacity 4480Gbps • Forwarding Rate 3333Mpps
	DC-RS-8616	• 16-Slot Chassis (2 slot management blades, 14 slot business blade) • Number of Management Engine slots - 2 • Port density per chassis 384 x GE, 320 x 10GE, 32 x 40GE • Dimensions (W x D x H) 440mm x 450mm x 842mm(19U) • Switching Capacity 8960 Gbps • Forwarding performance 6667 Mpps

PRODUCT	MODEL No.	DESCRIPTION
L2 Web Smart Switch		
	AP-SG4500WM-10GT-P-2SFP	• 8 *10/100/1000Mbps PoE with 2×100/1000Base-X (SFP) Uplink Ports • PoE+, up to 120W • AC power adapter • Switching capacity: 20Gbps • Forwarding rate: 14.88Mpps
	AP-GS3016P-WM	• 16 *Gigabit PoE ports+2 *Gigabit SFP optical ports • Complies with IEEE802.3, IEEE802.3u, IEEE802.3x, IEEE802.3ab, and IEEE802.3z standards • RJ45 port supports 10/100/1000Mbps adaptation • Supports automatic port flipping (Auto MDI/MDIX) • PoE Power Budget 300W • 1U rack installation • The panel indicator lights will monitor the working status and assist in fault analysis
	AP-GS3024P-WM	• 24 *Gigabit PoE ports+2 *Gigabit SFP optical ports • Complies with IEEE802.3, IEEE802.3u, IEEE802.3x, IEEE802.3ab, and IEEE802.3z standards • RJ45 port supports 10/100/1000Mbps adaptation • Supports automatic port flipping (Auto MDI/MDIX) • PoE Power Budget 400W • 1U rack installation
	AP-BSG1905Q-XF1	• 2.5G Web-Smart Ethernet Switch 5×2.5G RJ45 Port+ 1 Uplink 10G SFP+ Fiber Port • Bandwidth 45Gbps • Support 802.3Q VLAN, QOS, port aggregation, port mirroring, cable detection, loop protection, port statistics, port flow control, bandwidth control • Support Web management, SNMP Management • 6KV lightning protection, 8kv anti- static • PoE Power Budget 65W • Working Temperature -10°C ~ 50°C
	AP-BGS1908MP-XF1	• 8 *100/1000/2500Mbps PoE ports+1 *10G SFP+ port • Complies with IEEE 802.3, IEEE 802.3u, IEEE 802.3ab, IEEE 802.3bz, IEEE 802.3ae, IEEE 802.3x standards • PoE port supports 100/1000/2500Mbps adaptive • PoE Power Budget 150W • The panel indicator lights will monitor the working status and assist in fault analysis
Layer 2 PoE		
	AP-ESG-3010P	• 8Ports 100/1000Mbps PoE with 2*1G SFP Uplink + 1 Console Port • Rack Mount • Power Budget 120W • PoE/PoE+ • Switching Capacity 20Gbps • Packet Forwarding 14.9Mpps • Jumbo Frame • MAC Address 8K
	AP-ESG3024P	• 24Ports 100/1000Mbps PoE with 4*1G Combo Uplink Ports + 1 Console Port • Rack Mount • Power Budget 400W • PoE/PoE+ • Switching Capacity 56Gbps • Packet Forwarding 41.6Mpps • Jumbo Frame • MAC Address 8K
	AP-ESG3048P	• 48 Ports PoE Gigabit L2+ Management with 4*10G Uplink 1 Console Port, 1Reset • Power Input -AC100-240V/50-60Hz • Power Budget 800W • Buffer Memory 32MByte • Switching Capacity 176Gbps • Packet Forwarding 131Mpps • Jumbo Frame 12kbytes • MAC Address 32K
	AP-SG4500-10GT-P-2SFP	• 8Ports 10/100/1000 Base-T+2x100/100 Base-X (SFP) + 1 Console, 1 Reset Port • Power Budget 120W • PoE/PoE+ • Switching Capacity 20Gbps • Forwarding 14.88Mpps • Jumbo Frame 10K • MAC Address 8K • Support Cloud Management
	AP-SG4500WM-10GT-P-2SFP	• 8Ports 10/100/1000Base-T+2x100/1000Base-X (SFP) • Power Budget 120W • PoE/PoE+ • AC Power adapter • Switching capacity: 20Gbps • Forwarding rate: 14.88Mpps • MAC Address 8K • Support Cloud Management
	AP-SG4500-12GT-P-4XFP	• 8Ports 100/1000Mbps PoE with 4*10G Uplink Ports + 1 Console Port • Power Budget 125W • PoE/PoE+ • Switching Capacity 96Gbps • Packet Forwarding 71.4Mpps • Jumbo Frame • MAC Address 16K • Layer 2 Feature L2+ • Support Cloud Management
	AP-SG4500-28GT-P-4SFP	• 24Ports 100/1000Mbps PoE with 4*1G Uplink Ports + 1 Console Port • Power Budget 370W • PoE/PoE+ • Switching Capacity 56Gbps • Packet Forwarding 41.6Mpps • Jumbo Frame • MAC Address 16K • Support Cloud Management
	AP-SG4500-28GT-P-4XFP	• 24Ports 100/1000Mbps PoE with 4*10G Uplink Ports + 1 Console Port • Power Budget 370W • PoE/PoE+ • Switching Capacity 128Gbps • Packet Forwarding 95Mpps • Jumbo Frame • MAC Address 16K • Layer 2 Feature L2+ • Support Cloud Management
	AP-SG4500-52GT-P-4XFP	• 48Ports 10/100/1000Mbps PoE with 6*10G Uplink Ports + 1 Console Port • Power Budget 740W • PoE/PoE+ • Switching Capacity 216Gbps • Packet Forwarding 161Mpps • Jumbo Frame 12K bytes • MAC Address 32K • Support Cloud Management


PRODUCT	MODEL No.	DESCRIPTION
Layer - 3 Multi Gigabit PoE		
	AP-SG6500M-18X-P-6XG	• 12Ports x1G/2.5G/5G/10GBase T+6 x 10G/25GE (SFP28) ports • Power Supply Modular • PoE /PoE+ /PoE++ (90w) • PoE Budget 530w with 1 PSU and 1060w 2 PSUs • Switching Capacity 540Gbps • Packet Forwarding 405Mpps • Jumbo Frame 12K • MAC Address 32K
	AP-SG6500M-30X-P-4XP2Q	• 24Ports 100/1000M/2.5GBase T+4 x 10GE(SFP+) + 2 x 40G(QSFP+) ports • Power Supply Fixed AC & 48VDC RPS • PoE/PoE+ /PoE++(60w) • PoE Budget Up to 530w with 1 PSU and 1060w with 2 PSUs • Switching Capacity 360Gbps • Packet Forwarding 256Mpps • Jumbo Frame 12K
	AP-SG6500E-28X-P-4XG	• 24Ports 100/1000Mbps with 4*10G SFP Uplink + 1 Console Port • AC Power Supply • PoE+ • PoE Budget 370w • Switching Capacity 128Gbps • Packet Forwarding 95Mpps • Jumbo Frame 12K • MAC Address 16K
	AP-SG6500E-52X-P-4XG	• 48Ports 100/1000Mbps with 4*10G Uplink Ports+1 Console Port • Dual Power AC/DC • PoE+ • PoE Budget 740w • Switching Capacity 176Gbps • Packet Forwarding 131Mpps • Jumbo Frame 10K • MAC Address 16K
Industrial PoE		
	AP-IGS9006P	• 4Ports Gigabit L2 Managed Industrial PoE Switch with 2*1G SFP Uplink, 1 Console Port • Maximum output of an 802.3AF/AT port is 30W • Bandwidth 12Gbps • Power Supply 4PIN Industrial Terminal, DC48-55V wide voltage input • Port surge protection: common mode 6KV, differential mode 2KV; ESD static: Air 15KV, contact 8KV • Operating temperature -40°C to 75°C • Cloud Managed
	AP-IGS9010P	• 10Ports Gigabit L2 Managed Industrial PoE Switch • 8 Ports Gigabit PoE + 2 Gigabit SFP + 1 Console Port • Switching Capacity 20Gbps • Packet Forwarding Rate 8.92Mpps • Power Supply 4PIN Industrial Terminal, DC48-55V wide voltage input • MAC Address 8K • Operating temperature -40°C to 75°C • Cloud Managed
	AP-IGS9014P	• 12Ports Gigabit L2 Managed Industrial PoE Switch • 8 Ports Gigabit PoE + 4 Gigabit SFP • Switching Capacity 24Gbps • Packet Forwarding Rate 17.86Mpps • Power Supply 4PIN Industrial Terminal, DC44-57V wide voltage input • MAC Address 16K • Operating temperature -40°C to 75°C • Cloud Managed
	AP-IGS9020P	• 20Ports Gigabit L2 Managed Industrial PoE Switch • 16 Ports Gigabit PoE + 4 Gigabit SFP • Switching Capacity 40Gbps • Packet Forwarding Rate 29.76Mpps • Power Supply 4PIN Industrial Terminal, DC44-57V wide voltage input • MAC Address 16K • Operating temperature -40°C to 75°C • Cloud Managed
	AP-IGS9028P	• 28Ports Gigabit Industrial L2 Managed PoE Switch • 24 Ports Gigabit PoE + 4 Gigabit SFP • Switching Capacity 56Gbps • Packet Forwarding Rate 41.66Mpps • Power Supply 4PIN Industrial Terminal, DC44-57V wide voltage input • MAC Address 16K • Operating temperature -40°C to 75°C • Cloud Managed
Unmanaged PoE Switch		
	AP-BSG1804Q1-P-XF1	• 4×2.5G PoE Port+ 1 Uplink 2.5G Ethernet Port + 1 Uplink 10G SFP+ Fiber Port • PoE/PoE+ • Bandwidth 45Gbps • POE Priority (from 1 to 4 ports in sequence) • DIP Switch Setting for VLAN mode • Support PoE MAX indicator, • Port Surge Protection: General mode 4KV, differential mode 2KV; ESD Air 8KV, Contact 6KV
	AP-BSG1808Q-P-4XF1	• 8×2.5G PoE Port+1*10G SFP+ Uplink Fiber Port • PoE/PoE+ • Bandwidth 60Gbps • POE Priority (from 1 to 4 ports in sequence) • DIP Switch Setting for VLAN mode • Support PoE MAX indicator, • Port Surge Protection: General mode 4KV, differential mode 2KV; ESD Air 8KV, Contact 6KV

PRODUCT	MODEL No.	DESCRIPTION
Unmanaged PoE Switch		
	AP-ES106P	• 4Ports 100Mbps PoE with 2*100Mbps Uplink Ports • PoE Power Budget 65W • Power Supply Internal • Long Range Up to 250mtrs • IEEE802.3 af/at • PoE Watchdog • Port Lightning Protection 4KV/ ESD8KV
	AP-ES108P-2GE	• 8Ports 100Mbps PoE with 2*1000Mbps (Copper) Uplink Ports • PoE Power Budget 120W • Power Supply Internal • Long Range Up to 250mtrs • IEEE802.3 af/at • PoE Watchdog • Port Lightning Protection 4KV/ ESD8KV
	AP-ES1216	• 16Ports 100Mbps PoE with 2*GE (Copper)+1SFP Uplink Ports • PoE Power Budget 200W • Power Supply Internal • Long Range Up to 250mtrs • IEEE802.3 af/at • PoE Watchdog • Port Lightning Protection 4KV/ ESD8KV
	AP-ES1024P	• 24Ports 100Mbps PoE with 2*GE (Copper)+1SFP Uplink Ports • PoE Power Budget 300W • Power Supply Internal • Long Range Up to 250mtrs • IEEE802.3 af/at • PoE Watchdog • Port Lightning Protection 4KV/ ESD8KV
	AP-ESG1906P-2GE	• 4Ports 10/100/1000M PoE Switch + 2 Uplink 10/100/1000M Ethernet ports, Support IEEE802.3af/at, each port 15.4W/30W. Internal Power Supply 52V1.25A 65W. • Support VLAN Mode and Extend 250meters • Support PoE Watchdog function • Bandwidth 12.0Gbps • Support Port Surge protection 4KV, ESD 8KV; Power Surge protection 4KV (AirPro box) • electric smelting from 400V to 450V
	AP-ESG1906P-2SF	• 4Ports 100/1000Mbps PoE with 2*1G SFP Uplink Ports • PoE Power Budget 120W • Power Supply Internal • Port 3&4 Support Long Range 250mtr • Port 1 Support up to 60W Ultra thin PoE • PoE Watchdog • Port Lightning Protection 4KV/ ESD8KV
	AP-ESG1910P-2GE	• 8Ports 100/1000Mbps PoE with 2 GE Uplink Ports • PoE Power Budget 120W • Power Supply Internal • Distance Up to 100mtrs • IEEE802.3 af/at • Port Lightning Protection 4KV/ ESD8KV
	AP-ESG1910P-2SF	• 8Ports 100/1000Mbps PoE with 2*1G SFP Uplink Ports • PoE Power Budget 120W • Power Supply Internal • Port 7 & 8 Support Long Range Up to 250mtrs • IEEE802.3 af/at • PoE Watchdog • Port Lightning Protection 4KV/ ESD8KV
	AP-ESG4016P-2G2FX	• 16Ports 100/1000Mbps PoE with 2*1000Mbps (Copper) + 2*1G SFP Uplink Port • PoE Power Budget 220W • Power Supply Internal • Port 9-16 Support Long Range Up to 250mtrs • IEEE802.3 af/at • Port Lightning Protection 4KV/ ESD8KV
	AP-ESG4024P-2G2FX	• 24Ports 100/1000Mbps PoE with 2*1000Mbps (Copper) + 2*1G SFP Uplink Ports • PoE Power Budget 320W • Power Supply Internal • Port 17-24 Support Long Range Up to 250mtrs • IEEE802.3 af/at • Port Lightning Protection 4KV/ ESD8KV

PRODUCT	MODEL No.	DESCRIPTION
Unmanaged Data Switch		
	AP-GS1008	• 8Ports 10/100/1000 Mbps • Desktop/Wall Mount • Switching Capacity 1.6Gbps • MAC Address 2K
	AP-SG1016	• 16Ports 10/100/1000 Mbps • Rack Mount • Switching Capacity 32Gbps • Packet Forwarding 23.8Mpps • MAC Address 8K • Loop Protection • QoS Port 1-8 support Auto QoS
	AP-SG1024	• 24Ports 10/100/1000 Mbps • Rack Mount • Switching Capacity 48Gbps • Packet Forwarding 35.71Mpps • MAC Address 8K • Loop Protection • QoS Port 1-8 Support Auto QoS
Access Switch - Layer 2		
	AP-SG4500-10GT-2SFP	• 8Ports 100/1000Mbps with 2*1G SFP Uplink + 1 Console Port • Rack Mount • Switching Capacity 20Gbps • Packet Forwarding 14.9Mpps • Jumbo Frame 10K • MAC Address 8K • Layer 2 Feature • VLAN Table 4K • Ring STP/RSTP/ERPS • Support Cloud Management
	AP-SG4500-12GT-4XFP	• 8Ports 100/1000Mbps with 4*10G Uplink Ports + 1 Console Port • Rack Mount • Switching Capacity 96Gbps • Packet Forwarding 71.4Mpps • Jumbo Frame 10K • MAC Address 16K • Layer 2 Feature L2+ • VLAN Table 4K • Ring STP/RSTP/ERPS • Support Cloud Management
	AP-SG4500-28GT-4SFP	• 24Ports 100/1000Mbps with 4*1G Uplink Ports + 1 Console Port • Rack Mount • Switching Capacity 56Gbps • Packet Forwarding 41.6Mpps • Jumbo Frame 10K • MAC Address 16K • Layer 2 Feature • VLAN Table 4K • Ring STP/RSTP/ERPS • Support Cloud Management
	AP-SG4500-28GT-4XFP	• 24Ports 100/1000Mbps with 4*10G Uplink Ports+1 Console Port • Rack Mount • Switching Capacity 128Gbps • Packet Forwarding 95Mpps • Jumbo Frame 10K • MAC Address 16K • Layer 2 Feature L2+ • VLAN Table 4K • Support Cloud Management
	AP-SG4500-52GT-4XFP	• 48Ports 100/1000Mbps with 4*10G Uplink Ports+1 Console Port • Rack Mount • Switching Capacity 176Gbps • Packet Forwarding 131Mpps • Jumbo Frame 10K • MAC Address 16K • Layer 2 Feature L2+ • VLAN Table 4K • Support Cloud Management
	AP-SG4500-52GT-4SFP	• 48Ports 100/1000Mbps with 4*1G Uplink Ports+1 Console Port • Rack Mount • Switching Capacity 104Gbps • Packet Forwarding 77.4Mpps • Jumbo Frame 10K • MAC Address 16K • Layer 2 Feature L2+ • VLAN Table 4K • Support Cloud Management

PRODUCT	MODEL No.	DESCRIPTION
Outdoor Access Point		
	AIR-AP669ODU-BE	• 10Gbps Tri-Band Wi-Fi 7 High Power Outdoor Access Point • 1 × 10Gbps WAN PoE Port with 1 × 2.5Gbps LAN Port & 1 × 10G SFP Port • Power Input: 48V DC via 802.3bt PoE • Data Rate: 2.4GHz – 1376Mbps + 5GHz – 4804Mbps + 6GHz – 4804Mbps • Radio Chain Streams: 2.4GHz: 4×4 + 5GHz: 4×4 + 6GHz: 4×4 • Antenna Gain: External 8 × 6dBi Omni Antenna • Concurrent Users: Up to 500 • BSSID per Radio: 16 • Tx Power: High Power Outdoor Performance • IP68 Industrial Grade Weatherproof Enclosure
	AIR-AP667ODU-BE	• 7Gbps Dual-Band Wi-Fi 7 High Power Outdoor Access Point • 1 × 10Gbps WAN PoE Port with 1 × 10G SFP Port • Power Input: 48V DC via 802.3bt PoE • Data Rate: 2.4GHz – 1376Mbps + 5GHz – 5616Mbps • Radio Chain Streams: 2.4GHz: 4×4 + 5GHz: 4×4 • Antenna Gain: External 4 × 6dBi Omni Antenna • Concurrent Users: Up to 300 • BSSID per Radio: 16 • Tx Power: High Power Outdoor Design • Ip68 Industrial-Grade Weatherproof Enclosure
	AIR AP690IX (ODU)	• 1.75 Gbps Dual Band 11AX High Power Wi-Fi6 Outdoor AP • 575Mbps on 2.4Ghz & 1.2Gbps on 5Ghz • 1*WAN*100/1000 PoE/1*SFP Port / 1Console Port, PoE+ • Maximum Data Rate 575Mbps on 2.4Ghz and 1.2Gbps on 5Ghz • Radio Chain Streams 2x2 • Antenna Gain 10dbi Internal Panel Antenna • Tx Power 28dbm • NAT/Bridge • IP68 Rating • Cloud Managed
	AIR AP690EX (ODU)	• 1.75 Gbps Dual Band 11AX High Power Wi-Fi6 Outdoor AP • 575Mbps on 2.4Ghz & 1.2Gbps on 5Ghz • No. of Ports 1*WAN Gigabit PoE+1SFP Port +1Console Port, PoE+ • Maximum Data Rate 575Mbps on 2.4Ghz and 1.2Gbps on 5Ghz • Radio Chain Streams 2x2 • Antenna Gain External Omni Antenna/ Panel Antenna option • Tx Power 28dbm • NAT/Bridge • IP68 Rating • Cloud Managed
	AIR-AP690IX-V2 (ODU)	• 2.97Gbps Dual-Band 802.11b/g/n/ax High Power Outdoor Access Point • 2.5G WAN PoE / 1Gigabit LAN Port • Power Input: 48V DC via 802.3at PoE+ • Data Rate: 2.4GHz – 575Mbps + 5GHz – 2400Mbps • Radio Chain Streams: 2×2 (2.4GHz) + 4×4 (5GHz) • Antenna Type: Internal Antenna (2.4G: 5dBi, 5G: 6dBi) • Tx Power: High Power Outdoor Coverage • Concurrent Users: Up to 254 • BSSID per Radio: 16 • IP66 Industrial-Grade Weatherproof Enclosure • Cloud Management
Outdoor P2P/P2M		
	Air Connect-2	• 300Mbps 2.4Ghhz Outdoor AP • 1*WAN PoE 100Mbps/1*LAN 100Mbps • Mounting Pole Mount/Wall Mount • Tx Power 22dbm • Passive PoE 24V/1 Amp • Antenna Gain 10dbi Panel • Antenna Direction 60Degree Horizontal • Distance Up to 1Km
	Air Bridge Lite-5	• 900Mbps 5Ghz Outdoor High Power AP • 1*WAN PoE 100Mbps /1*LAN 100Mbps • Mounting Pole Mount/Wall Mount • Tx Power 22dbm • Passive PoE 24V/1 Amp • Antenna Gain 12dbi MIMO Panel • Antenna Direction 60Degree Horizontal • Distance Up to 2Km
	Air Bridge5ac-Ex	• 900Mbps 5Ghz Outdoor High Power AP • 1*WAN PoE 100Mbps /1*LAN 100Mbps • Mounting Pole Mount/Wall Mount • Tx Power 22dbm • Passive PoE 24V/1 Amp • Antenna Gain 12dbi MIMO Panel • Antenna Direction 60Degree Horizontal • Distance Up to 2Km
	Air Setu	• 900Mbps 5Ghz Outdoor High Power AP • 1*WAN PoE 100/1000Mbps/1*LAN 100/1000Mbps & 12v DC Power • Mounting Pole Mount/Wall Mount • Tx Power 27dbm • PoE Af • Antenna Gain 14dbi MIMO Panel • Antenna Direction 60Degree Horizontal • Distance Upto 5Km
	Air Setu Lite 5G CPE	• 866Mbps 5Ghz Outdoor High Power AP • 1*WAN PoE 100/1000Mbps/1*LAN 100/1000Mbps & 12v DC Power • Mounting Pole Mount/Wall Mount • Tx Power 27dbm • PoE Af • Antenna Gain 15dbi MIMO Panel • Antenna Direction 60Degree Horizontal • Distance Upto 5Km
	Air Setu5ac	• 866Mbps 5Ghz Outdoor High Power AP • 1*WAN PoE 100/1000Mbps/1*LAN 100/1000Mbps & 12v DC Power • Mounting Pole Mount/Wall Mount • Tx Power 27dbm • PoE Af • Antenna Gain 14dbi MIMO Panel • Antenna Direction 60Degree Horizontal • Distance Upto 5Km

PRODUCT	MODEL No.	DESCRIPTION
Access Point - Enterprise (Wi-Fi 6)		
	AIR-AP605C-X1-V2	• 1.75Gbps Dual Band 11ax Wi-Fi Ceiling Mount AP • 1*WAN *10/100/1000Mbps PoE • Power 12V DC/1.5Amp Or PoE af • Data Rate 575Mbps on 2.4G & 1.2Gbps on 5Ghz • Radio Chain Streams 2x2 • Antenna Gain 4*5dbi • NAT/Bridge • Multiple SSID Up to 8 • Cloud Managed
	AIR-AP605C-X1-R2	• 3Gbps Dual Band 11ax Wi-Fi Ceiling Mount AP • 1*WAN *10/100/1000Mbps PoE/1*LAN 10/100/1000Mbps • Data Rate 575Mbps on 2.4G & 1.2Gbps on 5Ghz • Radio Chain Streams 2x2 • Hotspot2.0 /Passpoint support • Antenna Gain 4*5dbi • NAT/Bridge • Cloud Managed
	AIR-AP605C-AX-R2	• 2.97Gbps Dual Band 11ax Wi-Fi6 Ceiling Mount AP • 1*WAN *10/100/1000Mbps PoE/1*LAN*10/100/1000Mbps/1 Console Port • Power 12V DC/1.5Amp Or PoE af/at • Data Rate 575Mbps on 2.4G & 2.4Gbps on 5Ghz • Radio Chain Streams 4 • Antenna Gain 4*5dbi • NAT/Bridge • Multiple SSID Up to 32 • BLE Support • Cloud Managed
	AIR-AP610C-AX	• 3Gbps Dual Band 11ax High Power Ceiling Mount AP • 1*WAN *100/1000/2.5G PoE/1*LAN*1WAN PoE 100/1000/2.5G/1 Console Port • BLE Support • Power 12V DC/1.5Amp Or PoE at • Data Rate 575Mbps on 2.4Ghz & 2.4Gbps on 5Ghz • Radio Chain Streams 4x4 • Antenna Gain 6*5dbi • Multiple SSID Up to 32 • Cloud Managed
	AIR-AP620C-AX	• 6Gbps Dual band 11ax Wi-Fi 6 Ceiling Mount • 1*WAN PoE*100/1000/2.5G/5G&1 Console Port • BLE Support • Power 12V DC/1.5Amp Or PoE at • Data Rate 1.2Gbps on 2.4Ghz and 4.8Gbps on 5Ghz • Radio Chain Streams 8x8 • Antenna Gain 6*5dbi • Multiple SSID Up to 32 • Cloud Managed
	AIR-WAP602-X1	• 1.75Gbps Dual Band 11ax Wi-Fi6 In-Wall AP • 1*WAN PoE 10/100/1000Mbps + 1*LAN 10/100/1000Mbps • Power PoE af • 575Mbps on 2.4Ghz & 1.2Gbps on 5Ghz • Radio Chain Streams 2x2 • Antenna Gain 4*3dbi • NAT/Bridge • Multiple SSID Up to 8 • Cloud Managed
	AIR-WAP605-AX	• 1.75Gbps Dual Band 11ax Wi-Fi6 In-Wall AP • 1*WAN PoE 10/100/1000Mbps + 4*LAN*10/100/1000 Mbps with 1 Passthrough Port • Power PoE af • 575Mbps on 2.4Ghz & 1.2Gbps on 5Ghz • Radio Chain Streams 2x2 • Antenna Gain 4*3dbi • NAT/Bridge • Multiple SSID Up to 32 • Cloud Managed
	AIR-WAP605-AX-R2	• 1.75Gbps Dual Band 11ax Wi-Fi6 In-Wall AP • 1*WAN PoE 10/100/1000Mbps + 4*LAN*10/100/1000 Mbps with 1 Passthrough Port, 1 LAN PoE Out af • Power PoE af • 575Mbps on 2.4Ghz & 1.2Gbps on 5Ghz • Radio Chain Streams 2x2 • Antenna Gain 4*3dbi • NAT/Bridge • Multiple SSID Up to 32 • Cloud Managed
	AIR-WAP610-AX	• 3Gbps Dual Band 11ax Wi-Fi6 In-Wall AP • 1*WAN PoE 10/100/1000Mbps + 4*LAN*10/100/1000 Mbps with BLE • Power PoE af • 575Mbps on 2.4Ghz & 2.4Gbps on 5Ghz • Radio Chain Streams 2x2 • Antenna Gain 4*3dbi • NAT/Bridge • Multiple SSID Up to 32 • Cloud Managed

PRODUCT	MODEL No.	DESCRIPTION
Access Point - Enterprise (Wi-Fi 7)		
	AIR-AP660C-BE	• 3.6Gbps Dual Band Wi-Fi 7 Ceiling Mount Access Point • 1 × WAN Port (2.5Gigabit) 48V 802.3at PoE • Power 48V DC PoE or via WAN Port • Data Rate 2.4GHz: 574Mbps + 5GHz: 2882Mbps • Radio Chain Streams 2.4GHz: 2×2 + 5GHz: 4×4 • Antenna Gain 4dBi • Concurrent Users Up to 256 • BSSID per Radio: 16 • Cloud Management Supported • Hardware Controller Supported • VLAN / Dynamic VLAN Supported
	AIR-AP666C-BE	• 6Gbps Tri-Band Wi-Fi 7 Ceiling Mount Access Point • 1 × 2.5Gbps WAN PoE Port, 1 × 2.5Gbps LAN Port & 1 × 10Gbps SFP Port • Power Input: 48V DC via 802.3bt PoE • Data Rate: 2.4GHz – 574Mbps + 5GHz (Low) – 2402Mbps + 5GHz (High) – 2402Mbps • Radio Chain Streams: 2.4GHz: 2×2 + 5GHz: 4×4 + 5GHz: 4×4 • Antenna Gain: 4dBi • Concurrent Users: Up to 500 • BSSID per Radio: 16 • Cloud Management Supported • Hardware Controller Supported • VLAN / Dynamic VLAN Supported
	AIR-AP669C-BE	• 9Gbps Tri-Band Wi-Fi 7 Ceiling Mount Access Point • 1 × 2.5Gbps WAN PoE Port, 1 × 2.5Gbps LAN Port & 1 × 10Gbps SFP Port • Power Input: 48V DC via 802.3bt PoE • Data Rate: 2.4GHz – 574Mbps + 5GHz – 4804Mbps + 6GHz – 4804Mbps • Radio Chain Streams: 2.4GHz: 2×2 + 5GHz: 8×8 + 6GHz: 4×4 • Antenna Gain: 4dBi • Concurrent Users: Up to 500 • BSSID per Radio: 16 • Cloud Management Supported • Hardware Controller Supported • VLAN / Dynamic VLAN Supported
WLAN Smart Controllers		
	AP-WLC7008	• 6*Gigabit Ports with 2*1G SFP Combo ports +2*USB+1*Console default 32Licenses, max AP support 224 • Wi-Fi Roaming • SSID Based VLAN Tag • HA Support • Multiple SSID Config. • AP to AP Load Balance • MAC Address 16K
	AP-WLC7028	• 24Port 1GE+2Combo+2*10G SFP+ & 1*Console+1*USB • Default License 16 AP, Max support up to 256 AP's • Hotspot2.0/ Passpoint open roaming • HA Support • 802.1x authentication • Multiple SSID Config. • AP to AP Load Balance • MAC Address 16K
	AP-WLC7036	• 6*1G Ports with 2*10G SFP Slot Optional Ports, 1*Console+1*USB • Max support up to 512 AP's • Band Steering • Wi-Fi Roaming • HA Support • SSID Based VLAN Tag • Multiple SSID Config. • MAC Address 16K
	AP-WLC7045	• 16Gigabit Ports with 8 SFP Ports + 4*10SFP + 1*Console Port • Max support up to 1000 AP's • Band Steering • Hotspot2.0/ Passpoint open roaming • HA Support • SSID Based VLAN Tag • Multiple SSID Config. • MAC Address 16K

PRODUCT	MODEL No.	DESCRIPTION
4G/5G CPE - Indoor Router		
	AP-LT5112	• 5G Sub-6 GHz + 4G/LTE Dual Connectivity Router (SA & NSA Modes) • Up to 3.2 Gbps Download / 900Mbps Upload Speed (5G NR Release 16) • 4 × Gigabit LAN Ports (Auto-MDI/MDI-X) + 1 USB 2.0 Port + 1 SIM Slot (2FF) • Dual-Band Wi-Fi 6 (802.11ac Wave 2) Up to 2400 Mbps (600 Mbps @ 2.4 GHz + 1800 Mbps @ 5 Ghz) • Advanced SX Antenna Technology for Extended Coverage (4×4 MIMO on High Band) • Automatic WAN Failover and Load Balancing (Dual WAN Interfaces) • Enterprise-Class VPN Support – IPSec / GRE / L2TP / PPTP / OpenVPN (Tunneling Client & Server)
	AP-LT5335P	• 5G Sub-6 GHz + 4G/LTE Dual-Mode CPE Router (SA & NSA) • Up to 7 Gbps Download / 2.5 Gbps Upload (5G SA) 1.6 Gbps DL / 200 Mbps UL (LTE Cat 19) • 1 × 2.5 Gigabit Ethernet Port (PoE) + 1 × SIM Slot (2FF + eSIM Support) • Wi-Fi 6 (802.11ax) Dual Band — 1201 Mbps @ 5 GHz + 574 Mbps @ 2.4 Ghz • Advanced 4×4 MIMO Directional Antenna for Extended Coverage (10 dBi @ 3300–4200 Mhz) • Automatic Carrier Aggregation (4CA DL / 2CA UL on 5G, 5CA DL / 2CA UL on LTE) • Operational Modes – Router / Bridge for Flexible Deployment • NAT, Static Routing, DMZ, DDNS, and Virtual Server Support
	AP-LT4505N	• 300Mbps -4G LTE Single SIM router with 1WAN*GE+ 3LAN GE+1USB+ 1SIM Slot • Power 12V DC /1.5Amp • Maximum PHY Rate 1000Mbps on LAN • Antenna Gain 2*5dbi • Multiple VPN Support-IPSec/GRE/L2TP/PPTP/Open VPN-Bridge/NAT • 4G Failover on EWAN and Vice versa • Antenna Gain 2*5dbi • Concurrent Users Up to 50
	AP-LT4525N	• 300Mbps -4G LTE Dual SIM router with 1WAN*GE+3LAN*GE +1*USB +2*SIM Slots • Power - 12V DC /1.5Amp • Maximum PHY Rate 1000Mbps on LAN • Antenna Gain 2*5dbi • Multiple VPN Support-IPSec/GRE/L2TP/PPTP/Open VPN-Bridge/NAT • 4G Failover on EWAN and Vice versa • Concurrent Users Up to 50
Router Gateway		
	AP-EG320	• SMB Gateway Router • 32 Aps management capability • Recommended Export Bandwidth 100Mbps • Recommended concurrent 300 users
	AP-EG320-R1	• SMB Gateway Router • 64 APs management capability • Recommended Export Bandwidth 250Mbps • Recommended concurrent 500 users
	AP-EG-520	• Campus Gateway Router • 512 APs management capability • Recommended Export Bandwidth 1500Mbps • Recommended concurrent 2000 users
	AP-EG-720	• Large Campus Gateway Router • 1024APs management capability • Recommended Export Bandwidth 2800Mbps • Recommended concurrent 5000 users
	AP-LB1000	• 5Port Gigabit with 1WAN*GE+4LAN GE Router cum Load Balancer (up to 4WAN Can Configure) • 1WAN 10/100/1000Mbps +4LAN* 10/100/1000 Mbps Default • Power 12V DC/1Amp • Maximum PHY Rate 1000Mbps on LAN • Managed Upto 32 AP's • NAT Mode • Concurrent Users Up to 100

PRODUCT	MODEL No.	DESCRIPTION
Media Converter & SFP		
	AP-XFP-MMF-10G	• 10G SFP Transceiver • Dual data-rate 10Gbps • Wavelength 850nm • Distance Upto 300m • Transmission Media MM Fiber • Compatible with RoHS • +3.3V single power supply • Operating case temperature: Standard: 0 to +70°C
	AP-XFP-SMF-SR-10G	• 10G SFP Transceiver • Dual data-rate 10Gbps • Wavelength 1310nm • Distance Upto 10km • Transmission Media MM Fiber • Compatible with RoHS • +3.3V single power supply • Operating case temperature: Standard: 0 to +70°C
	AP-10G-SMF-SFP+LR	• 10G SFP Transceiver • Data-rate 10Gbps • Wavelength 1310nm • Distance Upto 20km • Transmission Media Single mode Fiber • Compatible with RoHS • +3.3V single power supply • Operating case temperature: Standard: 0 to +70°C
	AP-10G-SMF-SFP+ER+	• 10G SFP BIDI Transceiver • Data-rate 10Gbps • Wavelength 1310nm • Distance Upto 40km • Transmission Media Single mode Fiber • Compatible with RoHS • +3.3V single power supply • Operating case temperature: Standard: 0 to +70°C
	AP-GLC-SFP-T1	• 1.25Gbps Copper SFP support 10/100/1000Mbps • Distance support up to 100mtrs • Hot-pluggable SFP • Extended case temperature range (-40°C to +85°C) • Compliant with IEEE Std 802.3TM-2002 • RoHS Compliant
	AP-GLC-SFP-T10	• Up to 10Gbps data links • RJ45 Max 30m • Fully metallic enclosure for low EMI • Compact RJ-45 Connector assembly • Hot-pluggable SFP footprint • Low power dissipation • Extended case temperature: 0°C to 70°C • RoHS compliant and Lead Free • Applications • 10 Gigabit Ethernet
	Visit our Website to get Latest Products and Company Information	
Air Pro		