

Algorithms and Data Structures 3 (course 1DL481)

Uppsala University – Spring 2024

Assignment 1

Prepared by Pierre Flener, Di Yuan, and Gustav Björdal

— Deadline: 13:00 on Friday 2 February 2024—

Recall that the assignments exercise the material of the lectures that is *not* covered by the exam. It is strongly recommended to read the *Submission Instructions* and *Grading Rules* at the end of this document even *before* attempting to solve the following problems. It is also strongly recommended to prepare and attend the help sessions, as huge time savings may ensue.

Problem 1: Mixed Integer Programming (MIP) (40% weight)

The aim of solving this problem is to get hands-on experience with declaratively encoding an important real-world problem into a linear objective function and a system of linear constraints over integer and real-number variables, towards impressive performance.

Background and Motivation: The following optimisation problem is motivated by locating emergency-response *service stations*, which have fire trucks, for example. In the planning process, the *service region* is divided into zones. Each *zone* represents a candidate location of an emergency-response service station. Each zone has a *demand*: the expected frequency of service request, based on historical data and estimation. When the emergency-response agency receives a call, originating from some zone, the operator usually dispatches a vehicle from the closest (measured in travel time) service station, which may or may not be in the same zone.

For a given planning solution, the service quality for a zone is based on the travel time of the closest vehicles. To account for the fact that one or even multiple vehicles of the closest service station may become occupied for serving other requests, we consider the average travel time of the closest vehicles, which may be located at different service stations. Furthermore, this average time is multiplied with the demand, so zones with high demand will receive more weight in the optimisation process.

Problem Specification: The *service station location problem* has the following inputs:

- z is the number of zones in the service region;
- s is the number of service stations to be located within the zones;
- v is the number of vehicles hosted at each service station;
- c is the number of vehicles considered for the average travel time of the closest vehicles;
- $Demand[i]$ is the demand of zone i , with $i \in 1 \dots z$;

- $Time[i, j]$ is the travel time from zone i to zone j ; note that the matrix need not be symmetric (hence pay attention to get the indices right); the travel time within a zone is typically a small value, though not zero.

The optimisation decision consists in selecting exactly s out of the z zones in order to locate service stations in distinct zones. The objective is to minimise the sum over all the zones of the average travel time of the c closest vehicles of each zone, multiplied by the demand of the zone.

Data Format: The problem parameters in the AMPL data files in <https://user.it.uu.se/~pierref/courses/AD3/assignments/servStatLoc-data.zip> are below, for $z = 10$ zones, $s = 2$ service stations, $v = 2$ vehicles per service station, and $c = 3$ closest vehicles:

```
param z := 10;
param s := 2;
param v := 2;
param c := 3;
param Demand :=
  1  0.000803429155663251
  2  0.000951406002100867
  ...
  10 0.000597429377117032;
param Time :=
  1  1  0.0010
  1  2  1.6420
  ...
  1  10 4.0630
  2  1  1.6420
  ...
  10 10 0.0010;
```

where:

- the parameter **Demand**, indexed over the zones, gives the z demand values $Demand[i]$;
- the parameter **Time** has z^2 elements specifying the travel times $Time[i, j]$; for example, the travel time from zone $i = 1$ to zone $j = 10$ is 4.063 in the data above.

In an AMPL model, the following declarations at <https://user.it.uu.se/~pierref/courses/AD3/assignments/servStatLoc.mod> match up with the AMPL data files:

```
param z; # number of zones
param s; # number of service stations
param v; # number of vehicles per service station
param c; # number of closest vehicles for average
set Zones := 1..z;
param Demand {Zones} >= 0; # Demand[i] = demand of zone i
param Time {Zones,Zones} >= 0; # Time[i,j] = time from zone i to j
```

See <https://user.it.uu.se/~pierref/courses/AD3/resources.html> for free-of-charge access to the world-class commercial MIP solver Gurobi via AMPL.

Tasks: You *must* follow the *structure* and instructions of the demo report:¹

- a. Describe a model of the service station location problem as a mixed integer linear program: what are the variables, their meanings, their constraints, and the objective function? Do not worry about symmetry in the search space: MIP solvers automatically exploit symmetries. **Hint:** For each zone, the actually closest vehicles can be determined by the minimisation process without representing them in the model, so that it suffices to represent the number of vehicles of each zone that serve each zone.
- b. Implement the resulting model into `servStatLoc.mod` and upload it without explaining and including it in the report, but indicate there the MIP solver and hardware² you chose for your experiments in the next tasks. All the syntax you need is in our slides <https://user.it.uu.se/~pierref/courses/AD3/slides/MIP.pdf>. Four points will be deducted from your score if your model has a nonlinear objective function or nonlinear constraints, such as the quadratic constraints and logic constraints that the language allows. One (possibly additional) point will be deducted from your score if your uploaded model does not correspond to the model you describe for Task a.
- c. Solve the problem for $z = 10, s \in 2..4, v = 2, c = 3$ using data files `location-010-0s-2` in order to see the impact on the optimal objective value when parameter `s` increases, as one then has a higher budget for service stations and more vehicles overall. For your convenience: the optimal objective value for $s = 2$ is 0.008740338682.
- d. Solve the problem for $z = 20, s \in 2..6, v = 2, c = 3$ using data files `location-020-0s-2` in order to see the impact on the optimal objective value when parameter `s` grows beyond 4. For your convenience: the optimal objective value for $s = 2$ is 0.02324626135.
- e. Solve the problem for $z = 40, s = 5, v = 2, c = 3$ using data file `location-040-05-2`.
- f. Solve the problem for $z = 80$ and $c = 3$ using the data files `location-080-08-2` and `location-080-16-1` in order to see the impact on the optimal objective value when distributing 16 vehicles for $s = 8$ with $v = 2$ versus $s = 16$ with $v = 1$.
- g. Solve the problem for $z = 120, s = 10, v = 2, c = 3$ using data file `location-120-10-2`. If your model times out, then propose an algorithm for delivering a not necessarily optimal solution, such that the algorithm is expected to take reasonable running time: describe the steps of the algorithm, but you do not need to implement and run it.
- h. Solve the problem for $z = 250, s = 12, v = 3, c = 4$ using data file `location-250-12-3`. If your model times out (but not on Task g), then follow the timeout instructions of Task g.
- i. Express and justify the size of the search space of a totally brute-force search algorithm in terms of the problem parameters z, s, v , and c . For each instance mentioned above that your chosen MIP solver solved to proven optimality without timing out, state how many candidate solutions this brute-force search algorithm has to examine per second in order to match your reported runtime performance.

Use a timeout of at least 300 seconds per run and report the performance (runtime, objective value, and optimality gap) over a *single* run per instance, as the recommended solvers are

¹Solo teams (except PhD students) may omit the potential algorithm design parts of Task g or h as well as the entire Task i, but are encouraged to perform them nevertheless.

²For the NEOS server, it suffices to say so; else, under Linux, do `lscpu` to find the specification, and under macOS, you find it via “About This Mac” in the Apple menu.

deterministic by default; a precision of two decimal places suffices here for the runtime and optimality gap, but the objective value should be given in full precision.³


Recall that MIP solvers are **exact**: for a minimisation problem, the *optimality gap* is the relative difference between the current upper bound u (the objective value of the currently best solution) and current lower bound ℓ (the objective value of the currently best leaf node) on the objective function, that is the ratio $\frac{u-\ell}{\ell}$, when a MIP solver is stopped prematurely; if $\ell = u$ then the optimality gap is zero and the MIP solver actually proved the optimality of its currently best solution.

Problem 2: Stochastic Local Search (SLS) (60% weight)

The aim of solving this problem is to get hands-on experience with procedurally encoding a hard combinatorial optimisation problem into an SLS algorithm that can near-optimally if not optimally solve the problem, with potentially impressive performance.

The *investment design problem* is about finding a matrix of v rows and b columns of 0-1 integer values, such that each row sums up to r , with $v \geq 2$ and $b \geq r \geq 1$, and the largest dot product between all pairs of rows is minimised. Equivalently, one has to find v subsets of size r within a given set of b elements, such that the largest intersection of any two of the v sets has minimal size. An instance of the problem is parametrised by a triple $\langle v, b, r \rangle$.

For example, the following figure shows two $\langle 10, 8, 3 \rangle$ investment designs, where grey cells represent value 1 and white cells represent value 0:



In these two investment designs, there are dot products (or: intersection sizes) of 0 to 2, so their largest dot products are both 2: this is minimal, as there exists no $\langle 10, 8, 3 \rangle$ investment design where 1 is the largest dot product [1].

This is an abstract description of a problem that appears in finance (see <https://imdb.com/title/tt1596363>: *The Big Short*), where the rows are the baskets (also known as subpools or tranches) of an investment portfolio and the columns correspond to the credits the baskets can invest in, so that the baskets are of equal size but minimal overlap. In a typical investment design in finance, we have $4 \leq v \leq 25$ and $250 \leq b \leq 500$, with $r \approx 100$.

A lower bound on the number λ of shared elements of any pair among v subsets of size r drawn from a given set of b elements is given in [1]:

$$\text{lb}(\lambda) = \left\lceil \frac{\left\lceil \frac{rv}{b} \right\rceil^2 ((rv) \bmod b) + \left\lfloor \frac{rv}{b} \right\rfloor^2 (b - ((rv) \bmod b)) - rv}{v(v-1)} \right\rceil \quad (1)$$

For 20 of the following 21 instances, the lower bound on λ is known to be feasible:

³Use the AMPL command `option solver gurobi; option gurobi_options 'outlev=1';` before you run `solve` in order to turn on verbose printing, which includes the optimality gap.

v	b	r	$\text{lb}(\lambda)$	v	b	r	$\text{lb}(\lambda)$	v	b	r	$\text{lb}(\lambda)$
10	360	120	32	9	70	35	16	19	19	9	4
12	200	75	25	11	150	50	14	11	22	10	4
9	300	100	25	6	60	30	12	9	36	12	3
15	350	100	24	6	50	25	10	16	16	6	2
10	325	100	24	10	100	30	7	15	21	7	2
13	250	80	22	8	28	14	6	12	44	11	2
10	350	100	22	10	37	14	5	10	30	9	2

For the instance $\langle 15, 21, 7 \rangle$ in the table, the lower bound 2 is infeasible and a best solution has $\lambda = 3$, but you are *not* allowed to exploit that knowledge in your algorithm. For the instance $\langle 10, 8, 3 \rangle$ discussed above, the lower bound is 1, which is infeasible [1].

Tasks: You *must* follow the *structure* and instructions of the demo report. Note that performing Tasks a to c is best done in parallel:⁴

- a. **SLS Algorithm.** Design an SLS algorithm for solving the investment design problem, by performing the following problem-independent steps while reading the skeleton code of Task b and addressing each of them in the report. Start with a very simple algorithm and test it on small instances; improve it only if it is too slow and test it on larger instances, etc, until you are satisfied with the performance (see the end of Task c for our requirements):
 1. Representation. Describe how to represent the problem: what are the variables, their meanings, their constraints, and the objective function?
 2. Initial Assignment. Describe an algorithm for generating (fast) a randomised initial assignment. **Hint:** Satisfy some or all of the constraints in the initial assignment.
 3. Move. Describe one or more *moves* that go from an assignment to a neighbouring assignment by changing the values of a few variables. **Hint:** If you followed the previous hint, then preserve the satisfaction of the chosen constraints by every move: your SLS algorithm will then always be at an assignment satisfying all those constraints and can focus on trying to satisfy the remaining constraints and optimising the *objective value* (that is, the value of the objective function).
 4. Constraints. Describe for each constraint how its satisfaction is either algorithmically checkable efficiently or guaranteed to be preserved by the previous two design choices.
 5. Neighbourhood. Describe a neighbourhood based on the proposed moves. Derive a formula for computing the size of the neighbourhood in terms of the problem parameters. Discuss whether the neighbourhood makes the search space *connected*, in the sense that every *feasible assignment* (that is, every assignment satisfying all the constraints, whether optimal or not) is reachable from every initial assignment (you only need to sketch a proof if the search space is connected, and give a counterexample otherwise). Note that the neighbourhood should *not* be of size 1: otherwise you are describing a greedy algorithm. **Hint:** Do not over-engineer the neighbourhood.
 6. Cost Function. Describe a cost function, whose value is to be minimised during search. Note that the cost function need not be equal to the objective function, but the cost value should decrease when the objective value decreases. Also note

⁴Solo teams (except PhD students) may omit reporting the local-search parameter fine-tuning part of Task c (but should still show the performance on *one* configuration of the local-search parameters) as well as the entire Task d, but are encouraged to perform them nevertheless.

that one can switch during search between alternative cost functions. **Hint:** If two assignments have the same objective value but one of them is somehow better, then a good cost function gives a lower value to the better assignment. For example, imagine the two equally good $\langle 10, 8, 3 \rangle$ investment designs in the drawings at page 4 were not optimal: the cost function can be based on a tiebreaker expressing why the right design is closer to a better design than the left one.

7. Probing. Describe how a neighbouring assignment, as reachable by a move, can be *probed* efficiently: describe how the cost function can be evaluated efficiently and incrementally, and describe the data structures used to do so. Give, without proof, the time complexity of probing; ideally, it is (sub-)linear in the problem parameters.
8. Heuristic. Describe a heuristic for *exploring* (via probing) your neighbourhood of Step 5 and *selecting* a neighbouring assignment to *commit* to. State whether the neighbourhood is explored exhaustively and, if so, how you determine when it was exhausted. Explain how you ensure that the same neighbour is not probed twice during a given exploration. **Hint:** It can be beneficial to explore the neighbourhood in a random order.
9. Optimality. Describe how you use a bound on the objective value in order to terminate sometimes the search with proven optimality, as part of the heuristic.
10. Meta-Heuristic. Describe a meta-heuristic based on tabu search: explain how the tabu list is represented; choose (a formula for) its size; explain how fine-grained its content is; and describe how it can be looked up and maintained efficiently. Note that the tabu list is not necessarily an actual list, but rather a concept. Make sure that worsening moves are sometimes made.
11. Random Restarts. Describe how to detect or guess that a random restart should be made, as part of the meta-heuristic.
12. Optional Tweaks. Describe ideas that you used in order to improve your algorithm.

Most of your effort should be spent on steps 6, 7, and 10.

- b. **Implementation.** Implement — in either Java, using the skeleton code at <https://user.it.uu.se/~pierref/courses/AD3/assignments/invDes.zip>, or any other *high-performance* programming language for which a compiler or interpreter is available on the Linux computers of the IT department (see <https://user.it.uu.se/~pierref/courses/AD3/resources.html>) — the SLS algorithm designed in Task a and upload it without including it in the report, but give there its compilation and running instructions. Because speed is of the essence for SLS, we recommend against Python for example.

An executable called `InvDes` must read the problem parameters v , b , r as command-line arguments, say `InvDes 10 8 3` or `java InvDes 10 8 3`, and write to standard output a line with the space-separated values of v , b , r , the lower bound $\text{lb}(\lambda)$ on λ , and the achieved λ , followed by one line per row of a $v \times b$ matrix representing the solution, the 0-1 cell values being space-separated. For example, the $\langle 10, 8, 3 \rangle$ design on the left at page 4 is represented by <https://user.it.uu.se/~pierref/courses/AD3/assignments/invDes-10-8-3.txt>.

You *must* experimentally pipe the output of `InvDes` into the polynomial-time solution checker at <https://user.it.uu.se/~pierref/courses/AD3/assignments> (for Linux and macOS), which reads such a solution from standard input, in order to gain confidence in the correctness of your implementation, for example by `InvDes 10 8 3 | invDesChecker`.

- c. **Experiments.** Indicate the hardware you chose for your experiments.⁵ Show, using table(s), how you evaluated the performance of your SLS algorithm and fine-tuned it via *at least two* configurations of values for the local-search parameters, by making experiments on the 21 instances in the table above, proceeding by increasing value of $\text{lb}(\lambda)$; craft smaller instances if initially needed.

Use a timeout of at least 300 seconds per run and report the *median* (not: average) performance (runtime, steps, and achieved λ) over *at least 5* independent runs per instance, as an SLS algorithm *must* be randomised by definition; a precision of one decimal place suffices here.

It is important that you automate the running of the experiments via a script. It is recommended to define an optional command-line flag, say `-p`, for the executable `InvDes` so as also to output the runtime (in seconds) and the number of steps in the first line of the output and to suppress the output of the $v \times b$ matrix representing the solution. The sharing of such scripts is allowed and even encouraged.

The larger instances in the table above may be difficult for your SLS algorithm, but you are expected to get very close to all their optimal values of λ discussed above; a minimum requirement for score 5 is to be within one unit of the actual optimum.

- d. **Exact Algorithm.** Outline (in plain English or in high-level pseudocode, but without an implementation) an exact algorithm (performing brute-force search, if you want) for the investment design problem. Express the size of the search space of your exact algorithm in terms of the problem parameters v , b , and r . For each instance in the table above that your SLS algorithm solves to proven optimality before timing out, state how many candidate solutions your exact algorithm would have to examine per second in order to match the runtime performance of the seemingly best configuration of values for the local-search parameters, according to Task c. Comment on those numbers.

References

- [1] O. Sivertsson, P. Flener, and J. Pearson. A bound on the overlap of same-sized sets. *Annals of Combinatorics*, 12(3):347–352, October 2008. Available at <https://dx.doi.org/10.1007/s00026-008-0355-0>.

Submission Instructions

- Address *each* task of *each* problem.
- You *must* follow the *structure* (using, in order to accelerate the grading, the numbering and ordering of the tasks in this assignment statement) and instructions of the demo report at <https://user.it.uu.se/~pierre/courses/AD3/demoReport>, whether or not you use L^AT_EX. Write with the precision that you would expect from a textbook.
- *Thoroughly* proofread, spellcheck, and grammar-check the report, including the comments in *all* code. In case you are curious about technical writing: the *English Style Guide* of UU at <https://mp.uu.se/en/web/info/stod/kommunikation-riktlinjer/sprak/eng-skrivregler> and the technical-writing *Checklist & Style Manual* of the Optimisation group at <https://optimisation.research.it.uu.se/checkList.pdf> offer many

⁵Hint: See footnote 2.

pieces of advice; common errors in English usage are discussed at <https://brians.wsu.edu/common-errors>; in particular, common errors in English usage by native Swedish speakers are listed at <https://www.crisluengo.net/english-language>.

- Match *exactly* the uppercase, lowercase, and layout conventions of any filenames and I/O texts imposed by the tasks, as we will process submitted source code automatically. Do *not* rename any of the provided skeleton codes, for the same reason. However, do not worry when *Studium* appends a version number to the filenames when you make multiple submission attempts until the deadline.
- Remember that when submitting you implicitly certify (a) that your report and all its uploaded attachments were produced solely by your team, except where explicitly stated otherwise and clearly referenced, (b) that each teammate can individually explain any part starting from the moment of submitting your report, and (c) that your report and attachments are not freely accessible on a public repository.
- Submit (by only *one* of the teammates) via *Studium* (whose clock may differ from yours) by the given *hard* deadline three solution files: your report as a *single* file in *PDF* format (all other formats will be rejected) and two compressed folders with all source-code files required to run your experiments of each problem.

Grading Rules

For each problem: *If* the requested source code exists, *and* it runs *without* runtime errors on the Linux computers of the IT department under the compiler, interpreter, or solver you indicate, *and* it computes *correct* and (*near*-)*optimal* solutions to *some* of our tests in *reasonable* time on that hardware, *then* you get at least 1 point (read on), *otherwise* your final score is 0 points. Furthermore:

- *If* the code *passes most* of our tests *and* the report addresses *all* the tasks and subtasks, *then* your final score is 3 or 4 or 5 points, depending *also* on the quality of the report part for this problem; you are *not* invited to the grading session for this problem.
- *If* the code *fails many* of our tests *or* the report does *not* address all the tasks and subtasks, *then* your initial score is 1 or 2 points, depending *also* on the quality of the report part for this problem; you *might be* invited to the grading session for this problem, where you can try and increase your initial score by 1 point into your final score.

However, *if* the assistants figure out a minor fix that is needed to make your code run as per your and our instructions, *then*, instead of giving 0 points up front, the assistants may at their discretion deduct 1 point from the score thus earned.

Let s_i be your final score on Problem i , whose stated weight is w_i : your final score on this assignment is $\sum_i (w_i \cdot 2 \cdot s_i)$, rounded to the *nearest* (possibly previous) integer, if both $s_i > 0$.

Considering there are three help sessions for each assignment, you *must* earn at least 3 points (of 10) on each assignment until the end of its grading session, including at least 1 point (of 5) on each problem and at least 10 points (of 20) over both assignments, in order to pass the *Assignments* part (2 credits) of the course, if you attend the guest lecture from industry.