

GETTING LOST IN CANADA

How To



Step-by-step instructions

Table of Contents

How To: Awning	3
How To: Battery	4
How To: Climate Control	6
How to: Empty sewage	7
How to: Power management	8
How To: Use water	9

How To: Awning

The awning is fully automated, easy stuff. The hardest part is finding the location of the awning control panel, next to the Garmin unit. The awning is located on the right side of the Garmin panel.

■ You should always keep an eye on the awning during operation.

To extend

1. Look at the Awning control panel, located just to the right of the Garmin panel
2. Make sure the left toggle is set to ON
3. Press (no need to hold) extend on the right switch
4. The awning will now extend
5. When done, you may set the left toggle to off

To retract

1. Look at the Awning control panel, located just to the right of the Garmin panel
2. Make sure the left toggle is set to ON
3. Press (no need to hold) retract on the right switch
4. The awning will now retract
5. When done, you may set the left toggle to off

How To: Battery

The van has been upgraded with two SOK 12V206H batteries, giving it 412 Ah of available energy. Which? ☐ SK12V206H ☐ SK12V206PH ☐ SK12V206P

There are several variables/configuration depending on the conditions.

1. Shore power, typically 30A circuit
2. Generator (2.8 KW)
3. Ford Alternator
4. Solar panels (220 W)
5. Inverter (2,000 W)
6. The Truma panel, left of the garmin control panel
7. The Disconnect button, right of the garmin panel
8. The Solar button, right of the garmin panel

Where	Generator 1	Inverter	Solar	Disc.	Truma	Notes
Storage	No	Charge if Disc.	No	☐ On ☐ Off	Off	At Indoor storage Household power (15 A)
Camping Plugged	No	Charge	On	On	On	Shore power (30 A)
Camping Unplugged	A/R 2	A/R 3	On	On	On	No shore power
On the road	A/R	Charge if Disc.	☐ A/R ☐ On	☐ Follow ☐ Off	Off	Ford alternator
Overnight, at home	No	Charge if Disc.	☐ A/R ☐ On	☐ Follow ☐ On	Off	No shore power

1 Generator is used primarily to recharge the battery, may be needed for AC

2 A/R means As required/needed, to charge the battery

3 Inverter used for appliances requiring 120 VAC

For reference

1. All off, drain is still about 3/4 A
18 Ah/day
126 Ah/week
540 Ah/month
2. Disconnect on, everything else off, drain is still about TBD ____ A

3. Inverter cost is roughly $\min(1.0, \text{loadWatts} / 11)$
0 W = 1.0A
100 W = 9 A
1200 Watts = 110 A

How To: Climate Control

One time (mostly)

You will be working on the Truma control (set to external control) — see Truma panel, far left .

1. Select Truma touchscreen — tool icons
2. Find the ACC setting
3. Ensure the Truma touchscreen — ACC/Auto mode is set to ON. This will allow communication between the Truma panel and the Garmin panel.

Day-to-day operation

1. On the Garmin, right-hand side, select home
2. Click on the gear next words "Temperature control"
Garmin temperature select screen
3. Adjust to the desired temperature with the up and down arrows (upper left corner) Garmin climate panel
4. If there is no 120 VAC, and you need AC, the Truma panel will display "W 45 H", indicating AC is disabled.

How to: Empty sewage

Getting ready - Have on hand

1. The sewer hose & fittings
2. A fresh-water hose
3. A black-water hose
4. Disposable gloves
5. Hand sanitizer

At the station

1. Remove the sewer cap from the outlet.
2. Connect the sewer hose: one end to the van's outlet, the other secured into the dump station drain.
3. Open the black water valve first and let it fully drain. Draining black first keeps the worst waste moving through the hose while it's cleanest.
4. Close the black water valve once it stops flowing.
5. Open the gray water valve and let it fully drain — the gray water rinses out residual solids left behind by the black tank.
6. Close the gray water valve.
7. Flush the black tank using the factory flush port: connect a fresh-water hose to the port, open the black valve again, and run water until it runs clear, then close the valve.
8. Rinse the sewer hose with a dump station rinse hose (or your fresh-water hose) while it's still connected, to flush out residue.
9. Disconnect the hose starting from the tank end, letting any residual liquid drain into the dump station opening.
10. Rinse the outlet cap and hose fittings, then recap the sewer outlet.

Hooking at the campground

1. Under construction
2. Under construction

How to: Power management

Managing power

Every system you use in the van needs power. And, Unlike at your home, power is limited and must be managed. Some systems provide you with the power, some use said power. The trick is to match the two.

How To: Use water

1. First step using placeholder
2. Second step placeholder
3. Third step placeholder