
Livrable 4 - SAE12

Romain Yermolov

Table des matières

1	Configuration du switch	3
2	Configuration du routeur	5

1 Configuration du switch

```

— minicom -D /dev/ttyS0 -b 9600
— en
— conf t
— no ip domain-lookup
— vlan 10
  — name Admin
— vlan 20
  — name Personnel
— vlan 30
  — name Production
— vlan 40
  — name Video
— interface f0/5 : PC qui hébergera la VM apache VLAN10
  — switchport mode access
  — switchport access vlan 10
  — no shut
  — exit
— interface f0/4 : PC qui hébergera une VM client VLAN 20
  — switchport mode access
  — switchport access vlan 20
  — no shut
  — exit

```

S1#show vlan

VLAN	Name	Status	Ports
1	default	active	Fa0/1, Fa0/2, Fa0/3, Fa0/6 Fa0/7, Fa0/8, Fa0/9, Fa0/10 Fa0/11, Fa0/12, Fa0/13, Fa0/14 Fa0/15, Fa0/16, Fa0/17, Fa0/18 Fa0/19, Fa0/20, Fa0/21, Fa0/22 Fa0/23, Fa0/24, Gi0/1, Gi0/2
10	Admin	active	Fa0/5
20	Personnel	active	Fa0/4
30	Production	active	
40	Video	active	
1002	fddi- default	act/unsup	
1003	token-ring- default	act/unsup	
1004	fddinet- default	act/unsup	

2 Configuration du routeur