

The `apxproof` package

Pierre Senellart

`pierre@senellart.com`

<http://github.com/PierreSenellart/apxproof>

2022/10/14 v1.2.4-dev

Abstract

This package makes it easier to write articles where proofs and other material are deferred to the appendix. The appendix material is written in the \LaTeX code along with the main text which it naturally complements, and it is automatically deferred. The package can automatically send proofs to the appendix, can repeat in the appendix the theorem environments stated in the main text, can section the appendix automatically based on the sectioning of the main text, and supports a separate bibliography for the appendix material.

1 Usage

The `apxproof` package is intended to simplify the writing of articles where some of the content needs to be deferred to an appendix. This is in particular useful for the submission of scientific articles to conferences or journals that limit the number of pages in the main text but allow an extra appendix, where proofs of theorems and other material can be added.

1.1 Basics

To use `apxproof`, first load it in the header of your document:

```
\usepackage{apxproof}
```

On its own, this does not do anything and should not change the appearance of your document. To add an appendix with some material from your document, use the `toappendix` environment:

```
toappendix    \begin{toappendix}
               ...
               \end{toappendix}
```

The content will appear at the end of your document, in an automatically generated section that refers to the current section in the main text.

Example 1. *Throughout this documentation, all examples produce content deferred to the appendix, at the very end of this document.*

```
\begin{toappendix}
```

```
This content is in the appendix.
\end{toappendix}
```

When the content to put in appendix is an entire section, make sure that `\section` is the very first command that appears within the `toappendix` environment. It will disable the automatic production of a section heading.

1.2 Repeated Theorems and Proofs

In some scientific papers that include proofs, it is common to defer proofs to the appendix. This can easily be achieved using the `appendixproof` environment:

```
appendixproof    \begin{appendixproof}
                  ...
                  \end{appendixproof}
```

This behaves like the `toappendix` environment, except that a proof environment is generated.

Example 2. *We now send a proof to the appendix:*

```
\begin{appendixproof}
This proof is in the appendix.
\end{appendixproof}
```

When deferring proofs to the appendix, an annoying problem is that the statement of the theorem remains in the main text; it is hard to read a proof that is far away from the statement it proves. `apxproof` solves this issue by allowing statements of theorems to be *repeated*: once in the main text, and once in the appendix before the proof of the statement. To use this feature, you can define a new *repeated theorem* environment using the `\newtheoremrep` command:

```
\newtheoremrep    \newtheoremrep{<name>}[<counter>]{<title>}[<countersec>]
```

Usage is exactly the same as that of AMS L^AT_EX's `\newtheorem` macro:

- `<name>` (e.g., `theorem`) is the name of an environment that is created for this kind of theorem;
- `<counter>` (e.g., `definition`) is an optional counter describing from which kind of environment the numbering of these environments should be inherited;
- `<title>` (e.g., `Theorem`) is the title that will be used to display this theorem environment;
- `<countersec>` (e.g., `section`) is an optional counter of a sectioning command indicating that counters for this theorem should be prefixed by this counter (and reset at each occurrence of the sectioning command).

`<counter>` and `<countersec>` should not be used together. What differs from `\newtheorem` is that, when the following is written:

```
\newtheoremrep{foobar}{Foobar}
```

then *two* environments are defined: the `foobar` environment, which behaves as if `\newtheorem` had been used, and the `foobarrep` environment, which results in the statement of this environment being repeated in the appendix.

`proof` One interesting feature of `apxproof` is that in most situations, there is no need to use the `appendixproof` environment. Indeed, the `proof` environment is redefined by `apxproof` to automatically put the proof either in the main text (if it follows a regular theorem) or in the appendix (if it follows a repeated theorem).

Example 3. Assume we have first defined a repeated theorem environment `foobar` as above. We can now use this theorem environment, first for a regular theorem in the main text, then for a theorem repeated in the main text and in the appendix:

```
\begin{foobar}
This foobar is a regular one, in the main text.
\end{foobar}
\begin{proof}
This is the proof of the regular foobar.
\end{proof}
```

We obtain:

Foobar 1. *This foobar is a regular one, in the main text.*

Proof. This is the proof of the regular foobar. □

Now, if we use a repeated theorem:

```
\begin{foobarrep}
This foobar is repeated in the appendix.
\end{foobarrep}
\begin{proof}
This is the proof of the repeated foobar.
\end{proof}
```

We now obtain:

Foobar 2. *This foobar is repeated in the appendix.*

Note that, since `hyperref` is loaded, there are hyperlinks created between the statements of the theorems in the main text and in the appendix.

When the proof is deferred to the appendix, it is common practice to add a proof sketch in the main text. `apxproof` defines a simple `proofsketch` environment for this purpose:

```
proofsketch    \begin{proofsketch}
                ...
                \end{proofsketch}
```

`inlineproof` The proof sketch is typeset similarly to a proof, but is always in the main text. Similarly, an `inlineproof` environment is provided so as to be able to have both a proof in the appendix (using the regular `proof` environment, or alternatively the `appendixproof` environment) and a different proof in the main text (using the `inlineproof` environment).

Example 4. *Here are simple examples of proof sketches and inline proofs:*

```
\begin{proofsketch}
This is a proof sketch.
\end{proofsketch}
```

Proof sketch. This is a proof sketch. □

```
\begin{inlineproof}
This is an inline proof.
\end{inlineproof}
```

Proof. This is an inline proof. □

1.3 Bibliography

By default, `apxproof` automatically adds a bibliography in the appendix with only the references cited in the appendix material. This allows for a clean separation of references used solely in the main text, and those used in the appendix.

Example 5. *Assume we have citations both in the main text and in the appendix.*

```
This is a citation in the main text~\cite{lamport86}.
\begin{toappendix}
This is a citation in the appendix~\cite{proofsAreHard}.
\end{toappendix}
```

This is a citation in the main text [1].

The bibliography in the appendix can use a different style and heading than the bibliography in the main text (and, by default, it does). See Section 1.5 for how to configure the appearance of that bibliography.

option
bibliography In order to use a single appendix for the main text and the bibliography, one can specify the value `common` to the `bibliography` option when loading the package. (By default this option is set to `separate`.)

1.4 Mode

option
appendix An optional $\langle mode \rangle$ can be specified when loading the package:

```
\usepackage[appendix= $\langle mode \rangle$ ]{apxproof}
```

$\langle mode \rangle$ can take one of the following three values:

append This is the default. Appendix material gathered by `apxproof` is appended to the main text.

inline In this mode, `apxproof` simply inlines the content along with the main text.

strip This mode functions similarly to `append` except that the appendix is not appended at the end of the document. All appendix material is therefore removed.

1.5 Customization

`apxproof` provides a few macros that can be redefined (using `\renewcommand`) to customize the appearance of the appendix:

<code>\mainbodyrepeatedtheorem</code>	<code>\mainbodyrepeatedtheorem</code> is a macro that is executed at the beginning of the body of every repeated theorem. This can be used to notify the reader that the theorem is repeated in appendix in some way, e.g., with a margin note.
<code>\appendixsectionformat</code>	<code>\appendixsectionformat{<number>}{<title>}</code> is a macro that indicates how to format the section titles in the Appendix, given the number and title of the section in the main text. By default, they appear as “Proofs for Section <i><number></i> (<i><title></i>)”.
<code>\appendixrefname</code>	<code>\appendixrefname</code> contains the heading that is displayed before the bibliography. By default, this is “References for the Appendix”. (Note that this command is also defined and used by the <code>memoir</code> document class.)
<code>\appendixbibliographystyle</code>	<code>\appendixbibliographystyle</code> contains the <code>.bst</code> bibliography style that is used in the bibliography in appendix. By default, this is <code>alpha</code> .
<code>\appendixbibliographyprelim</code>	<code>\appendixbibliographyprelim</code> contains arbitrary code that is executed just before the production of the bibliography in appendix, which can be used to configure the way it is displayed.
<code>\appendixprelim</code>	<code>\appendixprelim</code> contains arbitrary code that is executed just before the production of the appendix, which can be used to configure the way it is displayed. By default, this command contains <code>\clearpage\onecolumn</code> (the appendix is typeset on a new page in single-column mode) but redefining this option allows changing this behavior.
<i>option</i> <code>repeqn</code>	Another customization capability concerns <i>numbered equations</i> that are present within repeated theorems. An optional <code>repeqn</code> option can be specified when loading the package, which controls whether equation numbers should be as in the main text (by setting this option to <code>same</code> , the default) or independently numbered (by setting this option to <code>independent</code>). In the latter case, whenever a referenceable counter is set with <code>\label{<counter>}</code> , <code>\ref{<counter>}</code> references the counter in the main text, while <code>\ref{<counter>-apx}</code> references the counter in the appendix (except in <code>inline</code> mode, where both have the same effect).
<i>option</i> <code>forwardlinking</code>	Another customization option concerns hyperlinking. Usually, when <code>hyperref</code> is loaded, <code>foobarrep</code> environments in the main text have their number link to their repetition in the appendix. To suppress this behavior and have <code>foobarrep</code> environments treated as if <code>hyperref</code> were not loaded, one can specify the value <code>no</code> to the <code>forwardlinking</code> option when loading the package. (By default this option is set to <code>yes</code> .)

1.6 Advanced Features

We now describe a few advanced macros and environments, the usage of which is limited to special cases:

<code>nestedproof</code>	<code>nestedproof</code> is an environment that can be used within a <code>proof</code> environment deferred in the appendix; this is required because, for technical reasons, no <code>proof</code> environment can be nested within a deferred <code>proof</code> environment.
--------------------------	--

<code>\noproofinappendix</code>	<code>\noproofinappendix</code> can be used inside repeated theorems that are not followed by a <code>proof</code> or <code>appendixproof</code> environment; the point is to ensure that a further <code>proof</code> environment cannot be mistakenly understood as a proof of the repeated theorem. It should not be needed in most situations as <code>apxproof</code> tries figuring out when a proof follows a repeated theorem automatically, but may occasionally be needed in complex scenarios.
<code>\nosectionappendix</code>	<code>\nosectionappendix</code> is to be used inside a section that <i>does</i> contain appendix material, but for which a section in the appendix should not be created. This should be rarely needed. When this command is present, appendix material is appended to the end of the previously created section.

2 Supported Document Classes

Because `apxproof` modifies sectioning commands, bibliographies, and proofs, it may not work straight away with arbitrary document classes. It has currently been tested with and is supported for the following document classes:

- L^AT_EX standard document classes (e.g., `article.cls`)
- KOMA-Script (e.g., `scrartcl.cls`, `scrbook.cls`)
- `memoir.cls`
- ACM SIG Proceedings (e.g., `sig-alternate.cls`, `acmart.cls`)
- Springer's Lecture Notes in Computer Science (e.g., `llncls.cls`)
- Schloß Dagstuhl's Leibniz International Proceedings in Informatics (e.g., `lipics.cls`, `lipcs-v2016.cls`)

Other classes may work out of the box. Adding support for specific classes is possible and can be requested from the author of this package.

3 Known Issues and Limitations

We report here some issues we are currently aware of:

- When using `hyperref`, the appendix in the bibliography is not hyperlinked. This is to avoid possible issues with multiply defined bibliography entries.
- `appendixproof`, `proof`, `toappendix` environments cannot be nested. This is a limitation of the `fancyvrb` package that `apxproof` relies on. Note the existence of the `nestedproof` environment for nested proofs.
- `apxproof` poorly interacts with SyncT_EX: identifying which source line has produced which box does not work for appendix content managed by `apxproof` or repeated theorems. No obvious fix is known, though this issue will be investigated in the long term.
- Unless the `bibliography` option is set to `common`, the `bibunits` package is used to generate a second bibliography. This means any package, such as `biblatex`, that is incompatible with `bibunits` will not be compatible with `apxproof` unless `bibliography` is set to `common`.

Issues not listed here should be reported to the author.

4 License

Copyright © 2016–2024 by Pierre Senellart.

This work may be distributed and/or modified under the conditions of the L^AT_EX Project Public License, either version 1.3 of this license or (at your option) any later version. The latest version of this license is in <http://www.latex-project.org/lppl.txt> and version 1.3 or later is part of all distributions of L^AT_EX version 2005/12/01 or later.

5 Contact

- <https://github.com/PierreSenellart/apxproof>
- Pierre Senellart <pierre@senellart.com>

Bug reports and feature requests should preferably be submitted through the *Issues* feature of GitHub.

6 Acknowledgments

Thanks to Antoine Amarilli for feedback and proofreading. Thanks to K. D. Bauer for the implementation of the forward-linking mechanism, and for various bugfixes. Thanks to Leonid Kostrykin for an initial implementation of the `forwardlinking` option.

7 Implementation

We now describe the entire code of the package, in a literate programming fashion. Throughout the package, we use the `axp@` prefix to identify local macros and environment names, which are not meant to be used by the final user.

7.1 Dependencies

We first load a few package dependencies:

- `environ` to easily define the repeated theorem environments.

```
1 \RequirePackage{environ}
```

- `etoolbox` to define simple toggles.

```
2 \RequirePackage{etoolbox}
```

- `fancyvrb` for the bulk of the work of exporting appendix material in an auxiliary file.

```
3 \RequirePackage{fancyvrb}
```

- `ifthen` for easier comparison of character strings.

```
4 \RequirePackage{ifthen}
```

- `kvoptions` to manage options passed to the package.

```
5 \RequirePackage{kvoptions}
```

- `catchfile` to be able to check the content of files `\input` within appendix content.

```
6 \RequirePackage{catchfile}
```

- `amsthm` for its `\newtheorem` macro. Some document classes (e.g., `lipics`) preload `amsthm`: this is fine, `\RequirePackage{amsthm}` will simply have no effect. On the other hand, some other document classes (e.g., `llncs` or `sig-alternate`) define a `proof` environment that conflicts with `amsthm`, so we have to undefine this environment before loading `amsthm`. In that case, we reestablish the existing proof environments, in case they had been customized (e.g., `sig-alternate`)

```
7 \@ifpackageloaded{amsthm}{
8   }{
9     \let\apx@oldamsthmproof\proof
10    \let\apx@oldamsthmendproof\endproof
11    \let\proof\undefined
12    \let\endproof\undefined
13  }
14  \RequirePackage{amsthm}
15  \ifdefined\apx@oldamsthmproof
16    \let\proof\apx@oldamsthmproof
17    \let\endproof\apx@oldamsthmendproof
18  \fi
```

7.2 Option Processing

Many names throughout the package use an atrobase (`@`) to avoid name conflict with user-defined names. To simplify the compilation of the documentation, we simply make it a regular character in all the rest.

```
19 \makeatletter
```

We setup the processing of options using `keyval` facilities.

```
20 \SetupKeyvalOptions{
21   family=axp,
22   prefix=axp@
23 }
```

We declare the following options:

- `appendix`, with a default value of `append` (other possible values: `strip`, `inline`);
- `bibliography`, with a default value of `separate` (other possible value: `common`);
- `repeqn`, with a default value of `same` (other possible value: `independent`).

```
\axp@appendix
```

```
24 \DeclareStringOption[append]{appendix}
```


\axp@bibliography

```
25 \DeclareStringOption[separate]{bibliography}
```

\axp@repeqn

```
26 \DeclareStringOption[same]{repeqn}
```

\axp@forwardlinking

```
27 \DeclareStringOption[yes]{forwardlinking}
```

```
28 \ProcessLocalKeyvalOptions*
```

We check that the value of the options are valid, and add a message to the compilation log.

```
29 \ifthenelse{\equal{\axp@appendix}{append}}{
30   \message{apxproof: Appendix material appended to the document}
31 }{\ifthenelse{\equal{\axp@appendix}{strip}}{
32   \message{apxproof: Appendix material stripped}
33 }{\ifthenelse{\equal{\axp@appendix}{inline}}{
34   \message{apxproof: Appendix material inlined within the document}
35 }{
36   \errmessage{Error: unsupported option appendix=\axp@appendix\ for
37   package apxproof}
38 }}}
39 \ifthenelse{\equal{\axp@bibliography}{separate}}{
```

The external bibunits package is used to add a second bibliography for the appendix material.

```
40   \RequirePackage{bibunits}
41   \message{apxproof: Separate bibliography for appendix material}
42 }{\ifthenelse{\equal{\axp@bibliography}{common}}{
43   \message{apxproof: Common bibliography for appendix and main text}
44 }{
45   \errmessage{Error: unsupported option bibliography=\axp@bibliography\ for
46   package apxproof}
47 }}
48 \ifthenelse{\equal{\axp@repeqn}{same}}{
49   \message{apxproof: Repeated equations keep the same numbering}
50 }{\ifthenelse{\equal{\axp@repeqn}{independent}}{
51   \message{apxproof: Repeated equations are independently numbered}
52 }{
53   \errmessage{Error: unsupported option repeqn=\axp@repeqn\ for
54   package apxproof}
55 }}
```

\axp@forward@suppress

```
56 \newbool{axp@forward@suppress}
57 \ifthenelse{\equal{\axp@forwardlinking}{yes}}{
58 }{\ifthenelse{\equal{\axp@forwardlinking}{no}}{
59   \message{apxproof: Disable forward linking}
60   \global\booltrue{axp@forward@suppress}%
61 }{
62   \errmessage{Error: unsupported option forwardlinking=\axp@repeqn\ for
63   package apxproof}
64 }}
```

7.3 Macros Common to All Compilation Modes

`\axp@newtheoremrep@definetheorem` Common to all compilation modes, we define `\axp@newtheoremrep@definetheorem`. When called with first argument `foobar`, we first undefine the existing `foobar` environment (and its counter) if it has already been defined (e.g., by the document class), then invoke `\axp@newtheorem` for the regular version of the theorem `foobar`, saving and restoring any existing theorem counter unless the `\newtheoremdep` redefines the base counter.

```

65 \def\axp@newtheoremrep@definetheorem#1#2#3#4{%
66   \expandafter\let\csname #1\endcsname\undefined
67   \ifcsname c@#1\endcsname
68     \expandafter\expandafter\expandafter\let\expandafter\expandafter
69       \csname c@axp@#1\endcsname\csname c@#1\endcsname
70     \expandafter\let\csname c@#1\endcsname\undefined
71   \fi
72   \axp@newtheorem{#1}{#2}{#3}{#4}%
73   \ifcsname c@axp@#1\endcsname
74     \ifx\relax#2\relax
75       \expandafter\expandafter\expandafter\let\expandafter\expandafter
76         \csname c@#1\endcsname\csname c@axp@#1\endcsname
77     \else
78       \fi
79   \fi
80 }
```

`\axp@newtheorem` We introduce an intermediate `\axp@newtheorem` command to define a new theorem, differently depending on whether there is a section counter or not. This will be useful, in particular to allow changing this definition depending on the document class. This command uses two intermediary commands, `\@axp@newtheorem` and `\@@axp@newtheorem`, for the non-starred and starred versions.

```

81 \def\axp@newtheorem{\ifstar\@axp@newtheorem\@axp@newtheorem}
82 \def\@axp@newtheorem#1#2#3#4{%
83   \ifx\relax#4\relax
84     \newtheorem{#1}[#2]{#3}%
85   \else
86     \newtheorem{#1}{#3}[#4]%
87   \fi
88 }
89 \def\@@axp@newtheorem#1#2{%
90   \newtheorem*{#1}{#2}%
91 }
```

`\newtheoremrep` We define the high-level `\newtheoremrep` to have the same syntax as `amsthm`'s `\newtheorem`. For this purpose, we need a little trick to deal with the second and fourth optional arguments, which is what `\@oparg` and `\axp@newtheoremreptmp` are used for. `\axp@newtheoremrep` is defined differently depending on the compilation mode.

```

92 \newcommand\newtheoremrep[1]{%
93   \@oparg{\axp@newtheoremreptmp{#1}}[]%
94 }
95 \def\axp@newtheoremreptmp#1[#2]#3{%
96   \@oparg{\axp@newtheoremrep{#1}[#2]{#3}}[]%
97 }
```

`proofsketch` Simple `proofsketch` environment.

```
98 \newenvironment{proofsketch}{\begin{axp@oldproof}[Proof sketch]}\end{axp@oldproof}}
```

`\mainbodyrepeatedtheorem` We provide sensible defaults for these user-customizable macros. Even though they are not all useful in all modes, we define them for all modes so that a `\appendixrefname` `\renewcommand` works in all cases.

```
\appendixbibliographystyle \renewcommand{\mainbodyrepeatedtheorem}{}
\appendixbibliographyprelim 99 \newcommand{\mainbodyrepeatedtheorem}{}
\appendixprelim 100 \providecommand{\appendixrefname}{References for the Appendix}
\appendixsectionformat 101 \newcommand{\appendixbibliographystyle}{alpha}
102 \newcommand{\appendixbibliographyprelim}{}
103 \newcommand{\appendixprelim}{\clearpage\onecolumn}
104 \newcommand{\appendixsectionformat}[2]{Proofs for Section~#1\ (#2)}
```

`axp@oldproof` We save the definition of the existing proof environment.

```
105 \let\axp@oldproof\proof
106 \let\endaxp@oldproof\endproof
```

We define a utility macro that will be used to properly set the `\label` command (and its `amsmath` counterpart, `\label@in@display`) for equations within repeated theorems, depending on the compilation mode.

```
\axp@redefinelabels
107 \newcommand{\axp@redefinelabels}{%
108 \providecommand\label@in@display{}%
109 \ifthenelse{\equal{\axp@appendix}{inline}}{%
110 \let\axp@oldlabel\label
111 \let\axp@oldlabel@in@display\label@in@display
112 \renewcommand\label[1]{%
113 \axp@oldlabel{##1}%
114 \axp@oldlabel{##1-apx}%
115 }%
116 \renewcommand\label@in@display[1]{%
117 \axp@oldlabel@in@display{##1}%
118 \axp@oldlabel{##1-apx}%
119 }%
120 }{%
121 \let\axp@oldlabel\label
122 \let\axp@oldlabel@in@display\label@in@display
123 \renewcommand\label[1]{\axp@oldlabel{##1-apx}}%
124 \renewcommand\label@in@display[1]{\axp@oldlabel@in@display{##1-apx}}%
125 }%
126 }
```

7.3.1 Class-Specific Behavior

Finally, some class-specific behavior common to all compilation modes.

llncs and other Springer document classes

```
127 \ifdefined\spnewtheorem
```

`\axp@newtheorem` It is necessary to use `\spnewtheorem` instead of `\newtheorem` in Springer document classes to obtain standard formatting.

```

128 \def\@axp@newtheorem#1#2#3#4{%
129   \ifx\relax#4\relax
130     \ifx\relax#2\relax
131       \spnewtheorem{#1}{#3}{\bfseries}{\itshape}%
132     \else
133       \spnewtheorem{#1}[#2]{#3}{\bfseries}{\itshape}%
134     \fi
135   \else
136     \spnewtheorem{#1}{#3}[#4]{\bfseries}{\itshape}%
137   \fi
138 }
139 \def\@axp@newtheorem#1#2{%
140   \spnewtheorem*{#1}{#2}{\upshape\bfseries}{\itshape}%
141 }

```

proofsketch We redefine the `proofsketch` environment, which is used differently in the base class.

```
142 \renewenvironment{proofsketch}{\begin{axp@oldproof}[sketch]}\end{axp@oldproof}}
```

We have to redefine the macro `\@thmcountersep` for proper sectioned counters.

```

143 \def\@thmcountersep{.}
144 \fi

```

7.4 Inline Compilation Mode

```
145 \ifthenelse{\equal{\axp@appendix}{inline}}{
```

\axp@newtheoremrep In inline mode, `\axp@newtheoremrep` uses `\axp@newtheoremrep@definetheorem` to define the regular theorem environment and creates a repeated theorem environment that behaves exactly as the regular theorem environment, while calling `\axp@redefinelabels` to make sure that `-axp` variants of equation counters are defined.

```

146 \def\axp@newtheoremrep#1[#2]#3[#4]{%
147   \axp@newtheoremrep@definetheorem{#1}{#2}{#3}{#4}%
148   \NewEnviron{#1rep}[1][]{%
149     \ifx\relax#1\relax
150       \begin{#1}\axp@redefinelabels\BODY\end{#1}%
151     \else
152       \begin{#1}[##1]\axp@redefinelabels\BODY\end{#1}%
153     \fi
154   }
155 }

```

inlineproof In inline mode, these environments behave like the regular `proof` environment.

```

nestedproof 156 \let\inlineproof\proof
appendixproof 157 \let\endinlineproof\endproof
158 \let\nestedproof\proof
159 \let\endnestedproof\endproof
160 \let\appendixproof\proof
161 \let\endappendixproof\endproof

```

toappendix In inline mode, this environment and these macros are no-ops.

```

\noproofinappendix 162 \newenvironment{toappendix}{}{}
\nosectionappendix

```

```

163 \let\noproofinappendix\relax
164 \let\nosectionappendix\relax
165 }

```

7.5 Append or Strip Compilation Modes

```
166 {
```

We now deal with the case where `apxproof` really does something useful: either append the appendix material to the document, or strip it entirely.

7.5.1 Auxiliary File for the Appendix

`\axp@proofsfile` We open a new auxiliary file, with extension `.axp`, where the appendix material will be dumped.

```

167 \AtBeginDocument{
168   \newwrite\axp@proofsfile
169   \immediate\openout\axp@proofsfile=\jobname.axp
170 }

```

`\proof` At the beginning of this file, we make `@` a regular character (since it will be used in several places for internal names) and reestablish the original definition of the `\section` environment and the `\section` macro.

```

171 \AtBeginDocument{
172   \immediate\write\axp@proofsfile{%
173     \noexpand\makeatletter
174     \noexpand\let\noexpand\proof\noexpand\axp@oldproof
175     \noexpand\let\noexpand\endproof\noexpand\endaxp@oldproof
176     \noexpand\let\noexpand\claimproof\noexpand\axp@oldclaimproof
177     \noexpand\let\noexpand\endclaimproof\noexpand\endaxp@oldclaimproof
178     \noexpand\let\noexpand\section\noexpand\axp@oldsection
179   }
180 }

```

`\axp@unactivateeightbit` We need an auxiliary macro to disable active characters that have the high bit set when writing to the `.axp` file. See <https://tex.stackexchange.com/a/145361/166858>

```

181 \def\axp@unactivateeightbit{%
182   \count@=128%
183   \loop
184     \catcode\count@=12%
185     \ifnum\count@<255%
186       \advance\count@\@ne
187   \repeat}

```

`axp@VerbatimOut` Using the functionalities of the `fancyvrb` package, we define a custom verbatim environment `axp@VerbatimOut` that writes every line to the `\axp@proofsfile`.
`\FVB@axp@VerbatimOut`
`\FVE@axp@VerbatimOut` We also use the previous macro to disable active characters with the eighth bit set, and we make sure the catcode of `@` is reset for every verbatim environment, in case it is used by the user (e.g., as in the `xypic` package). Finally, as an additional precaution, we reset `\FV@CatCodesHook` that is for example set by the `commandchars` or `commentchar` option of `\fvset`.

```

188 \DefineVerbatimEnvironment{axp@VerbatimOut}{axp@VerbatimOut}{%
189 \def\FVB@axp@VerbatimOut{%
190 \@bsphack
191 \begingroup
192 \axp@unactivateeightbit
193 \FV@DefineWhiteSpace
194 \def\FV@Space{\space}%
195 \FV@DefineTabOut
196 \def\FV@ProcessLine{\immediate\write\axp@proofsfile}%
197 \let\FV@FontScanPrep\relax
198 \let\@noligs\relax
199 \def\FV@CatCodesHook{}%
200 \FV@Scan}
201 \def\FVE@axp@VerbatimOut{%
202 \immediate\write\axp@proofsfile{\noexpand\makeatletter}%
203 \endgroup\@esphack}

```

toappendix The entire content of this environment is put in appendix, starting a new appendix section beforehand if needed.

```

204 \newenvironment{toappendix}
205 {\axp@writesection\axp@VerbatimOut}
206 {\endaxp@VerbatimOut}

```

7.5.2 Definition of New Theorems

axp@seenrepththeorem Used to indicate whether a repeated theorem was just typeset, without its proof.

```

207 \newtoggle{axp@seenrepththeorem}

```

axp@rpcounter Sequentially incremented for every repeated theorem, used to create labels.

```

208 \newcounter{axp@rpcounter}

```

axp@equation Used to save the value of the equation counter, when **repeqn** is set to **same**.

```

axp@equationx 209 \newcounter{axp@equation}
210 \newcounter{axp@equationx}

```

axp@newtheoremrep With first argument **foobar**, we use **\axp@newtheoremrep@definetheorem** to define the regular version of the theorem **foobar**. We then patch **\begin{foobar}** so as not to expect a proof in the appendix and define an internal theorem **axp@foobarrp** that will be used in the appendix to restate the existing theorem.

```

211 \def\axp@newtheoremrep#1[#2]#3[#4]{%
212 \axp@newtheoremrep@definetheorem{#1}{#2}{#3}{#4}%
213 \expandafter\pretocmd\csname #1\endcsname{\noproofinappendix}{-}{-}%
214 \axp@newtheorem*\axp@#1rp}{#3}%
215 \axp@forward@setup{#1}{#2}{#3}{#4}%

```

We then define a **foobarrp** environment that increments the **axp@rpcounter** and typeset the regular **foobar** theorem with a label derived from the counter, along with a possible custom command to identify repeated theorems. We distinguish the case when the theorem argument has a note and when it does not. We save the equation counter before typesetting the theorem environment, to reset it to the same value in the repeated environment when **repeqn** is set to **same**.

```

216 \NewEnviron{#1rep}[1][ ]{%
217 \ifthenelse{\equal{\axp@repeqn}{same}}{%

```

```

218      \setcounter{axp@equation}{\value{equation}}%
219    }{}%
220    \addtocounter{axp@rpcounter}{1}%
221    \ifx\relax##1\relax
222      \axp@with@forward{#1}{\begin{#1}}\label{axp@r\roman{axp@rpcounter}}}%
223    \else
224      \axp@with@forward{#1}{\begin{#1}[\##1]}\label{axp@r\roman{axp@rpcounter}}}%
225    \fi
226    \mainbodyrepeatedtheorem
227    \BODY\end{#1}%

```

```

228 \global\toggletrue{axp@seenreptheorem}%
229 \global\expandafter\let\curname rplet\roman{axp@rpcounter}%
230 \endcsname
231 \BODY

```

```

232 \exp@writesection%
233 \immediate\write\exp@proofsfile{\noexpand\makeatletter}%
234 \ifthenelse{\equal{\exp@repeqn}{same}}{%
235   \immediate\write\exp@proofsfile{%
236     \noexpand\setcounter{exp@equationx}{\value{equation}}}%
237   \noexpand\setcounter{equation}{\theexp@equation}%
238   }%
239 }{%
240 \ifbool{exp@forward@suppress}{%
241   \global\def\exp@refstar{\ref*}
242 }{%
243   \global\def\exp@refstar{\ref}
244 }
245 \immediate\write\exp@proofsfile{%
246   \ifdefined\theopargself
247     \noexpand\theopargself
248   \else
249     \noexpand\pretocmd{\noexpand\@begintheorem}{%
250       \noexpand\patchcmd{\noexpand\thmhead}{\noexpand\@acmplainnotefont}{-}{-}%
251       \noexpand\patchcmd{\noexpand\thmhead}{\noexpand\the\noexpand\thm@notefont}{-}{-}%
252       \noexpand\patchcmd{\noexpand\thmhead}{({}{-})}{-}%
253       \noexpand\patchcmd{\noexpand\thmhead}{-}{-}{-}%
254     }{}{}
255   \fi
256   \noexpand\begin{exp@#1rp}

```

```

257      [%
258      \noexpand\axp@refstar{axp@r\roman{axp@rpcounter}}}%
259      \@ifnotempty{##1}{-%
260      \ifdefined\theopargself
261      \else
262      \ifdefined\@acmplainnotefont
263      \noexpand\@acmplainnotefont
264      \else
265      \noexpand\ifdefined\noexpand\thm@notefont
266      \noexpand\the\noexpand\thm@notefont
267      \noexpand\fi
268      \fi
269      \fi
270      {} (\unexpanded{##1})}%
271      ]%
272      ]%
273      \noexpand\axp@forward@target{axp@fw@r\roman{axp@rpcounter}}}%
274      \noexpand\axp@redefinlabels
275      \expandafter\noexpand\csname rplet\roman{axp@rpcounter}}%
276      \endcsname
277      \noexpand\end{axp@#1rp}
278      }%
279      \ifthenelse{\equal{axp@repeqn}{same}}{%
280      \immediate\write\axp@proofsfile{%
281      \noexpand\setcounter{equation}{\value{axp@equationx}}}%
282      }%
283      }{}%
284      }%
285      }

```

7.5.3 Forward-Linking Mechanism

When `hyperref` is loaded, `foobarrep` environments in the main text have their number link to their repetition in the appendix.

`\axp@with@forward` In order to make the number of the `foobarrep` theorem a link to its repeated version, we temporarily redefine the `\thefoobar` command, or, if we inherited the counter from a `bazbar` environment, the `\thebazbar` command. This seems to be the only robust way, to make the number a `\hyperlink`, without adding extensive dependence on internals of `amsthm`, the builtin `\newtheorem` and possibly document-class specific definitions.

In order to allow users to redefine `\thefoobar` without breaking this feature, we redefine `\thefoobar` only for the duration of the `\begin{foobar}` form, resetting it to the old value as soon as possible.

Redefining `\thefoobar` has the side effect of changing `\newlabel` entries in the `.aux` file, so we need to be able to disable addition of the hyperlink, which is why we use an intermediate `\axp@forward@link{<target>}{<text>}` macro. We also redefine `\theHfoobar` which is used by `hyperref` but not defined if `hyperref` was loaded after `\newtheoremrep` was used. and `\protect` it to output it verbatim into the `.aux` file.

These hyperlinks are of course disabled in the `strip` compilation mode.

```

286      \newcommand{\axp@with@forward}[2]{%

```



```

287 \ifthenelse{\equal{\axp@appendix}{strip}}{#2}{
288 \global\booltrue{axp@forward}}%
289 \ifcsundef{axp@old@the\csname axp@cn@#1\endcsname}{%
290 \csletcs{axp@old@the\csname axp@cn@#1\endcsname}{the\csname axp@cn@#1\endcsname}%
291 \csletcs{theH\csname axp@cn@#1\endcsname}{the\csname axp@cn@#1\endcsname}%
292 \csdef{the\csname axp@cn@#1\endcsname}{%
293 \protect\axp@forward@link{axp@fw@r\roman{axp@rpcounter}}}%
294 {\csname axp@old@the\csname axp@cn@#1\endcsname\endcsname}%
295 }%
296 }{}%
297 #2%
298 \ifcsdef{axp@old@the\csname axp@cn@#1\endcsname}{%
299 \csletcs{the\csname axp@cn@#1\endcsname}{axp@old@the\csname axp@cn@#1\endcsname}%
300 }{}%
301 \global\boolfalse{axp@forward}
302 }}%

```

`\axp@forward@link` Dummy macro, for handling the unwanted change of the `\newlabel` entry in the
`axp@forward` .aux file caused by changing the definition of `\thefoobar`.

```

303 \newbool{axp@forward}
304 \newcommand{\axp@forward@link}[2]{%
305 \ifboolexpr{ bool {axp@forward} and not bool {axp@forward@suppress} }{%
306 \ifcsdef{hyperlink}{%
307 \hyperlink{#1}{#2}%
308 }{%
309 #2%
310 }%
311 }{%
312 #2%
313 }%
314 }%

```

`\axp@forward@target` Provides the needed `\hypertarget`. Intended to be written to the .axp file.

```

315 \newcommand{\axp@forward@target}[2]{%
316 \ifcsname hypertarget\endcsname
317 \hypertarget{#1}{#2}%
318 \else
319 #2%
320 \fi
321 }

```

`\axp@forward@setup` In order to support counter inheritance with the first optional argument of `\newtheoremrep`, we need access to the name of the counter. For compliance with the behavior of `\@axp@newtheorem`, the first optional argument (#2) is ignored if the second optional argument (#4) is given.

```

322 \newcommand{\axp@forward@setup}[4]{%
323 \csdef{axp@cn@#1}{\ifblank{#4}{\ifblank{#2}{#1}{#2}}{#1}}%
324 }

```

7.5.4 Proof Environments

`\noproofinappendix` Utility macro that toggles `axp@seenrepththeorem` to false.

```

325 \newcommand\noproofinappendix{%

```

```

326   \global\togglefalse{axp@seenrepththeorem}%
327 }

```

appendixproof We dump the content of this in appendix, within an original **proof** environment, possibly after creating a new appendix section. We support optional arguments in proofs, but we need to be careful not to gobble any newline character, that would make it impossible to process the first line with **fancyvrb**.

```

328 \def\appendixproof{\catcode'\^M=\active\@ifnextchar[{\catcode'\^M=5\@appendixproof[axp@
329 \def\@appendixproof[#1]%
330   {%
331     \axp@writesection
332     \immediate\write\axp@proofsfile{%
333       \noexpand\makeatletter\noexpand\begin{#1}\noexpand\makeatother%
334     }%
335     \axp@VerbatimOut
336   }
337 \def\@@appendixproof[#1][#2]%
338   {%
339     \axp@writesection
340     \immediate\write\axp@proofsfile{%
341       \noexpand\makeatletter\noexpand\begin{#1}[\unexpanded{#2}]\noexpand\makeatother%
342     }%
343     \axp@VerbatimOut
344   }
345 \def\endappendixproof
346   {%
347     \endaxp@VerbatimOut
348     \immediate\write\axp@proofsfile{%
349       \noexpand\end{axp@oldproof}%
350     }%
351     \noproofinappendix
352   }

```

proof This environment either puts the proof in appendix, if we are after a repeated theorem without its proof, or inlines it otherwise. We support optional arguments in proofs, but we need to be careful not to gobble any newline character, that would make it impossible to process the first line with **fancyvrb**.

```

353 \def\proof{\catcode'\^M=\active\ltx@ifnextchar@nospace[{\catcode'\^M=5\axp@@proof}{\catcode'\^M=5\axp@@proof}]%
354 \def\axp@proof
355   {%
356     \iftoggle{axp@seenrepththeorem}{%
357       \appendixproof
358     }{%
359       \axp@oldproof
360     }%
361   }
362 \def\axp@@proof[#1]%
363   {%
364     \iftoggle{axp@seenrepththeorem}{%
365       \appendixproof[#1]
366     }{%
367       \axp@oldproof[#1]
368     }%

```

```

369   }
370   \def\endproof
371   {%
372     \iftoggle{axp@seenreptheorem}{%
373       \endappendixproof
374     }{%
375       \endaxp@oldproof
376     }%
377   }

```

claimproof If the **claimproof** environment exists (lipics document class or user-defined), we also redefine it, in the same way.

```

378   \AtBeginDocument{
379     \ifdefined\claimproof
380       \let\axp@oldclaimproof\claimproof
381       \let\endaxp@oldclaimproof\endclaimproof
382       \def\claimproof{\catcode'\^M=\active\ltx@ifnextchar@nospace[{\catcode'\^M=5\axp@@claimproof}]
383       \def\appendixclaimproof{\catcode'\^M=\active\ltx@ifnextchar[{\catcode'\^M=5\axp@@appendixproof}]
384       \def\axp@claimproof
385       {%
386         \iftoggle{axp@seenreptheorem}{%
387           \appendixclaimproof
388         }{%
389           \axp@oldclaimproof
390         }%
391       }
392       \def\axp@@claimproof[#1]%
393       {%
394         \iftoggle{axp@seenreptheorem}{%
395           \appendixclaimproof[#1]%
396         }{%
397           \axp@oldclaimproof[#1]%
398         }%
399       }
400       \def\endclaimproof
401       {%
402         \iftoggle{axp@seenreptheorem}{%
403           \endappendixclaimproof
404         }{%
405           \endaxp@oldclaimproof
406         }%
407       }
408       \def\endappendixclaimproof
409       {%
410         \endaxp@VerbatimOut
411         \immediate\write\axp@proofsfile{%
412           \noexpand\end{axp@oldclaimproof}}%
413       }%
414       \noproofinappendix
415     }
416   \fi
417 }

```

inlineproof These two environments are synonyms for the original **proof** environment.
nestedproof

```

418 \let\inlineproof\axp@oldproof
419 \let\endinlineproof\endaxp@oldproof
420 \let\nestedproof\axp@oldproof
421 \let\endnestedproof\endaxp@oldproof

```

7.5.5 Section Management

axp@seccounter Sequentially incremented for every section, used to create labels.

```
422 \newcounter{axp@seccounter}
```

\axp@sectitle Saves the title of the last encountered section.

```
423 \def\axp@sectitle{}
```

\axp@section This command **\axp@section** behaves similarly to **\axp@oldsection**, except that
\axp@@sectiontestinput it first tests whether a **\section** follows, and if so, does not produce anything. This
\axp@@sectiontestsection is useful to avoid producing empty sections in the appendix. Using the **catchfile**
package, we also check whether a **\section** is within an **\input** that immediately
follows.

```

424 \def\axp@section#1{%
425   \ifnextchar\input
426     {\axp@@sectiontestinput{#1}}%
427     {\axp@@sectiontestsection{#1}}%
428 }
429 \def\axp@@sectiontestinput#1\input#2{%
430   \CatchFileDef{\axp@tmp}{#2}{}%
431   \def\axp@tmptmp{\axp@@sectiontestsection{#1}}%
432   \expandafter\axp@tmptmp\axp@tmp%
433 }
434 \def\axp@@sectiontestsection#1{\ifnextchar\section{\makeatother}{\axp@oldsection{#1}\makeatother}}

```

\axp@oldsection We redefine the **\section** command to create a label based on **axp@seccounter**

\section and to store its title in **\axp@sectitle**. In order to support starred and unstarred

\@section versions, as well as the optional short-title argument, the intermediate macros

\@@section **\@section** and **\@@section** are needed.

```

435 \let\axp@oldsection\section
436 \def\section{\ifstar\@section\@@section}
437 \newcommand{\@section}[2][\relax]{\axp@@section{*}{#1}{#2}}%
438 \newcommand{\@@section}[2][\relax]{\axp@@section{}{#1}{#2}}%
439 \newcommand{\axp@@section}[3]{%
440   \global\def\axp@sectitle{#3}%
441   \ifx\relax#2\relax
442     \axp@oldsection#1{#3}%
443   \else
444     \axp@oldsection#1[#{#2}]{#3}%
445   \fi
446   \addtocounter{axp@seccounter}{1}%
447   \label{axp@s\roman{axp@seccounter}}}%
448 }

```

\nosectionappendix We remove the current section title, to indicate no section should be created in the appendix.

```

449 \newcommand{\nosectionappendix}{
450   \global\def\axp@sectitle{}%

```

451 }

`\axp@writesection` If `\axp@sectitle` is not empty, we create a new section in the appendix, referring to the main text section.

Here, we wrap `\ref{axp@si}` into `\axp@protectref@i`, in order to protect the label name from wrongly being converted to uppercase, e.g., in `fancyhdr` with `\pagestyle{fancy}`.

This macro is defined both in the `.aux` file (in order to ensure availability when typesetting the `\tableofcontents`), and immediately before typesetting the appendix section (to ensure availability in the `\section` command).

```

452 \newcommand\axp@writesection{%
453   \ifx\axp@sectitle\@empty
454   \else
455     \edef\axp@tmp{%
456       \noexpand\global\noexpand\def
457       \expandonce{\csname axp@protectref@\roman{axp@seccounter}\endcsname}{%
458         \noexpand\ref{axp@s\roman{axp@seccounter}}}%
459     }%
460   }%
461   \immediate\write\@auxout{\expandonce\axp@tmp}
462   \immediate\write\axp@proofsfile{%
463     \expandonce\axp@tmp^^J%
464     \noexpand\axp@section{%
465       \noexpand\appendixsectionformat{%
466         \protect
467         \expandonce{\csname axp@protectref@\roman{axp@seccounter}\endcsname}%
468         }{\expandonce\axp@sectitle}%
469       }%
470     }%
471     \nosectionappendix
472   \fi
473 }
```

Finally, in a somewhat ad hoc manner, we disable the whole section management for `\tableofcontents`, which may be typeset using a section heading, but for which automatic section management does not make sense.

```

\axp@oldtableofcontents
\tableofcontents 474 \let\axp@oldtableofcontents\tableofcontents
475 \def\tableofcontents{\let\section\axp@oldsection\axp@oldtableofcontents}}
```

7.5.6 Append Compilation Mode

```
476 \ifthenelse{\equal{\axp@appendix}{append}}{
```

`\axp@oldbibliography` Unless the bibliography option is set to `common`, we need to set the appendix bibliography source to be the same as that of the main text, thanks to `bibunits`'s `\defaultbibliography` macro.

```

477   \ifthenelse{\equal{\axp@bibliography}{separate}}{
478     \let\axp@oldbibliography\ bibliography
479     \renewcommand\ bibliography[1]{%
480       \defaultbibliography{#1}%
481       \axp@oldbibliography{#1}%

```

```

482     }
483   }{}

```

After the end of the main text, we add the appendix (after the command `\appendixprelim` is issued) within a `bibunit` environment so as to typeset a separate bibliography for the appendix (unless the `bibliography` option is set to `common`). This is done using `\pretocmd` on `\@enddocumenthook` instead of `\AtEndDocument` because we want the code to be run before any code in the `\@enddocumenthook` that has been set in the document class, as in the `amsart` document class. There is an extra test to ensure an empty bibliography environment is not produced. The name of the bibliography is changed to `\appendixrefname`; in most document classes, it is called `\refname` but it is occasionally (`scrartcl`, `scrreprt`) called `\bibname`. An ad-hoc test is added to fix a conflict with the `natbib` package which redefines `bibcite` at the end of the document.

```

484   \pretocmd{\@enddocumenthook}{%
485     \ifdefined\NAT@testdef
486       \renewcommand\bibcite[2]{%
487         \global\@namedef{b@#1\@extra@binfo}{#2}%
488       }
489     \fi
490     \appendixprelim
491     \appendix
492     \ifthenelse{\equal{\axp@bibliography}{separate}}{
493       \begin{bibunit}[\appendixbibliographystyle]
494     }{}
495     \immediate\closeout\axp@proofsfile
496     \input{\jobname.axp}
497     \ifthenelse{\equal{\axp@bibliography}{separate}}{
498       \ifdefined\refname
499         \renewcommand{\refname}{\appendixrefname}
500       \else\ifdefined\bibname
501         \renewcommand{\bibname}{\appendixrefname}
502       \fi\fi
503       \let\axp@oldthebibliography\thebibliography
504       \let\endaxp@oldthebibliography\endthebibliography
505       \renewenvironment{thebibliography}[1]{%
506         \def\axp@tmp{#1}%
507         \ifx\axp@tmp\empty
508           \gdef\axp@noappendixbibliography1\relax
509         \else
510           \begin{axp@oldthebibliography}{#1}%
511         \fi
512       }{%
513         \ifdefined\axp@noappendixbibliography\relax\else\end{axp@oldthebibliography}%
514       \fi}
515       \appendixbibliographyprelim
516       \putbib
517     \end{bibunit}
518     \ifdefined\NAT@testdef
519       \let\bibcite\NAT@testdef
520     \fi
521   }{}
522 }{}{}

```

523 }{}

7.5.7 Class-Specific Behavior

We conclude with some class-specific behavior.

ACM Document Classes (old versions, till 2017)

524 \ifdefined\acmtitlebox

We first redefine the `proofsketch` environment, which is used differently in the base class.

525 \renewenvironment{proofsketch}{\begin{axp@oldproof}[sketch]}\end{axp@oldproof}}

We adjust the styling of theorems for the needs of `apxproof`.

526 \newtheoremstyle{mystyle}

527 {6pt}

528 {6pt}

529 {\itshape}

530 {10pt}

531 {\scshape}

532 {..}

533 {.5em}

534 {}

535 \theoremstyle{mystyle}

\thebibliography The section title of the bibliography is in uppercase in these document classes. In addition, the `\thebibliography` macro hard-codes twice the section title, so we
\refname
\appendixrefname un-hardcode it so that it can be modified in the appendix.

536 \patchcmd{\thebibliography}{References}{\protect\refname}{}{}{}

537 \patchcmd{\thebibliography}{References}{\protect\refname}{}{}{}

538 \newcommand{\refname}{REFERENCES}

539 \renewcommand{\appendixrefname}{REFERENCES FOR THE APPENDIX}

540 \fi

lipcs

541 \ifdefined\lipics@opterrshort

\appendixbibliographyprelim The default bibliography in the `lipics` document class formatting is not compatible with the `alpha` bibliography style. We fix this here.

542 \renewcommand{\appendixbibliographyprelim}{%

543 \global\let\oldbiblabel\@biblabel

544 \def\@biblabel{\hspace*{-2em}\small\oldbiblabel}%

545 }

546 \fi

547 }

Change History

v1.0.0	Support of new ACM document class (<code>acmart.cls</code>)	23
General: Initial released version . . .		1
v1.0.1	<code>axp@newtheoremrep</code> : Better handling of note-free theorems in document classes that treat theorems differently when they have an empty note	14
General: Prevent empty bibliography environment; fix typos		1
v1.0.2	Fix incorrect use of <code>\noexpand</code> in optional argument of macro environment	15
<code>axp@newtheoremrep</code> : Fix display of repeated theorem counter in some document classes		15
Fix missing space between repeated theorem counter and theorem note		15
v1.0.3	<code>\FVE@axp@VerbatimOut</code> : Make <code>apxproof</code> compatible with independent use of <code>fancyvrb</code>	13
<code>\appendixbibliographyprelim</code> : Support for lipics-v2016		23
General: Note on entire sections in appendix		2
<code>proofsketch</code> : Ignore spaces after beginning of Proof sketch		11
v1.0.4	<code>\appendixsectionformat</code> : Fix missing space in default <code>\appendixsectionformat</code>	11
<code>\appendixprelim</code> : Configurable appendix style		11
<code>\axp@bibliography</code> : bibliography option		9
General: More faithful theorem style for ACM templates		23
More robust coherent styling of proof sketches		23
Re-establish custom proof environments		8
Show options commented on in margin and index		1
v1.0.5	<code>\axp@proofsfile</code> : Initialization deferred to <code>\AtBeginDocument</code> for compatibility with <code>\dumped</code> precompiled preambles (K. D. Bauer)	13
General: Ability to specify a sectioning counter in <code>newtheoremrep</code>		2
Fix compilation of <code>proofsketch</code> environment in inline mode		3
v1.0.6	<code>\axp@repeqn</code> : <code>repeqn</code> option	9
<code>\axp@newtheorem</code> : Introduce intermediary command for theorem macro		10
<code>\axp@writesection</code> : Fix extraneous space after section number in appendix titles		21
General: Better support of Springer document classes		11
Deal with document classes where the bibliography is called <code>\bibname</code>		22
v1.1.0	<code>\axp@unactivateeightbit</code> : Fix compilation of non-ASCII characters with <code>\usepackage[utf8]{inputenc}</code>	13
<code>\axp@writesection</code> : Make <code>\axp@tmp</code> wrapper more robust. Resolves issues from use of section title in <code>fancyhdr</code> , and in <code>\tableofcontents</code> (K. D. Bauer).		21
<code>\section</code> : Fix handling of fragile macros within section headings. See #22.		20
Rewrote definition of <code>\section</code> to enable optional argument. See #23. (K. D. Bauer)		20
<code>\tableofcontents</code> : Disable section management for table of contents		21
General: Added forward-link mechanism (K. D. Bauer)		16

v1.2.0		
\axp@newtheoremrep: Fix		document class 11
formatting of theorems without		General: Ad hoc fix for natbib
notes in some document classes		package conflict 22
in inline mode 12	v1.2.2	
\axp@newtheoremrep@definetheorem:		\axp@section: Detect a section
Restore predefined theorem		within an included file to avoid
counters 10		produced useless sections 20
\axp@redefinelabels: Fix extra		General: Compatibility with AMS
spacing erroneously introduced		document classes: do not use
within the		\AtEndDocument 22
\axp@redefinelabels macro . 11		axp@newtheoremrep: Fix handling
\mainbodyrepeatedtheorem:		of optional arguments of
Configurable repeated theorem		repeated theorems containing
command 11		optional arguments 14
General: Do not load bibunits if	v1.2.3	
bibliography is set to common . 9		\axp@forwardlinking:
axp@newtheoremrep: Fix display of		forwardlinking option 9
theorem notes 15		General: More robust redefinition of
proofsketch: Fix proof sketches in		thebibliography environment,
inline compilation mode for		for compatibility with tocbibind 22
Springer document classes . . . 12	v1.2.4	
v1.2.1		claimproof: Support for
\FVE@axp@VerbatimOut: Fix		claimproof environment from
compatibility with xypic		lipics 19
package 13		appendixproof: Support optional
Fix compatibility with other uses		arguments in proofs 18
of fancyvrb that set	v1.2.4-dev	
\FV@CatCodesHook 13		claimproof: Support for locally
\appendixrefname: Fix		defined claimproof
compatibility with memoir		environment 19

Index

Numbers written in *italic* refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; numbers in roman refer to the code lines where the entry is used.

Symbols	
\@@appendixproof 328, 337, 383	\@extra@binfo 487
\@@axp@newtheorem <u>81</u> , <u>128</u>	\@ifnextchar 328, 383, 425, 434
\@@section <u>435</u>	\@ifpackageloaded 7
\@acmplainnotefont 250, 262, 263	\@ifstar 81, 436
\@acmttitlebox 524	\@namedef 487
\@appendixproof 328, 329, 383	\@ne 186
\@auxout 461	\@noligs 198
\@axp@newtheorem <u>81</u> , <u>128</u>	\@oldbiblabel 543, 544
\@begintheorem 249	\@oparg 93, 96
\@biblabel 543, 544	\@section <u>435</u>
\@bsphack 190	\@thmcountersep 143
\@enddocumenthook 484	\^ 328, 353, 382, 383
\@esphack 203	

\backslash □	36, 45, 53, 62, 104	\backslash axp@proof	353, 354
		\backslash axp@proofsfile	167, 172, 196, 202, 233, 235, 245, 280, 332, 340, 348, 411, 462, 495
A		\backslash axp@redefinlabels	107, 150, 152, 274
\backslash active	328, 353, 382, 383	\backslash axp@refstar	241, 243, 258
\backslash advance	186	\backslash axp@repeqn	26, 48, 50, 53, 62, 217, 234, 279
\backslash appendix	491	\backslash axp@rpscounter	208
appendix (option)	4	\backslash axp@seccounter	422
\backslash appendixbibliographyprelim	5, 99, 515, 542	\backslash axp@section	424, 464
\backslash appendixbibliographystyle	5, 99, 493	\backslash axp@sectitle	423, 440, 450, 453, 468
\backslash appendixclaimproof	383, 387, 395	\backslash axp@seenrepththeorem	207
\backslash appendixprelim	5, 99, 490	\backslash axp@tmp	430, 432, 455, 461, 463, 506, 507
\backslash appendixproof (environment)	2, 156, 328	\backslash axp@tmptmp	431, 432
\backslash appendixrefname	5, 99, 499, 501, 536	\backslash axp@unactivateeightbit	181, 192
\backslash appendixsectionformat	5, 99, 465	\backslash axp@VerbatimOut	205, 335, 343
\backslash apx@oldamsthmndproof	10, 17	axp@VerbatimOut (environment)	188
\backslash apx@oldamsthmproof	9, 15, 16	\backslash axp@with@forward	222, 224, 286
\backslash AtBeginDocument	167, 171, 378	\backslash axp@writesection	205, 232, 331, 339, 452
\backslash axp@@@section	437, 438, 439	B	
\backslash axp@@claimproof	382, 392	\backslash bfseries	131, 133, 136, 140
\backslash axp@proof	353, 362	\backslash bibcite	486, 519
\backslash axp@@sectiontestinput	424	\backslash bibliography	477
\backslash axp@@sectiontestsection	424	bibliography (option)	4
\backslash axp@appendix	24, 29, 31, 33, 36, 109, 145, 287, 476	\backslash bibName	500, 501
\backslash axp@bibliography	25, 39, 42, 45, 477, 492, 497	\backslash BODY	150, 152, 227, 231
\backslash axp@claimproof	382, 384	\backslash boolfalse	301
\backslash axp@equation	209	\backslash booltrue	60, 288
\backslash axp@equationx	209	C	
\backslash axp@forward	303	\backslash CatchFileDef	430
\backslash axp@forward@link	293, 303	\backslash catcode	184, 328, 353, 382, 383
\backslash axp@forward@setup	215, 322	\backslash claimproof	176, 379, 380, 382
\backslash axp@forward@suppress	56	claimproof (environment)	378
\backslash axp@forward@target	273, 315	\backslash clearpage	103
\backslash axp@forwardlinking	27, 57, 58	\backslash closeout	495
\backslash axp@newtheorem	72, 81, 214	\backslash count@	182, 184, 185, 186
\backslash axp@newtheoremrep	96, 146, 211, 211	\backslash csdef	292
\backslash axp@newtheoremrep@definetheorem	65, 147, 212	\backslash csedef	323
\backslash axp@newtheoremreptmp	92	\backslash csletcs	290, 291, 299
\backslash axp@noappendixbibliography	508, 513	D	
\backslash axp@oldbibliography	477	\backslash DeclareStringOption	24, 25, 26, 27
\backslash axp@oldclaimproof	176, 380, 389, 397	\backslash defaultbibliography	480
\backslash axp@oldlabel	110, 113, 114, 118, 121, 123	\backslash DefineVerbatimEnvironment	188
\backslash axp@oldlabel@in@display	111, 117, 122, 124	E	
\backslash axp@oldproof	105, 174, 359, 367, 418, 420	\backslash empty	507
axp@oldproof (environment)	105	\backslash endappendixclaimproof	403, 408
\backslash axp@oldsection	178, 434, 435, 475	\backslash endappendixproof	161, 345, 373
\backslash axp@oldtableofcontents	474	\backslash endaxp@oldclaimproof	177, 381, 405
\backslash axp@oldthebibliography	503	\backslash endaxp@oldproof	106, 175, 375, 419, 421
		\backslash endaxp@oldthebibliography	504

<code>\endaxp@VerbatimOut</code>	206, 347, 410	<code>\label@in@display</code> 108, 111, 116, 122, 124	
<code>\endclaimproof</code>	177, 381, 400	<code>\lipics@opterrshort</code>	541
<code>\endinlineproof</code>	157, 419	<code>\loop</code>	183
<code>\endnestedproof</code>	159, 421	<code>\ltx@ifnextchar@nospace</code> . . .	353, 382
<code>\endproof</code>	10, 12, 17, 106, 157, 159, 161, 175, 370	M	
<code>\endthebibliography</code>	504	<code>\mainbodyrepeatedtheorem</code> . .	5, 99, 226
environments:		<code>\message</code> . .	30, 32, 34, 41, 43, 49, 51, 59
<code>appendixproof</code>	2, 156, 328	N	
<code>axp@oldproof</code>	105	<code>\NAT@testdef</code>	485, 518, 519
<code>axp@VerbatimOut</code>	188	<code>\nestedproof</code>	158, 420
<code>claimproof</code>	378	<code>nestedproof</code> (environment) .	5, 156, 418
<code>inlineproof</code>	3, 156, 418	<code>\newbool</code>	56, 303
<code>nestedproof</code>	5, 156, 418	<code>\newtheorem</code>	84, 86, 90
<code>proof</code>	3, 171, 353	<code>\newtheoremrep</code>	2, 92
<code>proofsketch</code>	3, 98	<code>\newtheoremstyle</code>	526
<code>toappendix</code>	1, 162, 204	<code>\noproofinappendix</code>	
<code>\errmessage</code>	36, 45, 53, 62	6, 162, 213, 325, 351, 414
<code>\expandonce</code>	457, 461, 463, 467, 468	<code>\nosectionappendix</code>	6, 162, 449, 471
F		O	
<code>forwardlinking</code> (option)	5	<code>\onecolumn</code>	103
<code>\FV@CatCodesHook</code>	199	<code>\openout</code>	169
<code>\FV@DefineTabOut</code>	195	options:	
<code>\FV@DefineWhiteSpace</code>	193	<code>appendix</code>	4
<code>\FV@FontScanPrep</code>	197	<code>bibliography</code>	4
<code>\FV@ProcessLine</code>	196	<code>forwardlinking</code>	5
<code>\FV@Scan</code>	200	<code>repeqn</code>	5
<code>\FV@Space</code>	194	P	
<code>\FVB@axp@VerbatimOut</code>	188	<code>\pretocmd</code>	213, 249, 484
<code>\FVE@axp@VerbatimOut</code>	188	<code>\ProcessLocalKeyvalOptions</code>	28
G		<code>\proof</code>	9, 11, 16, 105, 156, 158, 160, 174, 353
<code>\gdef</code>	508	<code>proof</code> (environment)	3, 171, 353
H		<code>\proofsketch</code>	142
<code>\hspace</code>	544	<code>proofsketch</code> (environment)	3, 98
<code>\hyperlink</code>	307	<code>\providecommand</code>	100, 108
<code>\hypertarget</code>	317	<code>\putbib</code>	516
I		R	
<code>\ifblank</code>	323	<code>\ref</code>	241, 243, 458
<code>\ifbool</code>	240	<code>\refname</code>	498, 499, 536
<code>\ifboolexpr</code>	305	<code>\repeat</code>	187
<code>\ifcsdef</code>	298, 306	<code>repeqn</code> (option)	5
<code>\ifcsname</code>	67, 73, 316	S	
<code>\ifcsundef</code>	289	<code>\scshape</code>	531
<code>\ifnum</code>	185	<code>\section</code>	171, 434, 435, 475
<code>\inlineproof</code>	156, 418	<code>\setcounter</code>	218, 236, 237, 281
<code>inlineproof</code> (environment) .	3, 156, 418	<code>\SetupKeyvalOptions</code>	20
<code>\input</code>	425, 429, 496	<code>\small</code>	544
<code>\itshape</code>	131, 133, 136, 140, 529	<code>\spnewtheorem</code>	127, 131, 133, 136, 140
L		T	
<code>\label</code>	110, 112, 121, 123, 222, 224, 447	<code>\tableofcontents</code>	474

<code>\the</code>	251, 266		U
<code>\theexp@equation</code>	237	<code>\unexpanded</code>	270, 341
<code>\thebibliography</code>	503, 536	<code>\upshape</code>	140
<code>\theopargself</code>	246, 247, 260		
<code>\theoremstyle</code>	535		V
<code>\thm@notefont</code>	251, 265, 266	<code>\value</code>	218, 236, 281
<code>\thmhead</code>	250, 251, 252, 253		
<code>toappendix</code> (environment) ..	1, 162, 204		W
<code>\togglefalse</code>	326	<code>\write</code> .	172, 196, 202, 233, 235, 245,
<code>\toggletrue</code>	228		280, 332, 340, 348, 411, 461, 462

References

- [1] Leslie Lamport. *L^AT_EX: A Document Preparation System*. Addison–Wesley Pub. Co., Reading, MA, 1986.

A Proofs for Section 1 (Usage)

Proof.

□

Foobar 2. *This foobar is repeated in the appendix.*

Proof.

□