

The apxproof package

Pierre Senellart

`pierre@senellart.com`

<http://github.com/PierreSenellart/apxproof>

2022/10/14 v1.2.4-dev

Abstract

This package makes it easier to write articles where proofs and other material are deferred to the appendix. The appendix material is written in the L^AT_EX code along with the main text which it naturally complements, and it is automatically deferred. The package can automatically send proofs to the appendix, can repeat in the appendix the theorem environments stated in the main text, can section the appendix automatically based on the sectioning of the main text, and supports a separate bibliography for the appendix material.

1 Usage

The `apxproof` package is intended to simplify the writing of articles where some of the content needs to be deferred to an appendix. This is in particular useful for the submission of scientific articles to conferences or journals that limit the number of pages in the main text but allow an extra appendix, where proofs of theorems and other material can be added.

1.1 Basics

To use `apxproof`, first load it in the header of your document:

```
\usepackage{apxproof}
```

On its own, this does not do anything and should not change the appearance of your document. To add an appendix with some material from your document, use the `toappendix` environment:

```
toappendix (env.)  \begin{toappendix}
                   ...
                   \end{toappendix}
```

The content will appear at the end of your document, in an automatically generated section that refers to the current section in the main text.

Example 1. *Throughout this documentation, all examples produce content deferred to the appendix, at the very end of this document.*

```
\begin{toappendix}
```

```
This content is in the appendix.
\end{toappendix}
```

When the content to put in appendix is an entire section, make sure that `\section` is the very first command that appears within the `toappendix` environment. It will disable the automatic production of a section heading.

1.2 Repeated Theorems and Proofs

In some scientific papers that include proofs, it is common to defer proofs to the appendix. This can easily be achieved using the `appendixproof` environment:

```
appendixproof (env.)    \begin{appendixproof}
                        ...
                        \end{appendixproof}
```

This behaves like the `toappendix` environment, except that a proof environment is generated.

Example 2. *We now send a proof to the appendix:*

```
\begin{appendixproof}
This proof is in the appendix.
\end{appendixproof}
```

When deferring proofs to the appendix, an annoying problem is that the statement of the theorem remains in the main text; it is hard to read a proof that is far away from the statement it proves. `apxproof` solves this issue by allowing statements of theorems to be *repeated*: once in the main text, and once in the appendix before the proof of the statement. To use this feature, you can define a new *repeated theorem* environment using the `\newtheoremrep` command:

```
\newtheoremrep    \newtheoremrep{<name>}[<counter>]{<title>}[<countersec>]
```

Usage is exactly the same as that of AMS L^AT_EX's `\newtheorem` macro:

- `<name>` (e.g., `theorem`) is the name of an environment that is created for this kind of theorem;
- `<counter>` (e.g., `definition`) is an optional counter describing from which kind of environment the numbering of these environments should be inherited;
- `<title>` (e.g., `Theorem`) is the title that will be used to display this theorem environment;
- `<countersec>` (e.g., `section`) is an optional counter of a sectioning command indicating that counters for this theorem should be prefixed by this counter (and reset at each occurrence of the sectioning command).

`<counter>` and `<countersec>` should not be used together. What differs from `\newtheorem` is that, when the following is written:

```
\newtheoremrep{foobar}{Foobar}
```

then *two* environments are defined: the `foobar` environment, which behaves as if `\newtheorem` had been used, and the `foobarrep` environment, which results in the statement of this environment being repeated in the appendix.

One interesting feature of `apxproof` is that in most situations, there is no need to `proof (env.)` use the `appendixproof` environment. Indeed, the `proof` environment is redefined by `apxproof` to automatically put the proof either in the main text (if it follows a regular theorem) or in the appendix (if it follows a repeated theorem).

Example 3. Assume we have first defined a repeated theorem environment `foobar` as above. We can now use this theorem environment, first for a regular theorem in the main text, then for a theorem repeated in the main text and in the appendix:

```
\begin{foobar}
This foobar is a regular one, in the main text.
\end{foobar}
\begin{proof}
This is the proof of the regular foobar.
\end{proof}
```

We obtain:

Foobar 1. *This foobar is a regular one, in the main text.*

Proof. This is the proof of the regular foobar. □

Now, if we use a repeated theorem:

```
\begin{foobarrep}
This foobar is repeated in the appendix.
\end{foobarrep}
\begin{proof}
This is the proof of the repeated foobar.
\end{proof}
```

We now obtain:

Foobar 2. *This foobar is repeated in the appendix.*

Note that, since `hyperref` is loaded, there are hyperlinks created between the statements of the theorems in the main text and in the appendix.

When the proof is deferred to the appendix, it is common practice to add a proof sketch in the main text. `apxproof` defines a simple `proofsketch` environment for this purpose:

```
proofsketch (env.) \begin{proofsketch}
...
\end{proofsketch}
```

The proof sketch is typeset similarly to a proof, but is always in the main text. Similarly, an `inlineproof` environment is provided so as to be able to have both a proof in the appendix (using the regular `proof` environment, or alternatively the `appendixproof` environment) and a different proof in the main text (using the `inlineproof` environment).

Example 4. *Here are simple examples of proof sketches and inline proofs:*

```
\begin{proofsketch}
This is a proof sketch.
\end{proofsketch}
```

Proof sketch. This is a proof sketch. □

```
\begin{inlineproof}
This is an inline proof.
\end{inlineproof}
```

Proof. This is an inline proof. □

1.3 Bibliography

By default, `apxproof` automatically adds a bibliography in the appendix with only the references cited in the appendix material. This allows for a clean separation of references used solely in the main text, and those used in the appendix.

Example 5. *Assume we have citations both in the main text and in the appendix.*

```
This is a citation in the main text~\cite{lamport86}.
\begin{toappendix}
This is a citation in the appendix~\cite{proofsAreHard}.
\end{toappendix}
```

This is a citation in the main text [1].

The bibliography in the appendix can use a different style and heading than the bibliography in the main text (and, by default, it does). See Section 1.5 for how to configure the appearance of that bibliography.

option `bibliography` In order to use a single appendix for the main text and the bibliography, one can specify the value `common` to the `bibliography` option when loading the package. (By default this option is set to `separate`.)

1.4 Mode

option `appendix` An optional $\langle mode \rangle$ can be specified when loading the package:

```
\usepackage[appendix= $\langle mode \rangle$ ]{apxproof}
```

$\langle mode \rangle$ can take one of the following three values:

append This is the default. Appendix material gathered by `apxproof` is appended to the main text.

inline In this mode, `apxproof` simply inlines the content along with the main text.

strip This mode functions similarly to **append** except that the appendix is not appended at the end of the document. All appendix material is therefore removed.

1.5 Customization

`apxproof` provides a few macros that can be redefined (using `\renewcommand`) to customize the appearance of the appendix:

- `\mainbodyrepeatedtheorem` `\mainbodyrepeatedtheorem` is a macro that is executed at the beginning of the body of every repeated theorem. This can be used to notify the reader that the theorem is repeated in appendix in some way, e.g., with a margin note.
 - `\appendixsectionformat` `\appendixsectionformat{<number>}{<title>}` is a macro that indicates how to format the section titles in the Appendix, given the number and title of the section in the main text. By default, they appear as “Proofs for Section *<number>* (*<title>*)”.
 - `\appendixrefname` `\appendixrefname` contains the heading that is displayed before the bibliography. By default, this is “References for the Appendix”. (Note that this command is also defined and used by the `memoir` document class.)
 - `\appendixbibliographystyle` `\appendixbibliographystyle` contains the `.bst` bibliography style that is used in the bibliography in appendix. By default, this is `alpha`.
 - `\appendixbibliographyprelim` `\appendixbibliographyprelim` contains arbitrary code that is executed just before the production of the bibliography in appendix, which can be used to configure the way it is displayed.
 - `\appendixprelim` `\appendixprelim` contains arbitrary code that is executed just before the production of the appendix, which can be used to configure the way it is displayed. By default, this command contains `\clearpage\onecolumn` (the appendix is typeset on a new page in single-column mode) but redefining this option allows changing this behavior.
- option* Another customization capability concerns *numbered equations* that are present within repeated theorems. An optional `repeqn` option can be specified when loading the package, which controls whether equation numbers should be as in the main text (by setting this option to `same`, the default) or independently numbered (by setting this option to `independent`). In the latter case, whenever a referenceable counter is set with `\label{<counter>}`, `\ref{<counter>}` references the counter in the main text, while `\ref{<counter>-apx}` references the counter in the appendix (except in `inline` mode, where both have the same effect).
- option* Another customization option concerns hyperlinking. Usually, when `hyperref` is loaded, `foobarrep` environments in the main text have their number link to their repetition in the appendix. To suppress this behavior and have `foobarrep` environments treated as if `hyperref` were not loaded, one can specify the value `no` to the `forwardlinking` option when loading the package. (By default this option is set to `yes`.)

1.6 Advanced Features

We now describe a few advanced macros and environments, the usage of which is limited to special cases:

- `nestedproof` (*env.*) `nestedproof` is an environment that can be used within a `proof` environment deferred in the appendix; this is required because, for technical reasons, no `proof` environment can be nested within a deferred `proof` environment.

`\noproofinappendix` `\noproofinappendix` can be used inside repeated theorems that are not followed by a `proof` or `appendixproof` environment; the point is to ensure that a further `proof` environment cannot be mistakenly understood as a proof of the repeated theorem. It should not be needed in most situations as `apxproof` tries figuring out when a proof follows a repeated theorem automatically, but may occasionally be needed in complex scenarios.

`\nosectionappendix` `\nosectionappendix` is to be used inside a section that *does* contain appendix material, but for which a section in the appendix should not be created. This should be rarely needed. When this command is present, appendix material is appended to the end of the previously created section.

2 Supported Document Classes

Because `apxproof` modifies sectioning commands, bibliographies, and proofs, it may not work straight away with arbitrary document classes. It has currently been tested with and is supported for the following document classes:

- L^AT_EX standard document classes (e.g., `article.cls`)
- KOMA-Script (e.g., `scrartcl.cls`, `scrbook.cls`)
- `memoir.cls`
- ACM SIG Proceedings (e.g., `sig-alternate.cls`, `acmart.cls`)
- Springer's Lecture Notes in Computer Science (e.g., `llncls.cls`)
- Schloß Dagstuhl's Leibniz International Proceedings in Informatics (e.g., `lipics.cls`, `lipcs-v2016.cls`)

Other classes may work out of the box. Adding support for specific classes is possible and can be requested from the author of this package.

3 Known Issues and Limitations

We report here some issues we are currently aware of:

- When using `hyperref`, the appendix in the bibliography is not hyperlinked. This is to avoid possible issues with multiply defined bibliography entries.
- `appendixproof`, `proof`, `toappendix` environments cannot be nested. This is a limitation of the `fancyvrb` package that `apxproof` relies on. Note the existence of the `nestedproof` environment for nested proofs.
- `apxproof` poorly interacts with SyncT_EX: identifying which source line has produced which box does not work for appendix content managed by `apxproof` or repeated theorems. No obvious fix is known, though this issue will be investigated in the long term.
- Unless the `bibliography` option is set to `common`, the `bibunits` package is used to generate a second bibliography. This means any package, such as `biblatex`, that is incompatible with `bibunits` will not be compatible with `apxproof` unless `bibliography` is set to `common`.

Issues not listed here should be reported to the author.

4 License

Copyright © 2016–2024 by Pierre Senellart.

This work may be distributed and/or modified under the conditions of the L^AT_EX Project Public License, either version 1.3 of this license or (at your option) any later version. The latest version of this license is in <http://www.latex-project.org/lppl.txt> and version 1.3 or later is part of all distributions of L^AT_EX version 2005/12/01 or later.

5 Contact

- <https://github.com/PierreSenellart/apxproof>
- Pierre Senellart <pierre@senellart.com>

Bug reports and feature requests should preferably be submitted through the *Issues* feature of GitHub.

6 Acknowledgments

Thanks to Antoine Amarilli for feedback and proofreading. Thanks to K. D. Bauer for the implementation of the forward-linking mechanism, and for various bugfixes. Thanks to Leonid Kostrykin for an initial implementation of the `forwardlinking` option.

7 Implementation

We now describe the entire code of the package, in a literate programming fashion. Throughout the package, we use the `axp@` prefix to identify local macros and environment names, which are not meant to be used by the final user.

7.1 Dependencies

We first load a few package dependencies:

- `environ` to easily define the repeated theorem environments.

```
1 \RequirePackage{environ}
```

- `etoolbox` to define simple toggles.

```
2 \RequirePackage{etoolbox}
```

- `fancyvrb` for the bulk of the work of exporting appendix material in an auxiliary file.

```
3 \RequirePackage{fancyvrb}
```

- `ifthen` for easier comparison of character strings.

```
4 \RequirePackage{ifthen}
```

- `kvoptions` to manage options passed to the package.

```
5 \RequirePackage{kvoptions}
```

- `catchfile` to be able to check the content of files `\input` within appendix content.

```
6 \RequirePackage{catchfile}
```

- `amsthm` for its `\newtheorem` macro. Some document classes (e.g., `lipics`) preload `amsthm`: this is fine, `\RequirePackage{amsthm}` will simply have no effect. On the other hand, some other document classes (e.g., `llncs` or `sig-alternate`) define a `proof` environment that conflicts with `amsthm`, so we have to undefine this environment before loading `amsthm`. In that case, we reestablish the existing proof environments, in case they had been customized (e.g., `sig-alternate`)

```
7 \@ifpackageloaded{amsthm}{
8   }{
9     \let\apx@oldamsthmproof\proof
10    \let\apx@oldamsthmendproof\endproof
11    \let\proof\undefined
12    \let\endproof\undefined
13  }
14  \RequirePackage{amsthm}
15  \ifdefined\apx@oldamsthmproof
16    \let\proof\apx@oldamsthmproof
17    \let\endproof\apx@oldamsthmendproof
18  \fi
```

7.2 Option Processing

Many names throughout the package use an atrobase (`@`) to avoid name conflict with user-defined names. To simplify the compilation of the documentation, we simply make it a regular character in all the rest.

```
19 \makeatletter
```

We setup the processing of options using `keyval` facilities.

```
20 \SetupKeyvalOptions{
21   family=axp,
22   prefix=axp@
23 }
```

We declare the following options:

- `appendix`, with a default value of `append` (other possible values: `strip`, `inline`);
- `bibliography`, with a default value of `separate` (other possible value: `common`);
- `repeqn`, with a default value of `same` (other possible value: `independent`).

```
\axp@appendix
```

```
24 \DeclareStringOption[append]{appendix}
```



```

\axp@bibliography
25 \DeclareStringOption[separate]{bibliography}

\axp@repeqn
26 \DeclareStringOption[same]{repeqn}

\axp@forwardlinking
27 \DeclareStringOption[yes]{forwardlinking}

28 \ProcessLocalKeyvalOptions*

We check that the value of the options are valid, and add a message to the
compilation log.
29 \ifthenelse{\equal{\axp@appendix}{append}}{
30   \message{apxproof: Appendix material appended to the document}
31 }{\ifthenelse{\equal{\axp@appendix}{strip}}{
32   \message{apxproof: Appendix material stripped}
33 }{\ifthenelse{\equal{\axp@appendix}{inline}}{
34   \message{apxproof: Appendix material inlined within the document}
35 }{
36   \errmessage{Error: unsupported option appendix=\axp@appendix\ for
37   package apxproof}
38 }}}
39 \ifthenelse{\equal{\axp@bibliography}{separate}}{

The external bibunits package is used to add a second bibliography for the appendix
material.
40 \RequirePackage{bibunits}
41 \message{apxproof: Separate bibliography for appendix material}
42 }{\ifthenelse{\equal{\axp@bibliography}{common}}{
43   \message{apxproof: Common bibliography for appendix and main text}
44 }{
45   \errmessage{Error: unsupported option bibliography=\axp@bibliography\ for
46   package apxproof}
47 }}
48 \ifthenelse{\equal{\axp@repeqn}{same}}{
49   \message{apxproof: Repeated equations keep the same numbering}
50 }{\ifthenelse{\equal{\axp@repeqn}{independent}}{
51   \message{apxproof: Repeated equations are independently numbered}
52 }{
53   \errmessage{Error: unsupported option repeqn=\axp@repeqn\ for
54   package apxproof}
55 }}

\axp@forward@suppress
56 \newbool{axp@forward@suppress}
57 \ifthenelse{\equal{\axp@forwardlinking}{yes}}{
58 }{\ifthenelse{\equal{\axp@forwardlinking}{no}}{
59   \message{apxproof: Disable forward linking}
60   \global\booltrue{axp@forward@suppress}%
61 }{
62   \errmessage{Error: unsupported option forwardlinking=\axp@repeqn\ for
63   package apxproof}
64 }}

```

7.3 Macros Common to All Compilation Modes

`\xp@newtheoremrep@definetheorem` Common to all compilation modes, we define `\xp@newtheoremrep@definetheorem`. When called with first argument `foobar`, we first undefine the existing `foobar` environment (and its counter) if it has already been defined (e.g., by the document class), then invoke `\axp@newtheorem` for the regular version of the theorem `foobar`, saving and restoring any existing theorem counter unless the `\newtheoremdep` redefines the base counter.

```

65 \def\xp@newtheoremrep@definetheorem#1#2#3#4{%
66   \expandafter\let\csname #1\endcsname\undefined
67   \ifcsname c@#1\endcsname
68     \expandafter\expandafter\expandafter\let\expandafter\expandafter
69       \csname c@axp@#1\endcsname\csname c@#1\endcsname
70     \expandafter\let\csname c@#1\endcsname\undefined
71   \fi
72   \xp@newtheorem{#1}{#2}{#3}{#4}%
73   \ifcsname c@axp@#1\endcsname
74     \ifx\relax#2\relax
75       \expandafter\expandafter\expandafter\let\expandafter\expandafter
76         \csname c@#1\endcsname\csname c@axp@#1\endcsname
77     \else
78       \fi
79   \fi
80 }
```

`\axp@newtheorem` We introduce an intermediate `\axp@newtheorem` command to define a new theorem, `\@axp@newtheorem` differently depending on whether there is a section counter or not. This will be `\@@axp@newtheorem` useful, in particular to allow changing this definition depending on the document class. This command uses two intermediary commands, `\@axp@newtheorem` and `\@@axp@newtheorem`, for the non-starred and starred versions.

```

81 \def\axp@newtheorem{\ifstar\@axp@newtheorem\@axp@newtheorem}
82 \def\@axp@newtheorem#1#2#3#4{%
83   \ifx\relax#4\relax
84     \newtheorem{#1}[#2]{#3}%
85   \else
86     \newtheorem{#1}{#3}[#4]%
87   \fi
88 }
89 \def\@@axp@newtheorem#1#2{%
90   \newtheorem*{#1}{#2}%
91 }
```

`\newtheoremrep` We define the high-level `\newtheoremrep` to have the same syntax as `amsthm`'s `\axp@newtheoremreptmp` `\newtheorem`. For this purpose, we need a little trick to deal with the second and fourth optional arguments, which is what `\@oparg` and `\axp@newtheoremreptmp` are used for. `\axp@newtheoremrep` is defined differently depending on the compilation mode.

```

92 \newcommand\newtheoremrep[1]{%
93   \@oparg{\axp@newtheoremreptmp{#1}}[]%
94 }
95 \def\axp@newtheoremreptmp#1[#2]#3{%
96   \@oparg{\axp@newtheoremrep{#1}[#2]{#3}}[]%
97 }
```

`proofsketch` (*env.*) Simple `proofsketch` environment.

```
98 \newenvironment{proofsketch}{\begin{axp@oldproof}[Proof sketch]}\end{axp@oldproof}}
```

`\mainbodyrepeatedtheorem` We provide sensible defaults for these user-customizable macros. Even though

`\appendixrefname` they are not all useful in all modes, we define them for all modes so that a

`\appendixbibliographystyle` `\renewcommand` works in all cases.

```
\appendixbibliographyprelim 99 \newcommand{\mainbodyrepeatedtheorem}{}
\appendixprelim 100 \providecommand{\appendixrefname}{References for the Appendix}
```

```
\appendixsectionformat 101 \newcommand{\appendixbibliographystyle}{alpha}
```

```
102 \newcommand{\appendixbibliographyprelim}{}
103 \newcommand{\appendixprelim}{\clearpage\onecolumn}
```

```
104 \newcommand{\appendixsectionformat}[2]{Proofs for Section~#1\ (#2)}
```

`axp@oldproof` (*env.*) We save the definition of the existing proof environment.

```
105 \let\axp@oldproof\proof
```

```
106 \let\endaxp@oldproof\endproof
```

We define a utility macro that will be used to properly set the `\label` command (and its `amsmath` counterpart, `\label@in@display`) for equations within repeated theorems, depending on the compilation mode.

`\axp@redefinelabels`

```
107 \newcommand{\axp@redefinelabels}{%
```

```
108 \providecommand\label@in@display{}%
```

```
109 \ifthenelse{\equal{\axp@appendix}{inline}}{%
```

```
110 \let\axp@oldlabel\label
```

```
111 \let\axp@oldlabel@in@display\label@in@display
```

```
112 \renewcommand\label[1]{%
```

```
113 \axp@oldlabel{##1}%
```

```
114 \axp@oldlabel{##1-apx}%
```

```
115 }%
```

```
116 \renewcommand\label@in@display[1]{%
```

```
117 \axp@oldlabel@in@display{##1}%
```

```
118 \axp@oldlabel{##1-apx}%
```

```
119 }%
```

```
120 }{%
```

```
121 \let\axp@oldlabel\label
```

```
122 \let\axp@oldlabel@in@display\label@in@display
```

```
123 \renewcommand\label[1]{\axp@oldlabel{##1-apx}}%
```

```
124 \renewcommand\label@in@display[1]{\axp@oldlabel@in@display{##1-apx}}%
```

```
125 }%
```

```
126 }
```

7.3.1 Class-Specific Behavior

Finally, some class-specific behavior common to all compilation modes.

llncs and other Springer document classes

```
127 \ifdefined\spnewtheorem
```

`\axp@newtheorem` It is necessary to use `\spnewtheorem` instead of `\newtheorem` in Springer document classes to obtain standard formatting.

```

128 \def\@axp@newtheorem#1#2#3#4{%
129   \ifx\relax#4\relax
130     \ifx\relax#2\relax
131       \spnewtheorem{#1}{#3}{\bfseries}{\itshape}%
132     \else
133       \spnewtheorem{#1}[#2]{#3}{\bfseries}{\itshape}%
134     \fi
135   \else
136     \spnewtheorem{#1}{#3}[#4]{\bfseries}{\itshape}%
137   \fi
138 }
139 \def\@axp@newtheorem#1#2{%
140   \spnewtheorem*{#1}{#2}{\upshape\bfseries}{\itshape}%
141 }

```

proofsketch We redefine the `proofsketch` environment, which is used differently in the base class.

```
142 \renewenvironment{proofsketch}{\begin{axp@oldproof}[sketch]}\end{axp@oldproof}}
```

We have to redefine the macro `\@thmcountersep` for proper sectioned counters.

```

143 \def\@thmcountersep{.}
144 \fi

```

7.4 Inline Compilation Mode

```
145 \ifthenelse{\equal{\axp@appendix}{inline}}{
```

\axp@newtheoremrep In inline mode, `\axp@newtheoremrep` uses `\axp@newtheoremrep@definetheorem` to define the regular theorem environment and creates a repeated theorem environment that behaves exactly as the regular theorem environment, while calling `\axp@redefinelabels` to make sure that `-axp` variants of equation counters are defined.

```

146 \def\axp@newtheoremrep#1[#2]#3[#4]{%
147   \axp@newtheoremrep@definetheorem{#1}{#2}{#3}{#4}%
148   \NewEnviron{#1rep}[1][]{%
149     \ifx\relax#1\relax
150       \begin{#1}\axp@redefinelabels\BODY\end{#1}%
151     \else
152       \begin{#1}[##1]\axp@redefinelabels\BODY\end{#1}%
153     \fi
154   }
155 }

```

inlineproof (*env.*) In inline mode, these environments behave like the regular `proof` environment.

```

nestedproof (env.) 156 \let\inlineproof\proof
appendixproof (env.) 157 \let\endinlineproof\endproof
158 \let\nestedproof\proof
159 \let\endnestedproof\endproof
160 \let\appendixproof\proof
161 \let\endappendixproof\endproof

```

toappendix (*env.*) In inline mode, this environment and these macros are no-ops.

```

\noproofinappendix 162 \newenvironment{toappendix}{}{}
\nosectionappendix

```

```

163 \let\noproofinappendix\relax
164 \let\nosectionappendix\relax
165 }

```

7.5 Append or Strip Compilation Modes

```
166 {
```

We now deal with the case where `apxproof` really does something useful: either append the appendix material to the document, or strip it entirely.

7.5.1 Auxiliary File for the Appendix

`\axp@proofsfile` We open a new auxiliary file, with extension `.axp`, where the appendix material will be dumped.

```

167 \AtBeginDocument{
168   \newwrite\axp@proofsfile
169   \immediate\openout\axp@proofsfile=\jobname.axp
170 }

```

`proof (env.)` At the beginning of this file, we make `@` a regular character (since it will be used in several places for internal names) and reestablish the original definition of the `proof` environment and the `\section` macro.

```

171 \AtBeginDocument{
172   \immediate\write\axp@proofsfile{%
173     \noexpand\makeatletter
174     \noexpand\let\noexpand\proof\noexpand\axp@oldproof
175     \noexpand\let\noexpand\endproof\noexpand\endaxp@oldproof
176     \noexpand\let\noexpand\claimproof\noexpand\axp@oldclaimproof
177     \noexpand\let\noexpand\endclaimproof\noexpand\endaxp@oldclaimproof
178     \noexpand\let\noexpand\section\noexpand\axp@oldsection
179   }
180 }

```

`\axp@unactivateeightbit` We need an auxiliary macro to disable active characters that have the high bit set when writing to the `.axp` file. See <https://tex.stackexchange.com/a/145361/166858>

```

181 \def\axp@unactivateeightbit{%
182   \count@=128%
183   \loop
184     \catcode\count@=12%
185     \ifnum\count@<255%
186       \advance\count@\@ne
187   \repeat}

```

`axp@VerbatimOut (env.)` Using the functionalities of the `fancyvrb` package, we define a custom verbatim environment `axp@VerbatimOut` that writes every line to the `\axp@proofsfile`.

`\FVB@axp@VerbatimOut` We also use the previous macro to disable active characters with the eighth bit set, and we make sure the catcode of `@` is reset for every verbatim environment, in case it is used by the user (e.g., as in the `xypic` package). Finally, as an additional precaution, we reset `\FV@CatCodesHook` that is for example set by the `commandchars` or `commentchar` option of `\fvset`.

```

188 \DefineVerbatimEnvironment{axp@VerbatimOut}{axp@VerbatimOut}{%
189 \def\FVB@axp@VerbatimOut{%
190 \@bsphack
191 \begingroup
192 \axp@unactivateeightbit
193 \FV@DefineWhiteSpace
194 \def\FV@Space{\space}%
195 \FV@DefineTabOut
196 \def\FV@ProcessLine{\immediate\write\axp@proofsfile}%
197 \let\FV@FontScanPrep\relax
198 \let\@noligs\relax
199 \def\FV@CatCodesHook{%
200 \FV@Scan}
201 \def\FVE@axp@VerbatimOut{%
202 \immediate\write\axp@proofsfile{\noexpand\makeatletter}%
203 \endgroup\@esphack}

```

toappendix (*env.*) The entire content of this environment is put in appendix, starting a new appendix section beforehand if needed.

```

204 \newenvironment{toappendix}
205 {\axp@writesection\axp@VerbatimOut}
206 {\endaxp@VerbatimOut}

```

7.5.2 Definition of New Theorems

axp@seenrepththeorem Used to indicate whether a repeated theorem was just typeset, without its proof.

```

207 \newtoggle{axp@seenrepththeorem}

```

axp@rpcounter Sequentially incremented for every repeated theorem, used to create labels.

```

208 \newcounter{axp@rpcounter}

```

axp@equation Used to save the value of the equation counter, when **repeqn** is set to **same**.

```

axp@equationx 209 \newcounter{axp@equation}
210 \newcounter{axp@equationx}

```

axp@newtheoremrep With first argument **foobar**, we use **\axp@newtheoremrep@definetheorem** to define the regular version of the theorem **foobar**. We then patch **\begin{foobar}** so as not to expect a proof in the appendix and define an internal theorem **axp@foobarrp** that will be used in the appendix to restate the existing theorem.

```

211 \def\axp@newtheoremrep#1[#2]#3[#4]{%
212 \axp@newtheoremrep@definetheorem{#1}{#2}{#3}{#4}%
213 \expandafter\pretocmd\csname #1\endcsname{\noproofinappendix}{-}{-}%
214 \axp@newtheorem*{axp@#1rp}{#3}%
215 \axp@forward@setup{#1}{#2}{#3}{#4}%

```

We then define a **foobarrp** environment that increments the **axp@rpcounter** and typeset the regular **foobar** theorem with a label derived from the counter, along with a possible custom command to identify repeated theorems. We distinguish the case when the theorem argument has a note and when it does not. We save the equation counter before typesetting the theorem environment, to reset it to the same value in the repeated environment when **repeqn** is set to **same**.

```

216 \NewEnviron{#1rep}[1][ ]{%
217 \ifthenelse{\equal{\axp@repeqn}{same}}{%

```

```

218     \setcounter{axp@equation}{\value{equation}}%
219   }{}%
220   \addtocounter{axp@rcounter}{1}%
221   \ifx\relax##1\relax
222     \axp@with@forward{#1}{\begin{#1}}\label{axp@r\roman{axp@rcounter}}}%
223   \else
224     \axp@with@forward{#1}{\begin{#1}[\{##1\}]\label{axp@r\roman{axp@rcounter}}}%
225   \fi
226   \mainbodyrepeatedtheorem
227   \BODY\end{#1}%

```

We set the `axp@seenrepththeorem` toggle to indicate that we are looking for the proof of the theorem, then store in a macro the content of the theorem's body.

```

228   \global\toggletrue{axp@seenrepththeorem}%
229   \global\expandafter\let\csname rplet\roman{axp@rcounter}%
230                               \endcsname
231   \BODY

```

Possibly after starting a new appendix section if needed, we typeset a repeated version of the theorem using the `axp@foobarrp` environment and a reference to the previously defined label. We use `\axp@redefinlabels` in this environment to avoid multiply defined labels. We have to deal in a careful way with theorem notes: we want to use a theorem note to display the number of the repeated theorem, but theorem notes are usually typeset in a much different way (different font, parentheses) than theorem headings. In the case of the Springer document classes, we use the `\theopargself` macro to disable parentheses. For other document classes, we need to manually patch the `\thmhead` command at the right time. We also specially cover the case of the ACM document class where `\@acmplainnotefont` is used instead of `\thm@notefont`.

```

232   \axp@writesection%
233   \immediate\write\axp@proofsfile{\noexpand\makeatletter}%
234   \ifthenelse{\equal{\axp@repeqn}{same}}{%
235     \immediate\write\axp@proofsfile{%
236       \noexpand\setcounter{axp@equationx}{\value{equation}}}%
237     \noexpand\setcounter{equation}{\theaxp@equation}%
238   }%
239   }{}%
240   \ifbool{axp@forward@suppress}{%
241     \global\def\axp@refstar{\ref*}
242   }{%
243     \global\def\axp@refstar{\ref}
244   }
245   \immediate\write\axp@proofsfile{%
246     \ifdefined\theopargself
247       \noexpand\theopargself
248     \else
249       \noexpand\pretocmd{\noexpand\@begintheorem}{%
250         \noexpand\patchcmd{\noexpand\thmhead}{\noexpand\@acmplainnotefont}{-}{-}%
251         \noexpand\patchcmd{\noexpand\thmhead}{\noexpand\the\noexpand\thm@notefont}{-}{-}%
252         \noexpand\patchcmd{\noexpand\thmhead}{(}{-}{-}%
253         \noexpand\patchcmd{\noexpand\thmhead}{)}{-}{-}%
254       }{}{}
255     \fi
256     \noexpand\begin{axp@#1rp}

```

```

257      [%
258      \noexpand\axp@refstar{axp@r\roman{axp@rpscounter}}}%
259      \@ifnotempty{##1}{%
260      \ifdefined\theopargself
261      \else
262      \ifdefined\@acmplainnotefont
263      \noexpand\@acmplainnotefont
264      \else
265      \noexpand\ifdefined\noexpand\thm@notefont
266      \noexpand\the\noexpand\thm@notefont
267      \noexpand\fi
268      \fi
269      \fi
270      {} (\unexpanded{##1})}%
271      ]%
272      ]%
273      \noexpand\axp@forward@target{axp@fw@r\roman{axp@rpscounter}}}%
274      \noexpand\axp@redefinlabels
275      \expandafter\noexpand\csname rplet\roman{axp@rpscounter}}%
276      \endcsname
277      \noexpand\end{axp@#1rp}
278      }%
279      \ifthenelse{\equal{axp@repeqn}{same}}{%
280      \immediate\write\axp@proofsfile%
281      \noexpand\setcounter{equation}{\value{axp@equationx}}%
282      }%
283      }{}%
284      }%
285      }

```

7.5.3 Forward-Linking Mechanism

When `hyperref` is loaded, `foobarrep` environments in the main text have their number link to their repetition in the appendix.

`\axp@with@forward` In order to make the number of the `foobarrep` theorem a link to its repeated version, we temporarily redefine the `\thefoobar` command, or, if we inherited the counter from a `bazbar` environment, the `\thebazbar` command. This seems to be the only robust way to make the number a `\hyperlink`, without adding extensive dependence on internals of `amsthm`, the builtin `\newtheorem` and possibly document-class specific definitions.

In order to allow users to redefine `\thefoobar` without breaking this feature, we redefine `\thefoobar` only for the duration of the `\begin{foobar}` form, resetting it to the old value as soon as possible.

Redefining `\thefoobar` has the side effect of changing `\newlabel` entries in the `.aux` file, so we need to be able to disable addition of the `hyperlink`, which is why we use an intermediate `\axp@forward@link{<target>}{<text>}` macro. We also redefine `\theHfoobar` which is used by `hyperref` but not defined if `hyperref` was loaded after `\newtheoremrep` was used and `\protect` it to output it verbatim into the `.aux` file.

These hyperlinks are of course disabled in the `strip` compilation mode.

```

286      \newcommand{\axp@with@forward}[2]{%

```



```

287 \ifthenelse{\equal{\axp@appendix}{strip}}{#2}{
288 \global\booltrue{axp@forward}}%
289 \ifcsundef{axp@old@the\csname axp@cn@#1\endcsname}{%
290 \csletcs{axp@old@the\csname axp@cn@#1\endcsname}{the\csname axp@cn@#1\endcsname}}%
291 \csletcs{theH\csname axp@cn@#1\endcsname}{the\csname axp@cn@#1\endcsname}}%
292 \csdef{the\csname axp@cn@#1\endcsname}{%
293 \protect\axp@forward@link{axp@fw@r\roman{axp@rpcounter}}}%
294 {\csname axp@old@the\csname axp@cn@#1\endcsname\endcsname}}%
295 }%
296 }{}%
297 #2%
298 \ifcsdef{axp@old@the\csname axp@cn@#1\endcsname}{%
299 \csletcs{the\csname axp@cn@#1\endcsname}{axp@old@the\csname axp@cn@#1\endcsname}}%
300 }{}%
301 \global\boolfalse{axp@forward}
302 }}%

```

`\axp@forward@link` Dummy macro, for handling the unwanted change of the `\newlabel` entry in the `.aux` file caused by changing the definition of `\thefoobar`. We also use `\texorpdfstring` to detect whether the reference appears within a PDF bookmark, in which case we skip the test altogether.

```

303 \newbool{axp@forward}
304 \newcommand{\axp@forward@link}[2]{%
305 \ifdefined\texorpdfstring\else\newcommand\texorpdfstring[2]{#2}\fi
306 \texorpdfstring{%
307 \ifboolexpr{ bool {axp@forward} and not bool {axp@forward@suppress} }{%
308 \ifcsdef{hyperlink}{%
309 \hyperlink{#1}{#2}}%
310 }{%
311 #2%
312 }%
313 }{%
314 #2%
315 }%
316 }{%
317 #2%
318 }%
319 }%

```

`\axp@forward@target` Provides the needed `\hypertarget`. Intended to be written to the `.axp` file.

```

320 \newcommand{\axp@forward@target}[2]{%
321 \ifcsname hypertarget\endcsname
322 \hypertarget{#1}{#2}}%
323 \else
324 #2%
325 \fi
326 }

```

`\axp@forward@setup` In order to support counter inheritance with the first optional argument of `\newtheoremrep`, we need access to the name of the counter. For compliance with the behavior of `\@axp@newtheorem`, the first optional argument (`#2`) is ignored if the second optional argument (`#4`) is given.

```

327 \newcommand{\axp@forward@setup}[4]{%

```

```

328   \csedef{axp@cn@#1}{\ifblank{#4}{\ifblank{#2}{#1}{#2}}{#1}}%
329   }

```

7.5.4 Proof Environments

`\noproofinappendix` Utility macro that toggles `axp@seenreptheorem` to false.

```

330   \newcommand\noproofinappendix{%
331     \global\togglefalse{axp@seenreptheorem}%
332   }

```

`appendixproof` (*env.*) We dump the content of this in appendix, within an original `proof` environment, possibly after creating a new appendix section. We support optional arguments in proofs, but we need to be careful not to gobble any newline character, that would make it impossible to process the first line with `fancyvrb`.

```

333   \def\appendixproof{\catcode'\^M=\active\@ifnextchar[{\catcode'\^M=5\@@appendixproof[axp@
334   \def\@@appendixproof[#1]%
335     {%
336       \axp@writesection
337       \immediate\write\axp@proofsfile{%
338         \noexpand\makeatletter\noexpand\begin{#1}\noexpand\makeatother%
339       }%
340       \axp@VerbatimOut
341     }
342   \def\@@appendixproof[#1][#2]%
343     {%
344       \axp@writesection
345       \immediate\write\axp@proofsfile{%
346         \noexpand\makeatletter\noexpand\begin{#1}[\unexpanded{#2}]\noexpand\makeatother%
347       }%
348       \axp@VerbatimOut
349     }
350   \def\endappendixproof
351     {%
352     \endaxp@VerbatimOut
353     \immediate\write\axp@proofsfile{%
354       \noexpand\end{axp@oldproof}%
355     }%
356     \noproofinappendix
357   }

```

`proof` (*env.*) This environment either puts the proof in appendix, if we are after a repeated theorem without its proof, or inlines it otherwise. We support optional arguments in proofs, but we need to be careful not to gobble any newline character, that would make it impossible to process the first line with `fancyvrb`.

```

358   \def\proof{\catcode'\^M=\active\ltx@ifnextchar@nospace[{\catcode'\^M=5\axp@@proof}{\catcode
359   \def\axp@proof
360     {%
361       \iftoggle{axp@seenreptheorem}{%
362         \appendixproof
363       }{%
364         \axp@oldproof
365       }%
366     }

```

```

367 \def\axp@@proof[#1]%
368   {%
369     \iftoggle{axp@seenreptheorem}{%
370       \appendixproof[#1]
371     }{%
372       \axp@oldproof[#1]
373     }%
374   }
375 \def\endproof
376   {%
377     \iftoggle{axp@seenreptheorem}{%
378       \endappendixproof
379     }{%
380       \endaxp@oldproof
381     }%
382   }

```

`claimproof (env.)` If the `claimproof` environment exists (lipics document class or user-defined), we also redefine it, in the same way.

```

383 \AtBeginDocument{
384   \ifdefined\claimproof
385     \let\axp@oldclaimproof\claimproof
386     \let\endaxp@oldclaimproof\endclaimproof
387     \def\claimproof{\catcode'\^M=\active\ltx@ifnextchar@nospace[{\catcode'\^M=5\axp@@claimproof}]
388     \def\appendixclaimproof{\catcode'\^M=\active\ltx@ifnextchar[{\catcode'\^M=5\@appendixproof}]
389     \def\axp@claimproof
390       {%
391         \iftoggle{axp@seenreptheorem}{%
392           \appendixclaimproof
393         }{%
394           \axp@oldclaimproof
395         }%
396       }
397     \def\axp@@claimproof[#1]%
398       {%
399         \iftoggle{axp@seenreptheorem}{%
400           \appendixclaimproof[#1]%
401         }{%
402           \axp@oldclaimproof[#1]%
403         }%
404       }
405     \def\endclaimproof
406       {%
407         \iftoggle{axp@seenreptheorem}{%
408           \endappendixclaimproof
409         }{%
410           \endaxp@oldclaimproof
411         }%
412       }
413     \def\endappendixclaimproof
414       {%
415         \endaxp@VerbatimOut
416         \immediate\write\axp@proofsfile{%
417         \noexpand\end{axp@oldclaimproof}}%

```

```

418     }%
419     \noproofinappendix
420   }
421   \fi
422 }

```

`inlineproof` (*env.*) These two environments are synonyms for the original `proof` environment.

`nestedproof` (*env.*)

```

423 \let\inlineproof\axp@oldproof
424 \let\endinlineproof\endaxp@oldproof
425 \let\nestedproof\axp@oldproof
426 \let\endnestedproof\endaxp@oldproof

```

7.5.5 Section Management

`axp@seccounter` Sequentially incremented for every section, used to create labels.

```

427 \newcounter{axp@seccounter}

```

`\axp@sectitle` Saves the title of the last encountered section.

```

428 \def\axp@sectitle{}

```

`\axp@section` This command `\axp@section` behaves similarly to `\axp@oldsection`, except that `\axp@@sectiontestinput` it first tests whether a `\section` follows, and if so, does not produce anything. This `\axp@@sectiontestsection` is useful to avoid producing empty sections in the appendix. Using the `catchfile` package, we also check whether a `\section` is within an `\input` that immediately follows.

```

429 \def\axp@section#1{%
430   \@ifnextchar\input
431     {\axp@@sectiontestinput{#1}}%
432     {\axp@@sectiontestsection{#1}}%
433 }
434 \def\axp@@sectiontestinput#1\input#2{%
435   \CatchFileDef{\axp@tmp}{#2}{}%
436   \def\axp@tmptmp{\axp@@sectiontestsection{#1}}%
437   \expandafter\axp@tmptmp\axp@tmp%
438 }
439 \def\axp@@sectiontestsection#1{\@ifnextchar\section{\makeatother}{\axp@oldsection{#1}\makeatother}

```

`\axp@oldsection` We redefine the `\section` command to create a label based on `axp@seccounter`

`\section` and to store its title in `\axp@sectitle`. In order to support starred and unstarred

`\@section` versions, as well as the optional short-title argument, the intermediate macros

`\@@section` `\@section` and `\@@@section` are needed.

```

440 \let\axp@oldsection\section
441 \def\section{\@ifstar\@section\@@section}
442 \newcommand{\@section}[2][\relax]{\axp@@@section*{#1}{#2}}%
443 \newcommand{\@@section}[2][\relax]{\axp@@@section{}{#1}{#2}}%
444 \newcommand{\axp@@@section}[3]{%
445   \global\def\axp@sectitle{#3}%
446   \ifx\relax#2\relax
447     \axp@oldsection#1{#3}%
448   \else
449     \axp@oldsection#1[{#2}]{#3}%
450   \fi
451   \addtocounter{axp@seccounter}{1}%

```

```

452   \label{axp@s\roman{axp@seccounter}}}%
453 }

```

`\nosectionappendix` We remove the current section title, to indicate no section should be created in the appendix.

```

454 \newcommand{\nosectionappendix}{
455   \global\def\axp@sectitle{}%
456 }

```

`\axp@writesection` If `\axp@sectitle` is not empty, we create a new section in the appendix, referring to the main text section.

Here, we wrap `\ref{axp@si}` into `\axp@protectref@i`, in order to protect the label name from wrongly being converted to uppercase, e.g., in `fancyhdr` with `\pagestyle{fancy}`.

This macro is defined both in the `.aux` file (in order to ensure availability when typesetting the `\tableofcontents`), and immediately before typesetting the appendix section (to ensure availability in the `\section` command).

```

457 \newcommand\axp@writesection{%
458   \ifx\axp@sectitle\@empty
459   \else
460     \edef\axp@tmp{%
461       \noexpand\global\noexpand\def
462       \expandonce{\csname axp@protectref@\roman{axp@seccounter}\endcsname}{%
463         \noexpand\ref{axp@s\roman{axp@seccounter}}}%
464     }%
465   }%
466   \immediate\write\@auxout{\expandonce\axp@tmp}
467   \immediate\write\axp@proofsfile{%
468     \expandonce\axp@tmp^^J%
469     \noexpand\axp@section{%
470       \noexpand\appendixsectionformat{%
471         \protect
472         \expandonce{\csname axp@protectref@\roman{axp@seccounter}\endcsname}%
473       }\expandonce\axp@sectitle}%
474     }%
475   }%
476   \nosectionappendix
477 \fi
478 }

```

Finally, in a somewhat ad hoc manner, we disable the whole section management for `\tableofcontents`, which may be typeset using a section heading, but for which automatic section management does not make sense.

```

\axp@oldtableofcontents
\tableofcontents 479 \let\axp@oldtableofcontents\tableofcontents
480 \def\tableofcontents{{\let\section\axp@oldsection\axp@oldtableofcontents}}

```

7.5.6 Append Compilation Mode

```

481 \ifthenelse{\equal{\axp@appendix}{append}}{

```

`\axp@oldbibliography` Unless the `bibliography` option is set to `common`, we need to set the appendix
`\bibliography` bibliography source to be the same as that of the main text, thanks to `bibunits`'s
`\defaultbibliography` macro.

```

482 \ifthenelse{\equal{\axp@bibliography}{separate}}{
483   \let\axp@oldbibliography\bibliography
484   \renewcommand\bibliography[1]{%
485     \defaultbibliography{#1}%
486     \axp@oldbibliography{#1}%
487   }
488 }{}

```

After the end of the main text, we add the appendix (after the command `\appendixprelim` is issued) within a `bibunit` environment so as to typeset a separate bibliography for the appendix (unless the `bibliography` option is set to `common`). This is done using `\pretocmd` on `\@enddocumenthook` instead of `\AtEndDocument` because we want the code to be run before any code in the `\@enddocumenthook` that has been set in the document class, as in the `amsart` document class. There is an extra test to ensure an empty bibliography environment is not produced. The name of the bibliography is changed to `\appendixrefname`; in most document classes, it is called `\refname` but it is occasionally (`scrartcl`, `scrreprt`) called `\bibname`. An ad-hoc test is added to fix a conflict with the `natbib` package which redefines `bibcite` at the end of the document.

```

489 \pretocmd{\@enddocumenthook}{%
490   \ifdefined\NAT@testdef
491     \renewcommand\bibcite[2]{%
492       \global\@namedef{b@#1\@extra@binfo}{#2}%
493     }
494   \fi
495   \appendixprelim
496   \appendix
497   \ifthenelse{\equal{\axp@bibliography}{separate}}{
498     \begin{bibunit}[\appendixbibliographystyle]
499   }{}
500   \immediate\closeout\axp@proofsfile
501   \input{\jobname.axp}
502   \ifthenelse{\equal{\axp@bibliography}{separate}}{
503     \ifdefined\refname
504       \renewcommand{\refname}{\appendixrefname}
505     \else\ifdefined\bibname
506       \renewcommand{\bibname}{\appendixrefname}
507     \fi\fi
508     \let\axp@oldthebibliography\thebibliography
509     \let\endaxp@oldthebibliography\endthebibliography
510     \renewenvironment{thebibliography}[1]{%
511       \def\axp@tmp{#1}%
512       \ifx\axp@tmp\empty
513         \gdef\axp@noappendixbibliography1\relax
514       \else
515         \begin{axp@oldthebibliography}{#1}%
516       \fi
517     }{%
518       \ifdefined\axp@noappendixbibliography\relax\else\end{axp@oldthebibliography}%
519     \fi}

```

```

520     \appendixbibliographyprelim
521     \putbib
522     \end{bibunit}
523     \ifdefined\NAT@testdef
524     \let\bibcite\NAT@testdef
525     \fi
526     }{}
527   }{}{}
528 }{}

```

7.5.7 Class-Specific Behavior

We conclude with some class-specific behavior.

ACM Document Classes (old versions, till 2017)

```
529 \ifdefined\acmtitlebox
```

We first redefine the `proofsketch` environment, which is used differently in the base class.

```
530 \renewenvironment{proofsketch}{\begin{axp@oldproof}[sketch]}\end{axp@oldproof}}
```

We adjust the styling of theorems for the needs of `apxproof`.

```

531 \newtheoremstyle{mystyle}
532   {6pt}
533   {6pt}
534   {\itshape}
535   {10pt}
536   {\scshape}
537   {.}
538   {.5em}
539   {}
540 \theoremstyle{mystyle}

```

`\thebibliography` The section title of the bibliography is in uppercase in these document classes. In addition, the `\thebibliography` macro hard-codes twice the section title, so we un-hardcode it so that it can be modified in the appendix.

```

\appendixrefname
541   \patchcmd{\thebibliography}{References}{\protect\refname}{}{}
542   \patchcmd{\thebibliography}{References}{\protect\refname}{}{}
543   \newcommand{\refname}{REFERENCES}
544   \renewcommand{\appendixrefname}{REFERENCES FOR THE APPENDIX}

545 \fi

```

lipcs

```
546 \ifdefined\lipics@opterrshort
```

`\appendixbibliographyprelim` The default bibliography in the `lipics` document class formatting is not compatible with the `alpha` bibliography style. We fix this here.

```

547 \renewcommand{\appendixbibliographyprelim}{%
548   \global\let\@oldbiblabel\@biblabel
549   \def\@biblabel{\hspace*{-2em}\small\@oldbiblabel}%
550 }

```

```
551  \fi
552 }
```


Change History

v1.0.0		<code>\axp@writesection</code> : Fix	
General: Initial released version . . .	1	extraneous space after section	
v1.0.1		number in appendix titles . . .	21
General: Prevent empty		<code>axp@newtheoremrep</code> : Better	
bibliography environment; fix		handling of note-free theorems	
typos	1	in document classes that treat	
v1.0.2		theorems differently when they	
<code>axp@newtheoremrep</code> : Fix display of		have an empty note	14
repeated theorem counter in		Fix incorrect use of <code>\noexpand</code>	
some document classes	15	in optional argument of macro	
Fix missing space between		environment	15
repeated theorem counter and		v1.1.0	
theorem note	15	General: Added forward-link	
v1.0.3		mechanism (K. D. Bauer) . . .	16
General: Note on entire sections in		<code>\appendixsectionformat</code> : Fix	
appendix	2	missing space in default	
<code>\appendixbibliographyprelim</code> :		<code>\appendixsectionformat</code> . . .	11
Support for lipics-v2016	23	<code>\axp@proofsfile</code> : Initialization	
<code>proofsketch</code> : Ignore spaces after		deferred to <code>\AtBeginDocument</code>	
beginning of Proof sketch . . .	11	for compatibility with <code>\dumped</code>	
v1.0.4		precompiled preambles (K. D.	
General: More faithful theorem		Bauer)	13
style for ACM templates	23	<code>\axp@redefinlabels</code> : Fix <code>\label</code>	
More robust coherent styling of		not being disabled in <code>amsmath</code>	
proof sketches	23	environments, where	
Re-establish custom proof		<code>\label@in@display</code> is used	
environments	8	instead (K. D. Bauer)	11
Show options commented on in		<code>\axp@repeqn</code> : <code>repeqn</code> option	9
margin and index	1	<code>\axp@unactivateeightbit</code> : Fix	
<code>\appendixprelim</code> : Configurable		compilation of non-ASCII	
appendix style	11	characters with	
<code>\axp@bibliography</code> : bibliography		<code>\usepackage[utf8]{inputenc}</code>	
option	9	13
v1.0.5		<code>\axp@writesection</code> : Make	
General: Ability to specify a		<code>\axp@tmp</code> wrapper more robust.	
sectioning counter in		Resolves issues from use of	
<code>newtheoremrep</code>	2	section title in <code>fancyhdr</code> , and in	
Fix compilation of <code>proofsketch</code>		<code>\tableofcontents</code> (K. D.	
environment in inline mode . . .	3	Bauer).	21
v1.0.6		<code>\FVE@axp@VerbatimOut</code> : Make	
General: Better support of Springer		<code>apxproof</code> compatible with	
document classes	11	independent use of <code>fancyvrb</code> . .	13
Deal with document classes		<code>\section</code> : Fix handling of fragile	
where the bibliography is called		macros within section headings.	
<code>\bibname</code>	22	See #22.	20
Support of new ACM document		Rewrote definition of <code>\section</code>	
class (<code>acmart.cls</code>)	23	to enable optional argument.	
<code>\axp@newtheorem</code> : Introduce		See #23. (K. D. Bauer)	20
intermediary command for		<code>\tableofcontents</code> : Disable section	
theorem macro	10	management for table of	
		contents	21

v1.2.0	of fancyvrb that set	
General: Do not load bibunits if	\FV@CatCodesHook	13
bibliography is set to common		9
\axp@newtheoremrep: Fix	General: Compatibility with AMS	
formatting of theorems without	document classes: do not use	
notes in some document classes	\AtEndDocument	22
in inline mode	\axp@section: Detect a section	
	within an included file to avoid	
\axp@newtheoremrep@definetheorem:	produced useless sections	20
Restore predefined theorem	axp@newtheoremrep: Fix handling	
counters	of optional arguments of	
	repeated theorems containing	
\axp@redefinelabels: Fix extra	optional arguments	14
spacing erroneously introduced		
within the	v1.2.3	
\axp@redefinelabels macro	General: More robust redefinition of	
	thebibliography environment,	
\mainbodyrepeatedtheorem:	for compatibility with tocibind	22
Configurable repeated theorem	\axp@forwardlinking:	
command	forwardlinking option	9
proofsketch: Fix proof sketches in		
inline compilation mode for	v1.2.4	
Springer document classes	appendixproof: Support optional	
	arguments in proofs	18
axp@newtheoremrep: Fix display of	claimproof: Support for	
theorem notes	claimproof environment from	
	lipics	19
v1.2.1	v1.2.4-dev	
General: Ad hoc fix for natbib	claimproof: Support for locally	
package conflict	defined claimproof	
	environment	19
\appendixrefname: Fix	axp@forward: Remove forward	
compatibility with memoir	linking command from PDF	
document class	bookmarks	17
\FVE@axp@VerbatimOut: Fix		
compatibility with xypic		
package		
Fix compatibility with other uses		

Index

Numbers written in *italic* refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; numbers in roman refer to the code lines where the entry is used.

Symbols	\@enddocumenthook	489
\@@appendixproof	\@esphack	203
\@@axp@newtheorem	\@extra@binfo	492
\@@section	\@ifnextchar	333, 388, 430, 439
\@acmplainnotefont	\@ifpackageloaded	7
\@acmttitlebox	\@ifstar	81, 441
\@appendixproof	\@namedef	492
\@auxout	\@ne	186
\@axp@newtheorem	\@noligs	198
\@begintheorem	\@oldbiblabel	548, 549
\@biblabel	\@oparg	93, 96
\@bsphack	\@section	440

<code>\@thmcountersep</code>	143	<code>\exp@oldthebibliography</code>	508
<code>_</code>	36, 45, 53, 62, 104	<code>\exp@proof</code>	358, 359
<code>\^</code>	333, 358, 387, 388	<code>\exp@proofsfile</code>	167, 172, 196, 202, 233, 235, 245, 280, 337, 345, 353, 416, 467, 500
A			
<code>\active</code>	333, 358, 387, 388	<code>\exp@redefinlabels</code>	107, 150, 152, 274
<code>\advance</code>	186	<code>\exp@refstar</code>	241, 243, 258
<code>\appendix</code>	496	<code>\exp@repeqn</code> 26, 48, 50, 53, 62, 217, 234, 279
<code>appendix (option)</code>	4	<code>\exp@rpcounter</code>	208
<code>\appendixbibliographyprelim</code>	5, 99, 520, 547	<code>\exp@seccounter</code>	427
<code>\appendixbibliographystyle</code>	5, 99, 498	<code>\exp@section</code>	429, 469
<code>\appendixclaimproof</code>	388, 392, 400	<code>\exp@sectitle</code>	428, 445, 455, 458, 473
<code>\appendixprelim</code>	5, 99, 495	<code>\exp@seenrepththeorem</code>	207
<code>\appendixproof</code>	160, 333, 362, 370	<code>\exp@tmp</code>	435, 437, 460, 466, 468, 511, 512
<code>appendixproof (env.)</code>	2, 156, 333	<code>\exp@tmptmp</code>	436, 437
<code>\appendixrefname</code>	5, 99, 504, 506, 541	<code>\exp@unactivateeightbit</code>	181, 192
<code>\appendixsectionformat</code>	5, 99, 470	<code>\exp@VerbatimOut</code>	205, 340, 348
<code>\apx@oldamsthmndproof</code>	10, 17	<code>exp@VerbatimOut (env.)</code>	188
<code>\apx@oldamsthmproof</code>	9, 15, 16	<code>\exp@with@forward</code>	222, 224, 286
<code>\AtBeginDocument</code>	167, 171, 383	<code>\exp@writesection</code>	205, 232, 336, 344, 457
<code>\exp@@@section</code>	442, 443, 444	B	
<code>\exp@claimproof</code>	387, 397	<code>\bfseries</code>	131, 133, 136, 140
<code>\exp@proof</code>	358, 367	<code>\bibcite</code>	491, 524
<code>\exp@sectiontestinput</code>	429	<code>\bibliography</code>	482
<code>\exp@sectiontestsection</code>	429	<code>bibliography (option)</code>	4
<code>\exp@appendix</code>	24, 29, 31, 33, 36, 109, 145, 287, 481	<code>\bibname</code>	505, 506
<code>\exp@bibliography</code>	25, 39, 42, 45, 482, 497, 502	<code>\BODY</code>	150, 152, 227, 231
<code>\exp@claimproof</code>	387, 389	<code>\boolfalse</code>	301
<code>\exp@equation</code>	209	<code>\booltrue</code>	60, 288
<code>\exp@equationx</code>	209	C	
<code>\exp@forward</code>	303	<code>\CatchFileDef</code>	435
<code>\exp@forward@link</code>	293, 303	<code>\catcode</code>	184, 333, 358, 387, 388
<code>\exp@forward@setup</code>	215, 327	<code>\claimproof</code>	176, 384, 385, 387
<code>\exp@forward@suppress</code>	56	<code>claimproof (env.)</code>	383
<code>\exp@forward@target</code>	273, 320	<code>\clearpage</code>	103
<code>\exp@forwardlinking</code>	27, 57, 58	<code>\closeout</code>	500
<code>\exp@newtheorem</code>	72, 81, 214	<code>\count@</code>	182, 184, 185, 186
<code>\exp@newtheoremrep</code>	96, 146, 211, 211	<code>\csdef</code>	292
<code>\exp@newtheoremrep@definetheorem</code>	65, 147, 212	<code>\csedef</code>	328
<code>\exp@newtheoremreptmp</code>	92	<code>\csletcs</code>	290, 291, 299
<code>\exp@noappendixbibliography</code>	513, 518	D	
<code>\exp@oldbibliography</code>	482	<code>\DeclareStringOption</code>	24, 25, 26, 27
<code>\exp@oldclaimproof</code>	176, 385, 394, 402	<code>\defaultbibliography</code>	485
<code>\exp@oldlabel</code>	110, 113, 114, 118, 121, 123	<code>\DefineVerbatimEnvironment</code>	188
<code>\exp@oldlabel@in@display</code>	111, 117, 122, 124	E	
<code>\exp@oldproof</code>	105, 174, 364, 372, 423, 425	<code>\empty</code>	512
<code>exp@oldproof (env.)</code>	105	<code>\endappendixclaimproof</code>	408, 413
<code>\exp@oldsection</code>	178, 439, 440, 480	<code>\endappendixproof</code>	161, 350, 378
<code>\exp@oldtableofcontents</code>	479	<code>\endexp@oldclaimproof</code>	177, 386, 410
		<code>\endexp@oldproof</code>	106, 175, 380, 424, 426

<code>\endaxp@oldthebibliography</code>	509		
<code>\endaxp@VerbatimOut</code>	206, 352, 415		
<code>\endclaimproof</code>	177, 386, 405		
<code>\endinlineproof</code>	157, 424		
<code>\endnestedproof</code>	159, 426		
<code>\endproof</code>	10,		
	12, 17, 106, 157, 159, 161, 175, 375		
<code>\endthebibliography</code>	509		
environments:			
<code>appendixproof</code>	2, 156, 333		
<code>axp@oldproof</code>	105		
<code>axp@VerbatimOut</code>	188		
<code>claimproof</code>	383		
<code>inlineproof</code>	3, 156, 423		
<code>nestedproof</code>	5, 156, 423		
<code>proof</code>	3, 171, 358		
<code>proofsketch</code>	3, 98		
<code>toappendix</code>	1, 162, 204		
<code>\errmessage</code>	36, 45, 53, 62		
<code>\expandonce</code>	462, 466, 468, 472, 473		
		F	
<code>forwardlinking</code> (option)	5		
<code>\FV@CatCodesHook</code>	199		
<code>\FV@DefineTabOut</code>	195		
<code>\FV@DefineWhiteSpace</code>	193		
<code>\FV@FontScanPrep</code>	197		
<code>\FV@ProcessLine</code>	196		
<code>\FV@Scan</code>	200		
<code>\FV@Space</code>	194		
<code>\FVB@axp@VerbatimOut</code>	188		
<code>\FVE@axp@VerbatimOut</code>	188		
		G	
<code>\gdef</code>	513		
		H	
<code>\hspace</code>	549		
<code>\hyperlink</code>	309		
<code>\hypertarget</code>	322		
		I	
<code>\ifblank</code>	328		
<code>\ifbool</code>	240		
<code>\ifboolexpr</code>	307		
<code>\ifcsdef</code>	298, 308		
<code>\ifcsname</code>	67, 73, 321		
<code>\ifcsundef</code>	289		
<code>\ifnum</code>	185		
<code>\inlineproof</code>	156, 423		
<code>\inlineproof</code> (env.)	3, 156, 423		
<code>\input</code>	430, 434, 501		
<code>\itshape</code>	131, 133, 136, 140, 534		
		L	
<code>\label</code>	110, 112, 121, 123, 222, 224, 452		
<code>\label@in@display</code>	108, 111, 116, 122, 124		
<code>\lipics@opterrshort</code>	546		
<code>\loop</code>	183		
<code>\ltx@ifnextchar@nospace</code>	358, 387		
		M	
<code>\mainbodyrepeatedtheorem</code>	5, 99, 226		
<code>\message</code>	30, 32, 34, 41, 43, 49, 51, 59		
		N	
<code>\NAT@testdef</code>	490, 523, 524		
<code>\nestedproof</code>	158, 425		
<code>nestedproof</code> (env.)	5, 156, 423		
<code>\newbool</code>	56, 303		
<code>\newtheorem</code>	84, 86, 90		
<code>\newtheoremrep</code>	2, 92		
<code>\newtheoremstyle</code>	531		
<code>\noproofinappendix</code>			
	6, 162, 213, 330, 356, 419		
<code>\nosectionappendix</code>	6, 162, 454, 476		
		O	
<code>\onecolumn</code>	103		
<code>\openout</code>	169		
options:			
<code>appendix</code>	4		
<code>bibliography</code>	4		
<code>forwardlinking</code>	5		
<code>repeqn</code>	5		
		P	
<code>\pretocmd</code>	213, 249, 489		
<code>\ProcessLocalKeyvalOptions</code>	28		
<code>\proof</code>	9,		
	11, 16, 105, 156, 158, 160, 174, 358		
<code>proof</code> (env.)	3, 171, 358		
<code>\proofsketch</code>	142		
<code>proofsketch</code> (env.)	3, 98		
<code>\providecommand</code>	100, 108		
<code>\putbib</code>	521		
		R	
<code>\ref</code>	241, 243, 463		
<code>\refname</code>	503, 504, 541		
<code>\repeat</code>	187		
<code>repeqn</code> (option)	5		
		S	
<code>\scshape</code>	536		
<code>\section</code>	171, 439, 440, 480		
<code>\setcounter</code>	218, 236, 237, 281		
<code>\SetupKeyvalOptions</code>	20		
<code>\small</code>	549		
<code>\spnewtheorem</code>	127, 131, 133, 136, 140		

T		\togglefalse 331	
\tableofcontents 479	\toggletrue 228
\texorpdfstring 305, 306	U	
\the 251, 266	\upshape 140
\theexp@equation 237	V	
\thebibliography 508, 541	\value 218, 236, 281
\theopargself 246, 247, 260	W	
\theoremstyle 540	\write	. 172, 196, 202, 233, 235, 245,
\thm@notefont 251, 265, 266		280, 337, 345, 353, 416, 466, 467
\thmhead 250, 251, 252, 253		
toappendix (env.) 1, 162, 204		

References

- [1] Leslie Lamport. *L^AT_EX: A Document Preparation System*. Addison–Wesley Pub. Co., Reading, MA, 1986.

A Proofs for Section 1 (Usage)

Proof.

□

Foobar 2. *This foobar is repeated in the appendix.*

Proof.

□