

The `apxproof` package

Pierre Senellart

`pierre@senellart.com`

<http://github.com/PierreSenellart/apxproof>

2019/10/08 v1.2.0-dev

Abstract

This package makes it easier to write articles where proofs and other material are deferred to the appendix. The appendix material is written in the \LaTeX code along with the main text which it naturally complements, and it is automatically deferred. The package can automatically send proofs to the appendix, can repeat in the appendix the theorem environments stated in the main text, can section the appendix automatically based on the sectioning of the main text, and supports a separate bibliography for the appendix material.

1 Usage

The `apxproof` package is intended to simplify the writing of articles where some of the content needs to be deferred to an appendix. This is in particular useful for the submission of scientific articles to conferences or journals that limit the number of pages in the main text but allow an extra appendix, where proofs of theorems and other material can be added.

1.1 Basics

To use `apxproof`, first load it in the header of your document:

```
\usepackage{apxproof}
```

On its own, this does not do anything and should not change the appearance of your document. To add an appendix with some material from your document, use the `toappendix` environment:

```
toappendix \begin{toappendix}
            ...
            \end{toappendix}
```

The content will appear at the end of your document, in an automatically generated section that refers to the current section in the main text.

Example 1. *Throughout this documentation, all examples produce content deferred to the appendix, at the very end of this document.*

```
\begin{toappendix}
This content is in the appendix.
\end{toappendix}
```

When the content to put in appendix is an entire section, make sure that `\section` is the very first command that appears within the `toappendix` environment. It will disable the automatic production of a section heading.

1.2 Repeated Theorems and Proofs

In some scientific papers that include proofs, it is common to defer proofs to the appendix. This can easily be achieved using the `appendixproof` environment:

```
appendixproof    \begin{appendixproof}
                  ...
                  \end{appendixproof}
```

This behaves like the `toappendix` environment, except that a proof environment is generated.

Example 2. *We now send a proof to the appendix:*

```
\begin{appendixproof}
This proof is in the appendix.
\end{appendixproof}
```

When deferring proofs to the appendix, an annoying problem is that the statement of the theorem remains in the main text; it is hard to read a proof that is far away from the statement it proves. `apxproof` solves this issue by allowing statements of theorems to be *repeated*: once in the main text, and once in the appendix before the proof of the statement. To use this feature, you can define a new *repeated theorem* environment using the `\newtheoremrep` command:

```
\newtheoremrep    \newtheoremrep{<name>}[<counter>]{<title>}[<countersec>]
```

Usage is exactly the same as that of AMS L^AT_EX's `\newtheorem` macro:

- `<name>` (e.g., `theorem`) is the name of an environment that is created for this kind of theorem;
- `<counter>` (e.g., `definition`) is an optional counter describing from which kind of environment the numbering of these environments should be inherited;
- `<title>` (e.g., `Theorem`) is the title that will be used to display this theorem environment;

- `\countersec` (e.g., `\section`) is an optional counter of a sectioning command indicating that counters for this theorem should be prefixed by this counter (and reset at each occurrence of the sectioning command).

`\counter` and `\countersec` should not be used together. What differs from `\newtheorem` is that, when the following is written:

```
\newtheoremrep{foobar}{Foobar}
```

then *two* environments are defined: the `foobar` environment, which behaves as if `\newtheorem` had been used, and the `foobarrep` environment, which results in the statement of this environment being repeated in the appendix.

One interesting feature of `apxproof` is that in most situations, there is no need to use the `appendixproof` environment. Indeed, the `proof` environment is redefined by `apxproof` to automatically put the proof either in the main text (if it follows a regular theorem) or in the appendix (if it follows a repeated theorem).

Example 3. Assume we have first defined a repeated theorem environment `foobar` as above. We can now use this theorem environment, first for a regular theorem in the main text, then for a theorem repeated in the main text and in the appendix:

```
\begin{foobar}
This foobar is a regular one, in the main text.
\end{foobar}
\begin{proof}
This is the proof of the regular foobar.
\end{proof}
```

We obtain:

Foobar 1. *This foobar is a regular one, in the main text.*

Proof. This is the proof of the regular foobar. □

Now, if we use a repeated theorem:

```
\begin{foobarrep}
This foobar is repeated in the appendix.
\end{foobarrep}
\begin{proof}
This is the proof of the repeated foobar.
\end{proof}
```

We now obtain:

Foobar 2. *This foobar is repeated in the appendix.*

Note that, since `hyperref` is loaded, there are hyperlinks created between the statements of the theorems in the main text and in the appendix.

When the proof is deferred to the appendix, it is common practice to add a proof sketch in the main text. `apxproof` defines a simple `proofsketch` environment for this purpose:

```
proofsketch      \begin{proofsketch}
                  ...
                  \end{proofsketch}
```

The proof sketch is typeset similarly to a proof, but is always in the main text. Similarly, an `inlineproof` environment is provided so as to be able to have both a proof in the appendix (using the regular `proof` environment, or alternatively the `appendixproof` environment) and a different proof in the main text (using the `inlineproof` environment).

Example 4. *Here are simple examples of proof sketches and inline proofs:*

```
\begin{proofsketch}
This is a proof sketch.
\end{proofsketch}
```

Proof sketch. This is a proof sketch. □

```
\begin{inlineproof}
This is an inline proof.
\end{inlineproof}
```

Proof. This is an inline proof. □

1.3 Bibliography

By default, `apxproof` automatically adds a bibliography in the appendix with only the references cited in the appendix material. This allows for a clean separation of references used solely in the main text, and those used in the appendix.

Example 5. *Assume we have citations both in the main text and in the appendix.*

```
This is a citation in the main text~\cite{lamport86}.
\begin{toappendix}
This is a citation in the appendix~\cite{proofsAreHard}.
\end{toappendix}
```

This is a citation in the main text [1].

The bibliography in the appendix can use a different style and heading than the bibliography in the main text (and, by default, it does). See Section 1.5 for how to configure the appearance of that bibliography.

option `bibliography` In order to use a single appendix for the main text and the bibliography, one can specify the value `common` to the `bibliography` option when loading the package. (By default this option is set to `separate`.)

1.4 Mode

option An optional $\langle mode \rangle$ can be specified when loading the package:
appendix `\usepackage[appendix= $\langle mode \rangle$]{apxproof}`

$\langle mode \rangle$ can take one of the following three values:

append This is the default. Appendix material gathered by `apxproof` is appended to the main text.

inline In this mode, `apxproof` simply inlines the content along with the main text.

strip This mode functions similarly to **append** except that the appendix is not appended at the end of the document. All appendix material is therefore removed.

1.5 Customization

`apxproof` provides a few macros that can be redefined (using `\renewcommand`) to customize the appearance of the appendix:

<code>\mainbodyrepeatedtheorem</code>	<code>\mainbodyrepeatedtheorem</code> is a macro that is executed at the beginning of the body of every repeated theorem. This can be used to notify the reader that the theorem is repeated in appendix in some way, e.g., with a margin note.
<code>\appendixsectionformat</code>	<code>\appendixsectionformat{$\langle number \rangle$}{$\langle title \rangle$}</code> is a macro that indicates how to format the section titles in the Appendix, given the number and title of the section in the main text. By default, they appear as “Proofs for Section $\langle number \rangle$ ($\langle title \rangle$)”.
<code>\appendixrefname</code>	<code>\appendixrefname</code> contains the heading that is displayed before the bibliography. By default, this is “References for the Appendix”.
<code>\appendixbibliographystyle</code>	<code>\appendixbibliographystyle</code> contains the <code>.bst</code> bibliography style that is used in the bibliography in appendix. By default, this is <code>alpha</code> .
<code>\appendixbibliographyprelim</code>	<code>\appendixbibliographyprelim</code> contains arbitrary code that is executed just before the production of the bibliography in appendix, which can be used to configure the way it is displayed.
<code>\appendixprelim</code>	<code>\appendixprelim</code> contains arbitrary code that is executed just before the production of the appendix, which can be used to configure the way it is displayed. By default, this command contains <code>\clearpage\onecolumn</code> (the appendix is typeset on a new page in single-column mode) but redefining this option allows changing this behavior.
<i>option</i> repeqn	Another customization capability concerns <i>numbered equations</i> that are present within repeated theorems. An optional repeqn option can be specified when loading the package, which controls whether equation numbers should be as in the main text (by setting this option to same , the default) or independently numbered (by

setting this option to `independent`). In the latter case, whenever a referenceable counter is set with `\label{<counter>}`, `\ref{<counter>}` references the counter in the main text, while `\ref{<counter>-apx}` references the counter in the appendix (except in `inline` mode, where both have the same effect).

1.6 Advanced Features

We now describe a few advanced macros and environments, the usage of which is limited to special cases:

<code>nestedproof</code>	<code>nestedproof</code> is an environment that can be used within a <code>proof</code> environment deferred in the appendix; this is required because, for technical reasons, no <code>proof</code> environment can be nested within a deferred <code>proof</code> environment.
<code>\noproofinappendix</code>	<code>\noproofinappendix</code> can be used inside repeated theorems that are not followed by a <code>proof</code> or <code>appendixproof</code> environment; the point is to ensure that a further <code>proof</code> environment cannot be mistakenly understood as a proof of the repeated theorem. It should not be needed in most situations as <code>apxproof</code> tries figuring out when a proof follows a repeated theorem automatically, but may occasionally be needed in complex scenarios.
<code>\nosectionappendix</code>	<code>\nosectionappendix</code> is to be used inside a section that <i>does</i> contain appendix material, but for which a section in the appendix should not be created. This should be rarely needed. When this command is present, appendix material is appended to the end of the previously created section.

2 Supported Document Classes

Because `apxproof` modifies sectioning commands, bibliographies, and proofs, it may not work straight away with arbitrary document classes. It has currently been tested with and is supported for the following document classes:

- L^AT_EX standard document classes (e.g., `article.cls`)
- KOMA-Script (e.g., `scrartcl.cls`, `scrbook.cls`)
- ACM SIG Proceedings (e.g., `sig-alternate.cls`, `acmart.cls`)
- Springer's Lecture Notes in Computer Science (e.g., `llncs.cls`)
- Schloß Dagstuhl's Leibniz International Proceedings in Informatics (e.g., `lipics.cls`, `lipics-v2016.cls`)

Other classes may work out of the box. Adding support for specific classes is possible and can be requested from the author of this package.

3 Known Issues and Limitations

We report here some issues we are currently aware of:

- When using `hyperref`, the appendix in the bibliography is not hyperlinked. This is to avoid possible issues with multiply defined bibliography entries.
- `appendixproof`, `proof`, `toappendix` environments cannot be nested. This is a limitation of the `fancyvrb` package that `apxproof` relies on. Note the existence of the `nestedproof` environment for nested proofs.
- `apxproof` poorly interacts with `SyncTeX`: identifying which source line has produced which box does not work for appendix content managed by `apxproof` or repeated theorems. No obvious fix is known, though this issue will be investigated in the long term.
- Unless the `bibliography` option is set to `common`, the `bibunits` package is used to generate a second bibliography. This means any package, such as `biblatex`, that is incompatible with `bibunits` will not be compatible with `apxproof` unless `bibliography` is set to `common`.

Issues not listed here should be reported to the author.

4 License

Copyright © 2016–2019 by Pierre Senellart.

This work may be distributed and/or modified under the conditions of the L^AT_EX Project Public License, either version 1.3 of this license or (at your option) any later version. The latest version of this license is in <http://www.latex-project.org/lppl.txt> and version 1.3 or later is part of all distributions of L^AT_EX version 2005/12/01 or later.

5 Contact

- <https://github.com/PierreSenellart/apxproof>
- Pierre Senellart <pierre@senellart.com>

Bug reports and feature requests should preferably be submitted through the *Issues* feature of GitHub.

6 Acknowledgments

Thanks to Antoine Amarilli for feedback and proofreading. Thanks to K. D. Bauer for the implementation of the forward-linking mechanism, and for various bugfixes.

7 Implementation

We now describe the entire code of the package, in a literate programming fashion. Throughout the package, we use the `axp@` prefix to identify local macros and environment names, which are not meant to be used by the final user.

7.1 Dependencies

We first load a few package dependencies:

- `environ` to easily define the repeated theorem environments.

```
1 \RequirePackage{environ}
```

- `etoolbox` to define simple toggles.

```
2 \RequirePackage{etoolbox}
```

- `fancyvrb` for the bulk of the work of exporting appendix material in an auxiliary file.

```
3 \RequirePackage{fancyvrb}
```

- `ifthen` for easier comparison of character strings.

```
4 \RequirePackage{ifthen}
```

- `kvoptions` to manage options passed to the package.

```
5 \RequirePackage{kvoptions}
```

- `amsthm` for its `\newtheorem` macro. Some document classes (e.g., `lipics`) preload `amsthm`: this is fine, `\RequirePackage{amsthm}` will simply have no effect. On the other hand, some other document classes (e.g., `llncs` or `sig-alternate`) define a `proof` environment that conflicts with `amsthm`, so we have to undefine this environment before loading `amsthm`. In that case, we reestablish the existing proof environments, in case they had been customized (e.g., `sig-alternate`)

```
6 \@ifpackageloaded{amsthm}{  
7   }{  
8     \let\apx@oldamsthmproof\proof  
9     \let\apx@oldamsthmendproof\endproof  
10    \let\proof\undefined  
11    \let\endproof\undefined  
12  }  
13  \RequirePackage{amsthm}  
14  \ifdefined\apx@oldamsthmproof  
15    \let\proof\apx@oldamsthmproof  
16    \let\endproof\apx@oldamsthmendproof  
17  \fi
```


7.2 Option Processing

Many names throughout the package use an arobase (@) to avoid name conflict with user-defined names. To simplify the compilation of the documentation, we simply make it a regular character in all the rest.

```
18 \makeatletter
```

We setup the processing of options using `keyval` facilities.

```
19 \SetupKeyvalOptions{
20   family=axp,
21   prefix=axp@
22 }
```

We declare the following options:

- `append`, with a default value of `append` (other possible values: `strip`, `inline`);
- `bibliography`, with a default value of `separate` (other possible value: `common`);
- `repeqn`, with a default value of `same` (other possible value: `independent`).

```
\axp@appendix
```

```
23 \DeclareStringOption[append]{appendix}
```

```
\axp@bibliography
```

```
24 \DeclareStringOption[separate]{bibliography}
```

```
\axp@repeqn
```

```
25 \DeclareStringOption[same]{repeqn}
```

```
26 \ProcessLocalKeyvalOptions*
```

We check that the value of the options are valid, and add a message to the compilation log.

```
27 \ifthenelse{\equal{\axp@appendix}{append}}{
28   \message{apxproof: Appendix material appended to the document}
29 }{\ifthenelse{\equal{\axp@appendix}{strip}}{
30   \message{apxproof: Appendix material stripped}
31 }{\ifthenelse{\equal{\axp@appendix}{inline}}{
32   \message{apxproof: Appendix material inlined within the document}
33 }{
34   \errmessage{Error: unsupported option appendix=\axp@appendix\ for
35   package apxproof}
36 }}}
37 \ifthenelse{\equal{\axp@bibliography}{separate}}{
```

The external `bibunits` package is used to add a second bibliography for the appendix material.

```
38 \RequirePackage{bibunits}
```

```

39 \message{apxproof: Separate bibliography for appendix material}
40 }\ifthenelse{\equal{\axp@bibliography}{common}}{\
41 \message{apxproof: Common bibliography for appendix and main text}
42 }{
43 \errmessage{Error: unsupported option bibliography=\axp@bibliography\ for
44 package apxproof}
45 }}
46 \ifthenelse{\equal{\axp@repeqn}{same}}{\
47 \message{apxproof: Repeated equations keep the same numbering}
48 }\ifthenelse{\equal{\axp@repeqn}{independent}}{\
49 \message{apxproof: Repeated equations are independently numbered}
50 }\
51 \errmessage{Error: unsupported option repeqn=\axp@repeqn\ for
52 package apxproof}
53 }}

```

7.3 Macros Common to All Compilation Modes

`\axp@newtheoremrep@definetheorem` Common to all compilation modes, we define `\axp@newtheoremrep@definetheorem`. When called with first argument `foobar`, we first undefine the existing `foobar` environment (and its counter) if it has already been defined (e.g., by the document class), then invoke `\axp@newtheorem` for the regular version of the theorem `foobar`, saving and restoring any existing theorem counter unless the `\newtheoremdep` redefines the base counter.

```

54 \def\axp@newtheoremrep@definetheorem#1#2#3#4{%
55 \expandafter\let\csname #1\endcsname\undefined
56 \ifcsname c@#1\endcsname
57 \expandafter\expandafter\expandafter\let\expandafter\expandafter
58 \csname c@axp@#1\endcsname\csname c@#1\endcsname
59 \expandafter\let\csname c@#1\endcsname\undefined
60 \fi
61 \axp@newtheorem{#1}{#2}{#3}{#4}%
62 \ifcsname c@axp@#1\endcsname
63 \ifx\relax#2\relax
64 \expandafter\expandafter\expandafter\let\expandafter\expandafter
65 \csname c@#1\endcsname\csname c@axp@#1\endcsname
66 \else
67 \fi
68 \fi
69 }

```

`\axp@newtheorem` We introduce an intermediate `\axp@newtheorem` command to define a new theorem, differently depending on whether there is a section counter or not. This will be
`\@axp@newtheorem` useful, in particular to allow changing this definition depending on the document
`\@@axp@newtheorem` class. This command uses two intermediary commands, `\@axp@newtheorem` and `\@@axp@newtheorem`, for the non-starred and starred versions.

```

70 \def\axp@newtheorem{\ifstar\@axp@newtheorem\@axp@newtheorem}
71 \def\@axp@newtheorem#1#2#3#4{%

```

```

72 \ifx\relax#4\relax
73   \newtheorem{#1}[#2]{#3}%
74 \else
75   \newtheorem{#1}{#3}[#4]%
76 \fi
77 }
78 \def\@@axp@newtheorem#1#2{%
79   \newtheorem*{#1}{#2}%
80 }

```

`\newtheoremrep` We define the high-level `\newtheoremrep` to have the same syntax as `amsthm`'s `\axp@newtheoremreptmp` `\newtheorem`. For this purpose, we need a little trick to deal with the second and fourth optional arguments, which is what `\@oparg` and `\axp@newtheoremreptmp` are used for. `\axp@newtheoremrep` is defined differently depending on the compilation mode.

```

81 \newcommand\newtheoremrep[1]{%
82   \@oparg{\axp@newtheoremreptmp{#1}}[]%
83 }
84 \def\axp@newtheoremreptmp#1[#2]#3{%
85   \@oparg{\axp@newtheoremrep{#1}[#2]{#3}}[]%
86 }

```

`proofsketch` Simple `proofsketch` environment.

```

87 \newenvironment{proofsketch}{\begin{axp@oldproof}[Proof sketch]}\end{axp@oldproof}}

```

`\mainbodyrepeatedtheorem` We provide sensible defaults for these user-customizable macros. Even though
`\appendixrefname` they are not all useful in all modes, we define them for all modes so that a
`\appendixbibliographystyle` `\renewcommand` works in all cases.

```

88 \newcommand{\mainbodyrepeatedtheorem}{}
89 \newcommand{\appendixrefname}{References for the Appendix}
90 \newcommand{\appendixbibliographystyle}{alpha}
91 \newcommand{\appendixbibliographyprelim}{}
92 \newcommand{\appendixprelim}{\clearpage\onecolumn}
93 \newcommand{\appendixsectionformat}[2]{Proofs for Section~#1\ (#2)}

```

`axp@oldproof` We save the definition of the existing `proof` environment.

```

94 \let\axp@oldproof\proof
95 \let\endaxp@oldproof\endproof

```

We define a utility macro that will be used to properly set the `\label` command (and its `amsmath` counterpart, `\label@in@display`) for equations within repeated theorems, depending on the compilation mode.

`\axp@redefinelabels`

```

96 \newcommand{\axp@redefinelabels}{%
97   \providecommand\label@in@display{}%
98   \ifthenelse{equal{\axp@appendix}{inline}}{%
99     \let\axp@oldlabel\label
100    \let\axp@oldlabel@in@display\label@in@display

```

```

101     \renewcommand\label[1]{%
102         \axp@oldlabel{##1}%
103         \axp@oldlabel{##1-axp}%
104     }%
105     \renewcommand\label@in@display[1]{%
106         \axp@oldlabel@in@display{##1}%
107         \axp@oldlabel{##1-axp}%
108     }%
109 }{%
110     \let\axp@oldlabel\label
111     \let\axp@oldlabel@in@display\label@in@display
112     \renewcommand\label[1]{\axp@oldlabel{##1-axp}}%
113     \renewcommand\label@in@display[1]{\axp@oldlabel@in@display{##1-axp}}%
114 }%
115 }

```

7.3.1 Class-Specific Behavior

Finally, some class-specific behavior common to all compilation modes.

llncs and other Springer document classes

```

116     \ifdefined\spnewtheorem

\@axp@newtheorem It is necessary to use \spnewtheorem instead of \newtheorem in Springer document
\@axp@newtheorem classes to obtain standard formatting.

117 \def\@axp@newtheorem#1#2#3#4{%
118     \ifx\relax#4\relax
119         \ifx\relax#2\relax
120             \spnewtheorem{#1}{#3}{\bfseries}{\itshape}%
121         \else
122             \spnewtheorem{#1}[#2]{#3}{\bfseries}{\itshape}%
123         \fi
124     \else
125         \spnewtheorem{#1}{#3}[#4]{\bfseries}{\itshape}%
126     \fi
127 }
128 \def\@axp@newtheorem#1#2{%
129     \spnewtheorem*{#1}{#2}{\upshape\bfseries}{\itshape}%
130 }

proofsketch We redefine the proofsketch environment, which is used differently in the base
              class.
131 \renewenvironment{proofsketch}{\begin{axp@oldproof}[sketch]}\end{axp@oldproof}}

We have to redefine the macro \@thmcountersep for proper sectioned counters.
132 \def\@thmcountersep{.}
133 \fi

```

7.4 Inline Compilation Mode

```

134 \ifthenelse{\equal{\axp@appendix}{inline}}{
\axp@newtheoremrep In inline mode, \axp@newtheoremrep uses \axp@newtheoremrep@definetheorem
to define the regular theorem environment and creates a repeated theorem envi-
ronment that behaves exactly as the regular theorem environment, while calling
\axp@redefinelabels to make sure that -axp variants of equation counters are
defined.
135 \def\axp@newtheoremrep#1[#2]#3[#4]{%
136 \axp@newtheoremrep@definetheorem{#1}{#2}{#3}{#4}%
137 \NewEnviron{#1rep}[1][]{%
138 \ifx\relax##1\relax
139 \begin{#1}\axp@redefinelabels\BODY\end{#1}%
140 \else
141 \begin{#1}[##1]\axp@redefinelabels\BODY\end{#1}%
142 \fi
143 }
144 }

inlineproof In inline mode, these environments behave like the regular proof environment.
nestedproof 145 \let\inlineproof\proof
appendixproof 146 \let\endinlineproof\endproof
147 \let\nestedproof\proof
148 \let\endnestedproof\endproof
149 \let\appendixproof\proof
150 \let\endappendixproof\endproof

toappendix In inline mode, this environment and these macros are no-ops.
\noproofinappendix 151 \newenvironment{toappendix}{}{}
\nosectionappendix 152 \let\noproofinappendix\relax
153 \let\nosectionappendix\relax
154 }

```

7.5 Append or Strip Compilation Modes

```
155 {
```

We now deal with the case where apxproof really does something useful: either append the appendix material to the document, or strip it entirely.

7.5.1 Auxiliary File for the Appendix

```

\axp@proofsfile We open a new auxiliary file, with extension .axp, where the appendix material
will be dumped.
156 \AtBeginDocument{
157 \newwrite\axp@proofsfile
158 \immediate\openout\axp@proofsfile=\jobname.axp
159 }

```

`proof` At the beginning of this file, we make `@` a regular character (since it will be used
`\section` in several places for internal names) and reestablish the original definition of the
`proof` environment and the `\section` macro.

```

160 \AtBeginDocument{
161   \immediate\write\axp@proofsfile{%
162     \noexpand\makeatletter
163     \noexpand\let\noexpand\proof\noexpand\axp@oldproof
164     \noexpand\let\noexpand\endproof\noexpand\endaxp@oldproof
165     \noexpand\let\noexpand\section\noexpand\axp@oldsection
166   }
167 }
```

`\axp@unactivateeightbit` We need an auxiliary macro to disable active characters that have the high bit set
when writing to the `.axp` file. See <https://tex.stackexchange.com/a/145361/166858>

```

168 \def\axp@unactivateeightbit{%
169   \count@=128%
170   \loop
171     \catcode\count@=12%
172     \ifnum\count@<255%
173     \advance\count@\@ne
174   \repeat}
```

`axp@VerbatimOut` Using the functionalities of the `fancyvrb` package, we define a custom verbatim
`\FVB@axp@VerbatimOut` environment `axp@VerbatimOut` that writes every line to the `\axp@proofsfile`.
`\FVE@axp@VerbatimOut` We also use the previous macro to disable active characters with the eighth bit set.

```

175 \DefineVerbatimEnvironment{axp@VerbatimOut}{axp@VerbatimOut}{-}
176 \def\FVB@axp@VerbatimOut{%
177   \@bsphack
178   \begingroup
179     \axp@unactivateeightbit
180     \FV@DefineWhiteSpace
181     \def\FV@Space{\space}%
182     \FV@DefineTabOut
183     \def\FV@ProcessLine{\immediate\write\axp@proofsfile}%
184     \let\FV@FontScanPrep\relax
185     \let\@noligs\relax
186     \immediate\write\axp@proofsfile{\noexpand\makeatother}
187     \FV@Scan}
188 \def\FVE@axp@VerbatimOut{%
189   \immediate\write\axp@proofsfile{\noexpand\makeatletter}%
190   \endgroup\@esphack}
```

`toappendix` The entire content of this environment is put in appendix, starting a new appendix
section beforehand if needed.

```

191 \newenvironment{toappendix}
192   {\axp@writesection\axp@VerbatimOut}
193   {\endaxp@VerbatimOut}
```

7.5.2 Definition of New Theorems

`axp@seenreptheorem` Used to indicate whether a repeated theorem was just typeset, without its proof.

```
194 \newtoggle{axp@seenreptheorem}
```

`axp@rpcounter` Sequentially incremented for every repeated theorem, used to create labels.

```
195 \newcounter{axp@rpcounter}
```

`axp@equation` Used to save the value of the `equation` counter, when `repeqn` is set to `same`.

```
axp@equationx 196 \newcounter{axp@equation}
```

```
197 \newcounter{axp@equationx}
```

`axp@newtheoremrep` With first argument `foobar`, we use `\axp@newtheoremrep@definetheorem` to define the regular version of the theorem `foobar`. We then patch `\begin{foobar}` so as not to expect a proof in the appendix and define an internal theorem `axp@foobarrp` that will be used in the appendix to restate the existing theorem.

```
198 \def\axp@newtheoremrep#1[#2]#3[#4]{%
199 \axp@newtheoremrep@definetheorem{#1}{#2}{#3}{#4}%
200 \expandafter\pretocmd\csname #1\endcsname{\noproofinappendix}{-}{-}%
201 \axp@newtheorem*{axp@#1rp}{#3}%
202 \axp@forward@setup{#1}{#2}{#3}{#4}%
```

We then define a `foobarrp` environment that increments the `axp@rpcounter` and typeset the regular `foobar` theorem with a label derived from the counter, along with a possible custom command to identify repeated theorems. We distinguish the case when the theorem argument has a note and when it does not. We save the equation counter before typesetting the theorem environment, to reset it to the same value in the repeated environment when `repeqn` is set to `same`.

```
203 \NewEnviron{#1rep}[1][]{%
204 \ifthenelse{\equal{\axp@repeqn}{same}}{%
205 \setcounter{axp@equation}{\value{equation}}}%
206 }{%
207 \addtocounter{axp@rpcounter}{1}%
208 \ifx\relax##1\relax
209 \axp@with@forward{#1}{\begin{#1}}\label{axp@r\roman{axp@rpcounter}}}%
210 \else
211 \axp@with@forward{#1}{\begin{#1}[##1]}\label{axp@r\roman{axp@rpcounter}}}%
212 \fi
213 \mainbodyrepeatedtheorem
214 \BODY\end{#1}%
```

We set the `axp@seenreptheorem` toggle to indicate that we are looking for the proof of the theorem, then store in a macro the content of the theorem's body.

```
215 \global\toggletrue{axp@seenreptheorem}%
216 \global\expandafter\let\csname rplet\roman{axp@rpcounter}%
217 \endcsname
218 \BODY
```

Possibly after starting a new appendix section if needed, we typeset a repeated version of the theorem using the `axp@foobarrp` environment and a reference to

the previously defined label. We use `\axp@redefinelabels` in this environment to avoid multiply defined labels. We have to deal in a careful way with theorem notes: we want to use a theorem note to display the number of the repeated theorem, but theorem notes are usually typeset in a much different way (different font, parentheses) than theorem headings. In the case of the Springer document classes, we use the `\theopargself` macro to disable parentheses. For other document classes, we need to manually patch the `\thmhead` command at the right time. We also specially cover the case of the ACM document class where `\acmplainnotefont` is used instead of `\thm@notefont`.

```

219     \axp@writesection%
220     \ifthenelse{equal{\axp@repeqn}{same}}{-%
221         \immediate\write\axp@proofsfile{%
222             \noexpand\setcounter{axp@equationx}{\value{equation}}}%
223             \noexpand\setcounter{equation}{\theaxp@equation}%
224         }%
225     }{}%
226     \immediate\write\axp@proofsfile{%
227         \ifdefined\theopargself
228             \noexpand\theopargself
229         \else
230             \noexpand\pretocmd{\noexpand\@begintheorem}{%
231                 \noexpand\patchcmd{\noexpand\thmhead}{\noexpand\@acmplainnotefont}{}{}{}%
232                 \noexpand\patchcmd{\noexpand\thmhead}{\noexpand\the\noexpand\thm@notefont}{}{}{}%
233                 \noexpand\patchcmd{\noexpand\thmhead}{(){}{}{}{}%
234                 \noexpand\patchcmd{\noexpand\thmhead}{)}{}{}{}%
235             }{}{}
236         \fi
237     \noexpand\begin{axp@#1rp}
238     [%
239         \noexpand\ref{axp@r\roman{axp@rpcounter}}}%
240         \@ifnotempty{##1}{-%
241             \ifdefined\theopargself
242             \else
243                 \ifdefined\@acmplainnotefont
244                     \noexpand\@acmplainnotefont
245                 \else
246                     \noexpand\ifdefined\noexpand\thm@notefont
247                         \noexpand\the\noexpand\thm@notefont
248                     \noexpand\fi
249                 \fi
250             \fi
251             {} (\unexpanded{##1})}%
252         }%
253     ]%
254     \noexpand\axp@forward@target{axp@fw@r\roman{axp@rpcounter}}{}%
255     \noexpand\axp@redefinelabels
256     \expandafter\noexpand\csname rplet\roman{axp@rpcounter}%
257                     \endcsname
258     \noexpand\end{axp@#1rp}

```



```

259     }}%
260     \ifthenelse{\equal{\axp@repeqn}{same}}{%
261         \immediate\write\axp@proofsfile{%
262             \noexpand\setcounter{equation}{\value{axp@equationx}}}%
263     }%
264     }{}%
265 }%
266 }

```

7.5.3 Forward-Linking Mechanism

When hyperref is loaded, `foobarrep` environments in the main text have their number link to their repetition in the appendix.

`\axp@with@forward` In order to make the number of the `foobarrep` theorem a link to its repeated version, we temporarily redefine the `\thefoobar` command, or, if we inherited the counter from a `bazbar` environment, the `\thebazbar` command. This seems to be the only robust way, to make the number a `\hyperlink`, without adding extensive dependence on internals of `amsthm`, the builtin `\newtheorem` and possibly document-class specific definitions.

In order to allow users to redefine `\thefoobar` without breaking this feature, we redefine `\thefoobar` only for the duration of the `\begin{foobar}` form, resetting it to the old value as soon as possible.

Redefining `\thefoobar` has the side effect of changing `\newlabel` entries in the `.aux` file, so we need to be able to disable addition of the hyperlink, which is why we use an intermediate `\axp@forward@link{<target>}{<text>}` macro. We also redefine `\theHfoobar` which is used by `hyperref` but not defined if `hyperref` was loaded after `\newtheoremrep` was used. and `\protect` it to output it verbatim into the `.aux` file.

These hyperlinks are of course disabled in the `strip` compilation mode.

```

267 \newcommand{\axp@with@forward}[2]{%
268     \ifthenelse{\equal{\axp@appendix}{strip}}{#2}{
269         \global\booltrue{axp@forward}%
270         \ifcsundef{axp@old@the\csname axp@cn@#1\endcsname}{%
271             \csletcs{axp@old@the\csname axp@cn@#1\endcsname}{the\csname axp@cn@#1\endcsname}%
272             \csletcs{theH\csname axp@cn@#1\endcsname}{the\csname axp@cn@#1\endcsname}%
273             \csdef{the\csname axp@cn@#1\endcsname}{%
274                 \protect\axp@forward@link{axp@fw@r\roman{axp@rpcounter}}{%
275                     {\csname axp@old@the\csname axp@cn@#1\endcsname\endcsname}%
276                 }%
277             }{}%
278             #2%
279             \ifcsdef{axp@old@the\csname axp@cn@#1\endcsname}{%
280                 \csletcs{the\csname axp@cn@#1\endcsname}{axp@old@the\csname axp@cn@#1\endcsname}%
281             }{}%
282             \global\boolfalse{axp@forward}
283         }}%

```

`\axp@forward@link` Dummy macro, for handling the unwanted change of the `\newlabel` entry in the `.aux` file caused by changing the definition of `\thefoobar`.

```

284   \newbool{axp@forward}
285   \newcommand{\axp@forward@link}[2]{%
286     \ifbool{axp@forward}{%
287       \ifcsdef{hyperlink}{%
288         \hyperlink{#1}{#2}%
289       }{%
290         #2%
291       }%
292     }{%
293       #2%
294     }%
295   }%

```

`\axp@forward@target` Provides the needed `\hypertarget`. Intended to be written to the `.axp` file.

```

296   \newcommand{\axp@forward@target}[2]{%
297     \ifcsname hypertarget\endcsname
298       \hypertarget{#1}{#2}%
299     \else
300       #2%
301     \fi
302   }

```

`\axp@forward@setup` In order to support counter inheritance with the first optional argument of `\newtheoremrep`, we need access to the name of the counter. For compliance with the behavior of `\@axp@newtheorem`, the first optional argument (`#2`) is ignored if the second optional argument (`#4`) is given.

```

303   \newcommand{\axp@forward@setup}[4]{%
304     \csedef{axp@cn@#1}{\ifblank{#4}{\ifblank{#2}{#1}{#2}}{#1}}%
305   }

```

7.5.4 Proof Environments

`\noproofinappendix` Utility macro that toggles `axp@seenreptheorem` to false.

```

306   \newcommand\noproofinappendix{%
307     \global\togglefalse{axp@seenreptheorem}%
308   }

```

`appendixproof` We dump the content of this in appendix, within an original `proof` environment, possibly after creating a new appendix section.

```

309   \newenvironment{appendixproof}
310     {%
311       \axp@writesection
312       \immediate\write\axp@proofsfile{%
313         \noexpand\begin{axp@oldproof}%
314       }%
315       \axp@VerbatimOut

```

```

316 }
317 {%
318   \endaxp@VerbatimOut
319   \immediate\write\axp@proofsfile{%
320     \noexpand\end{axp@oldproof}%
321   }%
322   \noproofinappendix
323 }

```

proof This environment either puts the proof in appendix, if we are after a repeated theorem without its proof, or inlines it otherwise.

```

324 \renewenvironment{proof}
325 {%
326   \iftoggle{axp@seenreptheorem}{%
327     \appendixproof
328   }{%
329     \axp@oldproof
330   }%
331 }
332 {%
333   \iftoggle{axp@seenreptheorem}{%
334     \endappendixproof
335   }{%
336     \endaxp@oldproof
337   }%
338 }

```

inlineproof These two environments are synonyms for the original **proof** environment.

nestedproof

```

339 \let\inlineproof\axp@oldproof
340 \let\endinlineproof\endaxp@oldproof
341 \let\nestedproof\axp@oldproof
342 \let\endnestedproof\endaxp@oldproof

```

7.5.5 Section Management

axp@seccounter Sequentially incremented for every section, used to create labels.

```

343 \newcounter{axp@seccounter}

```

\axp@sectitle Saves the title of the last encountered section.

```

344 \def\axp@sectitle{}

```

\axp@section This command behaves similarly to **\axp@oldsection**, except that it first tests whether a **\section** follows, and if so, does not produce anything. This is useful to avoid producing empty sections in the appendix. As usual, we have to process starred and unstarred version separately.

```

345 \def\axp@section{\@ifstar\axp@@section\axp@oldsection}
346 \def\axp@@section#1{%
347   \@ifnextchar\section{\axp@oldsection*{#1}}%
348 }

```

```

349 \def\axp@@section#1{%
350   \ifnextchar\section{}\{\axp@oldsection{#1}}%
351 }

\axp@oldsection We redefine the \section command to create a label based on axp@seccounter
\section and to store its title in \axp@sectitle. In order to support starred and unstarred
\@section versions, as well as the optional short-title argument, the intermediate macros
\@@section \@section and \@@section are needed.

352 \let\axp@oldsection\section
353 \def\section{\@ifstar\@section\@@section}
354 \newcommand{\@section}[2][\relax]{\axp@@section{*}{#1}{#2}}%
355 \newcommand{\@@section}[2][\relax]{\axp@@section{}{#1}{#2}}%
356 \newcommand{\axp@@section}[3]{%
357   \global\def\axp@sectitle{#3}%
358   \ifx\relax#2\relax
359     \axp@oldsection#1{#3}%
360   \else
361     \axp@oldsection#1[{#2}]{#3}%
362   \fi
363   \addtocounter{axp@seccounter}{1}%
364   \label{axp@s\roman{axp@seccounter}}}%
365 }

\nosectionappendix We remove the current section title, to indicate no section should be created in the
appendix.

366 \newcommand{\nosectionappendix}{%
367   \global\def\axp@sectitle{}%
368 }

\axp@writesection If \axp@sectitle is not empty, we create a new section in the appendix, referring
to the main text section.

Here, we wrap \ref{axp@si} into \axp@protectref@i, in order to protect
the label name from wrongly being converted to uppercase, e.g., in fancyhdr with
\pagestyle{fancy}.

This macro is defined both in the .aux file (in order to ensure availability
when typesetting the \tableofcontents), and immediately before typesetting the
appendix section (to ensure availability in the \section command).

369 \newcommand\axp@writesection{%
370   \ifx\axp@sectitle\@empty
371   \else
372     \edef\axp@tmp{%
373       \noexpand\global\noexpand\def
374       \expandonce{\csname axp@protectref@\roman{axp@seccounter}\endcsname}{%
375         \noexpand\ref{axp@s\roman{axp@seccounter}}}%
376     }%
377   }%
378   \immediate\write\@auxout{\expandonce\axp@tmp}
379   \immediate\write\axp@proofsfile{%

```

```

380     \expandonce\axp@tmp^^J%
381     \noexpand\axp@section{%
382         \noexpand\appendixsectionformat{%
383             \protect
384             \expandonce{\csname axp@protectref@\roman{axp@seccounter}\endcsname}%
385             }\expandonce\axp@sectitle}%
386     }%
387 }%
388 \nosectionappendix
389 \fi
390 }

```

Finally, in a somewhat ad hoc manner, we disable the whole section management for `\tableofcontents`, which may be typeset using a section heading, but for which automatic section management does not make sense.

```

\axp@oldtableofcontents
\tableofcontents 391 \let\axp@oldtableofcontents\tableofcontents
392 \def\tableofcontents{{\let\section\axp@oldsection\axp@oldtableofcontents}}

```

7.5.6 Append Compilation Mode

```

393 \ifthenelse{\equal{\axp@appendix}{append}}{
\axp@oldbibliography Unless the bibliography option is set to common, we need to set the appendix
\ bibliography bibliography source to be the same as that of the main text, thanks to bibunits's
\defaultbibliography macro.
394 \ifthenelse{\equal{\axp@bibliography}{separate}}{
395 \let\axp@oldbibliography\ bibliography
396 \renewcommand\ bibliography[1]{%
397 \defaultbibliography{#1}%
398 \axp@oldbibliography{#1}%
399 }
400 }{}

```

After the end of the main text, we add the appendix (after the command `\appendixprelim` is issued) within a `bibunit` environment so as to typeset a separate bibliography for the appendix (unless the `bibliography` option is set to `common`). There is an extra test to ensure an empty bibliography environment is not produced. The name of the bibliography is changed to `\appendixrefname`; in most document classes, it is called `\refname` but it is occasionally (`scrartcl`, `scrreprt`) called `\bibname`.

```

401 \AtEndDocument{
402 \appendixprelim
403 \appendix
404 \ifthenelse{\equal{\axp@bibliography}{separate}}{
405 \begin{bibunit}[\appendixbibliographystyle]
406 }{}
407 \immediate\closeout\axp@proofsfile

```

```

408     \input{\jobname.axp}
409     \ifthenelse{\equal{\axp@bibliography}{separate}}{
410         \ifdefined\refname
411             \renewcommand{\refname}{\appendixrefname}
412         \else\ifdefined\bibname
413             \renewcommand{\bibname}{\appendixrefname}
414         \fi\fi
415         \let\axp@oldthebibliography\thebibliography
416         \renewcommand\thebibliography[1]{%
417             \ifx\relax#1\relax\else\axp@oldthebibliography{#1}\fi}
418         \appendixbibliographyprelim
419         \putbib
420     \end{bibunit}
421 }{}
422 }
423 }{}

```

7.5.7 Class-Specific Behavior

We conclude with some class-specific behavior.

ACM Document Classes (old versions, till 2017)

```

424 \ifdefined\@acmtitlebox

```

We first redefine the `proofsketch` environment, which is used differently in the base class.

```

425 \renewenvironment{proofsketch}{\begin{axp@oldproof}[sketch]}\end{axp@oldproof}}

```

We adjust the styling of theorems for the needs of `apxproof`.

```

426 \newtheoremstyle{mystyle}
427     {6pt}
428     {6pt}
429     {\itshape}
430     {10pt}
431     {\scshape}
432     {.}
433     {.5em}
434     {}
435 \theoremstyle{mystyle}

```

`\thebibliography` The section title of the bibliography is in uppercase in these document classes. In addition, the `\thebibliography` macro hard-codes twice the section title, so we un-hardcode it so that it can be modified in the appendix.

```

436 \patchcmd{\thebibliography}{References}{\protect\refname}{}{}
437 \patchcmd{\thebibliography}{References}{\protect\refname}{}{}
438 \newcommand{\refname}{REFERENCES}
439 \renewcommand{\appendixrefname}{REFERENCES FOR THE APPENDIX}
440 \fi

```

lipics

```
441 \ifdefined\lipics@opterrshort
```

`\appendixbibliographyprelim` The default bibliography in the lipics document class formatting is not compatible with the alpha bibliography style. We fix this here.

```
442 \renewcommand{\appendixbibliographyprelim}{%
443 \global\let\oldbiblabel\@biblabel
444 \def\@biblabel{\hspace*{-2em}\small\oldbiblabel}%
445 }

446 \fi
447 }
```

Change History

v1.0.0	General: Initial released version . . . 1	Show options commented on in margin and index 1
v1.0.1	General: Prevent empty bibliography environment; fix typos 1	v1.0.5 General: Ability to specify a sectioning counter in newtheoremrep 2
v1.0.2	<code>\axp@newtheoremrep</code> : Fix display of repeated theorem counter in some document classes 16	Fix compilation of proofsketch environment in inline mode . . . 4
	Fix missing space between repeated theorem counter and theorem note 16	v1.0.6 <code>\axp@newtheorem</code> : Introduce intermediary command for theorem macro 10
v1.0.3	<code>\appendixbibliographyprelim</code> : Support for lipics-v2016 23	<code>\axp@writesection</code> : Fix extraneous space after section number in appendix titles . . . 20
	General: Note on entire sections in appendix 2	General: Better support of Springer document classes 12
	<code>proofsketch</code> : Ignore spaces after beginning of Proof sketch . . . 11	Deal with document classes where the bibliography is called <code>\bibname</code> 21
v1.0.4	<code>\appendixprelim</code> : Configurable appendix style 11	Support of new ACM document class (<code>acmart.cls</code>) 22
	<code>\axp@bibliography</code> : <code>bibliography</code> option 9	<code>\axp@newtheoremrep</code> : Better handling of note-free theorems in document classes that treat theorems differently when they have an empty note 15
	General: More faithful theorem style for ACM templates 22	Fix incorrect use of <code>\noexpand</code> in optional argument of macro environment 16
	More robust coherent styling of proof sketches 22	
	Re-establish custom proof environments 8	v1.1.0 <code>\FVE@axp@VerbatimOut</code> : Make

apxproof compatible with independent use of fancyvrb . . .	14	Rewrote definition of \section to enable optional argument. See #23. (K. D. Bauer)	20
\appendixsectionformat: Fix missing space in default \appendixsectionformat . . .	11	\tableofcontents: Disable section management for table of contents	21
\axp@proofsfile: Initialization deferred to \AtBeginDocument for compatibility with \dumped precompiled preambles (K. D. Bauer)	13	General: Added forward-link mechanism (K. D. Bauer) . . .	17
\axp@redefinlabels: Fix \label not being disabled in amsmath environments, where \label@in@display is used instead (K. D. Bauer)	11	v1.2.0 \axp@newtheoremrep: Fix formatting of theorems without notes in some document classes in inline mode	13
\axp@repeqn: repeqn option	9	\axp@newtheoremrep@definetheorem: Restore predefined theorem counters	10
\axp@unactivateeightbit: Fix compilation of non-ASCII characters with \usepackage[utf8]{inputenc}	14	\axp@redefinlabels: Fix extra spacing erroneously introduced within the \axp@redefinlabels macro . . .	11
\axp@writesection: Make \axp@tmp wrapper more robust. Resolves issues from use of section title in fancyhdr, and in \tableofcontents (K. D. Bauer).	20	\mainbodyrepeatedtheorem: Configurable repeated theorem command	11
\section: Fix handling of fragile macros within section headings. See #22.	20	General: Do not load binunits if bibliography is set to common . .	9
		axp@newtheoremrep: Fix display of theorem notes	16
		proofsketch: Fix proof sketches in inline compilation mode for Springer document classes . . .	12

Index

Numbers written in *italic* refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; numbers in roman refer to the code lines where the entry is used.

Symbols	
\@axp@newtheorem	70, <u>117</u>
\@section	<u>352</u>
\@acmplainnotefont	231, 243, 244
\@acmttitlebox	424
\@auxout	378
\@axp@newtheorem	70, <u>117</u>
\@begintheorem	230
\@biblabel	443, 444
\@bsphack	177
\@esphack	190
\@ifnextchar	347, 350
\@ifpackageloaded	6
\@ifstar	70, 345, 353
\@ne	173
\@noligs	185
\@oldbiblabel	443, 444
\@oparg	82, 85
\@section	<u>352</u>
\@thmcountersep	132

$\backslash \square$	34, 43, 51, 93	$\backslash \text{axp@rpcounter}$	195
		$\backslash \text{axp@seccounter}$	343
		$\backslash \text{axp@section}$	345, 381
		$\backslash \text{axp@ssectitle}$..	344, 357, 367, 370, 385
		$\backslash \text{axp@seenreptheorem}$	194
		$\backslash \text{axp@tmp}$	372, 378, 380
		$\backslash \text{axp@unactivateeightbit}$...	168, 179
		$\backslash \text{axp@VerbatimOut}$	192, 315
		axp@VerbatimOut (environment) ...	175
		$\backslash \text{axp@with@forward}$	209, 211, 267
		$\backslash \text{axp@writesection}$..	192, 219, 311, 369
A			
$\backslash \text{advance}$	173		
$\backslash \text{appendix}$	403		
appendix (option)	5		
$\backslash \text{appendixbibliographyprelim}$	5, 88, 418, 442		
$\backslash \text{appendixbibliographystyle}$..	5, 88, 405		
$\backslash \text{appendixprelim}$	5, 88, 402		
$\backslash \text{appendixproof}$	149, 327		
appendixproof (environment) ..	2, 145, 309		
$\backslash \text{appendixrefname}$..	5, 88, 411, 413, 436		
$\backslash \text{appendixsectionformat}$...	5, 88, 382		
$\backslash \text{apx@oldamsthmendproof}$	9, 16		
$\backslash \text{apx@oldamsthmproof}$	8, 14, 15		
$\backslash \text{AtBeginDocument}$	156, 160		
$\backslash \text{AtEndDocument}$	401		
$\backslash \text{axp@@@section}$	354, 355, 356		
$\backslash \text{axp@@section}$	345		
$\backslash \text{axp@@ssection}$	345		
$\backslash \text{axp@appendix}$	23,		
	27, 29, 31, 34, 98, 134, 268, 393		
$\backslash \text{axp@bibliography}$			
	24, 37, 40, 43, 394, 404, 409		
$\backslash \text{axp@equation}$	196		
$\backslash \text{axp@equationx}$	196		
$\backslash \text{axp@forward}$	284		
$\backslash \text{axp@forward@link}$	274, 284		
$\backslash \text{axp@forward@setup}$	202, 303		
$\backslash \text{axp@forward@target}$	254, 296		
$\backslash \text{axp@newtheorem}$	61, 70, 201		
$\backslash \text{axp@newtheoremrep}$..	85, 135, 198, 198		
$\backslash \text{axp@newtheoremrep@definetheorem}$	54, 136, 199		
$\backslash \text{axp@newtheoremreptmp}$	81		
$\backslash \text{axp@oldbibliography}$	394		
$\backslash \text{axp@oldlabel}$ 99, 102, 103, 107, 110, 112			
$\backslash \text{axp@oldlabel@in@display}$			
	100, 106, 111, 113		
$\backslash \text{axp@oldproof}$..	94, 163, 329, 339, 341		
axp@oldproof (environment)	94		
$\backslash \text{axp@oldsection}$..	165, 347, 350, 352, 392		
$\backslash \text{axp@oldtableofcontents}$	391		
$\backslash \text{axp@oldthebibliography}$...	415, 417		
$\backslash \text{axp@proofsfile}$..	156, 161, 183, 186,		
	189, 221, 226, 261, 312, 319, 379, 407		
$\backslash \text{axp@redefinelabels}$..	96, 139, 141, 255		
$\backslash \text{axp@repeqn}$..	25, 46, 48, 51, 204, 220, 260		
		B	
		$\backslash \text{bfseries}$	120, 122, 125, 129
		$\backslash \text{bibliography}$	394
		bibliography (option)	4
		$\backslash \text{bibname}$	412, 413
		$\backslash \text{BODY}$	139, 141, 214, 218
		$\backslash \text{boolfalse}$	282
		$\backslash \text{booltrue}$	269
		C	
		$\backslash \text{catcode}$	171
		$\backslash \text{clearpage}$	92
		$\backslash \text{closeout}$	407
		$\backslash \text{count@}$	169, 171, 172, 173
		$\backslash \text{csdef}$	273
		$\backslash \text{csedef}$	304
		$\backslash \text{csletcs}$	271, 272, 280
		D	
		$\backslash \text{DeclareStringOption}$	23, 24, 25
		$\backslash \text{defaultbibliography}$	397
		$\backslash \text{DefineVerbatimEnvironment}$	175
		E	
		$\backslash \text{endappendixproof}$	150, 334
		$\backslash \text{endaxp@oldproof}$..	95, 164, 336, 340, 342
		$\backslash \text{endaxp@VerbatimOut}$	193, 318
		$\backslash \text{endinlineproof}$	146, 340
		$\backslash \text{endnestedproof}$	148, 342
		$\backslash \text{endproof}$..	9, 11, 16, 95, 146, 148, 150, 164
		environments:	
		appendixproof	2, 145, 309
		axp@oldproof	94
		axp@VerbatimOut	175
		inlineproof	4, 145, 339
		nestedproof	6, 145, 339
		proof	3, 160, 324
		proofsketch	4, 87

toappendix	1, 151, 191	\openout	158
\errmessage	34, 43, 51	options:	
\expandonce	374, 378, 380, 384, 385	appendix	5
		bibliography	4
		repeqn	5
F		P	
\FV@DefineTabOut	182	\pretocmd	200, 230
\FV@DefineWhiteSpace	180	\ProcessLocalKeyvalOptions	26
\FV@FontScanPrep	184	\proof	8, 10, 15, 94, 145, 147, 149, 163
\FV@ProcessLine	183	proof (environment)	3, 160, 324
\FV@Scan	187	\proofsketch	131
\FV@Space	181	proofsketch (environment)	4, 87
\FVB@exp@VerbatimOut	175	\providecommand	97
\FVE@exp@VerbatimOut	175	\putbib	419
H		R	
\hspace	444	\ref	239, 375
\hyperlink	288	\refname	410, 411, 436
\hypertarget	298	\repeat	174
		repeqn (option)	5
I		S	
\ifblank	304	\scshape	431
\ifbool	286	\section	160, 347, 350, 352, 392
\ifcsdef	279, 287	\setcounter	205, 222, 223, 262
\ifcsname	56, 62, 297	\SetupKeyvalOptions	19
\ifcsundef	270	\small	444
\ifnum	172	\spnewtheorem	116, 120, 122, 125, 129
\inlineproof	145, 339	T	
inlineproof (environment)	4, 145, 339	\tableofcontents	391
\input	408	\the	232, 247
\itshape	120, 122, 125, 129, 429	\theexp@equation	223
		\thebibliography	415, 416, 436
L		\theopargself	227, 228, 241
\label	99, 101, 110, 112, 209, 211, 364	\theoremstyle	435
\label@in@display	97, 100, 105, 111, 113	\thm@notefont	232, 246, 247
\lipics@opterrshort	441	\thmhead	231, 232, 233, 234
\loop	170	toappendix (environment)	1, 151, 191
M		\togglefalse	307
\mainbodyrepeatedtheorem	5, 88, 213	\toggletrue	215
\message	28, 30, 32, 39, 41, 47, 49	U	
N		\unexpanded	251
\nestedproof	147, 341	\upshape	129
nestedproof (environment)	6, 145, 339	V	
\newbool	284	\value	205, 222, 262
\newtheorem	73, 75, 79	W	
\newtheoremrep	2, 81	\write	161, 183, 186, 189,
\newtheoremstyle	426		221, 226, 261, 312, 319, 378, 379
\noproofinappendix	6, 151, 200, 306, 322		
\nosectionappendix	6, 151, 366, 388		
O			
\onecolumn	92		

References

- [1] Leslie Lamport. *LaTeX: A Document Preparation System*. Addison–Wesley Pub. Co., Reading, MA, 1986.

A Proofs for Section 1 (Usage)

This content is in the appendix.

Proof. This proof is in the appendix.

□

Foobar 2. *This foobar is repeated in the appendix.*

Proof. This is the proof of the repeated foobar.

□

This is a citation in the appendix [Unk16].

References for the Appendix

[Unk16] Unknown. Proofs are hard, 2016.