The apxproof package

Pierre Senellart
pierre@senellart.com
http://github.com/PierreSenellart/apxproof

2026/06/02 v1.4.1-dev

Abstract

This package makes it easier to write articles where proofs and other material are deferred to the appendix. The appendix material is written in the LaTeX code along with the main text which it naturally complements, and it is automatically deferred. The package can automatically send proofs to the appendix, can repeat in the appendix the theorem environments stated in the main text, can section the appendix automatically based on the sectioning of the main text, and supports a separate bibliography for the appendix material.

1 Usage

The apxproof package is intended to simplify the writing of articles where some of the content needs to be deferred to an appendix. This is in particular useful for the submission of scientific articles to conferences or journals that limit the number of pages in the main text but allow an extra appendix, where proofs of theorems and other material can be added.

1.1 Basics

To use apxproof, first load it in the header of your document:

```
\usepackage{apxproof}
```

On its own, this does not do anything and should not change the appearance of your document. To add an appendix with some material from your document, use the `toappendix` environment:

`toappendix` (*env.*)

```
\begin{toappendix}
  ...
\end{toappendix}
```

The content will appear at the end of your document, in an automatically generated section that refers to the current section in the main text.

Example 1. *Throughout this documentation, all examples produce content deferred to the appendix, at the very end of this document.*

```
\begin{toappendix}
```

```
This content is in the appendix.
\end{toappendix}
```

When the content to put in appendix is an entire section, make sure that `\section` is the very first command that appears within the `toappendix` environment. It will disable the automatic production of a section heading.

1.2 Repeated Theorems and Proofs

In some scientific papers that include proofs, it is common to defer proofs to the appendix. This can easily be achieved using the `appendixproof` environment:

`appendixproof` (*env.*)

```
\begin{appendixproof}
  ...
\end{appendixproof}
```

This behaves like the `toappendix` environment, except that a proof environment is generated.

Example 2. *We now send a proof to the appendix:*

```
\begin{appendixproof}
This proof is in the appendix.
\end{appendixproof}
```

When deferring proofs to the appendix, an annoying problem is that the statement of the theorem remains in the main text; it is hard to read a proof that is far away from the statement it proves. apxproof offers two ways to address this.

`\newtheoremrep` `\newtheoremrep*` With `\newtheoremrep`, the statement of the theorem is *repeated* in the appendix, immediately above the deferred proof. With the starred variant `\newtheoremrep*`, the theorem is *not* repeated, but the proof is still automatically deferred to the appendix; this is convenient when the proofs are short enough or close enough to the main text that a restatement would be redundant, especially when combined with the `\appendixproofname` hook (see Section 1.5) to title proofs with the type and number of the theorem they refer to (e.g., "Proof of Theorem 1"). In summary, three behaviors are available for a theorem environment:

`\newtheorem` (LaTeX's standard command): the theorem appears in the main text only; the `proof` environment is left unchanged by apxproof.

`\newtheoremrep` : the theorem appears in the main text *and* is restated in the appendix above its proof; the `proof` that follows in the source is automatically deferred to the appendix.

`\newtheoremrep*` : the theorem appears in the main text only; the `proof` that follows is automatically deferred to the appendix, without restating the theorem there.

In all cases, theorems can share counters and a single document can mix the three behaviors freely.

To use the repeated-theorem feature, you can define a new *repeated theorem* environment using the `\newtheoremrep` command:

`\newtheoremrep` `\newtheoremrep{`⟨*name*⟩`}[`⟨*counter*⟩`]{`⟨*title*⟩`}[`⟨*countersec*⟩`]`

or, equivalently, its starred form to obtain a *proof-deferred* (but not repeated) theorem:

`\newtheoremrep*` `\newtheoremrep*{`⟨*name*⟩`}[`⟨*counter*⟩`]{`⟨*title*⟩`}[`⟨*countersec*⟩`]`

Usage of either form is exactly the same as that of AMS LaTeX's `\newtheorem` macro:

- ⟨*name*⟩ (e.g., `theorem`) is the name of an environment that is created for this kind of theorem;
- ⟨*counter*⟩ (e.g., `definition`) is an optional counter describing from which kind of environment the numbering of these environments should be inherited;
- ⟨*title*⟩ (e.g., `Theorem`) is the title that will be used to display this theorem environment;
- ⟨*countersec*⟩ (e.g., `section`) is an optional counter of a sectioning command indicating that counters for this theorem should be prefixed by this counter (and reset at each occurrence of the sectioning command).

⟨*counter*⟩ and ⟨*countersec*⟩ should not be used together. What differs from `\newtheorem` is that, when the following is written:

```
\newtheoremrep{foobar}{Foobar}
```

then *two* environments are defined: the `foobar` environment, which behaves as if `\newtheorem` had been used, and the `foobarrep` environment, which results in the statement of this environment being repeated in the appendix. The starred form `\newtheoremrep*{foobarstar}{Foobarstar}` similarly defines two environments `foobarstar` and `foobarstarrep`, except that `\begin{foobarstarrep}` does not produce any restatement of the theorem in the appendix; only the following `proof` is deferred.

`proof` (*env.*)

One interesting feature of apxproof is that in most situations, there is no need to use the `appendixproof` environment. Indeed, the `proof` environment is redefined by apxproof to automatically put the proof either in the main text (if it follows a regular theorem) or in the appendix (if it follows a repeated theorem).

Example 3. *Assume we have first defined a repeated theorem environment* `foobar` *as above. We can now use this theorem environment, first for a regular theorem in the main text, then for a theorem repeated in the main text and in the appendix:*

```
\begin{foobar}
This foobar is a regular one, in the main text.
\end{foobar}
\begin{proof}
This is the proof of the regular foobar.
\end{proof}
```

We obtain:

Foobar 1. *This foobar is a regular one, in the main text.*

Proof. This is the proof of the regular foobar. □

Now, if we use a repeated theorem:

```
\begin{foobarrep}
This foobar is repeated in the appendix.
\end{foobarrep}
\begin{proof}
This is the proof of the repeated foobar.
\end{proof}
```

We now obtain:

Foobar 2. *This foobar is repeated in the appendix.*

Note that, since `hyperref` *is loaded, there are hyperlinks created between the statements of the theorems in the main text and in the appendix.*

Example 4. *In contrast, the starred form of* `\newtheoremrep` *produces a theorem whose proof is deferred to the appendix* without *restating the theorem there. Assuming the declaration* `\newtheoremrep*{foobarstar}{Foobarstar}` *at the top of the document, writing:*

```
\begin{foobarstarrep}
This foobar will not be repeated in the appendix,
but the proof below will be deferred there.
\end{foobarstarrep}
\begin{proof}
This is the proof of the (non-repeated) foobar.
\end{proof}
```

yields:

Foobarstar 1. *This foobar will not be repeated in the appendix, but the proof below will be deferred there.*

In this mode, the title of the deferred proof in the appendix is controlled by the `\appendixproofname` *hook documented in Section 1.5; by default, this hook is empty, so proofs are titled simply "Proof." as usual. The forward hyperlink from the theorem number in the main text (when* hyperref *is loaded) points to the location of the proof in the appendix.*

When the proof is deferred to the appendix, it is common practice to add a proof sketch in the main text. apxproof defines a simple `proofsketch` environment for this purpose:

`proofsketch` (*env.*)

```
\begin{proofsketch}
  ...
\end{proofsketch}
```

The proof sketch is typeset similarly to a proof, but is always in the main text.

`inlineproof` (*env.*) Similarly, an `inlineproof` environment is provided so as to be able to have both a proof in the appendix (using the regular `proof` environment, or alternatively the `appendixproof` environment) and a different proof in the main text (using the `inlineproof` environment).

Example 5. *Here are simple examples of proof sketches and inline proofs:*

```
\begin{proofsketch}
This is a proof sketch.
\end{proofsketch}
```

Proof sketch. This is a proof sketch. □

```
\begin{inlineproof}
This is an inline proof.
\end{inlineproof}
```

Proof. This is an inline proof. □

1.3 Bibliography

By default, apxproof automatically adds a bibliography in the appendix with only the references cited in the appendix material. This allows for a clean separation of references used solely in the main text, and those used in the appendix.

Example 6. *Assume we have citations both in the main text and in the appendix.*

```
This is a citation in the main text~\cite{lamport86}.
\begin{toappendix}
This is a citation in the appendix~\cite{proofsAreHard}.
\end{toappendix}
```

This is a citation in the main text [1].

The bibliography in the appendix can use a different style and heading than the bibliography in the main text (and, by default, it does). See Section 1.5 for how to configure the appearance of that bibliography.

option `bibliography`

In order to use a single appendix for the main text and the bibliography, one can specify the value `common` to the `bibliography` option when loading the package.

option `bibengine`

By default, apxproof relies on the bibunits package to typeset a separate bibliography for the appendix material; this is the `bibengine=bibtex` mode (the default), suitable for documents that use bibtex (with or without natbib) for citations and references. Documents using biblatex can instead set `bibengine=biblatex`, in which case apxproof wraps the appendix material in a biblatex `refsection` environment and emits the appendix bibliography with `\printbibliography`. In this mode the user is responsible for loading biblatex and declaring bibliography resources with `\addbibresource` in the preamble; resources are shared between the main document and the appendix `refsection`, but citations and the printed bibliography are scoped independently. The `bibengine` option only has an effect when `bibliography=separate`. (By default this option is set to `separate`.)

1.4 Mode

option `appendix`

An optional ⟨*mode*⟩ can be specified when loading the package:

```
\usepackage[appendix=⟨mode⟩]{apxproof}
```

⟨*mode*⟩ can take one of the following four values:

`append` This is the default. Appendix material gathered by apxproof is appended to the main text.

`inline` In this mode, apxproof simply inlines the content along with the main text.

`strip` This mode functions similarly to `append` except that the appendix is not appended at the end of the document. All appendix material is therefore removed.

`chapterend` In this mode, appendix material for each chapter is gathered separately and emitted at the end of that chapter (i.e., just before the next `\chapter`, `\part`, `\frontmatter`, `\mainmatter`, or `\backmatter` command, or at the end of the document), using the `subappendices` environment from the appendix package. Only `bibliography=common` is supported in this mode. See Section 1.5 for the `\chapterappendixprelim` and `\flushchapterappendix` customization macros.

1.5 Customization

apxproof provides a few macros that can be redefined (using `\renewcommand`) to customize the appearance of the appendix:

`\mainbodyrepeatedtheorem` `\mainbodyrepeatedtheorem` is a macro that is executed at the beginning of the body of every repeated theorem. This can be used to notify the reader that the theorem is repeated in appendix in some way, e.g., with a margin note.

`\appendixsectionformat` `\appendixsectionformat{`⟨***number***⟩`}{`⟨***title***⟩`}` is a macro that indicates how to format the section titles in the Appendix, given the number and title of the section in the main text. By default, they appear as "Proofs for Section ⟨*number*⟩ (⟨*title*⟩)".

`\appendixproofname` `\appendixproofname{`⟨***type***⟩`}{`⟨***ref***⟩`}` is a macro that determines the title of a proof deferred to the appendix when it follows a `\newtheoremrep` or `\newtheoremrep*` environment. By default, this macro is empty, which means proofs are titled "Proof." as usual. When redefined to a non-empty value, the expansion is used as the title of the appendix proof; ⟨*type*⟩ is the title of the theorem environment (e.g., `Theorem`) and ⟨*ref*⟩ is a reference to the theorem statement in the main text. To title all such proofs "Proof of ⟨*type*⟩ ⟨*number*⟩", one would typically write:

```
\renewcommand{\appendixproofname}[2]{Proof of #1~#2}
```

This hook applies whether the theorem is restated in the appendix (`\newtheoremrep`) or not (`\newtheoremrep*`). It has no effect on manually written `appendixproof` environments or on proofs given an explicit optional title.

`\appendixrefname` `\appendixrefname` contains the heading that is displayed before the bibliography. By default, this is "References for the Appendix". (Note that this command is also defined and used by the `memoir` document class.)

`\appendixbibliographystyle` `\appendixbibliographystyle` contains the `.bst` bibliography style that is used in the bibliography in appendix. By default, this is `alpha`.

`\appendixbibliographyprelim` `\appendixbibliographyprelim` contains arbitrary code that is executed just before the production of the bibliography in appendix, which can be used to configure the way it is displayed.

`\appendixprelim` `\appendixprelim` contains arbitrary code that is executed just before the production of the appendix, which can be used to configure the way it is displayed. By default, this command contains `\clearpage\onecolumn` (the appendix is typeset on a new page in single-column mode) but redefining this option allows changing this behavior. This macro has no effect in `chapterend` mode; use `\chapterappendixprelim` instead.

`\chapterappendixprelim` `\chapterappendixprelim` (`chapterend` mode only) contains arbitrary code that is executed just before each chapter's appendix block. By default, this command contains `\clearpage` (each chapter appendix starts on a new page). This macro has no effect in `append` or `strip` mode; use `\appendixprelim` instead.

`\flushchapterappendix` `\flushchapterappendix` (`chapterend` mode only) manually emits the current chapter's accumulated appendix material at the point of invocation, and starts a fresh per-chapter buffer. The package automatically inserts an equivalent flush before each `\chapter`, `\part`, `\frontmatter`, `\mainmatter`, `\backmatter`, and at the end of the document, so this macro is only useful in unusual document structures where an appendix needs to be emitted at a location that is not a standard structural boundary.

option `repeqn` Another customization capability concerns *numbered equations* that are present within repeated theorems. An optional `repeqn` option can be specified when loading the package, which controls whether equation numbers should be as in the main text (by setting this option to `same`, the default) or independently numbered (by setting this option to `independent`). In the latter case, whenever a referenceable counter is set with `\label{`⟨*counter*⟩`}`, `\ref{`⟨*counter*⟩`}` references the counter in the main text, while `\ref{`⟨*counter*⟩`-apx}` references the counter in the appendix (except in `inline` mode, where both have the same effect).

Enhanced cross-referencing packages are supported: the optional argument that cleveref adds to `\label` (as in `\label[equation]{`⟨*counter*⟩`}`) may be used within repeated material, and so may the `\zlabel` command of zref-clever, both giving rise to the same `-apx` variants as `\label` does.

option `forwardlinking` Another customization option concerns hyperlinking. Usually, when hyperref is loaded, `foobarrep` environments in the main text have their number link to their repetition in the appendix. To suppress this behavior and have `foobarrep` environments treated as if hyperref were not loaded, one can specify the value `no` to the `forwardlinking` option when loading the package. (By default this option is set to `yes`.)

1.6 Advanced Features

We now describe a few advanced macros and environments, the usage of which is limited to special cases:

`nestedproof` (*env.*) `nestedproof` is an environment that can be used within a `proof` environment deferred in the appendix; this is required because, for technical reasons, no `proof` environment can be nested within a deferred `proof` environment.

`\noproofinappendix` `\noproofinappendix` can be used inside repeated theorems that are not followed by a `proof` or `appendixproof` environment; the point is to ensure that a further `proof` environment cannot be mistakenly understood as a proof of the repeated theorem. It should not be needed in most situations as apxproof tries figuring out when a proof follows a repeated theorem automatically, but may occasionally be needed in complex scenarios.

`\nosectionappendix` `\nosectionappendix` is to be used inside a section that *does* contain appendix material, but for which a section in the appendix should not be created. This should be rarely needed. When this command is present, appendix material is appended to the end of the previously created section.

1.7 Grouping Appendix Material Under a Single Section

By default, apxproof produces one section in the appendix for each section of the main text that contains appendix material (with the format controlled by `\appendixsectionformat`). If you would rather have a single section in the appendix (e.g., titled "Proofs") with the per-section entries appearing as *subsections* of that single section, two recipes are available.

The first is fully explicit: disable the automatic per-section heading with `\nosectionappendix`, and write the desired structure directly inside `toappendix` environments.

```
\begin{toappendix}
  \section{Proofs}
\end{toappendix}

\section{First}\label{sec:first}
\nosectionappendix
\begin{toappendix}
  \subsection{Proofs of Section~\ref{sec:first}}
\end{toappendix}

% ... theorems and proofs of section ``First'' ...

\section{Second}\label{sec:second}
\nosectionappendix
\begin{toappendix}
  \subsection{Proofs of Section~\ref{sec:second}}
\end{toappendix}

% ... theorems and proofs of section ``Second'' ...
```

The reader of the source can then see exactly what will be produced in the appendix, at the cost of some verbosity.

The second recipe is more concise. The section level used by apxproof for the auto-generated appendix headings is swapped from `\section` to `\subsection` for the duration of an explicit `\begingroup`/`\endgroup` group:

```
\begin{toappendix}
  \section{Proofs}
  \begingroup\makeatletter
    \let\axp@oldsection\subsection
  \makeatother
\end{toappendix}

\section{First}\label{sec:first}
% ... theorems and proofs of section ``First'' ...

\section{Second}\label{sec:second}
% ... theorems and proofs of section ``Second'' ...

\begin{toappendix}
  \endgroup
\end{toappendix}
```

The wrapping `\section{Proofs}` is written once, and every subsequent auto-generated appendix section heading is demoted to a `\subsection` for the scope of the group. The trade-off is that this recipe relies on an internal macro (`\axp@oldsection`) and on a manually balanced `\begingroup`/`\endgroup` pair across two separate `toappendix` environments.

2 Supported Document Classes

Because apxproof modifies sectioning commands, bibliographies, and proofs, it may not work straight away with arbitrary document classes. It has currently been tested with and is supported for the following document classes:

- LaTeX standard document classes (e.g., `article.cls`)
- KOMA-Script (e.g., `scrartcl.cls`, `scrbook.cls`)
- `memoir.cls`
- ACM SIG Proceedings (e.g., `sig-alternate.cls`, `acmart.cls`)
- Springer's Lecture Notes in Computer Science (e.g., `llncs.cls`)
- Schloß Dagstuhl's Leibniz International Proceedings in Informatics (e.g., `lipics.cls`, `lipcs-v2016.cls`)

Other classes may work out of the box. Adding support for specific classes is possible and can be requested from the author of this package.

3 Known Issues and Limitations

We report here some issues we are currently aware of:

- When using hyperref, the appendix in the bibliography is not hyperlinked. This is to avoid possible issues with multiply defined bibliography entries.

- `appendixproof`, `proof`, `toappendix` environments cannot be nested. This is a limitation of the fancyvrb package that apxproof relies on. Note the existence of the `nestedproof` environment for nested proofs.
- apxproof poorly interacts with SyncTEX: identifying which source line has produced which box does not work for appendix content managed by apxproof or repeated theorems. No obvious fix is known, though this issue will be investigated in the long term.
- By default, when `bibliography=separate`, apxproof uses the bibunits package to generate a second bibliography. Packages incompatible with bibunits (notably biblatex) will therefore not work in that default configuration. For biblatex users, set `bibengine=biblatex` (in addition to `bibliography=separate`) to use biblatex's own `refsection` machinery instead. The `bibliography=common` mode remains a third option that works with most bibliography packages.
- With cleveref, the optional argument of `\label` is lost within amsmath display environments (`equation`, `align`, etc.): the label ends up named `[`⟨*type*⟩`]{`⟨*counter*⟩`}` and cannot be referenced. This is unrelated to apxproof, and happens just as well in a document that does not use it; it is a consequence of amsmath now saving the meaning of `\label` in the `begindocument/end` hook, thereby overwriting the redefinition of `\ltx@label` on which cleveref relies. Plain `\label` is unaffected, and so is zref-clever.
- In the optional title of a proof, a cross-reference that itself takes an optional argument (typically `\zcref[`⟨*options*⟩`]{`⟨*labels*⟩`}`) must be surrounded by braces, as in `\begin{proof}[Proof of {\zcref[noname]{thm:x}}]`, since the `]` would otherwise be taken to end the title. This is a general LaTeX requirement about optional arguments within optional arguments, and applies just as well without apxproof. Such a braced cross-reference is however invisible to the token scan of the title, so `\apxproofhook` does not fire for that proof.

Issues not listed here should be reported to the author.

4 License

Copyright © 2016–2026 by Pierre Senellart.

This work may be distributed and/or modified under the conditions of the LaTeX Project Public License, either version 1.3 of this license or (at your option) any later version. The latest version of this license is in http://www.latex-project.org/lppl.txt and version 1.3 or later is part of all distributions of LaTeX version 2005/12/01 or later.

5 Contact

- https://github.com/PierreSenellart/apxproof
- Pierre Senellart <pierre@senellart.com>

Bug reports and feature requests should preferably be submitted through the *Issues* feature of GitHub.

6 Acknowledgments

Thanks to Antoine Amarilli for feedback and proofreading. Thanks to K. D. Bauer for the implementation of the forward-linking mechanism, and for various bugfixes. Thanks to Leonid Kostrykin for an initial implementation of the `forwardlinking` option.

7 Implementation

We now describe the entire code of the package, in a literate programming fashion. Throughout the package, we use the `axp@` prefix to identify local macros and environment names, which are not meant to be used by the final user.

7.1 Dependencies

We first load a few package dependencies:

- environ to easily define the repeated theorem environments.

```
\RequirePackage{environ}
```

- etoolbox to define simple toggles.

```
\RequirePackage{etoolbox}
```

- fancyvrb for the bulk of the work of exporting appendix material in an auxiliary file.

```
\RequirePackage{fancyvrb}
```

- ifthen for easier comparison of character strings.

```
\RequirePackage{ifthen}
```

- kvoptions to manage options passed to the package.

```
\RequirePackage{kvoptions}
```

- catchfile to be able to check the content of files `\input` within appendix content.

```
\RequirePackage{catchfile}
```

- amsthm for its `\newteorem` macro. Some document classes (e.g., lipics) preload amsthm: this is fine, `\RequirePackage{amsthm}` will simply have no effect. On the other hand, some other document classes (e.g., llncs or sig-alternate) define a `proof` environment that conflicts with amsthm, so we have to undefine this environment before loading amsthm. In that case, we reestablish the existing proof environments, in case they had been customized (e.g., sig-alternate)

```
\@ifpackageloaded{amsthm}{
```

```
    }{
      \let\apx@oldamsthmproof\proof
      \let\apx@oldamsthmendproof\endproof
      \let\proof\undefined
      \let\endproof\undefined
    }
  \RequirePackage{amsthm}
  \ifdefined\apx@oldamsthmproof
    \let\proof\apx@oldamsthmproof
    \let\endproof\apx@oldamsthmendproof
  \fi
```

7.2 Option Processing

Many names throughout the package use an arobase (`@`) to avoid name conflict with user-defined names. To simplify the compilation of the documentation, we simply make it a regular character in all the rest.

```
\makeatletter
```

We setup the processing of options using keyval facilities.

```
\SetupKeyvalOptions{
  family=axp,
  prefix=axp@
}
```

We declare the following options:

- `appendix`, with a default value of `append` (other possible values: `strip`, `inline`);
- `bibliography`, with a default value of `separate` (other possible value: `common`);
- `repeqn`, with a default value of `same` (other possible value: `independent`).

`\axp@appendix`

```
\DeclareStringOption[append]{appendix}
```

`\axp@bibliography`

```
\DeclareStringOption[separate]{bibliography}
```

`\axp@bibengine`

```
\DeclareStringOption[bibtex]{bibengine}
```

`\axp@repeqn`

```
\DeclareStringOption[same]{repeqn}
```

`\axp@forwardlinking`

```
\DeclareStringOption[yes]{forwardlinking}
```

```
\ProcessLocalKeyvalOptions*
```

We check that the value of the options are valid, and add a message to the compilation log.

```
\ifthenelse{\equal{\axp@appendix}{append}}{
  \message{apxproof: Appendix material appended to the document}
}{\ifthenelse{\equal{\axp@appendix}{strip}}{
  \message{apxproof: Appendix material stripped}
}{\ifthenelse{\equal{\axp@appendix}{inline}}{
  \message{apxproof: Appendix material inlined within the document}
}{\ifthenelse{\equal{\axp@appendix}{chapterend}}{
  \message{apxproof: Appendix material appended at the end of each chapter}
}{
  \errmessage{Error: unsupported option appendix=\axp@appendix\ for
  package apxproof}
}}}}
\ifthenelse{\equal{\axp@bibengine}{bibtex}}{
}{\ifthenelse{\equal{\axp@bibengine}{biblatex}}{
}{
  \errmessage{Error: unsupported option bibengine=\axp@bibengine\ for
  package apxproof}
}}
\ifthenelse{\equal{\axp@bibliography}{separate}}{
```

In `bibengine=bibtex` mode (the default), the external bibunits package is used to add a second bibliography for the appendix material. In `bibengine=biblatex` mode, no extra package is loaded here: biblatex is expected to have been loaded by the user, and its `refsection` environment is used at appendix typeset time to scope citations.

```
  \ifthenelse{\equal{\axp@bibengine}{bibtex}}{
    \RequirePackage{bibunits}
    \message{apxproof: Separate bibliography for appendix material (bibunits)}
  }{
    \message{apxproof: Separate bibliography for appendix material (biblatex)}
  }
}{\ifthenelse{\equal{\axp@bibliography}{common}}{
  \message{apxproof: Common bibliography for appendix and main text}
}{
  \errmessage{Error: unsupported option bibliography=\axp@bibliography\ for
  package apxproof}
}}
\ifthenelse{\equal{\axp@appendix}{chapterend}
            \AND\equal{\axp@bibliography}{separate}}{
  \PackageError{apxproof}{%
    bibliography=separate is not supported with appendix=chapterend}{%
    Use bibliography=common instead.}
}{}
\ifthenelse{\equal{\axp@repeqn}{same}}{
  \message{apxproof: Repeated equations keep the same numbering}
}{\ifthenelse{\equal{\axp@repeqn}{independent}}{
  \message{apxproof: Repeated equations are independently numbered}
}{
  \errmessage{Error: unsupported option repeqn=\axp@repeqn\ for
  package apxproof}
}}
```

\axp@forward@suppress

```
\newbool{axp@forward@suppress}
\ifthenelse{\equal{\axp@forwardlinking}{yes}}{
}{\ifthenelse{\equal{\axp@forwardlinking}{no}}{
  \message{apxproof: Disable forward linking}
  \global\booltrue{axp@forward@suppress}%
}{
  \errmessage{Error: unsupported option forwardlinking=\axp@repeqn\ for
  package apxproof}
}}
```

7.3 Macros Common to All Compilation Modes

\axp@newtheoremrep@definetheorem Common to all compilation modes, we define \axp@newtheoremrep@definetheorem. When called with first argument foobar, we first undefine the existing foobar environment (and its counter) if it has already been defined (e.g., by the document class), then invoke \axp@newtheorem for the regular version of the theorem foobar, saving and restoring any existing theorem counter unless the \newtheoremdep redefines the base counter.

```
\def\axp@newtheoremrep@definetheorem#1#2#3#4{%
  \expandafter\let\csname #1\endcsname\undefined
  \expandafter\let\csname the#1\endcsname\undefined
  \ifcsname c@#1\endcsname
    \expandafter\expandafter\expandafter\let\expandafter\expandafter
      \csname c@axp@#1\endcsname\csname c@#1\endcsname
    \expandafter\let\csname c@#1\endcsname\undefined
  \fi
  \axp@newtheorem{#1}{#2}{#3}{#4}%
  \ifcsname c@axp@#1\endcsname
    \ifx\relax#2\relax
      \expandafter\expandafter\expandafter\let\expandafter\expandafter
        \csname c@#1\endcsname\csname c@axp@#1\endcsname
    \else
    \fi
  \fi
}
```

\axp@newtheorem \@axp@newtheorem \@@axp@newtheorem We introduce an intermediate \axp@newtheorem command to define a new theorem, differently depending on whether there is a section counter or not. This will be useful, in particular to allow changing this definition depending on the document class. This command uses two intermediary commands, \@axp@newtheorem and \@@axp@newtheorem, for the non-starred and starred versions.

```
\def\axp@newtheorem{\@ifstar\@@axp@newtheorem\@axp@newtheorem}
\def\@axp@newtheorem#1#2#3#4{%
  \ifx\relax#4\relax
    \newtheorem{#1}[#2]{#3}%
  \else
    \newtheorem{#1}{#3}[#4]%
  \fi
}
\def\@@axp@newtheorem#1#2{%
  \newtheorem*{#1}{#2}%
}
```

\newtheoremrep
\axp@newtheoremreptmp

We define the high-level \newtheoremrep to have the same syntax as amsthm's \newtheorem, plus an optional * variant that defers the proof to the appendix without restating the theorem. For this purpose, we need a little trick to deal with the second and fourth optional arguments, which is what \@oparg and \axp@newtheoremreptmp are used for. \axp@newtheoremrep is defined differently depending on the compilation mode.

```
\newcommand\newtheoremrep{%
  \@ifstar{\axp@newtheoremrep@star}{\axp@newtheoremrep@nostar}%
}
\newcommand\axp@newtheoremrep@star[1]{%
  \global\csdef{axp@proofof@#1}{}%
  \@oparg{\axp@newtheoremreptmp{#1}}[]%
}
\newcommand\axp@newtheoremrep@nostar[1]{%
  \global\csundef{axp@proofof@#1}%
  \@oparg{\axp@newtheoremreptmp{#1}}[]%
}
\def\axp@newtheoremreptmp#1[#2]#3{%
  \@oparg{\axp@newtheoremrep{#1}[#2]{#3}}[]%
}
```

proofsketch (*env.*)

Simple proofsketch environment.

```
  \newenvironment{proofsketch}{\begin{axp@oldproof}[Proof sketch]}{\end{axp@oldproof}}
```

\mainbodyrepeatedtheorem
\appendixrefname
\appendixbibliographystyle
\appendixbibliographyprelim
\appendixprelim
\appendixsectionformat
\appendixproofname

We provide sensible defaults for these user-customizable macros. Even though they are not all useful in all modes, we define them for all modes so that a \renewcommand works in all cases.

```
\newcommand{\mainbodyrepeatedtheorem}{}
\providecommand{\appendixrefname}{References for the Appendix}
\newcommand{\appendixbibliographystyle}{alpha}
\newcommand{\appendixbibliographyprelim}{}
\newcommand{\appendixprelim}{\clearpage\onecolumn}
\newcommand{\appendixsectionformat}[2]{Proofs for Section~#1\ (#2)}
\newcommand{\appendixproofname}[2]{}
```

axp@oldproof (*env.*)

We save the definition of the existing proof environment.

```
  \let\axp@oldproof\proof
  \let\endaxp@oldproof\endproof
```

We define a utility macro that will be used to properly set the \label command (and its amsmath counterpart, \label@in@display) for equations within repeated theorems, depending on the compilation mode.

Some packages, cleveref in particular, give \label (and \label@in@display) an optional argument specifying the type of the counter being labeled. Our replacements must therefore look for such an optional argument and pass it on unchanged, or the opening bracket would be taken as the label name and the rest of the argument typeset as text. We do *not* pass the optional argument on to the extra -apx label of the repeated material: that label is set within an unnumbered copy of the theorem, where overriding the counter type would apply to state that cleveref did not set up, and the type of the counter (for equations, the only case where the -apx label is really of use) is correctly inferred from the context anyway.

zref-clever, the maintained successor of cleveref, does not touch `\label` at all: it sets its own labels through `\zlabel`, and, with its `labelhook` option (set by default), also through the kernel's `label` hook, so that a plain `\label` sets a zref label as well. The latter needs nothing from us, since our replacement of `\label` calls the original one. A `\zlabel` used directly, however, must be given the same treatment as `\label`; it has no optional argument.

`\axp@label`
`\axp@label@in@display`

```
\def\axp@label{\@ifnextchar[\axp@label@opt\axp@label@noopt}%]
\def\axp@label@opt[#1]#2{\axp@label@do{[#1]}{#2}}
\def\axp@label@noopt#1{\axp@label@do{}{#1}}
\def\axp@label@in@display{%
  \@ifnextchar[\axp@label@in@display@opt\axp@label@in@display@noopt}%]
\def\axp@label@in@display@opt[#1]#2{\axp@label@in@display@do{[#1]}{#2}}
\def\axp@label@in@display@noopt#1{\axp@label@in@display@do{}{#1}}
```

`\axp@redefinelabels`

```
\newcommand{\axp@redefinelabels}{%
  \providecommand\label@in@display{}%
  \let\axp@oldlabel\label
  \let\axp@oldlabel@in@display\label@in@display
  \ifdefined\zlabel\let\axp@oldzlabel\zlabel\fi
  \ifthenelse{\equal{\axp@appendix}{inline}}{%
    \def\axp@label@do##1##2{%
      \axp@oldlabel##1{##2}%
      \axp@oldlabel{##2-apx}%
    }%
    \def\axp@label@in@display@do##1##2{%
      \axp@oldlabel@in@display##1{##2}%
      \axp@oldlabel{##2-apx}%
    }%
    \def\axp@zlabel##1{\axp@oldzlabel{##1}\axp@oldzlabel{##1-apx}}%
  }{%
    \def\axp@label@do##1##2{\axp@oldlabel{##2-apx}}%
    \def\axp@label@in@display@do##1##2{\axp@oldlabel@in@display{##2-apx}}%
    \def\axp@zlabel##1{\axp@oldzlabel{##1-apx}}%
  }%
  \let\label\axp@label
  \let\label@in@display\axp@label@in@display
  \ifdefined\zlabel\let\zlabel\axp@zlabel\fi
}
```

7.3.1 Class-Specific Behavior

Finally, some class-specific behavior common to all compilation modes.

llncs and other Springer document classes

```
  \ifdefined\spnewtheorem
```

`\@axp@newtheorem`
`\@@axp@newtheorem`

It is necessary to use `\spnewtheorem` instead of `\newtheorem` in Springer document classes to obtain standard formatting.

```
\def\@axp@newtheorem#1#2#3#4{%
  \ifx\relax#4\relax
```

```
    \ifx\relax#2\relax
      \spnewtheorem{#1}{#3}{\bfseries}{\itshape}%
    \else
      \spnewtheorem{#1}[#2]{#3}{\bfseries}{\itshape}%
    \fi
  \else
    \spnewtheorem{#1}{#3}[#4]{\bfseries}{\itshape}%
  \fi
}
\def\@@axp@newtheorem#1#2{%
  \spnewtheorem*{#1}{#2}{\upshape\bfseries}{\itshape}%
}
```

`proofsketch` We redefine the `proofsketch` environment, which is used differently in the base class.

```
\renewenvironment{proofsketch}{\begin{axp@oldproof}[sketch]}{\end{axp@oldproof}}
```

We have to redefine the macro `\@thmcountersep` for proper sectioned counters.

```
\def\@thmcountersep{.}
  \fi
```

acmart Some versions of acmart define a `\ACM@origsection` macro and verify that `\section` has the same content. We need to update `\ACM@origsection` accordingly.

```
\ifdefined\ACM@origsection
  \AtBeginDocument{\let\ACM@origsection\section}
\fi
```

7.4 Inline Compilation Mode

```
\ifthenelse{\equal{\axp@appendix}{inline}}{
```

`\axp@newtheoremrep` In inline mode, `\axp@newtheoremrep` uses `\axp@newtheoremrep@definetheorem` to define the regular theorem environment and creates a repeated theorem environment that behaves exactly as the regular theorem environment, while calling `\axp@redefinelabels` to make sure that `-axp` variants of equation counters are defined.

```
  \def\axp@newtheoremrep#1[#2]#3[#4]{%
    \axp@newtheoremrep@definetheorem{#1}{#2}{#3}{#4}%
    \NewEnviron{#1rep}[1][]{%
      \ifx\relax##1\relax
        \begin{#1}\axp@redefinelabels\BODY\end{#1}%
      \else
        \begin{#1}[##1]\axp@redefinelabels\BODY\end{#1}%
      \fi
    }
  }
```

`inlineproof` (*env.*) `nestedproof` (*env.*) `appendixproof` (*env.*) In inline mode, these environments behave like the regular `proof` environment.

```
  \let\inlineproof\proof
  \let\endinlineproof\endproof
  \let\nestedproof\proof
  \let\endnestedproof\endproof
```

```
\let\appendixproof\proof
\let\endappendixproof\endproof
```

`toappendix` (*env.*) In inline mode, this environment and these macros are no-ops.

`\noproofinappendix` `\nosectionappendix`

```
\newenvironment{toappendix}{}{}
\let\noproofinappendix\relax
\let\nosectionappendix\relax

}
```

7.5 Append, Strip, or Chapter End Compilation Modes

```
{
```

We now deal with the case where apxproof really does something useful: either append the appendix material to the document, or strip it entirely.

7.5.1 Auxiliary File for the Appendix

`\axp@proofsfile` We open a new auxiliary file, with extension `.axp`, where the appendix material will be dumped.

```
\AtBeginDocument{
  \newwrite\axp@proofsfile
  \ifthenelse{\equal{\axp@appendix}{chapterend}}{%
    \axp@openchapterfile
  }{%
    \immediate\openout\axp@proofsfile=\jobname.axp
  }%
}
```

`proof` (*env.*) `\section` At the beginning of this file, we make `@` a regular character (since it will be used in several places for internal names) and reestablish the original definition of the `proof` environment and the `\section` macro.

```
\newcommand{\axp@writeproofsfilepreamble}{%
  \immediate\write\axp@proofsfile{%
    \noexpand\makeatletter
    \noexpand\let\noexpand\proof\noexpand\axp@replayproof
    \noexpand\let\noexpand\endproof\noexpand\endaxp@oldproof
    \noexpand\let\noexpand\claimproof\noexpand\axp@oldclaimproof
    \noexpand\let\noexpand\endclaimproof\noexpand\endaxp@oldclaimproof
    \noexpand\let\noexpand\section\noexpand\axp@oldsection
  }%
}
\AtBeginDocument{
  \ifthenelse{\equal{\axp@appendix}{chapterend}}{}{%
    \axp@writeproofsfilepreamble
  }%
}
```

`\axp@unactivateeightbit` We need an auxiliary macro to disable active characters that have the high bit set when writing to the `.axp` file. See https://tex.stackexchange.com/a/145361/166858

```
\def\axp@unactivateeightbit{%
  \count@=128%
```

```
    \loop
      \catcode\count@=12%
      \ifnum\count@<255%
      \advance\count@\@ne
    \repeat}
```

`axp@VerbatimOut` (*env.*) `\FVB@axp@VerbatimOut` `\FVE@axp@VerbatimOut` Using the functionalities of the fancyvrb package, we define a custom verbatim environment `axp@VerbatimOut` that writes every line to the `\axp@proofsfile`. We also use the previous macro to disable active characters with the eighth bit set, and we make sure the catcode of `@` is reset for every verbatim environment, in case it is used by the user (e.g., as in the xypic package). Finally, as an additional precaution, we reset `\FV@CatCodesHook` that is for example set by the `commandchars` or `commentchar` option of `\fvset`.

```
\DefineVerbatimEnvironment{axp@VerbatimOut}{axp@VerbatimOut}{}
\def\FVB@axp@VerbatimOut{%
  \@bsphack
  \begingroup
    \axp@unactivateeightbit
    \FV@DefineWhiteSpace
    \def\FV@Space{\space}%
    \FV@DefineTabOut
    \def\FV@ProcessLine{\immediate\write\axp@proofsfile}%
    \let\FV@FontScanPrep\relax
    \let\@noligs\relax
    \def\FV@CatCodesHook{}%
    \FV@Scan}
\def\FVE@axp@VerbatimOut{%
    \immediate\write\axp@proofsfile{\noexpand\makeatletter}%
    \endgroup\@esphack}
```

`\axp@markchapterhasappendix` No-op by default; overridden in `chapterend` mode to set a flag indicating that the current chapter has appendix content.

```
\newcommand{\axp@markchapterhasappendix}{}
```

`toappendix` (*env.*) The entire content of this environment is put in appendix, starting a new appendix section beforehand if needed.

```
\newenvironment{toappendix}
  {\axp@markchapterhasappendix\axp@writesection\axp@VerbatimOut}
  {\endaxp@VerbatimOut}
```

7.5.2 Definition of New Theorems

`axp@seenreptheorem` Used to indicate whether a repeated theorem was just typeset, without its proof.

```
\newtoggle{axp@seenreptheorem}
```

`axp@rpcounter` Sequentially incremented for every repeated theorem, used to create labels.

```
\newcounter{axp@rpcounter}
```

`axp@equation` `axp@equationx` Used to save the value of the `equation` counter, when `repeqn` is set to `same`.

```
\newcounter{axp@equation}
\newcounter{axp@equationx}
```

`axp@newtheoremrep` With first argument `foobar`, we use `\axp@newtheoremrep@definetheorem` to define the regular version of the theorem `foobar`. We then patch `\begin{foobar}` so as not to expect a proof in the appendix and define an internal theorem `axp@foobarrp` that will be used in the appendix to restate the existing theorem. In the starred mode, the theorem is not restated in the appendix, so we do not define the `axp@foobarrp` environment.

```
\def\axp@newtheoremrep#1[#2]#3[#4]{%
  \axp@newtheoremrep@definetheorem{#1}{#2}{#3}{#4}%
  \expandafter\pretocmd\csname #1\endcsname{\noproofinappendix}{}{}%
  \ifcsdef{axp@proofof@#1}{}{%
    \axp@newtheorem*{axp@#1rp}{#3}%
  }%
  \axp@forward@setup{#1}{#2}{#3}{#4}%
```

We then define a `foobarrep` environment that increments the `axp@rpcounter` and typeset the regular `foobar` theorem with a label derived from the counter, along with a possible custom command to identify repeated theorems. We distinguish the case when the theorem argument has a note and when it does not. We save the equation counter before typesetting the theorem environment, to reset it to the same value in the repeated environment when `repeqn` is set to `same`.

```
  \NewEnviron{#1rep}[1][]{%
    \ifthenelse{\equal{\axp@repeqn}{same}}{%
      \setcounter{axp@equation}{\value{equation}}%
    }{}%
    \addtocounter{axp@rpcounter}{1}%
    \ifx\relax##1\relax
      \axp@with@forward{#1}{\begin{#1}}\label{axp@r\roman{axp@rpcounter}}%
    \else
      \axp@with@forward{#1}{\begin{#1}[{##1}]}\label{axp@r\roman{axp@rpcounter}}%
    \fi
    \mainbodyrepeatedtheorem
    \BODY\end{#1}%
```

We set the `axp@seenreptheorem` toggle to indicate that we are looking for the proof of the theorem, then store in a macro the content of the theorem's body.

```
    \global\toggletrue{axp@seenreptheorem}%
    \global\expandafter\let\csname rplet\roman{axp@rpcounter}%
                            \endcsname
    \BODY
```

Possibly after starting a new appendix section if needed, we typeset a repeated version of the theorem using the `axp@foobarrp` environment and a reference to the previously defined label. We use `\axp@redefinelabels` in this environment to avoid multiply defined labels. We have to deal in a careful way with theorem notes: we want to use a theorem note to display the number of the repeated theorem, but theorem notes are usually typeset in a much different way (different font, parentheses) than theorem headings. In the case of the Springer document classes, we use the `\theopargself` macro to disable parentheses. For other document classes, we need to manually patch the `\thmhead` command at the right time. We also specially cover the case of the ACM document class where `\@acmplainnotefont` is used instead of `\thm@notefont`.

```
    \axp@markchapterhasappendix
    \axp@writesection%
```

```
      \immediate\write\axp@proofsfile{\noexpand\makeatletter}%
      \ifthenelse{\equal{\axp@repeqn}{same}}{%
        \immediate\write\axp@proofsfile{%
          \noexpand\setcounter{axp@equationx}{\value{equation}}%
          \noexpand\setcounter{equation}{\theaxp@equation}%
        }%
      }{}%
      \ifbool{axp@forward@suppress}{%
        \global\def\axp@refstar{\ref*}
      }{%
        \global\def\axp@refstar{\ref}
      }
```

We write the auto-title state to the `.axp` file so that the following deferred proof can title itself via `\appendixproofname`. In starred mode, we also emit a forward-link target into the appendix so that hyperlinks from the inline theorem number always land somewhere defined, even if the user does not provide a proof.

```
      \immediate\write\axp@proofsfile{%
        \noexpand\gdef\noexpand\axp@nextproofof@type{#3}%
        \noexpand\gdef\noexpand\axp@nextproofof@label{axp@r\roman{axp@rpcounter}}%
      }%
      \ifcsdef{axp@proofof@#1}{%
        \immediate\write\axp@proofsfile{%
          \noexpand\axp@forward@target{axp@fw@r\roman{axp@rpcounter}}{}%
        }%
      }{%
```

In the default (unstarred) mode, we emit the repeated version of the theorem to the appendix; the forward-link target sits inside the restated theorem. In starred mode, we skip this block entirely.

```
        \immediate\write\axp@proofsfile{{%
          \ifdefined\theopargself
            \noexpand\theopargself
          \else
            \noexpand\pretocmd{\noexpand\@begintheorem}{%
              \noexpand\patchcmd{\noexpand\thmhead}{\noexpand\@acmplainnotefont}{}{}{}%
              \noexpand\patchcmd{\noexpand\thmhead}{\noexpand\the\noexpand\thm@notefont}{}{}{
              \noexpand\patchcmd{\noexpand\thmhead}{(}{}{}{}%
              \noexpand\patchcmd{\noexpand\thmhead}{)}{}{}{}%
            }{}{}
          \fi
          \noexpand\begin{axp@#1rp}
            [%
              \noexpand\axp@refstar{axp@r\roman{axp@rpcounter}}%
              \@ifnotempty{##1}{%
                \ifdefined\theopargself
                \else
                  \ifdefined\@acmplainnotefont
                    \noexpand\@acmplainnotefont
                  \else
                    \noexpand\ifdefined\noexpand\thm@notefont
                      \noexpand\the\noexpand\thm@notefont
                    \noexpand\fi
                  \fi
                \fi
```

```
                {} (\unexpanded{{##1}})%
              }%
            ]%
            \noexpand\axp@forward@target{axp@fw@r\roman{axp@rpcounter}}{}%
            \noexpand\axp@redefinelabels
            \expandafter\noexpand\csname rplet\roman{axp@rpcounter}%
                                \endcsname
          \noexpand\end{axp@#1rp}
        }}%
      }%
      \ifthenelse{\equal{\axp@repeqn}{same}}{%
        \immediate\write\axp@proofsfile{%
          \noexpand\setcounter{equation}{\value{axp@equationx}}%
        }%
      }{}%
    }%
  }
```

7.5.3 Forward-Linking Mechanism

When hyperref is loaded, `foobarrep` environments in the main text have their number link to their repetition in the appendix.

`\axp@with@forward` In order to make the number of the `foobarrep` theorem a link to its repeated version, we temporarily redefine the `\thefoobar` command, or, if we inherited the counter from a `bazbar` environment, the `\thebazbar` command. This seems to be the only robust way to make the number a `\hyperlink`, without adding extensive dependence on internals of `amsthm`, the builtin `\newtheorem` and possibly document-class specific definitions.

In order to allow users to redefine `\thefoobar` without breaking this feature, we redefine `\thefoobar` only for the duration of the `\begin{foobar}` form, resetting it to the old value as soon as possible.

Redefining `\thefoobar` has the side effect of changing `\newlabel` entries in the `.aux` file, so we need to to be able to disable addition of the hyperlink, which is why we use an intermediate `\axp@forward@link{`⟨*target*⟩`}{`⟨*text*⟩`}` macro, We also redefine `\theHfoobar` which is used by `hyperref` but not defined if `hyperref` was loaded after `\newtheoremrep` was used and `\protect` it to output it verbatim into the `.aux` file.

These hyperlinks are of course disabled in the `strip` compilation mode.

```
  \newcommand{\axp@with@forward}[2]{%
    \ifthenelse{\equal{\axp@appendix}{strip}}{#2}{
      \global\booltrue{axp@forward}%
      \ifcsundef{axp@old@the\csname axp@cn@#1\endcsname}{%
        \csletcs{axp@old@the\csname axp@cn@#1\endcsname}{the\csname axp@cn@#1\endcsname}%
        \csletcs{theH\csname axp@cn@#1\endcsname}{the\csname axp@cn@#1\endcsname}%
        \csdef{the\csname axp@cn@#1\endcsname}{%
          \protect\axp@forward@link{axp@fw@r\roman{axp@rpcounter}}%
            {\csname axp@old@the\csname axp@cn@#1\endcsname\endcsname}%
        }%
      }{}%
      #2%
      \ifcsdef{axp@old@the\csname axp@cn@#1\endcsname}{%
```

```
        \csletcs{the\csname axp@cn@#1\endcsname}{axp@old@the\csname axp@cn@#1\endcsname}%
      }{}%
      \global\boolfalse{axp@forward}
    }}%
```

`\axp@forward@link` `axp@forward` Dummy macro, for handling the unwanted change of the `\newlabel` entry in the `.aux` file caused by changing the definition of `\thefoobar`. We also use `\texorpdfstring` to detect whether the reference appears within a PDF bookmark, in which case we skip the test altogether.

```
\newbool{axp@forward}
\newcommand{\axp@forward@link}[2]{%
  \ifdefined\texorpdfstring\else\newcommand\texorpdfstring[2]{#2}\fi
  \texorpdfstring{%
    \ifboolexpr{ bool {axp@forward} and not bool {axp@forward@suppress} }{%
      \ifcsdef{hyperlink}{%
        \hyperlink{#1}{#2}%
      }{%
        #2%
      }%
    }{%
      #2%
    }%
  }{%
    #2%
  }%
}%
```

`\axp@forward@target` Provides the needed `\hypertarget`. Intended to be written to the `.axp` file.

```
\newcommand{\axp@forward@target}[2]{%
  \ifcsname hypertarget\endcsname
    \hypertarget{#1}{#2}%
  \else
    #2%
  \fi
}
```

`\axp@forward@setup` In order to support counter inheritance with the first optional argument of `\newtheoremrep`, we need access to the name of the counter. For compliance with the behavior of `\@axp@newtheorem`, the first optional argument (`#2`) is ignored if the second optional argument (`#4`) is given. We also check whether `aliascnt` was used to define this counter; if so, we use the original name as the counter name to handle the way such aliases work.

```
\newcommand{\axp@forward@setup}[4]{%
  \csedef{axp@cn@#1}{\ifblank{#4}{\ifblank{#2}{#1}{\ifcsdef{AC@cnt@#1}{#1}{#2}}}{#1}}%
}
```

7.5.4 Proof Environments

`\noproofinappendix` Utility macro that toggles `axp@seenreptheorem` to false.

```
\newcommand\noproofinappendix{%
  \global\togglefalse{axp@seenreptheorem}%
}
```

`\axp@apxproofstart` Helper invoked from the `.axp` file at appendix typeset time to open a deferred proof. Reads the `\axp@nextproofof@*` state (set by the preceding `theoremrep`) and consults `\appendixproofname` to decide whether to pass an optional title argument.

```
\gdef\axp@nextproofof@type{}
\gdef\axp@nextproofof@label{}
```

`\apxproofhook` A hook fired, inside the proof environment, each time a deferred proof is typeset in the appendix (and also for an inline proof whose title names its result through a `\ref`, see `\axp@inlineproofhook` below). Its argument is the label of the theorem the proof establishes: the automatic `axp@r`⟨*n*⟩ label of the preceding `theoremrep` for a deferred proof, or the target of the title's `\ref` for a titled inline proof. A companion package (such as proofgraph) can thereby attribute, to the right result, the references the proof makes (which are only executed at typeset time). It is a no-op by default.

```
\providecommand\apxproofhook[1]{}
\def\axp@apxproofstart#1{%
  \protected@xdef\axp@apxproofstart@title{%
    \appendixproofname{\axp@nextproofof@type}%
                      {\noexpand\ref{\axp@nextproofof@label}}%
  }%
  \ifx\axp@apxproofstart@title\@empty
    \begin{#1}%
  \else
    \expandafter\axp@apxproofstart@withtitle
      \expandafter{\axp@apxproofstart@title}{#1}%
  \fi
  \apxproofhook{\axp@nextproofof@label}%
}
\def\axp@apxproofstart@withtitle#1#2{\begin{#2}[#1]}
```

`\axp@inlineproofhook` A proof that is *not* deferred (no preceding `theoremrep`, so it is typeset inline) never goes through `\axp@apxproofstart`, hence never fires `\apxproofhook`. When such a proof carries an explicit title that names its result through a `\ref` (the idiom `\begin{proof}[of Theorem~\ref{thm:x}]`), we fire the hook here, inside the proof, with that target, so a companion package can attribute the proof to it. We only fire when a cross-reference is found in the title (the result is then unambiguous). The title is scanned for the first `\ref` (or `\cref`, `\Cref`, `\autoref`, `\vref`, `\zcref`) by pure token matching, never typesetting it: a title typically contains an active `~` and may carry other fragile material, which an auxiliary typeset pass would perturb or, with `\protect` neutralised, send into an infinite loop. zref-clever's `\zcref` is the only one of these that is not simply ⟨*cs*⟩`{`⟨*label*⟩`}`: it is `\zcref*[`⟨*options*⟩`]{`⟨*labels*⟩`}`, whose star and options are to be skipped and whose mandatory argument is a comma-separated list, of which we keep the first label. Each grabber is handed the whole remainder of the title and swallows it up to `\axp@refstop`, so that nothing of it is left to be typeset.

```
\newif\ifaxp@inlineproofof
\long\def\axp@inlineproofhook#1{%
  \global\axp@inlineproofoffalse
  \axp@tryrefcmd\ref{#1}%
  \ifaxp@inlineproofof\else\axp@tryrefcmd\cref{#1}\fi
  \ifaxp@inlineproofof\else\axp@tryrefcmd\Cref{#1}\fi
```

```
    \ifaxp@inlineproofof\else\axp@tryrefcmd\autoref{#1}\fi
    \ifaxp@inlineproofof\else\axp@tryrefcmd\vref{#1}\fi
    \ifaxp@inlineproofof\else
      \axp@tryrefcmd@\zcref\axp@grabzcarg{#1}%
    \fi
    \ifaxp@inlineproofof\apxproofhook{\axp@inlineproofof@label}\fi
  }
  \let\axp@refmark\relax
  \long\def\axp@tryrefcmd#1#2{\axp@tryrefcmd@#1\axp@grabarg{#2}}
  \long\def\axp@tryrefcmd@#1#2#3{%
    \in@{#1}{#3}%
    \ifin@
      \long\def\axp@grabref##1#1##2\axp@refstop{#2##2\axp@refstop}%
      \axp@grabref#3\axp@refmark\axp@refstop
    \fi
  }
  \long\def\axp@grabarg#1#2\axp@refstop{%
    \global\axp@inlineproofoftrue\xdef\axp@inlineproofof@label{#1}}
  \def\axp@grabzcarg{\@ifstar\axp@grabzcarg@i\axp@grabzcarg@i}
  \def\axp@grabzcarg@i{\@ifnextchar[\axp@grabzcarg@opt\axp@grabzcarg@ii}%]
  \def\axp@grabzcarg@opt[#1]{\axp@grabzcarg@ii}
  \long\def\axp@grabzcarg@ii#1{%
    \axp@grabzcarg@iii#1,\@nil
    \axp@gobbletorefstop}
  \long\def\axp@grabzcarg@iii#1,#2\@nil{%
    \global\axp@inlineproofoftrue\xdef\axp@inlineproofof@label{#1}}
  \long\def\axp@gobbletorefstop#1\axp@refstop{}
```

Proofs placed by hand in a `toappendix` environment are written verbatim to the `.axp` file and replayed there with `\proof` let to `\axp@oldproof` (see `\axp@writeproofsfilepreamble`). Such proofs therefore never reach `\axp@@proof`. So that a titled one still fires `\apxproofhook`, we let, at replay time, `\proof` to `\axp@replayproof`, which reproduces the inline behaviour: open the `amsthm` proof, then fire the hook for the title's `\ref`.

```
  \def\axp@replayproof{\@ifnextchar[{\axp@replayproof@opt}{\axp@oldproof}}
  \def\axp@replayproof@opt[#1]{\axp@oldproof[#1]\axp@inlineproofhook{#1}}
```

`appendixproof` (*env.*) We dump the content of this in appendix, within an original `proof` environment, possibly after creating a new appendix section. We support optional arguments in proofs, but we need to be careful not to gobble any newline character, that would make it impossible to process the first line with fancyvrb. When the proof is auto-routed from a `theoremrep` (the toggle `axp@seenreptheorem` is true at this point and no explicit optional argument was given), we delegate the proof opening to `\axp@apxproofstart` so that `\appendixproofname` is consulted at appendix typeset time. A user-supplied optional argument or a manual `\appendixproof` call (toggle false) bypasses this and uses the standard "Proof." heading.

```
  \def\appendixproof{\catcode`\^^M=\active\@ifnextchar[{\catcode`\^^M=5\@@appendixproof[axp@c
  \def\@appendixproof[#1]%
    {%
      \axp@markchapterhasappendix
      \axp@writesection
      \iftoggle{axp@seenreptheorem}{%
        \immediate\write\axp@proofsfile{%
```

```
          \noexpand\makeatletter\noexpand\axp@apxproofstart{#1}\noexpand\makeatother%
        }%
      }{%
        \immediate\write\axp@proofsfile{%
          \noexpand\makeatletter\noexpand\begin{#1}\noexpand\makeatother%
        }%
      }%
      \axp@VerbatimOut
    }
  \def\@@appendixproof[#1][#2]%
    {%
      \axp@markchapterhasappendix
      \axp@writesection
      \immediate\write\axp@proofsfile{%
        \noexpand\makeatletter\noexpand\begin{#1}[\unexpanded{#2}]\noexpand\makeatother%
      }%
      \axp@VerbatimOut
    }
  \def\endappendixproof
    {%
      \endaxp@VerbatimOut
      \immediate\write\axp@proofsfile{%
        \noexpand\end{axp@oldproof}%
      }%
      \noproofinappendix
    }
```

`proof` (*env.*) This environment either puts the proof in appendix, if we are after a repeated theorem without its proof, or inlines it otherwise. We support optional arguments in proofs, but we need to be careful not to gobble any newline character, that would make it impossible to process the first line with fancyvrb.

```
\def\proof{\catcode`\^^M=\active\ltx@ifnextchar@nospace[{\catcode`\^^M=5\axp@@proof}{\catco
\def\axp@proof
  {%
    \iftoggle{axp@seenreptheorem}{%
      \appendixproof
    }{%
      \axp@oldproof
    }%
  }
\def\axp@@proof[#1]%
  {%
    \iftoggle{axp@seenreptheorem}{%
      \appendixproof[#1]
    }{%
      \axp@oldproof[#1]%
      \axp@inlineproofhook{#1}%
    }%
  }
\def\endproof
  {%
    \iftoggle{axp@seenreptheorem}{%
      \endappendixproof
    }{%
```

```
      \endaxp@oldproof
    }%
  }
```

`claimproof` (*env.*) If the `claimproof` environment exists (lipics document class or user-defined), we also redefine it, in the same way.

```
\AtBeginDocument{
  \ifdefined\claimproof
  \let\axp@oldclaimproof\claimproof
  \let\endaxp@oldclaimproof\endclaimproof
  \def\claimproof{\catcode`\^^M=\active\ltx@ifnextchar@nospace[{\catcode`\^^M=5\axp@@claimp
  \def\appendixclaimproof{\catcode`\^^M=\active\@ifnextchar[{\catcode`\^^M=5\@@appendixproo
  \def\axp@claimproof
    {%
      \iftoggle{axp@seenreptheorem}{%
        \appendixclaimproof
      }{%
        \axp@oldclaimproof
      }%
    }
  \def\axp@@claimproof[#1]%
    {%
      \iftoggle{axp@seenreptheorem}{%
        \appendixclaimproof[#1]%
      }{%
        \axp@oldclaimproof[#1]%
      }%
    }
  \def\endclaimproof
    {%
      \iftoggle{axp@seenreptheorem}{%
        \endappendixclaimproof
      }{%
        \endaxp@oldclaimproof
      }%
    }
  \def\endappendixclaimproof
  {%
    \endaxp@VerbatimOut
    \immediate\write\axp@proofsfile{%
    \noexpand\end{axp@oldclaimproof}%
    }%
    \noproofinappendix
  }
  \fi
}
```

`inlineproof` (*env.*) These two environments are synonyms for the original `proof` environment.
`nestedproof` (*env.*)

```
\let\inlineproof\axp@oldproof
\let\endinlineproof\endaxp@oldproof
\let\nestedproof\axp@oldproof
\let\endnestedproof\endaxp@oldproof
```

7.5.5 Section Management

`axp@seccounter` Sequentially incremented for every section, used to create labels.

```
\newcounter{axp@seccounter}
```

`\axp@sectitle` Saves the title of the last encountered section.

```
\def\axp@sectitle{}
```

`\axp@section` `\axp@@sectionskippar` `\axp@@sectiontestinput` `\axp@@sectiontestinclude` `\axp@@sectionfinishinclude` `\axp@@sectiontestsection` This command `\axp@section` behaves similarly to `\axp@oldsection`, except that it first tests whether a `\section` follows, and if so, does not produce anything. This is useful to avoid producing empty sections in the appendix. Using the catchfile package, we also check whether a `\section` is within an `\input` or `\include` that immediately follows. We also skip any `\par` tokens (produced by blank lines) before performing the check.

```
\def\axp@section#1{%
  \@ifnextchar\par
    {\axp@@sectionskippar{#1}}%
    {\@ifnextchar\input
      {\axp@@sectiontestinput{#1}}%
      {\@ifnextchar\include
        {\axp@@sectiontestinclude{#1}}%
        {\axp@@sectiontestsection{#1}}}}%
}
\def\axp@@sectionskippar#1\par{\axp@section{#1}}
\def\axp@@sectiontestinput#1\input#2{%
  \CatchFileDef{\axp@tmp}{#2}{}%
  \def\axp@tmptmp{\axp@@sectiontestsection{#1}}%
  \expandafter\axp@tmptmp\axp@tmp%
}
\def\axp@@sectiontestinclude#1\include#2{%
  \set@curr@file{#2}%
  \edef\axp@tmp{\@strip@tex@ext\@curr@file.tex}%
  \expandafter\CatchFileDef\expandafter\axp@tmp\expandafter{\axp@tmp}{}%
  \def\axp@tmptmp{\axp@@sectionfinishinclude{#1}{#2}}%
  \expandafter\axp@tmptmp\axp@tmp\@nil
}
\long\def\axp@@sectionfinishinclude#1#2#3#4\@nil{%
  \ifx#3\section
    \makeatother
  \else
    \axp@oldsection{#1}\makeatother
  \fi
  \include{#2}%
}
\def\axp@@sectiontestsection#1{\@ifnextchar\section{\makeatother}{\axp@oldsection{#1}\makea
```

`\axp@oldsection` `\section` `\@section` `\@@section` We redefine the `\section` command to create a label based on `axp@seccounter` and to store its title in `\axp@sectitle`. In order to support starred and unstarred versions, as well as the optional short-title argument, the intermediate macros `\@section` and `\@@section` are needed.

```
\let\axp@oldsection\section
\def\section{\@ifstar\@section\@@section}
\newcommand{\@section}[2][\relax]{\axp@@@section{*}{#1}{#2}}%
```

```
\newcommand{\@@section}[2][\relax]{\axp@@@section{}{#1}{#2}}%
\newcommand{\axp@@@section}[3]{%
  \global\def\axp@sectitle{#3}%
  \ifx\relax#2\relax
    \axp@oldsection#1{#3}%
  \else
    \axp@oldsection#1[{#2}]{#3}%
  \fi
  \addtocounter{axp@seccounter}{1}%
  \label{axp@s\roman{axp@seccounter}}%
}
```

`\nosectionappendix` We remove the current section title, to indicate no section should be created in the appendix.

```
\newcommand{\nosectionappendix}{
  \global\def\axp@sectitle{}%
}
```

`\axp@writesection` If `\axp@sectitle` is not empty, we create a new section in the appendix, referring to the main text section.

Here, we wrap `\ref{axp@si}` into `\axp@protectref@i`, in order to protect the label name from wrongly being converted to uppercase, e.g., in fancyhdr with `\pagestyle{fancy}`.

This macro is defined both in the `.aux` file (in order to ensure availability when typesetting the `\tableofcontents`), and immediately before typesetting the appendix section (to ensure availability in the `\section` command).

```
\newcommand\axp@writesection{%
  \ifx\axp@sectitle\@empty
  \else
    \edef\axp@tmp{%
      \noexpand\global\noexpand\def
      \expandonce{\csname axp@protectref@\roman{axp@seccounter}\endcsname}{%
        \noexpand\ref{axp@s\roman{axp@seccounter}}%
      }%
    }%
    \immediate\write\@auxout{\expandonce\axp@tmp}
    \immediate\write\axp@proofsfile{%
      \expandonce\axp@tmp^^J%
      \noexpand\axp@section{%
        \noexpand\appendixsectionformat{%
          \protect
          \expandonce{\csname axp@protectref@\roman{axp@seccounter}\endcsname}%
        }{\expandonce\axp@sectitle}%
      }%
    }%
    \nosectionappendix
  \fi
}
```

Finally, in a somewhat ad hoc manner, we disable the whole section management for `\tableofcontents`, which may be typeset using a section heading, but for which automatic section management does not make sense.

\axp@oldtableofcontents
\tableofcontents

```
\let\axp@oldtableofcontents\tableofcontents
\def\tableofcontents{{\let\section\axp@oldsection\axp@oldtableofcontents}}
```

7.5.6 Append Compilation Mode

```
\ifthenelse{\equal{\axp@appendix}{append}}{
```

\axp@oldbibliography
\bibliography

In `bibengine=bibtex` mode, when the `bibliography` option is set to `separate`, we need to set the appendix bibliography source to be the same as that of the main text, thanks to bibunits's `\defaultbibliography` macro. In `bibengine=biblatex` mode, no such rebinding is needed: biblatex resources declared with `\addbibresource` are visible to all `refsection`s globally.

```
  \ifthenelse{\equal{\axp@bibliography}{separate}
              \AND\equal{\axp@bibengine}{bibtex}}{
    \let\axp@oldbibliography\bibliography
    \renewcommand\bibliography[1]{%
      \defaultbibliography{#1}%
      \axp@oldbibliography{#1}%
    }
  }{}
```

After the end of the main text, we add the appendix (after the command `\appendixprelim` is issued) within a `bibunit` environment so as to typeset a separate bibliography for the appendix (unless the `bibliography` option is set to `common`). This is done using `\pretocmd` on `\@enddocumenthook` instead of `\AtEndDocument` because we want the code to be run before any code in the `\@enddocumenthook` that has been set in the document class, as in the amsart document class. There is an extra test to ensure an empty bibliography environment is not produced. The name of the bibliography is changed to `\appendixrefname`; in most document classes, it is called `\refname` but it is occasionally (`scrartcl`, `scrreprt`) called `\bibname`. An ad-hoc test is added to fix a conflict with the natbib package which redefines `bibcite` at the end of the document.

```
  \pretocmd{\@enddocumenthook}{%
    \ifdefined\NAT@testdef
      \renewcommand\bibcite[2]{%
        \global\@namedef{b@#1\@extra@binfo}{#2}%
      }
    \fi
    \appendixprelim
    \appendix
    \ifthenelse{\equal{\axp@bibliography}{separate}}{
      \ifthenelse{\equal{\axp@bibengine}{bibtex}}{
        \begin{bibunit}[\appendixbibliographystyle]
      }{
        \begin{refsection}
      }
    }{}
      \immediate\closeout\axp@proofsfile
      \input{\jobname.axp}
    \ifthenelse{\equal{\axp@bibliography}{separate}}{
      \ifthenelse{\equal{\axp@bibengine}{bibtex}}{
        \ifdefined\refname
```

```
            \renewcommand{\refname}{\appendixrefname}
          \else\ifdefined\bibname
            \renewcommand{\bibname}{\appendixrefname}
          \fi\fi
          \let\axp@oldthebibliography\thebibliography
          \let\endaxp@oldthebibliography\endthebibliography
          \renewenvironment{thebibliography}[1]{%
            \def\axp@tmp{#1}%
            \ifx\axp@tmp\empty
              \gdef\axp@noappendixbibliography1\relax
            \else
              \begin{axp@oldthebibliography}{#1}%
            \fi
          }{%
            \ifdefined\axp@noappendixbibliography\relax\else\end{axp@oldthebibliography}%
          \fi}
          \appendixbibliographyprelim
          \putbib
          \end{bibunit}
        }{
          \appendixbibliographyprelim
          \printbibliography[title=\appendixrefname]
          \end{refsection}
        }
        \ifdefined\NAT@testdef
          \let\bibcite\NAT@testdef
        \fi
      }{}
    }{}{}
  }{}
```

7.5.7 Chapter End Compilation Mode

In `chapterend` mode, appendix material for each chapter is gathered in a per-chapter auxiliary file and emitted immediately after that chapter's content (and bibliography). This requires the `appendix` package for its `subappendices` environment.

```
  \ifthenelse{\equal{\axp@appendix}{chapterend}}{
    \RequirePackage{appendix}
```

`\chapterappendixprelim` `\axp@beginchapterappendix` `\axp@endchapterappendix` User-customizable hooks surrounding each chapter's appendix block. By default they open and close a `subappendices` environment.

```
    \newcommand{\chapterappendixprelim}{\clearpage}
    \newcommand{\axp@beginchapterappendix}{%
      \chapterappendixprelim
      \begin{subappendices}%
    }
    \newcommand{\axp@endchapterappendix}{%
      \end{subappendices}%
    }
```

`axp@chaptercounter` `axp@chapterhasappendix` `\axp@currentaxpfile` Counter for unique per-chapter file names, a boolean tracking whether the current chapter has any appendix content, and the current file name.

```
\newcounter{axp@chaptercounter}
\newbool{axp@chapterhasappendix}
\def\axp@currentaxpfile{}
```

`\axp@markchapterhasappendix` Override the no-op to set the boolean when content is written.

```
\renewcommand{\axp@markchapterhasappendix}{%
  \global\booltrue{axp@chapterhasappendix}%
}
```

`\axp@openchapterfile` Open a fresh auxiliary file for the current chapter. We write `\begingroup` first so that all the preamble `\let` assignments (and any catcode changes from `\makeatletter`) are scoped to this chapter's appendix and do not leak into the rest of the document when the file is `\input`'d. We also reset the section-title tracker and the repeated-theorem toggle so that state from the previous chapter cannot bleed into the new file.

```
\newcommand{\axp@openchapterfile}{%
  \edef\axp@currentaxpfile{\jobname-\arabic{axp@chaptercounter}.axp}%
  \immediate\openout\axp@proofsfile=\axp@currentaxpfile
  \immediate\write\axp@proofsfile{\noexpand\begingroup}%
  \axp@writeproofsfilepreamble
  \global\boolfalse{axp@chapterhasappendix}%
  \global\def\axp@sectitle{}%
  \global\togglefalse{axp@seenreptheorem}%
}
```

`\axp@flushchapterappendix` Close the current chapter's auxiliary file (appending `\endgroup` to close the group opened in `\axp@openchapterfile`) and, if it contains any content, emit it inside a `subappendices` block.

```
\newcommand{\axp@flushchapterappendix}{%
  \immediate\write\axp@proofsfile{\noexpand\endgroup}%
  \immediate\closeout\axp@proofsfile
  \ifbool{axp@chapterhasappendix}{%
    \axp@beginchapterappendix
    \input{\axp@currentaxpfile}%
    \axp@endchapterappendix
  }{}%
}
```

`\axp@chapterboundary` `\flushchapterappendix` `\axp@chapterboundary` flushes the previous chapter's auxiliary file, increments the counter, and opens the next one. It is used as a hook for `\chapter`, `\part`, and the `book`-class matter-switching commands `\frontmatter`, `\mainmatter`, `\backmatter`, so that per-chapter appendices are emitted before any of these structural transitions (otherwise the appendix of the last chapter of a part/matter would end up under the next part/matter). `\flushchapterappendix` is a public alias for the same operation, which can be invoked manually wherever an appendix flush boundary is needed (e.g., before a bibliography that does not produce its own chapter heading).

```
\newcommand{\axp@chapterboundary}{%
  \axp@flushchapterappendix
  \stepcounter{axp@chaptercounter}%
  \axp@openchapterfile
}
\let\flushchapterappendix\axp@chapterboundary
```

`\axp@hookboundary` Helper to install `\axp@chapterboundary` as a `\pretocmd` hook on a structural command (`\chapter`, `\part`, `\frontmatter`, etc.), issuing a package warning if the hook fails.

```
    \newcommand{\axp@hookboundary}[1]{%
      \pretocmd{#1}{\axp@chapterboundary}{}{%
        \PackageWarning{apxproof}{%
          Could not hook into \string#1;^^J%
          chapter appendices may not be emitted correctly}}%
    }
```

At the start of each `\chapter`, `\part`, or matter-switching command, run the boundary hook. At `\end{document}`, flush the last chapter's file.

```
    \AtBeginDocument{%
      \ifdef{\chapter}{%
        \axp@hookboundary{\chapter}%
      }{%
        \PackageWarning{apxproof}{%
          appendix=chapterend used but \string\chapter\space
          is not defined}%
      }%
      \ifdef{\part}{\axp@hookboundary{\part}}{}%
      \ifdef{\frontmatter}{\axp@hookboundary{\frontmatter}}{}%
      \ifdef{\mainmatter}{\axp@hookboundary{\mainmatter}}{}%
      \ifdef{\backmatter}{\axp@hookboundary{\backmatter}}{}%
    }
    \pretocmd{\@enddocumenthook}{%
      \axp@flushchapterappendix
    }{}{}
}{}
```

7.5.8 Class-Specific Behavior

We conclude with some class-specific behavior.

ACM Document Classes (old versions, till 2017)

```
\ifdefined\@acmtitlebox
```

We first redefine the `proofsketch` environment, which is used differently in the base class.

```
\renewenvironment{proofsketch}{\begin{axp@oldproof}[sketch]}{\end{axp@oldproof}}
```

We adjust the styling of theorems for the needs of apxproof.

```
\newtheoremstyle{mystyle}
  {6pt}
  {6pt}
  {\itshape}
  {10pt}
  {\scshape}
  {.}
  {.5em}
  {}
\theoremstyle{mystyle}
```

\thebibliography \refname \appendixrefname The section title of the bibliography is in uppercase in these document classes. In addition, the \thebibliography macro hard-codes twice the section title, so we un-hardcode it so that it can be modified in the appendix.

```
    \patchcmd{\thebibliography}{References}{\protect\refname}{}{}
    \patchcmd{\thebibliography}{References}{\protect\refname}{}{}
    \newcommand{\refname}{REFERENCES}
    \renewcommand{\appendixrefname}{REFERENCES FOR THE APPENDIX}

  \fi
```

lipcs

```
  \ifdefined\lipics@opterrshort
```

\appendixbibliographyprelim The default bibliography in the lipics document class formatting is not compatible with the alpha bibliography style. We fix this here.

```
    \renewcommand{\appendixbibliographyprelim}{%
      \global\let\@oldbiblabel\@biblabel
      \def\@biblabel{\hspace*{-2em}\small\@oldbiblabel}%
    }

  \fi
}
```

Change History

v1.0.0
General: Initial released version . . 1
v1.0.1
General: Prevent empty bibliography environment; fix typos 1
v1.0.2
axp@newtheoremrep: Fix display of repeated theorem counter in some document classes 20
Fix missing space between repeated theorem counter and theorem note 20
v1.0.3
General: Note on entire sections in appendix 2
\appendixbibliographyprelim: Support for lipics-v2016 34
proofsketch: Ignore spaces after beginning of Proof sketch . . . 15
v1.0.4
General: More faithful theorem style for ACM templates 33
More robust coherent styling of proof sketches 33
Re-establish custom proof environments 11
Show options commented on in margin and index 1
\appendixprelim: Configurable appendix style 15
\axp@bibliography: bibliography option 12
v1.0.5
General: Ability to specify a sectioning counter in newtheoremrep 2
Fix compilation of proofsketch environment in inline mode . . . 4
v1.0.6
General: Better support of Springer document classes 16
Deal with document classes where the bibliography is called \bibname 30
Support of new ACM document class (acmart.cls) 34
\axp@newtheorem: Introduce intermediary command for theorem macro 14

\axp@writesection: Fix extraneous space after section number in appendix titles . . . 29
axp@newtheoremrep: Better handling of note-free theorems in document classes that treat theorems differently when they have an empty note 20
Fix incorrect use of \noexpand in optional argument of macro environment 20
v1.1.0
General: Added forward-link mechanism (K. D. Bauer) . . . 22
\appendixsectionformat: Fix missing space in default \appendixsectionformat . . . 15
\axp@proofsfile: Initialization deferred to \AtBeginDocument for compatibility with \dumped precompiled preambles (K. D. Bauer) 18
\axp@redefinelabels: Fix \label not being disabled in amsmath environments, where \label@in@display is used instead (K. D. Bauer) 16
\axp@repeqn: repeqn option 12
\axp@unactivateeightbit: Fix compilation of non-ASCII characters with \usepackage[utf8]{inputenc} 18
\axp@writesection: Make \axp@tmp wrapper more robust. Resolves issues from use of section title in fancyhdr, and in \tableofcontents (K. D. Bauer). 29
\FVE@axp@VerbatimOut: Make apxproof compatible with independent use of fancyvrb . . 19
\section: Fix handling of fragile macros within section headings. See #22. 28
Rewrote definition of \section to enable optional argument. See #23. (K. D. Bauer) 28
\tableofcontents: Disable section management for table of contents 30
v1.2.0
General: Do not load bibunits if bibliography is set to common 13
\axp@newtheoremrep: Fix formatting of theorems without notes in some document classes in inline mode 17
\axp@newtheoremrep@definetheorem: Restore predefined theorem counters 14
\axp@redefinelabels: Fix extra spacing erroneously introduced within the \axp@redefinelabels macro . 16
\mainbodyrepeatedtheorem: Configurable repeated theorem command 15
proofsketch: Fix proof sketches in inline compilation mode for Springer document classes . . . 17
axp@newtheoremrep: Fix display of theorem notes 20
v1.2.1
General: Ad hoc fix for natbib package conflict 30
\appendixrefname: Fix compatibility with memoir document class 15
\FVE@axp@VerbatimOut: Fix compatibility with xypic package 19
Fix compatibility with other uses of fancyvrb that set \FV@CatCodesHook 19
v1.2.2
General: Compatibility with AMS document classes: do not use \AtEndDocument 30
\axp@section: Detect a section within an included file to avoid produced useless sections 28
axp@newtheoremrep: Fix handling of optional arguments of repeated theorems containing optional arguments 20
v1.2.3
General: More robust redefinition of thebibliography environment, for compatibility with tocbibind 30
\axp@forwardlinking: forwardlinking option 12
v1.2.4
appendixproof: Support optional arguments in proofs 25
claimproof: Support for claimproof environment from lipics 27

v1.2.5
`claimproof`: Support for locally defined `claimproof` environment 27
`axp@forward`: Remove forward linking command from PDF bookmarks 23
v1.2.6
General: Fix compilation issues in recent versions of acmart 17
`\axp@forward@setup`: Support for `aliascnt` counters 23
`\axp@newtheoremrep@definetheorem`: Undefine counter printing command to avoid warning . . 14
v1.3.0
General: Added `chapterend` appendix mode 31
`\axp@section`: Detect a section within an `\include`'d file 28
Skip blank lines before detecting a section command 28
v1.4.0
General: Documented workarounds for grouping per-section appendices under a single wrapping section. See #56. . . . 8
Flush `chapterend` appendices at `\part`, `\frontmatter`, `\mainmatter`, and `\backmatter` boundaries so the last chapter of a part/matter is not emitted under the next one 31
Public `\flushchapterappendix` macro for manually emitting the current chapter's accumulated appendix in `chapterend` mode 31
`appendixproof`: Route deferred proofs through `\axp@apxproofstart` to support `\appendixproofname` 25
`\appendixproofname`: Added `\appendixproofname` hook for customizing the title of a proof deferred to the appendix 15
`\axp@apxproofstart`: Helper that consults `\appendixproofname` at appendix typeset time to auto-title deferred proofs 24
`\axp@bibengine`: `bibengine` option to select the engine used for separate bibliographies: bibunits (default) or biblatex. See #29. 12
`\axp@newtheoremreptmp`: Added starred form of `\newtheoremrep` for proof-deferred theorems that are not restated in the appendix 15
`\bibliography`: Only rebind for bibunits engine. See #29. . . . 30
`axp@newtheoremrep`: Write auto-title state for `\appendixproofname` hook . . . 21
v1.4.1
`\apxproofhook`: Hook fired when a deferred proof is typeset, or for an inline proof whose title names its result through a `\ref`; used by the proofgraph package 24
`\axp@inlineproofhook`: Recognize `\zcref` of zref-clever in the title of an inline proof 24
`\axp@label@in@display`: Support `\zlabel` of zref-clever 16
Support the optional argument that cleveref adds to `\label` (R. Rowe) 16

Index

Numbers written in italic refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; numbers in roman refer to the code lines where the entry is used.

Symbols

`\@@appendixproof` 451, 467, 515
`\@@axp@newtheorem` 101, 168
`\@@section` 587
`\@acmplainnotefont` 315, 327, 328
`\@acmtitlebox` 750
`\@appendixproof` 451, 452, 515
`\@auxout` 613
`\@axp@newtheorem` 101, 168
`\@begintheorem` 314

\@biblabel 769, 770
\@bsphack 242
\@curr@file 573
\@enddocumenthook 637, 746
\@esphack 255
\@extra@binfo 640
\@ifnextchar 136, 140, 441, 449, 451, 515, 557, 559, 561, 586
\@ifpackageloaded 7
\@ifstar 101, 113, 440, 588
\@namedef 640
\@ne 238
\@nil 444, 446, 576, 578
\@noligs 250
\@oldbiblabel 769, 770
\@oparg 117, 121, 124
\@section 587
\@strip@tex@ext 573
\@thmcountersep 183
\␣ 39, 45, 58, 72, 81, 132
\^ 451, 484, 514, 515

A

\ACM@origsection 185, 186
\active 451, 484, 514, 515
\advance 238
\AND 62, 630
\appendix 644
appendix (option) 5
\appendixbibliographyprelim 7, 127, 673, 677, 768
\appendixbibliographystyle 7, 127, 647
\appendixclaimproof 515, 519, 527
\appendixprelim 7, 127, 643
\appendixproof 203, 451, 488, 496
appendixproof (env.) 2, 199, 451
\appendixproofname 2, 6, 127, 404
\appendixrefname 6, 127, 657, 659, 678, 762
\appendixsectionformat . . 6, 127, 617
\apx@oldamsthmendproof 10, 17
\apx@oldamsthmproof 9, 15, 16
\apxproofhook 401, 427
\arabic 704
\AtBeginDocument 186, 210, 228, 510, 733
\autoref 422
\axp@@@section 589, 590, 591
\axp@@claimproof 514, 524
\axp@@proof 484, 493
\axp@@sectionfinishinclude 556
\axp@@sectionskippar 556
\axp@@sectiontestinclude 556
\axp@@sectiontestinput 556
\axp@@sectiontestsection 556
\axp@appendix 24, 30, 32, 34, 36, 39, 61, 148, 188, 212, 229, 353, 628, 687
\axp@apxproofstart 399, 458
\axp@apxproofstart@title 403, 407, 411
\axp@apxproofstart@withtitle 410, 415
\axp@beginchapterappendix . . 689, 716
\axp@bibengine 26, 42, 43, 45, 49, 630, 646, 655
\axp@bibliography 25, 48, 55, 58, 62, 629, 645, 654
\axp@chapterboundary 721, 728
\axp@chaptercounter 697
\axp@chapterhasappendix 697
\axp@claimproof 514, 516
\axp@currentaxpfile 697, 704, 705, 717
\axp@endchapterappendix . . . 689, 718
\axp@equation 262
\axp@equationx 262
\axp@flushchapterappendix 712, 722, 747
\axp@forward 369
\axp@forward@link 359, 369
\axp@forward@setup 270, 393
\axp@forward@suppress 75
\axp@forward@target . . . 307, 338, 386
\axp@forwardlinking 28, 76, 77
\axp@gobbletorefstop 445, 448
\axp@grabarg 430, 438
\axp@grabref 434, 435
\axp@grabzcarg 425, 440
\axp@grabzcarg@i 440, 441
\axp@grabzcarg@ii 441, 442, 443
\axp@grabzcarg@iii 444, 446
\axp@grabzcarg@opt 441, 442
\axp@hookboundary 727, 735, 741, 742, 743, 744
\axp@inlineproofhook 416, 499
\axp@inlineproofof@label 427, 439, 447
\axp@inlineproofoffalse 418
\axp@inlineproofoftrue 439, 447
\axp@label 136, 163
\axp@label@do 137, 138, 149, 159
\axp@label@in@display 136, 164
\axp@label@in@display@do 141, 142, 153, 160
\axp@label@in@display@noopt 140, 142
\axp@label@in@display@opt . . 140, 141
\axp@label@noopt 136, 138
\axp@label@opt 136, 137
\axp@markchapterhasappendix 256, 258, 287, 454, 469, 700
\axp@newtheorem 92, 101, 268
\axp@newtheoremrep . 124, 189, 264, 264
\axp@newtheoremrep@definetheorem 84, 190, 265

\axp@newtheoremrep@nostar . . 113, 119
\axp@newtheoremrep@star . . . 113, 115
\axp@newtheoremreptmp 112
\axp@nextproofof@label 303, 400, 405, 413
\axp@nextproofof@type . . 302, 399, 404
\axp@noappendixbibliography 666, 671
\axp@oldbibliography 629
\axp@oldclaimproof . 223, 512, 521, 529
\axp@oldlabel . 145, 150, 151, 155, 159
\axp@oldlabel@in@display 146, 154, 160
\axp@oldproof 134, 449, 450, 490, 498, 550, 552
axp@oldproof (env.) 134
\axp@oldsection 225, 582, 586, 587, 627
\axp@oldtableofcontents 626
\axp@oldthebibliography 661
\axp@oldzlabel 147, 157, 161
\axp@openchapterfile . . . 213, 703, 724
\axp@proof 484, 485
\axp@proofsfile 210, 219, 248, 254, 289, 291, 301, 306, 310, 346, 457, 461, 471, 479, 543, 614, 652, 705, 706, 713, 714
\axp@redefinelabels 143, 193, 195, 339
\axp@refmark 429, 435
\axp@refstar 297, 299, 323
\axp@refstop 434, 435, 438, 448
\axp@repeqn 27, 67, 69, 72, 81, 272, 290, 345
\axp@replayproof 221, 449
\axp@replayproof@opt 449, 450
\axp@rpcounter 261
\axp@seccounter 554
\axp@section 556, 616
\axp@sectitle 555, 592, 602, 605, 620, 709
\axp@seenreptheorem 260
\axp@tmp 567, 569, 573, 574, 576, 607, 613, 615, 664, 665
\axp@tmptmp 568, 569, 575, 576
\axp@tryrefcmd 419, 420, 421, 422, 423, 430
\axp@tryrefcmd@ 425, 430, 431
\axp@unactivateeightbit . . . 233, 244
\axp@VerbatimOut 258, 465, 474
axp@VerbatimOut (env.) 240
\axp@with@forward 277, 279, 352
\axp@writeproofsfilepreamble 218, 230, 707
\axp@writesection 258, 288, 455, 470, 604
\axp@zlabel 157, 161, 165

B

\backmatter 744
\bfseries 171, 173, 176, 180
\bibcite 639, 682
bibengine (option) 5
\bibliography 629
bibliography (option) 5
\bibname 658, 659
\BODY 193, 195, 282, 286
\boolfalse 367, 708
\booltrue 79, 354, 701

C

\CatchFileDef 567, 574
\catcode 236, 451, 484, 514, 515
\chapter 734, 735, 738
\chapterappendixprelim 7, 689
\claimproof 223, 511, 512, 514
claimproof (env.) 510
\clearpage 131, 689
\closeout 652, 714
\count@ 234, 236, 237, 238
\Cref 421
\cref 420
\csdef 116, 358
\csedef 394
\csletcs 356, 357, 365
\csundef 120

D

\DeclareStringOption 24, 25, 26, 27, 28
\defaultbibliography 633
\DefineVerbatimEnvironment 240

E

\empty 665
\endappendixclaimproof 535, 540
\endappendixproof 204, 476, 505
\endaxp@oldclaimproof . . 224, 513, 537
\endaxp@oldproof 135, 222, 507, 551, 553
\endaxp@oldthebibliography 662
\endaxp@VerbatimOut 259, 478, 542
\endclaimproof 224, 513, 532
\endinlineproof 200, 551
\endnestedproof 202, 553
\endproof 10, 12, 17, 135, 200, 202, 204, 222, 502
\endthebibliography 662
environments:
appendixproof 2, 199, 451
axp@oldproof 134
axp@VerbatimOut 240
claimproof 510
inlineproof 4, 199, 550
nestedproof 8, 199, 550
proof 3, 218, 484

proofsketch 4, 126
toappendix 1, 205, 257
\errmessage 39, 45, 58, 72, 81
\expandonce . . . 609, 613, 615, 619, 620

F
\flushchapterappendix 7, 721
forwardlinking (option) 7
\frontmatter 742
\FV@CatCodesHook 251
\FV@DefineTabOut 247
\FV@DefineWhiteSpace 245
\FV@FontScanPrep 249
\FV@ProcessLine 248
\FV@Scan 252
\FV@Space 246
\FVB@axp@VerbatimOut 240
\FVE@axp@VerbatimOut 240

G
\gdef 302, 303, 399, 400, 666

H
\hspace 770
\hyperlink 375
\hypertarget 388

I
\ifaxp@inlineproofof 416, 420, 421, 422, 423, 424, 427
\ifblank 394
\ifbool 296, 715
\ifboolexpr 373
\ifcsdef 267, 305, 364, 374, 394
\ifcsname 87, 93, 387
\ifcsundef 355
\ifdef 734, 741, 742, 743, 744
\ifin@ 433
\ifnum 237
\in@ 432
\include 561, 571, 584
\inlineproof 199, 550
inlineproof (env.) 4, 199, 550
\input 559, 566, 653, 717
\itshape 171, 173, 176, 180, 755

L
\label 145, 163, 277, 279, 599
\label@in@display 144, 146, 164
\lipics@opterrshort 767
\long 417, 430, 431, 434, 438, 443, 446, 448, 578
\loop 235
\ltx@ifnextchar@nospace . . . 484, 514

M
\mainbodyrepeatedtheorem . 6, 127, 281
\mainmatter 743
\message 31, 33, 35, 37, 51, 53, 56, 68, 70, 78

N
\NAT@testdef 638, 681, 682
\nestedproof 201, 552
nestedproof (env.) 8, 199, 550
\newbool 75, 369, 698
\newif 416
\newtheorem 104, 106, 110
\newtheoremrep 2, 3, 112
\newtheoremrep* 2, 3
\newtheoremstyle 752
\noproofinappendix 8, 205, 266, 396, 482, 546
\nosectionappendix . . . 8, 205, 601, 623

O
\onecolumn 131
\openout 215, 705
options:
appendix 5
bibengine 5
bibliography 5
forwardlinking 7
repeqn 7

P
\PackageError 63
\PackageWarning 729, 737
\par 557, 565
\part 741
\pretocmd 266, 314, 637, 728, 746
\printbibliography 678
\ProcessLocalKeyvalOptions 29
\proof 9, 11, 16, 134, 199, 201, 203, 221, 484
proof (env.) 3, 218, 484
\proofsketch 182
proofsketch (env.) 4, 126
\protected@xdef 403
\providecommand 128, 144, 401
\putbib 674

R
\ref 297, 299, 405, 419, 610
\refname 656, 657, 762
\repeat 239
repeqn (option) 7

S
\scshape 757

\section . . 186, 218, 579, 586, 587, 627
\set@curr@file 572
\setcounter 273, 292, 293, 347
\SetupKeyvalOptions 20
\small 770
\spnewtheorem . 167, 171, 173, 176, 180
\stepcounter 723
\string 730, 738

T

\tableofcontents 626
\texorpdfstring 371, 372
\the 316, 331
\theaxp@equation 293
\thebibliography 661, 762
\theopargself 311, 312, 325
\theoremstyle 761
\thm@notefont 316, 330, 331
\thmhead 315, 316, 317, 318
toappendix (env.) 1, 205, 257
\togglefalse 397, 710
\toggletrue 283

U

\upshape 180

V

\value 273, 292, 347
\vref 423

W

\write 219, 248, 254, 289, 291, 301, 306, 310, 346, 457, 461, 471, 479, 543, 613, 614, 706, 713

X

\xdef 439, 447

Z

\zcref 425
\zlabel 147, 165

References

[1] Leslie Lamport. *LaTeX: A Document Preparation System.* Addison–Wesley Pub. Co., Reading, MA, 1986.

A Proofs for Section 1 (Usage)

Proof. □

Foobar 2. *This foobar is repeated in the appendix.*

Proof. □

Proof. □