# 1 Labels set with the standard command

Here labels are set with `\label`, which zref-clever picks up through the kernel's label hook.

**Theorem 1.** *A theorem, with an equation:*

$$1 = 1 \tag{1}$$

References: theorem 1, equation (1), and the appendix copy of the equation, equation (1).

# 2 Labels set with the zref command

**Theorem 2.** *Another theorem, with an equation:*

$$2 = 2 \tag{2}$$

References: theorem 2, equation (2), and the appendix copy of the equation, equation (2).

# 3 Proof titles naming their result

**Lemma 1.** *A lemma whose proof is not deferred.*

**Lemma 2.** *Another one.*

*Proof of lemma 1.* [hook: `lem:one`] Inline proof, whose title names its result. □

*Proof of lemma 2.* [hook: `lem:two`] Inline proof, whose title names its result in the starred form. □

# A Proofs for Section 1 (Labels set with the standard command)

**Theorem 1.** *A theorem, with an equation:*

$$1 = 1 \tag{1}$$

*Proof.* [hook: `axp@ri`] Deferred proof, referring to equation (1). □

# B Proofs for Section 2 (Labels set with the zref command)

**Theorem 2.** *Another theorem, with an equation:*

$$2 = 2 \tag{2}$$

*Proof.* [hook: `axp@rii`] Deferred proof, referring to equation (2). □