TS250F_400V

panel saw

- stable and precise table saw with aluminium sliding table
- largely dimensioned, stable outrigger table
- smoothly running saw blade height and angle adjustment
- large and precison-ground grey cast iron table with extension
- cross cut fence tilts 45° (left/right) and extentable (1230 - 2275 mm)
- rip fence with quick release clamp
- saw blade tilt (90-45°)
- CEE plug with phase inverter

included in delivery: T.C.T. (Tungsten-Carbide-Tipped) general purpose blade with Ø 254 x 30 x 3,0 mm- 36 teeth, sliding table, edging shoe, push stick, sliding wood, table extension / widening, extentable cross-cut fence



YOUR JOB. OUR TOOLS.

Technical modifications and errors excepted. RRP in Euro incl. VAT.

TS250F_400V

panel saw

technical details

motor power s6 in W	2900	motor power s1 in W	2100
voltage	400V / 50Hz	table size in mm	800 x 350
table height in mm	900	dust collector port in mm	Ø100 (Ø30)
sliding table in mm	1650 x 250	outrigger table in mm	595 x 460
table extension in mm	405 x 210	table widening in mm	800 x 320
total dimensions in mm	2180(-3225) x 2930 x 1150	max. cutting height 90° in mm	80
max. trimming in mm	1250	max. cutting height 45° in mm	50
max. cutting width at parallel fence in mm	640	sawblade in mm	254 (/30)
sawblade speed in min-1	4000	sound power level in dB(A)	95,7
sound pressure level in dB(A)	86,5	net weight in kg	192
gross weight in kg	233	packaging height in mm	1.035
packaging width in mm	760	packaging length in mm	970
EAN code	9120039901121		

YOUR JOB. OUR TOOLS.

Technical modifications and errors excepted. RRP in Euro incl. VAT.