

EXPERIMENT: 26

Write a program to search any goal given an input graph using AO* algorithm.

Program :

Cost to find the AND and OR path

def Cost(H, condition, weight = 1):

 cost = {}

 if 'AND' in condition:

 AND_nodes = condition['AND']

 Path_A = ' AND '.join(AND_nodes)

 PathA = sum(H[node]+weight for node in AND_nodes)

 cost[Path_A] = PathA

 if 'OR' in condition:

 OR_nodes = condition['OR']

 Path_B = ' OR '.join(OR_nodes)

 PathB = min(H[node]+weight for node in OR_nodes)

 cost[Path_B] = PathB

 return cost

Update the cost

def update_cost(H, Conditions, weight=1):

 Main_nodes = list(Conditions.keys())

 Main_nodes.reverse()

 least_cost= {}

 for key in Main_nodes:

```

condition = Conditions[key]

print(key,':', Conditions[key], '>>>', Cost(H, condition, weight))

c = Cost(H, condition, weight)

H[key] = min(c.values())

least_cost[key] = Cost(H, condition, weight)

return least_cost

```

Print the shortest path

```

def shortest_path(Start, Updated_cost, H):

    Path = Start

    if Start in Updated_cost.keys():

        Min_cost = min(Updated_cost[Start].values())

        key = list(Updated_cost[Start].keys())

        values = list(Updated_cost[Start].values())

        Index = values.index(Min_cost)

        # FIND MINIMUM PATH KEY

        Next = key[Index].split()

        # ADD TO PATH FOR OR PATH

        if len(Next) == 1:

            Start = Next[0]

            Path += '<--' + shortest_path(Start, Updated_cost, H)

        # ADD TO PATH FOR AND PATH

    else:

```

```
Path += '<--(' + key[Index] + ') '
```

```
Start = Next[0]
```

```
Path += '[' + shortest_path(Start, Updated_cost, H) + ' + '
```

```
Start = Next[-1]
```

```
Path += shortest_path(Start, Updated_cost, H) + ']'
```

```
return Path
```

```
H = {'A': -1, 'B': 5, 'C': 2, 'D': 4, 'E': 7, 'F': 9, 'G': 3, 'H': 0, 'I': 0, 'J': 0}
```

```
Conditions = {
```

```
'A': {'OR': ['B'], 'AND': ['C', 'D']},
```

```
'B': {'OR': ['E', 'F']},
```

```
'C': {'OR': ['G'], 'AND': ['H', 'I']},
```

```
'D': {'OR': ['J']}
```

```
}
```

```
# weight
```

```
weight = 1
```

```
# Updated cost
```

```
print('Updated Cost :')
```

```
Updated_cost = update_cost(H, Conditions, weight=1)
```

```
print('*'*75)
```

```
print('Shortest Path :\n',shortest_path('A', Updated_cost,H))
```

OUTPUT:

```
Updated Cost :
D : {'OR': ['J']} >>> {'J': 1}
C : {'OR': ['G'], 'AND': ['H', 'I']} >>> {'H AND I': 2, 'G': 4}
B : {'OR': ['E', 'F']} >>> {'E OR F': 8}
A : {'OR': ['B'], 'AND': ['C', 'D']} >>> {'C AND D': 5, 'B': 9}
*****
Shortest Path :
A<--(C AND D) [C<--(H AND I) [H + I] + D<--J]
```