

ArrayLists

Exercise

- Write a program that reads a file and displays the words of that file as a list.
 - First display all words.
 - Then display them with all plurals (ending in "s") capitalized.
 - Then display them in reverse order.
 - Then display them with all plural words removed.
- Should we solve this problem using an array?
 - Why or why not?

Naive solution

```
String[] allWords = new String[1000];  
int wordCount = 0;
```

```
Scanner input = new Scanner(new File("data.txt"));  
while (input.hasNext()) {  
    String word = input.next();  
    allWords[wordCount] = word;  
    wordCount++;  
}
```

- Problem: You don't know how many words the file will have.
 - Hard to create an array of the appropriate size.
 - Later parts of the problem are more difficult to solve.
- Luckily, there are other ways to store data besides in an array.


Collections

- **collection**: an object that stores data; a.k.a. "data structure"
 - the objects stored are called **elements**
 - some collections maintain an ordering; some allow duplicates
 - typical operations: *add*, *remove*, *clear*, *contains* (search), *size*
 - examples found in the Java class libraries:
 - `ArrayList`, `LinkedList`, `HashMap`, `TreeSet`, `PriorityQueue`
 - all collections are in the `java.util` package

```
import java.util.*;
```

Lists

- **list**: a collection storing an ordered sequence of elements
 - each element is accessible by a 0-based **index**
 - a list has a **size** (number of elements that have been added)
 - elements can be added to the front, back, or elsewhere
 - in Java, a list can be represented as an **ArrayList** object



Idea of a list

- Rather than creating an array of boxes, create an object that represents a "list" of items. (initially an empty list.)

`[]`

- You can add items to the list.
 - The default behavior is to add to the end of the list.

`[hello, ABC, goodbye, okay]`

- The list object keeps track of the element values that have been added to it, their order, indexes, and its total size.
 - Think of an "array list" as an automatically resizing array object.
 - Internally, the list is implemented using an array and a size field.

ArrayList methods (10.1)

<code>add (value)</code>	appends value at end of list
<code>add (index, value)</code>	inserts given value just before the given index, shifting subsequent values to the right
<code>clear()</code>	removes all elements of the list
<code>indexOf (value)</code>	returns first index where given value is found in list (-1 if not found)
<code>get (index)</code>	returns the value at given index
<code>remove (index)</code>	removes/returns value at given index, shifting subsequent values to the left
<code>set (index, value)</code>	replaces value at given index with given value
<code>size()</code>	returns the number of elements in list
<code>toString()</code>	returns a string representation of the list such as "[3, 42, -7, 15]"

ArrayList methods 2

addAll (list) addAll (index , list)	adds all elements from the given list to this list (at the end of the list, or inserts them at the given index)
contains (value)	returns true if given value is found somewhere in this list
containsAll (list)	returns true if this list contains every element from given list
equals (list)	returns true if given other list contains the same elements
iterator() listIterator()	returns an object used to examine the contents of the list (seen later)
lastIndexOf (value)	returns last index value is found in list (-1 if not found)
remove (value)	finds and removes the given value from this list
removeAll (list)	removes any elements found in the given list from this list
retainAll (list)	removes any elements <i>not</i> found in given list from this list
subList (from , to)	returns the sub-portion of the list between indexes from (inclusive) and to (exclusive)
toArray ()	returns the elements in this list as an array

Type Parameters (Generics)

```
ArrayList<Type> name = new ArrayList<Type>();
```

- When constructing an `ArrayList`, you must specify the type of elements it will contain between `<` and `>`.
 - This is called a *type parameter* or a *generic* class.
 - Allows the same `ArrayList` class to store lists of different types.

```
ArrayList<String> names = new ArrayList<String>();  
names.add("Marty Stepp");  
names.add("Stuart Reges");
```

ArrayList vs. array

- construction

```
String[] names = new String[5];
```

```
ArrayList<String> list = new ArrayList<String>();
```

- storing a value

```
names[0] = "Jessica";
```

```
list.add("Jessica");
```

- retrieving a value

```
String s = names[0];
```

```
String s = list.get(0);
```

ArrayList vs. array 2

- doing something to each value that starts with "B"

```
for (int i = 0; i < names.length; i++) {  
    if (names[i].startsWith("B")) { ... }  
}
```

```
for (int i = 0; i < list.size(); i++) {  
    if (list.get(i).startsWith("B")) { ... }  
}
```

- seeing whether the value "Benson" is found

```
for (int i = 0; i < names.length; i++) {  
    if (names[i].equals("Benson")) { ... }  
}
```

```
if (list.contains("Benson")) { ... }
```

Exercise, revisited

- Write a program that reads a file and displays the words of that file as a list.
 - First display all words.
 - Then display them in reverse order.
 - Then display them with all plurals (ending in "s") capitalized.
 - Then display them with all plural words removed.

Exercise solution (partial)

```
ArrayList<String> allWords = new ArrayList<String>();
Scanner input = new Scanner(new File("words.txt"));
while (input.hasNext()) {
    String word = input.next();
    allWords.add(word);
}
System.out.println(allWords);

// remove all plural words
for (int i = 0; i < allWords.size(); i++) {
    String word = allWords.get(i);
    if (word.endsWith("s")) {
        allWords.remove(i);
        i--;
    }
}
```

ArrayList as parameter

```
public static void name(ArrayList<Type> name) {
```

- Example:

```
// Removes all plural words from the given list.
```

```
public static void removePlural(ArrayList<String> list) {  
    for (int i = 0; i < list.size(); i++) {  
        String str = list.get(i);  
        if (str.endsWith("s")) {  
            list.remove(i);  
            i--;  
        }  
    }  
}
```

- You can also return a list:

```
public static ArrayList<Type> methodName(params) 14
```

ArrayList of primitives?

- The type you specify when creating an `ArrayList` must be an object type; it cannot be a primitive type.

```
// illegal -- int cannot be a type parameter  
ArrayList<int> list = new ArrayList<int>();
```

- But we can still use `ArrayList` with primitive types by using special classes called *wrapper* classes in their place.

```
// creates a list of ints  
ArrayList<Integer> list = new ArrayList<Integer>();
```

Wrapper classes



Primitive Type	Wrapper Type
int	Integer
double	Double
char	Character
boolean	Boolean

- A wrapper is an object whose sole purpose is to hold a primitive value.
- Once you construct the list, use it with primitives as normal:

```
ArrayList<Double> grades = new ArrayList<Double>();  
grades.add(3.2);  
grades.add(2.7);  
...  
double myGrade = grades.get(0);
```


Exercise

- Write a program that reads a file full of numbers and displays all the numbers as a list, then:
 - Prints the average of the numbers.
 - Prints the highest and lowest number.
 - Filters out all of the even numbers (ones divisible by 2).

Exercise solution (partial)

```
ArrayList<Integer> numbers = new ArrayList<Integer>();
Scanner input = new Scanner(new File("numbers.txt"));
while (input.hasNextInt()) {
    int n = input.nextInt();
    numbers.add(n);
}
System.out.println(numbers);
filterEvens(numbers);
System.out.println(numbers);
...

// Removes all elements with even values from the given list.
public static void filterEvens(ArrayList<Integer> list) {
    for (int i = list.size() - 1; i >= 0; i--) {
        int n = list.get(i);
        if (n % 2 == 0) {
            list.remove(i);
        }
    }
}
```

Out-of-bounds

- Legal indexes are between **0** and the **list's size() - 1**.
 - Reading or writing any index outside this range will cause an `IndexOutOfBoundsException`.

```
ArrayList<String> names = new ArrayList<String>();  
names.add("Marty");    names.add("Kevin");  
names.add("Vicki");    names.add("Larry");  
System.out.println(names.get(0));           // okay  
System.out.println(names.get(3));           // okay  
System.out.println(names.get(-1));         // exception  
names.add(9, "Aimee");                     // exception
```

<i>index</i>	<i>0</i>	<i>1</i>	<i>2</i>	<i>3</i>
<i>value</i>	Marty	Kevin	Vicki	Larry

ArrayList "mystery"

```
ArrayList<Integer> list = new ArrayList<Integer>();  
for (int i = 1; i <= 10; i++) {  
    list.add(10 * i);    // [10, 20, 30, 40, ..., 100]  
}
```

- What is the output of the following code?

```
for (int i = 0; i < list.size(); i++) {  
    list.remove(i);  
}  
System.out.println(list);
```

- Answer:

```
[20, 40, 60, 80, 100]
```

ArrayList "mystery" 2

```
ArrayList<Integer> list = new ArrayList<Integer>();  
for (int i = 1; i <= 5; i++) {  
    list.add(2 * i);    // [2, 4, 6, 8, 10]  
}
```

- What is the output of the following code?

```
int size = list.size();  
for (int i = 0; i < size; i++) {  
    list.add(i, 42);    // add 42 at index i  
}  
System.out.println(list);
```

- Answer:

```
[42, 42, 42, 42, 42, 2, 4, 6, 8, 10]
```

ArrayList as parameter

```
public static void name(ArrayList<Type> name) {
```

- Example:

```
// Removes all plural words from the given list.
```

```
public static void removePlural(ArrayList<String> list) {  
    for (int i = 0; i < list.size(); i++) {  
        String str = list.get(i);  
        if (str.endsWith("s")) {  
            list.remove(i);  
            i--;  
        }  
    }  
}
```

- You can also return a list:

```
public static ArrayList<Type> methodName(params)
```

Exercise

- Write a method `addStars` that accepts an array list of strings as a parameter and places a `*` after each element.
 - Example: if an array list named `list` initially stores:
`[the, quick, brown, fox]`
 - Then the call of `addStars(list);` makes it store:
`[the, *, quick, *, brown, *, fox, *]`
- Write a method `removeStars` that accepts an array list of strings, assuming that every other element is a `*`, and removes the stars (undoing what was done by `addStars` above).

Exercise solution

```
public static void addStars(ArrayList<String> list) {  
    for (int i = 0; i < list.size(); i += 2) {  
        list.add(i, "*");  
    }  
}
```

```
public static void removeStars(ArrayList<String> list) {  
    for (int i = 0; i < list.size(); i++) {  
        list.remove(i);  
    }  
}
```