

Summary: Lecture 5

Summary for the chapters X and X . [6]

Reduction

Examples of NP-problems:

- Travelling Salesman Problem
- SATISFIABLE
- REACHABILITY (in P)
- CIRCUIT VALUE (in P)




Figure 1: P and NP sets [3]

- reduction: a problem is at least as hard as another
- problem A is at least as hard as problem B if B reduces to A
- B reduces to A if there is a transformation R
 - R produces for every input x of B an equivalent input $R(x)$ of A
 - the answer of input x on B and input $R(x)$ on A have to be the same
- to solve B on input x , A can be solved instead with input $R(x)$

Reduction

Problem A is at least as hard as problem B if B reduces to A .

Transformation function:

- transformation function R should not be too hard to compute
→ R should be limited
- efficient reduction R : $\log n$ space bounded

Transformation function

A language L_1 is reducible to L_2 if there is a function R computable by a deterministic Turing Machine in space $O(\log n)$ and $x \in L_1 \Leftrightarrow R(x) \in L_2$.

R is called a reduction from L_1 to L_2 .

- A Turing Machine M that computes a reduction R halts for all inputs x after a polynomial number of steps.
 - there are $O(n \cdot c^{\log n})$ possible configurations for M on an input of length n
 - deterministic: no configuration can be repeated
 - computation of length at most $O(n^k)$

Reduction HAMILTONIAN PATH to SATISFIABLE

Problem: HAMILTON PATH

The Hamiltonian Path problem asks whether there is a route in a directed graph G from a start node to an ending node, visiting each node exactly once. (Is there a path in G that visits each node one?) [1]

Problem: SAT

The SAT (satisfiability) problem is the problem of determining if there exists an interpretation that satisfies a given Boolean formula. [7]

- HAMILTON PATH can be reduced to SAT
→ demonstrates HAMILTON PATH is not significantly harder than SAT
- construct a boolean expression $R(G)$ that is satisfiable only if G has a Hamilton path
→ write a logical formula that only becomes true when HP is true
- instance: Graph $G = (V, E)$ with n nodes $(1, 2, \dots, n)$
- $R(G)$ has n^2 boolean variables $x_{i,j}$ then
- node j is the i th node in the HAMILTON PATH
- $R(G)$ is in conjunctive normal form (CNF: $(a \vee b) \wedge (\neg a \vee c)$)
- conjuncted clauses of $R(x)$:
 - each node j must appear in the path $x_{1,j} \vee x_{2,j} \vee \dots \vee x_{n,j}$ – for every node j
 - no node j appears twice in the path: $\neg x_{i,j} \vee \neg x_{k,j}$ for all i, j, k with $i \neq k$
 - every position i on the path must be occupied – $x_{i,1} \vee x_{i,2} \vee \dots \vee x_{i,n}$ for each i
 - no two nodes j and k occupy the same position in the path – $\neg x_{i,j} \vee \neg x_{i,k}$ for all i, j, k with $j \neq k$
 - nonadjacent nodes i and j cannot be adjacent in the path – $\neg x_{k,i} \vee \neg x_{k+1,j}$ for all $(i, j) \notin E$ and $k = 1, 2, \dots, n - 1$

[4]

Proof idea:

- to show:
 - for any graph G , $R(G)$ has a satisfying truth assignment only if and only if G has a Hamilton path
 - R can be computed in space $\log n$
-

TODO

proof

Questions:

Boolean Circuit

A Boolean circuit is a mathematical tree model for logic formulas. Boolean circuits are defined in terms of the logic gates they contain. For example, a circuit might contain binary AND and OR gates and unary NOT gates, or be entirely described by binary NAND gates.




Figure 2: Boolean circuit example [2]

Reduction REACHABILITY PATH to CIRCUIT VALUE

Problem: GRAPH REACHABILITY

Given a graph G and two nodes $n_1, n_2 \in V$, is there path from n_1 to n_2 ?
A graph $G = (V, E)$ is a finite set V of nodes and a set E of edges as node pairs.

REACHABILITY can be nondeterministically solved in space $\log n$.

Problem: CIRCUIT VALUE

The CIRCUIT VALUE Problem is the problem of computing the output of a given Boolean circuit on a given input.

In terms of time complexity, it can be solved in linear time (topological sort).

The problem is closely related to the SAT (Boolean Satisfiability) problem which is complete for NP and its complement, which is complete for co-NP.

- REACHABILITY can be reduced to CIRCUIT VALUE
→ demonstrates REACHABILITY is not significantly harder than CIRCUIT VALUE
- construct a variable-free circuit $R(G)$ that has *true* as output only if G has a path from the start node to node n
- (both problems are in P)
- instance: Graph $G = (V, E)$ with n nodes $(1, 2, \dots, n)$
- [5]

TODO

construct reduction

proof

Questions:

Reduction CIRCUIT SAT to SAT

Problem: CIRCUIT SAT

The circuit satisfiability problem (CIRCUIT SAT) is the decision problem of determining whether a given Boolean circuit has an assignment of its inputs that makes the output true.

TODO

construction of reduction

proof idea

Questions:

Further examples

TODO

Questions:

Closedness under Composition

TODO

Questions:

References

- [1] J. Baumgardner, K. Acker, O. Adefuye, and et al. "Solving a Hamiltonian Path Problem with a bacterial computer". In: *J Biol Eng* 3.11 (2009). DOI: <https://doi.org/10.1186/1754-1611-3-11>.
- [2] *Image source: Boolean Circuit*. https://upload.wikimedia.org/wikipedia/en/thumb/d/df/Three_input_Boolean_circuit.jpg/300px-Three_input_Boolean_circuit.jpg.
- [3] *Image source: P-NP sets*. <https://www.techno-science.net/actualite/np-conjecture-000-000-partie-denouee-N21607.html>.
- [4] Prof. Yuh-Dauh Lyuu. *Lecture slides on Reduction of hamiltonian path to sat*. <https://www.csie.ntu.edu.tw/~lyuu/complexity/2011/20111018.pdf>. 2011.
- [5] Prof. Yuh-Dauh Lyuu. *Lecture slides on Reduction of reachability to circuit value*. https://www.csie.ntu.edu.tw/~lyuu/complexity/2004/c_20041020.pdf. 2004.
- [6] Christos H. Papadimitriou. *Computational Complexity*. Addison-Wesley Publishing Company, 1994.
- [7] Prof. Dr. Thomas Schwentick. *Lecture slides in Grundbegriffe der theoretischen Informatik*. https://www.cs.tu-dortmund.de/nps/de/Studium/Ordnungen_Handbuecher_Beschluesse/Modulhandbuecher/Archiv/Bachelor_LA_GyGe_Inf_Modellv/_Module/INF-BfP-GTI/index.html.