

Summary: Lecture 8

Summary for the chapters 9.3 and 9.4. [2, 1]

Undirected graph

An undirected graph G is a pair of sets (V, E) where V is the finite set of nodes and E is a set of unordered pairs in V that are symmetric:

$$\forall i, j \in E, i \neq j : (i, j) \in E \Rightarrow (j, i) \in E$$

IndependentSet

IndependentSet

INDEPENDENTSET

Input: An undirected Graph $G = (V, E)$ and a number k .

Question: Is there a set $I \subseteq V$ of $k = |I|$ nodes with no edges in between? (INDEPENDENTSET)

INDEPENDENTSET is NP-complete.

Proof idea:

- triangle construction

TODO

Questions:

HamiltonPath is NP-complete

HAMILTONPATH is NP-complete.

Proof idea:

- Another reduction from 3SAT

TODO

Questions:

TSP(D)

TSP(D)

TSP(D) is a decision version of TSP.

Input: A $n \times n$ distance matrix and a bound $B \in \mathbb{N}$

Question: Is there a round tour of length $\leq B$ that visits all *cities*?

TSP(D) is NP-complete.

Proof idea:

- budget of nodes is $B = |V| + 1$

TODO

Questions:

Knapsack

Knapsack

KNAPSACK is NP-complete.

- filled in in one dimensional array onthe board
-

TODO

Questions:

References

- [1] Martin Berglund. *Lecture notes in Computational Complexity*.
- [2] Christos H. Papadimitriou. *Computational Complexity*. Addison-Wesley Publishing Company, 1994.