

Adapting Coreference Resolution Models through Active Learning

ACL 2022

**Michelle Yuan¹ Patrick Xia² Chandler May²
Benjamin Van Durme² Jordan Boyd-Graber¹**

¹Department of Computer Science
University of Maryland

²Department of Computer Science
Johns Hopkins University



Coreference Resolution (CR)

The task of discovering spans of text that refer to the same entity

Source
(Finance)

Traders said **municipals** were underpinned by influences, including the climb in Treasury issue prices. Also, **municipal bonds** lured buying because the stock market remains wobbly, traders contended. Mainly though, it was a favorable outlook for yesterday's new supply that propped up **municipals**, some traders said. Among the new issues was Massachusetts's \$230 million of **general obligation bonds**. **The bonds** were won by a Goldman Sachs & Co. group with a true interest cost of 7.17%.

Cluster: { **municipals** , **municipal bonds** , **municipals** , **general obligation bonds** , **The bonds** }

Coreference Resolution (CR)

The task of discovering spans of text that refer to the same entity

Source
(Finance)

Traders said **municipals** were underpinned by influences, including the climb in Treasury issue prices. Also, **municipal bonds** lured buying because the stock market remains wobbly, traders contended. Mainly though, it was a favorable outlook for yesterday's new supply that propped up **municipals**, some traders said. Among the new issues was Massachusetts's \$230 million of **general obligation bonds**. **The bonds** were won by a Goldman Sachs & Co. group with a true interest cost of 7.17%.

Cluster: { **municipals** , **municipal bonds** , **municipals** , **general obligation bonds** , **The bonds** }

Neural, end-to-end models (Lee et al., 2018; Joshi et al., 2020) are SOTA for OntoNotes 5.0

Problem: Adapting CR Models

Models trained on OntoNotes may not immediately generalize to new domains

Source
(Finance)

Traders said **municipals** were underpinned by influences, including the climb in Treasury issue prices. Also, **municipal bonds** lured buying because the stock market remains wobbly, traders contended. Mainly though, it was a favorable outlook for yesterday's new supply that propped up **municipals**, some traders said. Among the new issues was Massachusetts's \$230 million of **general obligation bonds**. **The bonds** were won by a Goldman Sachs & Co. group with a true interest cost of 7.17%.

Cluster: { **municipals**, **municipal bonds**, **municipals**, **general obligation bonds**, **The bonds** }

Target
(Science)

A molecule is a group of atoms held together by **chemical bonds**. Imagine you and your friends standing in a circle holding hands. Each person stands for one atom, your hands represent **the bonds**, and the entire circle represents a molecule.

Problem: Adapting CR Models

Models trained on OntoNotes may not immediately generalize to new domains

Source
(Finance)

Traders said **municipals** were underpinned by influences, including the climb in Treasury issue prices. Also, **municipal bonds** lured buying because the stock market remains wobbly, traders contended. Mainly though, it was a favorable outlook for yesterday's new supply that propped up **municipals**, some traders said. Among the new issues was Massachusetts's \$230 million of **general obligation bonds**. **The bonds** were won by a Goldman Sachs & Co. group with a true interest cost of 7.17%.

Cluster: { **municipals**, **municipal bonds**, **municipals**, **general obligation bonds**, **The bonds** }

Target
(Science)

A molecule is a group of atoms held together by **chemical bonds**. Imagine you and your friends standing in a circle holding hands. Each person stands for one atom, your hands represent **the bonds**, and the entire circle represents a molecule.

Impedes immediate application for scenarios like distinguishing entities in scientific articles

Problem: Adapting CR Models

- (Xia and Van Durme, 2021) show the benefits of *continued training* where a model trained on OntoNotes is further trained on the target dataset

Problem: Adapting CR Models

- (Xia and Van Durme, 2021) show the benefits of *continued training* where a model trained on OntoNotes is further trained on the target dataset
- However, they assume labeled data already exist in the target domain

Problem: Adapting CR Models

- (Xia and Van Durme, 2021) show the benefits of *continued training* where a model trained on OntoNotes is further trained on the target dataset
- However, they assume labeled data already exist in the target domain
- How can we adapt CR models without requiring large amounts of newly annotated data?

Method: Active Learning

Find particular spans of text for users to label

Target
(Science)

(1)

A molecule is a group of atoms held together by **chemical bonds** . Imagine you and your friends standing in a circle holding hands. Each person stands for one atom, your hands represent **the bonds** , and the entire circle represents a molecule.

Active query: **the bonds** Answer: **chemical bonds**

Queries: **the bonds**

(2)

Dr. Raizman thinks the animals help decrease patients' stress by increasing the release of oxytocin, which is the hormone that **bonds** mothers to babies. Studies have shown patients who spend time with dogs have higher levels of dopamine.

Active query: **bonds** Answer: **query is not entity**

Queries: **bonds**

Method: Active Learning

Find particular spans of text for users to label

Target
(Science)

(1)

A molecule is a group of atoms held together by **chemical bonds** . Imagine you and your friends standing in a circle holding hands. Each person stands for one atom, your hands represent **the bonds** , and the entire circle represents a molecule.

Active query: **the bonds** Answer: **chemical bonds**

Queries: **the bonds**

(2)

Dr. Raizman thinks the animals help decrease patients' stress by increasing the release of oxytocin, which is the hormone that **bonds** mothers to babies. Studies have shown patients who spend time with dogs have higher levels of dopamine.

Active query: **bonds** Answer: **query is not entity**

Queries: **bonds**

The goal is to adapt the model to the target domain by continue training it on these newly labeled spans

Method: Active Learning

We explore active learning for adapting CR models by:

1. Sampling spans according to different sources of model uncertainty

Method: Active Learning

We explore active learning for adapting CR models by:

1. Sampling spans according to different sources of model uncertainty
2. Understanding the trade-off between reading and labeling costs

Uncertainty Sampling

- A common active learning strategy is to sample data that the model is most uncertain about

Uncertainty Sampling

- A common active learning strategy is to sample data that the model is most uncertain about
- Maximum entropy sampling (Lewis and Gale, 1994) chooses data with highest predictive entropy

Uncertainty Sampling

- A common active learning strategy is to sample data that the model is most uncertain about
- Maximum entropy sampling (Lewis and Gale, 1994) chooses data with highest predictive entropy
- For CR, these strategies are not as straightforward because the model has different scores for mention detection and clustering

Decomposing Decisions in CR

1. Mention detection:

- Given a span of text x , let X be the random variable encoding whether x is an entity mention (1) or not (0)
- The CR model first scores $P(X = 1)$, which is the likelihood of x being an entity mention

Decomposing Decisions in CR

1. Mention detection:

- Given a span of text x , let X be the random variable encoding whether x is an entity mention (1) or not (0)
- The CR model first scores $P(X = 1)$, which is the likelihood of x being an entity mention

2. Mention clustering:

- Given span x , let C be the random variable associated with the entity cluster of x
- For spans that are likely entity mentions, the CR model determines $P(C = c | X = 1)$ for each observed entity cluster c

Maximum Entropy Sampling for CR

ment-ent: Mention detection entropy

$$\begin{aligned} H_{\text{MENT}}(X) &= H(X) \\ &= - \sum_{i=0}^1 P(X = i) \log P(X = i). \end{aligned} \tag{1}$$

Samples spans that challenge mention detection (e.g. class-ambiguous words like “park”).

Maximum Entropy Sampling for CR

clust-ent: Mention clustering entropy

$$\begin{aligned} H_{\text{CLUST}}(x) &= H(C | X = 1) \\ &= - \sum_{c \in \mathcal{C}} P(C = c | X = 1) \log \\ &\quad P(C = c | X = 1). \end{aligned} \tag{2}$$

Entropy computation does not explicitly address uncertainty in mention detection.

Maximum Entropy Sampling for CR

cond-ent: Conditional entropy

$$\begin{aligned} H_{\text{COND}}(X) &= H(C | X) \\ &= \sum_{i=0}^1 P(X = i) H(C | X = i) \\ &= P(X = 1) H(C | X = 1) \\ &= P(X = 1) H_{\text{CLUST}}(X). \end{aligned} \tag{3}$$

Samples words like pronouns because they are obviously entity mentions but difficult to cluster.

Maximum Entropy Sampling for CR

joint-ent: Joint entropy

$$\begin{aligned} H_{\text{JOINT}}(x) &= H(X, C) = H(X) + H(C | X) \\ &= H_{\text{MENT}}(x) + H_{\text{COND}}(x). \end{aligned} \tag{4}$$

Samples spans that are difficult to detect as entity mentions *and* too confusing to cluster.


Experiments: Baselines

1. **random:** Sample from all spans in the document
2. **random-ment:** Like other uncertainty strategies, sample only from the pool of spans that are likely entity mentions

Experiments: Datasets


1. **OntoNotes 5.0 (source):** Most common dataset for training and evaluating CR that contains news articles and telephone conversations (Pradhan et al., 2013). Only non-singletons are annotated.
2. **PreCo (target):** Large corpus of grade-school reading comprehension texts with annotated singletons (Chen et al., 2018).

Evaluating Active Learning



- Test Avg. F1 on PreCo of models trained with each strategy
- Each cycle simulates fifty spans from one document being labeled
- **Ment-ent**, **clust-ent**, and **joint-ent** are effective while **random** performs worst

Reading and Labeling Trade-off



- Test Avg F1 on PreCo of models trained with each strategy
- Each column varies in max. number of docs. read per cycle
- Each row varies in number of labeled spans per cycle
- For unconstrained reading, model training is unstable

Reading and Labeling for Humans

Three users label spans sampled from PreCo

Text

Two new studies have investigated why fewer women , compared to men , study and work in the so-called STEM subjects in the United States : science , technology , engineering and mathematics . The American Association of University Women (AAUW) examined existing research . Its report `` Why So Few ? '' suggested ways to interest more girls and women in the STEM fields . The researchers found that cultural and environmental factors make a difference . Researcher Christianne Corbett says more boys than girls score very high on math

Active query: Researcher Christianne Corbett Answer: The researchers

Queries: the STEM fields The researchers Researcher Christianne Corbett Iceland

Overlapping Candidates

(1) The researchers

(n)o previous mention

(q)uery is not entity

Reading and Labeling for Humans

Three users label spans sampled from PreCo

Text

Two new studies have investigated why fewer women , compared to men , study and work in the so-called STEM subjects in the United States : science , technology , engineering and mathematics . The American Association of University Women (AAUW) examined existing research . Its report `` Why So Few ? '' suggested ways to interest more girls and women in the STEM fields . The researchers found that cultural and environmental factors make a difference . Researcher Christianne Corbett says more boys than girls score very high on math

Active query: Researcher Christianne Corbett Answer: The researchers

Queries: the STEM fields The researchers Researcher Christianne Corbett Iceland

Overlapping Candidates

(1) The researchers


(n)o previous mention

(q)uery is not entity

Users complete two twenty-five minute sessions:

1. **FewDocs:** Read fewer docs. and label multiple spans per doc.
2. **ManyDocs:** Read more docs. and label one span per doc.

Reading and Labeling for Humans



- Each color indicates one of three users and the linetype designates the session
- Black dots mark the first span labeled in a different document
- Users label at least twice as many spans during **FewDocs** than they do for **ManyDocs**

Summary

1. To reduce annotation for transferring coreference resolution models, we use active learning to choose text spans for users to label

Summary

1. To reduce annotation for transferring coreference resolution models, we use active learning to choose text spans for users to label
2. We explore various aspects of active learning for coreference resolution, like sources of model uncertainty and the trade-off between reading and labeling

Summary

1. To reduce annotation for transferring coreference resolution models, we use active learning to choose text spans for users to label
2. We explore various aspects of active learning for coreference resolution, like sources of model uncertainty and the trade-off between reading and labeling
3. Surprisingly, sampling by mention detection entropy is more useful for domains like PreCo

Summary

1. To reduce annotation for transferring coreference resolution models, we use active learning to choose text spans for users to label
2. We explore various aspects of active learning for coreference resolution, like sources of model uncertainty and the trade-off between reading and labeling
3. Surprisingly, sampling by mention detection entropy is more useful for domains like PreCo
4. In both simulations and the user study, there are more benefits from sampling spans from the same document rather than different contexts

Thanks

Any Questions?

myuan@cs.umd.edu



DEPARTMENT OF
COMPUTER SCIENCE

References I

Xilun Chen, Yu Sun, Ben Athiwaratkun, Claire Cardie, and Kilian Weinberger. Adversarial deep averaging networks for cross-lingual sentiment classification. 6:557–570, 2018. doi: 10.1162/tacI_a_00039.

Mandar Joshi, Danqi Chen, Yinhan Liu, Daniel S Weld, Luke Zettlemoyer, and Omer Levy. SpanBERT: Improving pre-training by representing and predicting spans. 8:64–77, 2020. doi: 10.1162/tacI_a_00300.

Kenton Lee, Luheng He, and Luke Zettlemoyer. Higher-order coreference resolution with coarse-to-fine inference. 2018. doi: 10.18653/v1/N18-2108.

David D. Lewis and William A. Gale. A sequential algorithm for training text classifiers. 1994.

Sameer Pradhan, Alessandro Moschitti, Nianwen Xue, Hwee Tou Ng, Anders Björkelund, Olga Uryupina, Yuchen Zhang, and Zhi Zhong. Towards robust linguistic analysis using OntoNotes. 2013. URL <https://www.aclweb.org/anthology/W13-3516>.

References II

Patrick Xia and Benjamin Van Durme. Moving on from OntoNotes: Coreference resolution model transfer. 2021. doi: 10.18653/v1/2021.emnlp-main.425.