

Interactive Refinement of Cross-Lingual Word Embeddings

Michelle Yuan^{1*} Mozhi Zhang^{1*} Benjamin Van Durme² Leah Findlater³ Jordan Boyd-Graber¹

¹University of Maryland ²John Hopkins University ³University of Washington *Equal contribution

NLP for Low-resource Languages


- ▶ Scarcity of both labeled and unlabeled data holds back applications in low-resource languages
- ▶ Cross-lingual word embeddings (CLWE) can bridge the gap by mapping words from different languages to a shared vector space

NLP for Low-resource Languages

- ▶ Scarcity of both labeled and unlabeled data holds back applications in low-resource languages
- ▶ Cross-lingual word embeddings (CLWE) can bridge the gap by mapping words from different languages to a shared vector space

How can we quickly refine CLWE for low-resource NLP?

Refining CLWE




Refining CLWE

lackluster
•
uninspiring terme
■
mediocre plat
• ■
disappointing
•
décevant
■

suffisant decent
■ •
géniale excellent
■ •
exceptional
•

Refining CLWE



Classification clime: Areas in embedding space where words induce similar labels for a task

Classifying Interactively with Multilingual Embeddings

CLIME

Classifying Interactively with Multilingual Embeddings

1. Select keywords with *gradient-based salience* (Li et al., 2016)

CLIME

Classifying Interactively with Multilingual Embeddings

1. Select keywords with *gradient-based salience* (Li et al., 2016)
2. Collect user feedback

CLIME

Classifying Interactively with Multilingual Embeddings

1. Select keywords with *gradient-based salience* (Li et al., 2016)
2. Collect user feedback
3. Refine embeddings on user feedback through *retrofitting* (Mrkšić et al., 2017)

Keyword Selection

1. **Local salience** of word x_i in x :

$$S_{\mathbf{x}}(x_i) = \left\| \nabla_{\mathbf{E}_{x_i}} L(\mathbf{x}, y) \right\|_2.$$

Keyword Selection

1. **Local salience** of word x_i in x :

$$S_{\mathbf{x}}(x_i) = \left\| \nabla_{\mathbf{E}_{x_i}} L(\mathbf{x}, y) \right\|_2.$$

2. **Global salience** of word w :

$$S(w) = \text{IDF}(w, \mathbf{X}) \cdot \sum_{\mathbf{x} \in \mathbf{X}: w \in \mathbf{x}} S_{\mathbf{x}}(w).$$

Keyword Selection

1. **Local salience** of word x_i in x :

$$S_{\mathbf{x}}(x_i) = \left\| \nabla_{\mathbf{E}_{x_i}} L(\mathbf{x}, y) \right\|_2.$$

2. **Global salience** of word w :

$$S(w) = \text{IDF}(w, \mathbf{X}) \cdot \sum_{\mathbf{x} \in \mathbf{X}: w \in \mathbf{x}} S_{\mathbf{x}}(w).$$

3. Select keywords that have highest global salience

Keyword Selection

Example sentences

A disappointing dinner...meatballs were undercooked. (negative)

I was frustrated with the customer service. Very disappointing. (negative)

An exceptional film. (positive)

I disliked waiting in line, but the ride was exceptional. (positive)

Keyword Selection

Compute local salience

A disappointing dinner...meatballs were undercooked. (negative)

I was frustrated with the customer service. Very disappointing. (negative)

An exceptional film. (positive)

I disliked waiting in line, but the ride was exceptional. (positive)

Keyword Selection


Find words with highest global salience

disappointing

exceptional

Keyword Selection

Areas to focus on in embedding space



User Interface

Which words are close in meaning to

awesome

ENGLISH

awesomeness	✓	✗
amazing	✓	✗
terrific	✓	✗
gorgeous	✓	✗
hilarious	✓	✗
incredible	✓	✗
funny	✓	✗
fantastic	✓	✗
seary	✓	✗
wew	✓	✗

Add word

FRENCH

incroyable	✓	✗
incroyablement	✓	✗
sympa	✓	✗
amusant	✓	✗
génial	✓	✗
géniale	✓	✗
étonnant	✓	✗
geek	✓	✗
!	✓	✗
marrant	✓	✗

Add word

Retrofitting CLWE

1. **Feedback cost:** Pull positive neighbors p closer and negative neighbors n away

$$C_f(\mathbf{E}) = \sum_{k \in \mathcal{K}} \left(\sum_{n \in \mathcal{N}_k} \mathbf{E}_k^\top \mathbf{E}_n - \sum_{p \in \mathcal{P}_k} \mathbf{E}_k^\top \mathbf{E}_p \right).$$

Retrofitting CLWE

1. **Feedback cost:** Pull positive neighbors p closer and negative neighbors n away

$$C_f(\mathbf{E}) = \sum_{k \in \mathcal{K}} \left(\sum_{n \in \mathcal{N}_k} \mathbf{E}_k^\top \mathbf{E}_n - \sum_{p \in \mathcal{P}_k} \mathbf{E}_k^\top \mathbf{E}_p \right).$$

2. **Regularization:** Updated embeddings should not be too far away from original embeddings

$$R(\mathbf{E}) = \sum_{w \in \mathcal{V}} \left\| \hat{\mathbf{E}}_w - \mathbf{E}_w \right\|_2^2.$$

Retrofitting CLWE

1. **Feedback cost:** Pull positive neighbors p closer and negative neighbors n away

$$C_f(\mathbf{E}) = \sum_{k \in \mathcal{K}} \left(\sum_{n \in \mathcal{N}_k} \mathbf{E}_k^\top \mathbf{E}_n - \sum_{p \in \mathcal{P}_k} \mathbf{E}_k^\top \mathbf{E}_p \right).$$


2. **Regularization:** Updated embeddings should not be too far away from original embeddings

$$R(\mathbf{E}) = \sum_{w \in \mathcal{V}} \left\| \hat{\mathbf{E}}_w - \mathbf{E}_w \right\|_2^2.$$


3. **Total loss function:**

$$C(\mathbf{E}) = C_f(\mathbf{E}) + \lambda R(\mathbf{E}).$$


Retrofitting CLWE



Retrofitting CLWE



Retrofitting CLWE



Experiments: Task

Document classification for detecting medical emergencies in low-resource languages

Experiments: Task

Document classification for detecting medical emergencies in low-resource languages

Ilocano ... Nagtalinaed dagiti pito a balod ti Bureau of Jail Management and Penology (BJMP) ditoy ciudad ti Laoag iti isolation room gapo iti tuko ...

Experiments: Setting

- ▶ **Source language:** English
- ▶ **Target language:** Ilocano
- ▶ **Embeddings:** fastText aligned with RCSLS
- ▶ **Classifier:** CNN (max-pooling)

Experiments: User Study

We want to classify documents into two categories:

1. Documents describing a medical emergency.
2. Documents **not** describing a medical emergency.

Which words are likely to appear in the same category as

ambulance

ENGLISH			ILOCANO		
ambulances	✓	✗	ospital	✓	✗
medics	✓	✗	nars	✓	✗
hospital	✓	✗	tulong	✓	✗
emergency	✓	✗	pagbakuitan	✓	✗
nurses	✓	✗	pammaregta	✓	✗
Add word			Add word		

Experiments: Methods

- ▶ **Base:** original CLWE and original training dataset
- ▶ **Active:** original CLWE and training dataset augmented by active learning
- ▶ **CLIME:** refined CLWE and original training dataset
- ▶ **A+C:** refined CLWE and training dataset augmented by active learning


Experiments: Results

Base


54.3%

A single vertical bar chart with a dark red bar. The bar is positioned on the left side of the chart area. The value '54.3%' is displayed in black text above the top of the bar.


Experiments: Results



Experiments: Results



Experiments: Results



References I

- Jiwei Li, Xinlei Chen, Eduard Hovy, and Dan Jurafsky. 2016. Visualizing and understanding neural models in NLP. In *NAACL*.
- Nikola Mrkšić, Ivan Vulić, Diarmuid Ó Séaghdha, Ira Leviant, Roi Reichart, Milica Gašić, Anna Korhonen, and Steve Young. 2017. Semantic specialisation of distributional word vector spaces using monolingual and cross-lingual constraints. *TACL*, 5:309–324.