



414078-HS2018-0 - C++ Programming II

EXERCISE-04

TABLE OF CONTENTS

1	Introduction	1
2	Submission	1
3	Thread basics	2
4	Data Races	2

1 Introduction

This exercise gives an introduction to threads and data races. In particular, you will learn the following topics when completing this exercise:

- ▶ Starting and Stopping threads
- ▶ Passing parameters to threads by value and reference, hence creating shared memory between threads
- ▶ Implement a (thread safe) file logger class
- ▶ Using mutex, lock_guard and call_once to synchronise threads

2 Submission

Submit your source code (as a zip-file) to Ilias **before the deadline** specified in Ilias.

3 Thread basics

In order to demonstrate the effects of data races a log file class is implemented and multiple threads are logging to it.

- ▶ Implement a class `ThreadLogFile` which opens a file stream, e.g. "threadLog.txt" when constructed and closes the file when destructed.
- ▶ Implement a member function `print` which takes the thread ID and an `int` value as parameters.
- ▶ For simplicity, implement a global function `logToFile`, which internally calls `print`, such that the following code:

```
LogFile log;  
logToFile(log, 1);
```

produces a file log similar to:

Log from thread: 139939765286656 with value: 1

- ▶ Next, create a thread which writes the value 2 to the same log file.
- ▶ Create a vector of threads and in a for loop, fill it with `N` threads logging to the file with the parameter value being the loop counter. Choose `N` to be a multiple number of supported threads by your system, i.e. $10 \cdot N$.
- ▶ Verify that the output file is messed up, i.e. not thread safe. It will look similar to:

```
Log from thread: 139939765286656 with value: 1  
Log from thread: Log from thread: 139939748501248139939740108543  
Log from thread: 139939765286656 with value: 1  
Log from thread: Log from thread: 139939748501248139939740108543  
with value: 4
```

- ▶ Make sure to join all the threads within an additional loop.

4 Data Races

In the first section of this exercise you've created a situation where multiple threads are racing for the same resource, namely the log file. Fix the issue, i.e. extend class `ThreadLogFile` to be thread safe using RAII methods provided by STL.

- ▶ Verify that the output will look similar to:

```
From 139629015045888: 2  
From 139629015045888: 0  
From 139628917028608: 3  
From 139628998260480: 2  
From 139628891850496: 6  
.  
.  
.
```

- ▶ Within the `print()` function of class `ThreadLogFile`, add a header line to your log file. Make sure the header is written only once with minimal overhead.