```
                        <E1EVMPAR SEGMENT="1">
                            <PARAM_NAME>PARTITION_KEY_HINT</PARAM_NAME>
                            <PARAM_VALUE>0080001326</PARAM_VALUE>
                        </E1EVMPAR>
                        <E1EVMPAR SEGMENT="1">
                            <PARAM_NAME>ACTUAL_TECHNICAL_TIMEZONE</PARAM_NAME>
                            <PARAM_VALUE>CET</PARAM_VALUE>
                        </E1EVMPAR>
                    </E1EVMHDR02>
                </IDOC>
            </EVMSTA02>
        </soap-env:Body>
    </soap-env:Envelope>
```

Notes

You can use the following GTT standard events:

- GTTUpdatePlanEvent
- GTTDelayedEvent
- GTTOnTimeEvent
- GTTDeletionEvent

Response

Response Codes

The following HTTP response codes may occur:

Code	HTTP Description	Track and Trace Semantic
200	OK	EM IDOC is received successfully
400	Bad Request	Something is not correct in the payload
401	Unauthorized	There is no authentication passed with the request
403	Forbidden	The user does not have the right privileges
404	Not Found	Request URI is not correct
500	Internal Server Error	An unspecified error occurred during request processing

Response Body

Message in XML format.

Sample Code

```
<SOAP-ENV:Envelope xmlns:SOAP-ENV="http://schemas.xmlsoap.org/soap/envelope/">
    <SOAP-ENV:Header/>
    <SOAP-ENV:Body>
```

```
            <EVMSTA02Response xmlns="urn:sap-com:document:sap:idoc:soap:messages">
                <IdocAssign>
                    <TransferId xmlns="urn:sap-com:document:sap:idoc:soap:messages">0000000002705455
                    <DbId xmlns="urn:sap-com:document:sap:idoc:soap:messages">0000000002705455</DbId
                </IdocAssign>
            </EVMSTA02Response>
        </SOAP-ENV:Body>
    </SOAP-ENV:Envelope>
```

Receive a Combined EM IDOC

Request

Request URI

- For HTTP basic authentication:

  https://<server address>/api/idoc/em/v1/TrackedProcessAndEvent

Request Method

POST

Request Body

EM IDOC in XML format

Sample Code

```
<soap-env:Envelope xmlns:soap-env="http://schemas.xmlsoap.org/soap/envelope/">
    <soap-env:Header>
        <msgID:messageId xmlns:msgID="http://www.sap.com/webas/640/soap/features/messageId/">uui
    </soap-env:Header>
    <soap-env:Body>
        <GTTMSG01 xmlns="urn:sap-com:document:sap:idoc:soap:messages">
            <IDOC BEGIN="1">
                <EDI_DC40 SEGMENT="1">
                    <TABNAM>EDI_DC40</TABNAM>
                    <MANDT>910</MANDT>
                    <DOCNUM>0000000002368243</DOCNUM>
                    <DOCREL>755</DOCREL>
                    <STATUS>30</STATUS>
                    <DIRECT>1</DIRECT>
                    <OUTMOD>2</OUTMOD>
                    <IDOCTYP>EVMSTA02</IDOCTYP>
                    <MESTYP>EVMSTA</MESTYP>
                    <SNDPOR>SAPQM7</SNDPOR>
                    <SNDPRT>LS</SNDPRT>
                    <SNDPRN>QM7CLNT910</SNDPRN>
                    <RCVPOR>GTTV2ACCEV</RCVPOR>
                    <RCVPRT>LS</RCVPRT>
                    <RCVPRN>GTTV2ACC</RCVPRN>
                    <CREDAT>20200428</CREDAT>
```

```
                    <CRETIM>104329</CRETIM>
                    <ARCKEY>urn:sap.com:msgid=0894EF4591011EDAA2A58AA1AF6843F4</ARCKEY>
                    <SERIAL>20200428104329</SERIAL>
                </EDI_DC40>
                <E1EHPAO SEGMENT="1">
                    <APPSYS>QM7CLNT910</APPSYS>
                    <APPOBJTYPE>YSHIPMENT_ACC</APPOBJTYPE>
                    <APPOBJID>0000008888</APPOBJID>
                    <E1EHPCP SEGMENT="1">
                        <PARAMNAME>FORWARDING_AGENT_NAME</PARAMNAME>
                        <PARAMINDEX>0000000000</PARAMINDEX>
                        <VALUE>VENDOR</VALUE>
                    </E1EHPCP>
                    <E1EHPCP SEGMENT="1">
                        <PARAMNAME>PARTITION_KEY_HINT</PARAMNAME>
                        <PARAMINDEX>0000000000</PARAMINDEX>
                        <VALUE>00001</VALUE>
                    </E1EHPCP>
                    <E1EHPCP SEGMENT="1">
                        <PARAMNAME>ACTUAL_TECHNICAL_DATETIME</PARAMNAME>
                        <PARAMINDEX>0000000000</PARAMINDEX>
                        <VALUE>020201125034043</VALUE>
                    </E1EHPCP>
                    <E1EHPCP SEGMENT="1">
                        <PARAMNAME>ACTUAL_TECHNICAL_TIMEZONE</PARAMNAME>
                        <PARAMINDEX>0000000000</PARAMINDEX>
                        <VALUE>CET</VALUE>
                    </E1EHPCP>
                    <E1EHPCP SEGMENT="1">
                        <PARAMNAME>GTT_OTL_LOCID</PARAMNAME>
                        <PARAMINDEX>0000000001</PARAMINDEX>
                        <VALUE>LOCID001</VALUE>
                    </E1EHPCP>
                    <E1EHPCP SEGMENT="1">
                        <PARAMNAME>GTT_OTL_LOCTYPE</PARAMNAME>
                        <PARAMINDEX>0000000001</PARAMINDEX>
                        <VALUE>OneTimeLocation</VALUE>
                    </E1EHPCP>
                    <E1EVMHDR02 SEGMENT="1">
                        <EVTID>ARRIV_CARR</EVTID>
                        <EVTDAT>20200428</EVTDAT>
                        <EVTTIM>104300</EVTTIM>
                        <EVTZON>CET</EVTZON>
                        <E1EVMTID SEGMENT="1">
                            <TRXCOD>SHP_NO</TRXCOD>
                            <TRXID>0000001452</TRXID>
                        </E1EVMTID>
                        ...
                    </E1EVMHDR02>
                </E1EHPAO>
            </IDOC>
        </GTTMSG01>
    </soap-env:Body>
```

```
</soap-env:Envelope>
```

Response

Response Codes

The following HTTP response codes may occur:

Code	HTTP Description	Track and Trace Semantic
200	OK	EM IDOC is received successfully
400	Bad Request	Something is not correct in the payload
401	Unauthorized	There is no authentication passed with the request
403	Forbidden	The user does not have the right privileges
404	Not Found	Request URI is not correct
500	Internal Server Error	An unspecified error occurred during request processing

Response Body

Message in XML format

Sample Code

```
<SOAP-ENV:Envelope xmlns:SOAP-ENV="http://schemas.xmlsoap.org/soap/envelope/">
    <SOAP-ENV:Header/>
    <SOAP-ENV:Body>
        <GTTMSG01Response xmlns="urn:sap-com:document:sap:idoc:soap:messages">
            <IdocAssign>
                <TransferId xmlns="urn:sap-com:document:sap:idoc:soap:messages">0000000002705455
                <DbId xmlns="urn:sap-com:document:sap:idoc:soap:messages">0000000002705455</DbId
            </IdocAssign>
        </GTTMSG01Response>
    </SOAP-ENV:Body>
</SOAP-ENV:Envelope>
```

IDOC PREDEFINED PARAMETERS

Avoid using the prefix “GTT_” when defining your own field names. Field names that start with “GTT_” are reserved in the IDOC payload.

Object [IDOC Basic Type]		Parameter
Tracked Process & Planned Event [EHPOST01, GTTMSG01]	***Tracked Process***	Altkey: ***xri://sap.com/id:party:system:type:id*** • “xri://sap.com/id” is fixed • party: get from the token’s tenant

• system: first read from `ORIGINAL_SRC_SYSTEM` (Segment: E1EHPCP) if there is no such field in the payload; then read from “APPSYS” • Type: get from the trackingIdType of tracked process, which is maintained in the Tracked Process header • id: `APPOBJID` For example:xri://sap.com/id: LBN#10000001: D2OCLNT100: OBP10_DELIV: 0080000020
TRACKING • is fixed
Altkey: ***xri://sap.com/id:party:system:type:id*** • “xri://sap.com/id” is fixed • party: get from the token’s tenant • system:`APPSYS/E1EHPTID-AYPPSYS` (Segment: E1EHPAO) • Type: `TRXCOD` • id: `TRXCID` For example:xri://sap.com/id: LBN#10000001: D2OCLNT100: OBP10_DELIV: 0080000020
`START_DATE`
`TIMZON`
`END_DATE`
`TIMZON`
`ACTION:` • S Set(Create) -> ‘ADD’ • C Change -> ‘ADD’ • D Delete -> ‘DELETE’ Default ‘ADD’
`GTT_OTL_LOCID`
`GTT_OTL_LOCTYPE`
`GTT_OTL_TIMEZONE`
`GTT_OTL_LONGITUDE`
`GTT_OTL_LATITUDE`
`GTT_OTL_UNLOCODE`
`GTT_OTL_IATA_CODE`
`GTT_OTL_DESCRIPTION`

	GTT_OTL_COUNTRY_CODE
	GTT_OTL_CITY_NAME
	GTT_OTL_REGION_CODE
	GTT_OTL_HOUSE_NUMBER
	GTT_OTL_STREET_NAME
	GTT_OTL_POSTAL_CODE
	GTT_OTL_EMAIL_ADDRESS
	GTT_OTL_PHONE_NUMBER
	ACTUAL_BUSINESS_DATETIME
	ACTUAL_BUSINESS_TIMEZONE
	ACTUAL_TECHNICAL_DATETIME
	ACTUAL_TECHNICAL_TIMEZONE
	PARTITION_KEY_HINT
	PLANNED_EVENT_UPDATE_STRATEGY
	REPORTED_BY
	YN_SHP_HDR_DLV_NO
	YN_SHP_HDR_DLV_NO_LOGSYS
Planned Event	MILESTONE
	Location Altkey:***xri://sap.com/id:party:system:Location:object type:location id*** • “xri://sap.com/id” is fixed • party: get from the token’s tenant • system: get from the IDOC header: sndprn • “Location” is fixed • object type: LOCTYPE • location id: LOCID1 For example:xri://sap.com/id:LBN#10002424:Q8JCLNT774:Location:shippingPoint:4711
	LOCID2
	MILESTONENUM
	MSG_EXP_DATETIME
	MSG_EXP_TZONE
	MSG_ER_EXP_DTIME
	MSG_EXP_TZONE

		MSG_LT_EXP_DTIME
		MSG_EXP_TZONE
		EVT_EXP_DATETIME
		EVT_EXP_TZONE
		EVT_ER_EXP_DTIME
		EVT_LT_EXP_DTIME
Actual Event [EVMSTA02, GTTMSG01]	(Common Code)	SRCTX
		SRCID
		Altkey: ***xri://sap.com/id:party:system:type:id*** • "xri://sap.com/id" is fixed • party: get from the token's tenant • system: first read from ORIGINAL_SRC_SYSTEM (Segment: E1EVMPAR), if there is no such field in the payload; then read from IDOC header: sndprn • type: TRXCOD • id: TRXID For example:xri://sap.com/id: LBN#10000001: Q8JCLNT774: OBP10_DELIV: 0080000020
		Location Altkey:***xri://sap.com/id:party:system:Location:object type:location id*** • "xri://sap.com/id" is fixed • party: get from the token's tenant • system: get from the IDOC header: sndprn • "Location" is fixed • object type: LOCCOD • location id: LOCID1 For example:xri://sap.com/id: LBN#10000001:Q8JCLNT774:Location:shippingPoint:4711
		LOCID2
		MESSAGE_SOURCE_TYPE
		TRACKING • is fixed
		Altkey: ***xri://sap.com/id:party:system:type:id*** • "xri://sap.com/id" is fixed • party: get from the token's tenant • system: APPSYS

		• type: APPOBJTYPE; get from the trackingIdType of tracked process, which is maintained in the Tracked Process header • id: APPOBJID For example:xri://sap.com/id: LBN#10000001: D2OCLNT100: OBP10_DELIV: 0080000020
		START_DATE
		START_TIME
		TIMZON
		END_DATE
		END_TIME
		TIMZON
		ACTION: • A Active -> 'ADD' • D Deactive-> 'Delete' Default 'ADD'
		EVTDAT
		EVTTIM
		EVTZON
		ACTUAL_TECHNICAL_DATETIME
		ACTUAL_TECHNICAL_TIMEZONE
		PARTITION_KEY_HINT
		REPORTED_BY
	GTT Standard Event	***GTTUpdatePlanEvent***	PLANNED_EVENT_MILESTONE or PLANNED_EVENT_CODE
			PLANNED_EVENT_LOCID1 or PLANNED_LOCATION_ID
			PLANNED_EVENT_LOCTYPE or PLANNED_LOCATION_TYPE
			PLANNED_EVENT_LOCID2 or PLANNED_EVENT_MATCH_KEY
			IS_FINAL_PLANNED_EVENT

	PLANNED_EVENT_MILESTONENUM or PLANNED_PAYLOAD_SEQUENCE
	PLANNED_EVENT_MSG_EXP_DATETIME or PLANNED_TECHNICAL_TIMESTAMP
	PLANNED_EVENT_MSG_ER_EXP_DTIME or PLANNED_TECH_TS_EARLIST
	PLANNED_EVENT_MSG_LT_EXP_DTIME or PLANNED_TECH_TS_LATEST
	PLANNED_EVENT_EVT_EXP_DATETIME or PLANNED_BUSINESS_TIMESTAMP
	PLANNED_EVENT_EVT_ER_EXP_DTIME or PLANNED_BIZ_TS_EARLIST
	PLANNED_EVENT_EVT_LT_EXP_DTIME or PLANNED_BIZ_TS_LATEST
	PLANNED_EVENT_EVT_EXP_TZONE or PLANNED_BUSINESS_TIMEZONE
	ACTION_CODE
GTTDelayedEvent, ***GTTOnTimeEvent***	REF_PLANNED_EVENT_MILESTONE or REF_PLANNED_EVENT_CODE
	REF_PLANNED_LOCID1 or REF_PLANNED_LOCATION_ID
	REF_PLANNED_EVENT_LOCTYPE or REF_PLANNED_LOCATION_TYPE

			REF_PLANNED_EVENT_LOCID2 or REF_PLANNED_EVENT_MATCH_KEY

Write Service

Description

- technical name: GTT_V2_HTTP_EVENT_INGESTION
- purpose: for ingesting tracked processes and actual events
- protocol: HTTP
- same service used separately to:
    - to create and update tracked process
    - to post events

Create and Update Tracked Process

Request

Request URI

- For HTTP basic authentication:

  https://<server address>/api/inbound/rest/v1/{model namespace}.{write service name}/{tracked process event name}

  Example

  https://*<server address>*/api/inbound/rest/v1/com.lbngttapps.gtt.app.gttft1.gttft1WriteService/DeliveryItemEvent

HTTP Method

Post

Request Header

Pass additional information with the request.

Request Header Properties

Property	Type	Mandatory	Description
LBN-GTT-Source-Id	String	No	An ID to represent which source system the message comes from
LBN-GTT-Message-Number	String	No	The message's ID in the source system