| | | |
|---|---|---|
| | | **Data Type** xsd:string |
| **D_337**<br>Time | Time expressed in 24-hour clock time as follows: HHMM, or HHMMSS, or HHMMSSD, or HHMMSSDD, where H = hours (00-23), M = minutes (00-59), S = integer seconds (00-59) and DD = decimal seconds; decimal seconds are expressed as follows: D = tenths (0-9) and DD = hundredths (00-99) | **Cardinality** **min:** 1 **max:** 1<br>**Primitive Type** String<br>**Length** **min:** 6 **max:** 6<br>**External Category** Element<br>**Data Type** xsd:string |
| **D_28**<br>Group Control Number | Assigned number originated and maintained by the sender | **Cardinality** **min:** 1 **max:** 1<br>**Primitive Type** String<br>**Length** **min:** 9 **max:** 9<br>**External Category** Element<br>**Data Type** xsd:string |
| **D_455**<br>Responsible Agency Code | Code identifying the issuer of the standard; this code is used in conjunction with Data Element 480<br><br>**Selected Values**<br>All Values in Codelist | **Cardinality** **min:** 1 **max:** 1<br>**Primitive Type** String<br>**Length** **min:** 1 **max:** 1<br>**External Category** Element<br>**Data Type** xsd:string<br><br>**Codelist Id** D_455<br>**Type System** Customer_TS<br>**Version Mode** Local<br>**Version** 1.1 |
| **D_480**<br>Version / Release / Industry Identifier Code | Code indicating the version, release, subrelease, and industry identifier of the EDI standard being used, including the GS and GE segments; if code in DE455 in GS segment is X, then in DE 480 positions 1-3 are the version number; positions 4-6 are the release and subrelease, level of the version; and positions 7-12 are the industry or trade association identifiers (optionally assigned by user); if code in DE455 in GS segment is T, then other formats are allowed<br><br>**Selected Values**<br>All Values in Codelist | **Cardinality** **min:** 1 **max:** 1<br>**Primitive Type** String<br>**Length** **min:** 6 **max:** 6<br>**External Category** Element<br>**Data Type** xsd:string<br><br>**Codelist Id** D_480<br>**Type System** Customer_TS<br>**Version Mode** Local<br>**Version** 1.1 |

## 2.5 S_GE — Functional Group Trailer

### Structure

| Node | Card. | Prim.Type | Pos. | Length | Codelists |
|---|---|---|---|---|---|
| **Interchange** — Interchange Structure | 1 .. 1 | | | | |
| ├ **FunctionalGroup** — Functional Group | 1 .. 1 | | | | |
| │ └ **S_GE** — Functional Group Trailer | 1 .. 1 | | | | |
| │ ├ **D_97** — Number of Transaction Sets Included | 1 .. 1 | String | | 1 .. 1 | |
| │ └ **D_28** — Group Control Number | 1 .. 1 | String | | 9 .. 9 | |

### Documentation

**Definition** To indicate the end of a functional group and to provide control information Comments 1. The use of identical data interchange control numbers in the associated functional group header and trailer is designed to maximize functional group integrity. The control number is the same as that used in the corresponding header. Semantic Notes: 1. The data interchange control number GE02 in this trailer must be identical to the same data element in the associated functional group header, GS06.

### Properties

**Identifier** S_GE

**Name** Functional Group Trailer

**Cardinality** min: 1 max: 1

### Syntax Type Related

**External Category** Element

### Leaf Elements

| Identifier/Name | Description/Notes/Code Values | Properties |
|---|---|---|
| **D_97**<br>Number of Transaction Sets Included | Total number of transaction sets included in the functional group or interchange (transmission) group terminated by the trailer containing this data element | **Cardinality** min: 1 max: 1<br>**Primitive Type** String<br>**Length** min: 1 max: 1<br>**External Category** Element<br>**Data Type** xsd:string |
| **D_28**<br>Group Control Number | Assigned number originated and maintained by the sender | **Cardinality** min: 1 max: 1<br>**Primitive Type** String<br>**Length** min: 9 max: 9<br>**External Category** Element<br>**Data Type** xsd:string |

## 2.6 S_IEA — Interchange Control Trailer

### Structure

| Node | Card. | Prim.Type | Pos. | Length | Codelists |
|---|---|---|---|---|---|
| **Interchange** — Interchange Structure | 1 .. 1 | | | | |
| └ **S_IEA** — Interchange Control Trailer | 1 .. 1 | | | | |
| ├ **D_I16** — Number of Included Functional Groups | 1 .. 1 | String | | 1 .. 1 | |
| └ **D_I12** — Interchange Control Number | 1 .. 1 | String | | 9 .. 9 | |

### Documentation

**Definition** To define the end of an interchange of zero or more functional groups and interchange-related control segments

### Properties

**Identifier** S_IEA

**Name** Interchange Control Trailer

**Cardinality** min: 1 max: 1

### Syntax Type Related

**External Category** Element

### Leaf Elements

| Identifier/Name | Description/Notes/Code Values | Properties |
|---|---|---|
| **D_I16**<br>Number of Included Functional Groups | A count of the number of functional groups included in an interchange | **Cardinality** min: 1 max: 1<br>**Primitive Type** String<br>**Length** min: 1 max: 1<br>**External Category** Element<br>**Data Type** xsd:string |
| **D_I12**<br>Interchange Control Number | A control number assigned by the interchange sender | **Cardinality** min: 1 max: 1<br>**Primitive Type** String<br>**Length** min: 9 max: 9<br>**External Category** Element<br>**Data Type** xsd:string |

# 3 OVERVIEW MESSAGE

## General Information

| | |
|---|---|
| **Name** | SAP_LBN_ANSI_X12_204 |
| **Direction** | Out |
| **Status** | Active |
| **Message Type** | Motor Carrier Load Tender |
| **Type System** | ASC_X12 |
| **Version** | 004010 |
| **External Category** | Transaction Set |

## Documentation

| | |
|---|---|
| **Summary** | ANSI_X12_204 |
| **Definition** | This Draft Standard for Trial Use contains the format and establishes the data contents of the Motor Carrier Load Tender Transaction Set (204) for use within the context of an Electronic Data Interchange (EDI) environment. This transaction set can be used to allow shippers or other interested parties to offer (tender) a shipment to a full load (truckload) motor carrier including detailed scheduling, equipment requirements, commodities, and shipping instructions pertinent to a load tender. It is not to be used to provide a motor carrier with data relative to a Less-than-Truckload bill of lading, pick-up notification, or manifest. |

## Notes

| | |
|---|---|
| **Usage 1** | The G61 segment contains the person or company to be contacted by the carrier in case of emergency. |
| **Usage 2** | US Fluid Ounce (ISO code: OZA) is not supported by the ANSI X12 204 Volume Unit Qualifier. Therefore, when the source volume unit is OZA, it is mapped to V (Liter). The volume value is converted from US Fluid Ounce to Liter using the standard conversion factor (1 US Fluid Ounce = 0.0295735295625 Liter) to preserve the original quantity. |
| **Comment 1** | The three examples are messages for creation, update and cancellation of a freight order. |
| **Example 1** | ISA*00* *00* *ZZ*10010001397 *ZZ*10010001844<br>*220224*1550*U*00401*000000164*0*P*>~<br>GS*PO*10010001397*10010001844*20220224*155034*000000164*X*004010~<br>ST*204*0001~<br>B2****FreightOrderId**PP~<br>B2A*00*LT~<br>L11*SenderSystemId*06~<br>L11*PurchasingParty*CN~<br>L11*BillFromParty*12~<br>NTE*TRA*1863 KMT~<br>N7**equipmentNumber*********CN*******3****22R1~<br>M7*sealNumber1*sealNumber2~<br>S5*1*CL~<br>G62*69*20201214*U*2300*UT~<br>G62*69*20201214*U*1700*CT~<br>N1*SF*LoadingLocationName*93*loadingLocationId~<br>N3*LoadingHouseName~<br>N4*LoadingLocationCity*TN*Postalcode*US~<br>OID*FreightOrderId~<br>L5*110*Stainless Steel Container 1000L***CNT~<br>AT8*G*L*2229*1~<br>G61*SH*contactName~<br>S5*2*CU~<br>G62*70*20201217*X*2259*UT~<br>G62*70*20201217*X*1659*CT~<br>N1*ST*UnloadingLocationName*93*UnloadingLocationId~<br>N3*UnloadingAddress~<br>N4*UnloadingLocationCity*US*37347-5319*US~<br>OID*FreightOrderId~<br>L5*120*Stainless Steel Container 1000L***CNT~<br>AT8*G*L*2229*2~<br>L3*totalGrossWeight*G*******93*X**K~<br>SE*28*0001~<br>GE*1*000000164~<br>IEA*1*000000164~ |
| **Example 2** | ISA*00* *00* *ZZ*10010001397 *ZZ*10010001844<br>*220224*1550*U*00401*000000165*0*P*>~<br>GS*PO*10010001397*10010001844*20220224*155034*000000165*X*004010~ |

ST*204*0001~
B2****FreightOrderId**PP~
B2A*04*LT~
L11*SenderSystemId*06~
L11*PurchasingParty*CN~
L11*BillFromParty*12~
NTE*TRA*1863 KMT~
N7**equipmentNumber*********CN*******3****22R1~
M7*sealNumber1*sealNumber2~
S5*1*CL~
G62*69*20201214*U*2300*UT~
G62*69*20201214*U*1700*CT~
N1*SF*LoadingLocationName*93*loadingLocationId~
N3*LoadingHouseName~
N4*LoadingLocationCity*TN*Postalcode*US~
OID*FreightOrderId~
L5*110*Stainless Steel Container 1000L***CNT~
AT8*G*L*2229*1~
G61*SH*contactName~
LH1*EA*1*UN1987*******II~
LH2*6.1*P****CE*50.0~
LFH*ADI*ADR (European Agreem~
LFH*ADI*ent concerning the I~
LFH*ADI*nternational Carriag~
LFH*ADI*e of Dangerous Goods~
LFH*ADI* by Road): ...~
S5*2*CU~
G62*70*20201217*X*2259*UT~
G62*70*20201217*X*1659*CT~
N1*ST*UnloadingLocationName*93*UnloadingLocationId~
N3*UnloadingAddress~
N4*UnloadingLocationCity*US*37347-5319*US~
OID*FreightOrderId~
L5*110*Stainless Steel Container 1000L***CNT~
AT8*G*L*2229*2~
G61*SH*ContractName~
LH1*EA*1*UN1987*******II~
LH2*6.1*P****CE*50.0~
LFH*ADI*ADR (European Agreem~
LFH*ADI*ent concerning the I~
LFH*ADI*nternational Carriag~
LFH*ADI*e of Dangerous Goods~
LFH*ADI* by Road): ...~
L3*totalGrossWeight*G*******93*X**K~
SE*43*0001~
GE*1*000000165~
IEA*1*000000165~

**Example 3**

ISA*00* *00* *ZZ*10010001397 *ZZ*10010001844 *220224*1550*U*00401*000000166*0*P*>~
GS*PO*10010001397*10010001844*20220224*155034*000000166*X*004010~
ST*204*0001~
B2****FreightOrderId**PP~
B2A*01*LT~
L11*SenderSystemId*06~
L11*PurchasingParty*CN~
L11*BillFromParty*12~
NTE*TRA*1863 KMT~
N7**equipmentNumber*********CN*******3****22R1~
M7*sealNumber1*sealNumber2~
S5*1*CL~
G62*69*20201214*U*2300*UT~
G62*69*20201214*U*1700*CT~
N1*SF*LoadingLocationName*93*loadingLocationId~
N3*LoadingHouseName~
N4*LoadingLocationCity*TN*Postalcode*US~
OID*FreightOrderId~
L5*110*Stainless Steel Container 1000L***CNT~
AT8*G*L*2229*1~
G61*SH*contactName~
S5*2*CU~
G62*70*20201217*X*2259*UT~
G62*70*20201217*X*1659*CT~
N1*ST*UnloadingLocationName*93*UnloadingLocationId~
N3*UnloadingAddress~
N4*UnloadingLocationCity*US*37347-5319*US~
OID*FreightOrderId~

L5*110*Stainless Steel Container 1000L***CNT~
AT8*G*L*2229*1~
L3*totalGrossWeight*G*******93*X**K~
SE*28*0001~
GE*1*000000166~
IEA*1*000000166~

### 3.1 Structure

The following table shows only the root element and the group elements.

| Node | Card. | Prim.Type | Pos. | Length | Codelists |
|---|---|---|---|---|---|
| **204** — Motor Carrier Load Tender | 1 .. 1 | | | | |
| ├ **ST** — Transaction Set Header - Motor Carrier Load Tender | 1 .. 1 | | 010 | | |
| ├ **B2** — Beginning Segment for Shipment Information Transaction | 1 .. 1 | | 020 | | |
| ├ **B2A** — Set Purpose | 1 .. 1 | | 030 | | |
| ├ **L11** — Business Instructions and Reference Number | 3 .. 50 | | 080 | | |
| ├ **NTE** — Note/Special Instruction | 0 .. 10 | | 130 | | |
| ├ **0200** — Loop 0200 | 0 .. 10 | | 200 | | |
| │ ├ **N7** — Equipment Details | 1 .. 1 | | 200 | | |
| │ ├ **N7B** — Additional Equipment Details | 0 .. 1 | | 205 | | |
| │ └ **M7** — Seal Numbers | 0 .. 2 | | 210 | | |
| ├ **0300** — Loop 0300 - Complete or Others | 2 .. 999 | | 010 | | |
| │ ├ **S5** — Stop Off Details | 1 .. 1 | | 010 | | |
| │ ├ **L11** — Business Instructions and Reference Number | 0 .. 50 | | 020 | | |
| │ ├ **G62** — Date/Time | 1 .. 2 | | 030 | | |
| │ ├ **0310** — Loop 0310 | 1 .. 1 | | 070 | | |
| │ │ ├ **N1** — Name | 1 .. 1 | | 070 | | |
| │ │ ├ **N3** — Address Information | 0 .. 2 | | 090 | | |
| │ │ ├ **N4** — Geographic Location | 0 .. 1 | | 100 | | |
| │ │ ├ **G61** — Contact - Telephone | 0 .. 1 | | 120 | | |
| │ │ └ **G61** — Contact - Electronic Mail | 0 .. 1 | | 120 | | |
| │ └ **0350** — Loop 0350 | 0 .. 999 | | 150 | | |
| │ ├ **OID** — Order Identification Detail | 1 .. 1 | | 150 | | |
| │ └ **0360** — Loop 0360 | 0 .. 99 | | 190 | | |
| │ ├ **L5** — Description, Marks and Numbers | 1 .. 1 | | 190 | | |
| │ ├ **AT8** — Shipment Weight, Packaging and Quantity Data | 0 .. 1 | | 195 | | |
| │ └ **0365** — Loop 0365 | 0 .. 99 | | 200 | | |
| │ ├ **G61** — Contact | 1 .. 1 | | 200 | | |
| │ └ **0370** — Loop 0370 | 0 .. 25 | | 203 | | |
| │ ├ **LH1** — Hazardous Identification Information | 1 .. 1 | | 203 | | |
| │ ├ **LH2** — Hazardous Classification Information | 0 .. 4 | | 204 | | |
| │ └ **LFH** — Freeform Hazardous Material Information | 0 .. 20 | | 206 | | |
| ├ **L3** — Total Weight and Charges | 1 .. 1 | | 010 | | |
| └ **SE** — Transaction Set Trailer | 1 .. 1 | | 020 | | |

# 4 DETAILS

## 4.1 204 — Motor Carrier Load Tender

### Structure

| Node | Card. | Prim.Type | Pos. | Length | Codelists |
|---|---|---|---|---|---|
| **204** — Motor Carrier Load Tender | 1 .. 1 | | | | |
| ├ **ST** — Transaction Set Header - Motor Carrier Load Tender | 1 .. 1 | | 010 | | |
| ├ **B2** — Beginning Segment for Shipment Information Transaction | 1 .. 1 | | 020 | | |
| ├ **B2A** — Set Purpose | 1 .. 1 | | 030 | | |
| ├ **L11** — Business Instructions and Reference Number | 3 .. 50 | | 080 | | |
| ├ **NTE** — Note/Special Instruction | 0 .. 10 | | 130 | | |
| ├ **0200** — Loop 0200 | 0 .. 10 | | 200 | | |
| ├ **0300** — Loop 0300 - Complete or Others | 2 .. 999 | | 010 | | |
| ├ **L3** — Total Weight and Charges | 1 .. 1 | | 010 | | |
| └ **SE** — Transaction Set Trailer | 1 .. 1 | | 020 | | |

### Properties

**Identifier** 204

**Name** Motor Carrier Load Tender

**Cardinality** min: 1 max: 1

## 4.2 ST [143 = “204”] — Transaction Set Header - Motor Carrier Load Tender

### Structure

| Node | Card. | Prim.Type | Pos. | Length | Codelists |
|---|---|---|---|---|---|
| **204** — Motor Carrier Load Tender | 1 .. 1 | | | | |
| ├ **ST** — Transaction Set Header - Motor Carrier Load Tender | 1 .. 1 | | 010 | | |
| │ ├ **143** — Transaction Set Identifier Code | 1 .. 1 | Token | 01 | 3 .. 3 | 143 |
| │ └ **329** — Transaction Set Control Number | 1 .. 1 | String | 02 | 4 .. 9 | |

### Documentation

**Definition** To indicate the start of a transaction set and to assign a control number

### Properties

**Identifier** ST

**Name** Transaction Set Header - Motor Carrier Load Tender

**Cardinality** min: 1 max: 1

### Syntax Type Related

**External Category** Segment

**Position** 010

**Level** 2

### Notes

**Usage 1** The transaction set identifier (ST01) used by the translation routines of the interchange partners to select the appropriate transaction set definition (e.g. 204 selects the Motor Carrier Load Tender Transaction Set).

### Leaf Elements

| Identifier/Name | Description/Notes/Code Values | Properties |
|---|---|---|
| **143**<br>Transaction Set Identifier Code | Code uniquely identifying a Transaction Set<br><br>**Selected Values**<br>**Code** 204 **Name** Motor Carrier Load Tender | **Cardinality** min: 1 max: 1<br>**Primitive Type** Token<br>**Length** min: 3 max: 3<br>**External Category** Simple Data Element<br>**Data Type** ID<br>**Position** 01<br>**Fixed Value** 204<br><br>**Codelist Id** 143<br>**Type System** ASC_X12<br>**Version Mode** Current<br>**Version** 004010 |
| **329**<br>Transaction Set Control Number | Identifying control number that must be unique within the transaction set functional group assigned by the originator for a transaction set | **Cardinality** min: 1 max: 1<br>**Primitive Type** String<br>**Length** min: 4 max: 9<br>**External Category** Simple Data Element<br>**Data Type** AN<br>**Position** 02<br>**Fixed Value** 0001 |

## 4.3 B2 — Beginning Segment for Shipment Information Transaction

### Structure

| Node | Card. | Prim.Type | Pos. | Length | Codelists |
|---|---|---|---|---|---|
| **204** — Motor Carrier Load Tender | 1 .. 1 | | | | |
| ├ **B2** — Beginning Segment for Shipment Information Transaction | 1 .. 1 | | 020 | | |
| │ ├ **140** — Standard Carrier Alpha Code | 0 .. 1 | Token | 02 | 2 .. 4 | |
| │ ├ **145** — Shipment Identification Number | 1 .. 1 | String | 04 | 1 .. 30 | |
| │ ├ **146** — Shipment Method of Payment - Intermodal | 1 .. 1 | Token | 06 | 2 .. 2 | 146 |
| │ └ **147** — Shipment Qualifier | 0 .. 1 | Token | 07 | 1 .. 1 | 147 |

### Documentation

**Definition** To transmit basic data relating to shipment information

### Properties

**Identifier** B2

**Name** Beginning Segment for Shipment Information Transaction

**Cardinality** min: 1 max: 1

### Syntax Type Related

**External Category** Segment

**Position** 020

**Level** 2

### Notes

### Leaf Elements

| Identifier/Name | Description/Notes/Code Values | Properties |
|---|---|---|
| **140**<br>Standard Carrier Alpha Code | Standard Carrier Alpha Code<br><br>**Comment 1**<br>Is the SCAC number needed for road carriers? | **Cardinality** min: 0 max: 1<br>**Primitive Type** Token<br>**Length** min: 2 max: 4<br>**External Category** Simple Data Element<br>**Data Type** ID<br>**Position** 02 |
| **145**<br>Shipment Identification Number | Identification number assigned to the shipment by the shipper that uniquely identifies the shipment from origin to ultimate destination and is not subject to modification; (Does not contain blanks or special characters) | **Cardinality** min: 1 max: 1<br>**Primitive Type** String<br>**Length** min: 1 max: 30<br>**External Category** Simple Data Element<br>**Data Type** AN<br>**Position** 04 |
| **146 [147 = "I"]**<br>Shipment Method of Payment - Intermodal | Code identifying payment terms for transportation charges<br><br>**Constraint 1**<br>Only PP available as of now.<br><br>**Selected Values**<br>**Code** PP **Name** Prepaid (by Seller) | **Cardinality** min: 1 max: 1<br>**Primitive Type** Token<br>**Length** min: 2 max: 2<br>**External Category** Simple Data Element<br>**Data Type** ID<br>**Position** 06<br>**Fixed Value** PP<br><br>**Codelist Id** 146<br>**Type System** ASC_X12<br>**Version Mode** Current<br>**Version** 004010 |
| **147**<br>Shipment Qualifier | Code defining relationship of this shipment with respect to other shipments given to the carrier at the same time | **Cardinality** min: 0 max: 1<br>**Primitive Type** Token<br>**Length** min: 1 max: 1<br>**External Category** Simple Data Element |