4.10 M7 — Seal Numbers

Structure

Node	Card.	Prim.Type	Pos.	Length	Codelists
204 — Motor Carrier Load Tender	1 .. 1				
├ **0200** — Loop 0200	0 .. 10		200		
│ └ **M7** — Seal Numbers	0 .. 2		210		
│ ├ **225** — Seal Number	1 .. 1	String	01	2 .. 15	
│ ├ **225** — Seal Number	0 .. 1	String	02	2 .. 15	
│ ├ **225** — Seal Number	0 .. 1	String	03	2 .. 15	
│ └ **225** — Seal Number	0 .. 1	String	04	2 .. 15	

Documentation

Definition To record seal numbers used and the organization that applied the seals

Properties

Identifier M7

Name Seal Numbers

Cardinality min: 0 max: 2

Syntax Type Related

External Category Segment

Position 210

Level 3

Notes

Comment 1 M705 indicates the name of the organization which applied the seal(s).

Leaf Elements

Identifier/Name	Description/Notes/Code Values	Properties
225 Seal Number	Unique number on seal used to close a shipment	**Cardinality** min: 1 max: 1 **Primitive Type** String **Length** min: 2 max: 15 **External Category** Simple Data Element **Data Type** AN **Position** 01
225 Seal Number	Unique number on seal used to close a shipment	**Cardinality** min: 0 max: 1 **Primitive Type** String **Length** min: 2 max: 15 **External Category** Simple Data Element **Data Type** AN **Position** 02
225 Seal Number	Unique number on seal used to close a shipment	**Cardinality** min: 0 max: 1 **Primitive Type** String **Length** min: 2 max: 15 **External Category** Simple Data Element **Data Type** AN **Position** 03
225 Seal Number	Unique number on seal used to close a shipment	**Cardinality** min: 0 max: 1 **Primitive Type** String **Length** min: 2 max: 15 **External Category** Simple Data Element **Data Type** AN **Position** 04

4.11 0300 [163 = “CL” | “CN” | “CU” | “PL” | “PU”] — Loop 0300 - Complete or Others

Structure

Node	Card.	Prim.Type	Pos.	Length	Codelists
204 — Motor Carrier Load Tender	1 .. 1				
├ **0300** — Loop 0300 - Complete or Others	2 .. 999		010		
│ ├ **S5** — Stop Off Details	1 .. 1		010		
│ ├ **L11** — Business Instructions and Reference Number	0 .. 50		020		
│ ├ **G62** — Date/Time	1 .. 2		030		
│ ├ **0310** — Loop 0310	1 .. 1		070		
│ └ **0350** — Loop 0350	0 .. 999		150		

Properties

Identifier 0300

Name Loop 0300 - Complete or Others

Cardinality min: 2 max: 999

Qualification

Qualified By	Qualifying values	
	Code	**Description**
./S5/163	CL	Complete
	CN	Consolidate
	CU	Complete Unload
	PL	Part Load
	PU	Part Unload

Syntax Type Related

External Category Loop

Position 010

Level 2

Notes

Usage 1 The qualifier CN is used for a stop where neither a loading activity or an unloading activity is expected. In case there is both, loading and unloading activities at the same stop, the qualifiers for unloading CU or PU are used.

4.12 S5 — Stop Off Details

Structure

Node	Card.	Prim.Type	Pos.	Length	Codelists
204 — Motor Carrier Load Tender	1 .. 1				
├ **0300** — Loop 0300 - Complete or Others	2 .. 999		010		
│ ├ **S5** — Stop Off Details	1 .. 1		010		
│ │ ├ **165** — Stop Sequence Number	1 .. 1	Integer	01	1 .. 3	
│ │ └ **163** — Stop Reason Code	1 .. 1	Token	02	2 .. 2	163

Documentation

Definition To specify stop-off detail reference numbers and stop reason

Properties

Identifier S5

Name Stop Off Details

Cardinality min: 1 max: 1

Syntax Type Related

External Category Segment

Position 010

Level 3

Notes

Leaf Elements

Identifier/Name	Description/Notes/Code Values	Properties
165 Stop Sequence Number	Identifying number for the specific stop and the sequence in which the stop is to be performed	**Cardinality** min: 1 max: 1 **Primitive Type** Integer **Length** min: 1 max: 3 **Fraction Digits** 0 **Total Digits** 3 **External Category** Simple Data Element **Data Type** N0 **Position** 01 **Fixed Value** 1
163 Stop Reason Code	Code specifying the reason for the stop **Selected Values** **Code** CL **Name** Complete **Code** CN **Name** Consolidate **Code** CU **Name** Complete Unload **Code** PL **Name** Part Load **Code** PU **Name** Part Unload	**Cardinality** min: 1 max: 1 **Primitive Type** Token **Length** min: 2 max: 2 **External Category** Simple Data Element **Data Type** ID **Position** 02 **Codelist Id** 163 **Type System** ASC_X12 **Version Mode** Current **Version** 004010

4.13 L11 — Business Instructions and Reference Number

Structure

Node	Card.	Prim.Type	Pos.	Length	Codelists
204 — Motor Carrier Load Tender	1 .. 1				
├ **0300** — Loop 0300 - Complete or Others	2 .. 999		010		
│ ├ **L11** — Business Instructions and Reference Number	0 .. 50		020		
│ │ ├ **127** — Reference Identification - Delivery Quote Number or Others	1 .. 1	String	01	1 .. 30	
│ │ └ **128** — Reference Identification Qualifier	1 .. 1	Token	02	2 .. 3	128

Documentation

Definition To specify instructions in this business relationship or a reference number

Properties

Identifier L11

Name Business Instructions and Reference Number

Cardinality min: 0 max: 50

Syntax Type Related

External Category Segment

Position 020

Level 3

Notes

Leaf Elements

Identifier/Name	Description/Notes/Code Values	Properties
127 [128 = "DQ" | "PO"] Reference Identification - Delivery Quote Number or Others	Reference information as defined for a particular Transaction Set or as specified by the Reference Identification Qualifier	**Cardinality** min: 1 max: 1 **Primitive Type** String **Length** min: 1 max: 30 **External Category** Simple Data Element **Data Type** AN **Position** 01
128 Reference Identification Qualifier	Code qualifying the Reference Identification **Constraint 1** Only PO and DQ available as of now. **Selected Values** **Code** PO **Name** Purchase Order Number **Code** DQ **Name** Delivery Quote Number	**Cardinality** min: 1 max: 1 **Primitive Type** Token **Length** min: 2 max: 3 **External Category** Simple Data Element **Data Type** ID **Position** 02 **Codelist Id** 128 **Type System** ASC_X12 **Version Mode** Current **Version** 004010

4.14 G62 — Date/Time

Structure

Node	Card.	Prim.Type	Pos.	Length	Codelists
204 — Motor Carrier Load Tender	1 .. 1				
├ **0300** — Loop 0300 - Complete or Others	2 .. 999		010		
│ ├ **G62** — Date/Time	1 .. 2		030		
│ │ ├ **432** — Date Qualifier	1 .. 1	Token	01	2 .. 2	432
│ │ ├ **373** — Date	0 .. 1	Date	02	8 .. 8	
│ │ ├ **176** — Time Qualifier	1 .. 1	Token	03	1 .. 2	176
│ │ ├ **337** — Time	0 .. 1	Time	04	4 .. 4	
│ │ └ **623** — Time Code	1 .. 1	Token	05	2 .. 2	623

Documentation

Definition To specify pertinent dates and times

Properties

Identifier G62

Name Date/Time

Cardinality min: 1 max: 2

Syntax Type Related

External Category Segment

Position 030

Level 3

Notes

Usage 1 In case there is no loading or unloading activity at a stop, the value Notified is used for date and time qualifiers.

Leaf Elements

Identifier/Name	Description/Notes/Code Values	Properties
432 Date Qualifier	Code specifying type of date **Selected Values** **Code** 45 **Name** Notified **Code** 69 **Name** Scheduled Pick-Up Date **Code** 70 **Name** Scheduled Delivery Date	**Cardinality** min: 1 max: 1 **Primitive Type** Token **Length** min: 2 max: 2 **External Category** Simple Data Element **Data Type** ID **Position** 01 **Codelist Id** 432 **Type System** ASC_X12 **Version Mode** Current **Version** 004010
373 Date	Date expressed as CCYYMMDD	**Cardinality** min: 0 max: 1 **Primitive Type** Date **Length** min: 8 max: 8 **Date Time Format** CCYYMMDD **External Category** Simple Data Element **Data Type** DT **Position** 02
176 Time Qualifier	Code specifying the reported time **Selected Values** **Code** U **Name** Scheduled Pick Up Time **Code** X **Name** Scheduled Delivery Time **Code** N **Name** Notified	**Cardinality** min: 1 max: 1 **Primitive Type** Token **Length** min: 1 max: 2 **External Category** Simple Data Element **Data Type** ID **Position** 03 **Codelist Id** 176

		Type System ASC_X12 **Version Mode** Current **Version** 004010
337 Time	Time expressed in 24-hour clock time as follows: HHMM, or HHMMSS, or HHMMSSD, or HHMMSSDD, where H = hours (00-23), M = minutes (00-59), S = integer seconds (00-59) and DD = decimal seconds; decimal seconds are expressed as follows: D = tenths (0-9) and DD = hundredths (00-99)	**Cardinality** **min:** 0 **max:** 1 **Primitive Type** Time **Length** **min:** 4 **max:** 4 **Date Time Format** hhmm **External Category** Simple Data Element **Data Type** TM **Position** 04
623 Time Code	Code identifying the time. In accordance with International Standards Organization standard 8601, time can be specified by a + or - and an indication in hours in relation to Universal Time Coordinate (UTC) time; since + is a restricted character, + and - are substituted by P and M in the codes that follow **Tech. Info. 1** Currently it is not possible to determine if a local timezone is using DST or not. Hence the timezone codes without this indication are used, i.e. CT (Central Time) is transmitted instead of CS (Central Standard Time) resp. CD (Central Daylight Time). **Selected Values** **Code** UT **Name** Universal Time Coordinate **Code** 01 **Name** Equivalent to ISO P01 **Code** 02 **Name** Equivalent to ISO P02 **Code** 03 **Name** Equivalent to ISO P03 **Code** 04 **Name** Equivalent to ISO P04 **Code** 05 **Name** Equivalent to ISO P05 **Code** 06 **Name** Equivalent to ISO P06 **Code** 07 **Name** Equivalent to ISO P07 **Code** 08 **Name** Equivalent to ISO P08 **Code** 09 **Name** Equivalent to ISO P09 **Code** 10 **Name** Equivalent to ISO P10 **Code** 11 **Name** Equivalent to ISO P11 **Code** 12 **Name** Equivalent to ISO P12 **Code** 13 **Name** Equivalent to ISO M12 **Code** 14 **Name** Equivalent to ISO M11 **Code** 15 **Name** Equivalent to ISO M10 **Code** 16 **Name** Equivalent to ISO M09 **Code** 17 **Name** Equivalent to ISO M08 **Code** 18 **Name** Equivalent to ISO M07 **Code** 19 **Name** Equivalent to ISO M06 **Code** 20 **Name** Equivalent to ISO M05 **Code** 21 **Name** Equivalent to ISO M04 **Code** 22 **Name** Equivalent to ISO M03 **Code** 23 **Name** Equivalent to ISO M02 **Code** 24 **Name** Equivalent to ISO M01 **Code** AT **Name** Alaska Time **Code** CT **Name** Central Time **Code** ET **Name** Eastern Time **Code** MT **Name** Mountain Time **Code** HT **Name** Hawaii-Aleutian Time **Code** NT **Name** Newfoundland Time **Code** PT **Name** Pacific Time **Code** TT **Name** Atlantic Time	**Cardinality** **min:** 1 **max:** 1 **Primitive Type** Token **Length** **min:** 2 **max:** 2 **External Category** Simple Data Element **Data Type** ID **Position** 05 **Fixed Value** UT **Codelist Id** 623 **Type System** ASC_X12 **Version Mode** Current **Version** 004010

4.15 0310 — Loop 0310

Structure

Node	Card.	Prim.Type	Pos.	Length	Codelists
204 — Motor Carrier Load Tender	1 .. 1				
├ **0300** — Loop 0300 - Complete or Others	2 .. 999		010		
│ ├ **0310** — Loop 0310	1 .. 1		070		
│ │ ├ **N1** — Name	1 .. 1		070		
│ │ ├ **N3** — Address Information	0 .. 2		090		
│ │ ├ **N4** — Geographic Location	0 .. 1		100		
│ │ ├ **G61** — Contact - Telephone	0 .. 1		120		
│ │ └ **G61** — Contact - Electronic Mail	0 .. 1		120		

Properties

Identifier 0310

Name Loop 0310

Cardinality min: 1 max: 1

Syntax Type Related

External Category Loop

Position 070

Level 3

4.16 N1 — Name

Structure

Node	Card.	Prim.Type	Pos.	Length	Codelists
204 — Motor Carrier Load Tender	1 .. 1				
├ **0300** — Loop 0300 - Complete or Others	2 .. 999		010		
│ ├ **0310** — Loop 0310	1 .. 1		070		
│ │ ├ **N1** — Name	1 .. 1		070		
│ │ │ ├ **98** — Entity Identifier Code	1 .. 1	Token	01	2 .. 3	98
│ │ │ ├ **93** — Name	0 .. 1	String	02	1 .. 60	
│ │ │ ├ **66** — Identification Code Qualifier	0 .. 1	Token	03	1 .. 2	66
│ │ │ └ **67** — Identification Code - Code assigned by the organization originating the transaction set	0 .. 1	String	04	2 .. 80	

Documentation

Definition To identify a party by type of organization, name, and code

Properties

Identifier N1

Name Name

Cardinality min: 1 max: 1

Syntax Type Related

External Category Segment

Position 070

Level 4

Notes

Comment 1 This segment, used alone, provides the most efficient method of providing organizational identification. To obtain this efficiency the “ID Code” (N104) must provide a key to the table maintained by the transaction processing party.

Leaf Elements

Identifier/Name	Description/Notes/Code Values	Properties
98 Entity Identifier Code	Code identifying an organizational entity, a physical location, property or an individual **Selected Values** **Code** SF **Name** Ship From	**Cardinality** min: 1 max: 1 **Primitive Type** Token **Length** min: 2 max: 3 **External Category** Simple Data Element **Data Type** ID **Position** 01 **Fixed Value** SF **Codelist Id** 98 **Type System** ASC_X12 **Version Mode** Current **Version** 004010
93 Name	Free-form name	**Cardinality** min: 0 max: 1 **Primitive Type** String **Length** min: 1 max: 60 **External Category** Simple Data Element **Data Type** AN **Position** 02
66 Identification Code Qualifier	Code designating the system/method of code structure used for Identification Code (67) **Selected Values** **Code** 93 **Name** Code assigned by the organization originating the transaction set	**Cardinality** min: 0 max: 1 **Primitive Type** Token **Length** min: 1 max: 2 **External Category** Simple Data Element **Data Type** ID **Position** 03

		Fixed Value 93 **Codelist Id** 66 **Type System** ASC_X12 **Version Mode** Current **Version** 004010
67 [66 = “93”] Identification Code - Code assigned by the organization originating the transaction set	Code identifying a party or other code	**Cardinality** **min:** 0 **max:** 1 **Primitive Type** String **Length** **min:** 2 **max:** 80 **External Category** Simple Data Element **Data Type** AN **Position** 04

4.17 N3 — Address Information

Structure

Node	Card.	Prim.Type	Pos.	Length	Codelists
204 — Motor Carrier Load Tender	1 .. 1				
├ **0300** — Loop 0300 - Complete or Others	2 .. 999		010		
│ ├ **0310** — Loop 0310	1 .. 1		070		
│ │ ├ **N3** — Address Information	0 .. 2		090		
│ │ │ └ **166** — Address Information	1 .. 1	String	01	1 .. 55	

Documentation

Definition To specify the location of the named party

Properties

Identifier N3

Name Address Information

Cardinality min: 0 max: 2

Syntax Type Related

External Category Segment

Position 090

Level 4

Leaf Elements

Identifier/Name	Description/Notes/Code Values	Properties
166 Address Information	Address information **Comment 1** For the following country codes in N404 the house number is rendered before the street name in N301: US, CA, FR, UK, IE, AU and NZ All other countries will display the house number after the street name. The street name is shortened in case the combined string exceeds 55 characters.	**Cardinality** min: 1 max: 1 **Primitive Type** String **Length** min: 1 max: 55 **External Category** Simple Data Element **Data Type** AN **Position** 01