		Data Type xsd:string
D_337 Time	Time expressed in 24-hour clock time as follows: HHMM, or HHMMSS, or HHMMSSD, or HHMMSSDD, where H = hours (00-23), M = minutes (00-59), S = integer seconds (00-59) and DD = decimal seconds; decimal seconds are expressed as follows: D = tenths (0-9) and DD = hundredths (00-99)	**Cardinality** **min:** 1 **max:** 1 **Primitive Type** String **Length** **min:** 6 **max:** 6 **External Category** Element **Data Type** xsd:string
D_28 Group Control Number	Assigned number originated and maintained by the sender	**Cardinality** **min:** 1 **max:** 1 **Primitive Type** String **Length** **min:** 9 **max:** 9 **External Category** Element **Data Type** xsd:string
D_455 Responsible Agency Code	Code identifying the issuer of the standard; this code is used in conjunction with Data Element 480 **Selected Values** All Values in Codelist	**Cardinality** **min:** 1 **max:** 1 **Primitive Type** String **Length** **min:** 1 **max:** 1 **External Category** Element **Data Type** xsd:string **Codelist Id** D_455 **Type System** Customer_TS **Version Mode** Local **Version** 1.1
D_480 Version / Release / Industry Identifier Code	Code indicating the version, release, subrelease, and industry identifier of the EDI standard being used, including the GS and GE segments; if code in DE455 in GS segment is X, then in DE 480 positions 1-3 are the version number; positions 4-6 are the release and subrelease, level of the version; and positions 7-12 are the industry or trade association identifiers (optionally assigned by user); if code in DE455 in GS segment is T, then other formats are allowed **Selected Values** All Values in Codelist	**Cardinality** **min:** 1 **max:** 1 **Primitive Type** String **Length** **min:** 6 **max:** 6 **External Category** Element **Data Type** xsd:string **Codelist Id** D_480 **Type System** Customer_TS **Version Mode** Local **Version** 1.1

2.5 S_GE — Functional Group Trailer

Structure

Node	Card.	Prim.Type	Pos.	Length	Codelists
Interchange — Interchange Structure	1 .. 1				
├ **FunctionalGroup** — Functional Group	1 .. 1				
│ └ **S_GE** — Functional Group Trailer	1 .. 1				
│ ├ **D_97** — Number of Transaction Sets Included	1 .. 1	String		1 .. 1	
│ └ **D_28** — Group Control Number	1 .. 1	String		9 .. 9	

Documentation

Definition To indicate the end of a functional group and to provide control information Comments 1. The use of identical data interchange control numbers in the associated functional group header and trailer is designed to maximize functional group integrity. The control number is the same as that used in the corresponding header. Semantic Notes: 1. The data interchange control number GE02 in this trailer must be identical to the same data element in the associated functional group header, GS06.

Properties

Identifier S_GE

Name Functional Group Trailer

Cardinality min: 1 max: 1

Syntax Type Related

External Category Element

Leaf Elements

Identifier/Name	Description/Notes/Code Values	Properties
D_97 Number of Transaction Sets Included	Total number of transaction sets included in the functional group or interchange (transmission) group terminated by the trailer containing this data element	**Cardinality** min: 1 max: 1 **Primitive Type** String **Length** min: 1 max: 1 **External Category** Element **Data Type** xsd:string
D_28 Group Control Number	Assigned number originated and maintained by the sender	**Cardinality** min: 1 max: 1 **Primitive Type** String **Length** min: 9 max: 9 **External Category** Element **Data Type** xsd:string

2.6 S_IEA — Interchange Control Trailer

Structure

Node	Card.	Prim.Type	Pos.	Length	Codelists
Interchange — Interchange Structure	1 .. 1				
└ **S_IEA** — Interchange Control Trailer	1 .. 1				
├ **D_I16** — Number of Included Functional Groups	1 .. 1	String		1 .. 1	
└ **D_I12** — Interchange Control Number	1 .. 1	String		9 .. 9	

Documentation

Definition To define the end of an interchange of zero or more functional groups and interchange-related control segments

Properties

Identifier S_IEA

Name Interchange Control Trailer

Cardinality min: 1 max: 1

Syntax Type Related

External Category Element

Leaf Elements

Identifier/Name	Description/Notes/Code Values	Properties
D_I16 Number of Included Functional Groups	A count of the number of functional groups included in an interchange	**Cardinality** min: 1 max: 1 **Primitive Type** String **Length** min: 1 max: 1 **External Category** Element **Data Type** xsd:string
D_I12 Interchange Control Number	A control number assigned by the interchange sender	**Cardinality** min: 1 max: 1 **Primitive Type** String **Length** min: 9 max: 9 **External Category** Element **Data Type** xsd:string

3 OVERVIEW MESSAGE

General Information

Name	SAP_LBN_ANSI_X12_210
Direction	In
Status	Active
Message Type	Motor Carrier Freight Details and Invoice
Type System	ASC_X12
Version	004010
External Category	Transaction Set

Documentation

Definition This Draft Standard for Trial Use contains the format and establishes the data contents of the Motor Carrier Freight Details and Invoice Transaction Set (210) for use within the context of an Electronic Data Interchange (EDI) environment. The transaction set can be used to provide detail information for charges for services rendered by a motor carrier. It is used both as a motor carrier invoice to request payment or as details pertaining to motor freight shipment(s) charges.

Notes

Example 1

```
ISA*00*          *00*          *02*”Carrier LBNID”*01*”Shipper
LBNID”*220602*1059*U*00401*000001102*0*T*>~
GS*QM*”Carrier LBNID”*”Shipper LBNID”*20220602*105900*000001102*X*004010~
ST*210*11020001~
B3**Invoice Number*FreightOrder ID*PP**20220526*44537****SCAC~
C3*USD~
N9*12*BillFromParty~
N9*CN*PurchasingParty~
N9*06*System ID~
K1*free text*optional free text~
K1*free text~
LX*1~
L1****742315****TAX****VAT_DEST*******19*USD*141040~
LX*2~
L1**7423.15*RC*742315********UNLOADING~
SE*13*11020001~
GE*1*000000102~
IEA*1*000000102~
```

3.1 Structure

The following table shows the complete structure.

Node	Card.	Prim.Type	Pos.	Length	Codelists
210 — Motor Carrier Freight Details and Invoice	1 .. 1				
├ **ST** — Transaction Set Header	1 .. 1		010		
│ ├ **143** — Transaction Set Identifier Code	1 .. 1	Token	01	3 .. 3	143
│ └ **329** — Transaction Set Control Number	1 .. 1	String	02	4 .. 9	
├ **B3** — Beginning Segment for Carrier's Invoice	1 .. 1		020		
│ ├ **76** — Invoice Number	1 .. 1	String	02	1 .. 22	
│ ├ **145** — Shipment Identification Number	1 .. 1	String	03	1 .. 30	
│ ├ **146** — Shipment Method of Payment	1 .. 1	Token	04	2 .. 2	146
│ ├ **373** — Date	1 .. 1	Date	06	8 .. 8	
│ ├ **193** — Net Amount Due	1 .. 1	Decimal	07	1 .. 12	
│ └ **140** — Standard Carrier Alpha Code	1 .. 1	Token	11	2 .. 4	
├ **C3** — Currency	1 .. 1		040		
│ └ **100** — Currency Code	1 .. 1	Token	01	3 .. 3	ISO_4217
├ **N9** — Reference Identification	3 .. 300		060		
│ ├ **128** — Reference Identification Qualifier	1 .. 1	Token	01	2 .. 3	128
│ ├ **127** — Reference Identification - System Number	1 .. 1	String	02	1 .. 30	
│ ├ **127** — Reference Identification - Billing Account	0 .. 1	String	02	1 .. 30	
│ ├ **127** — Reference Identification - Purchasing Party	0 .. 1	String	02	1 .. 30	
│ ├ **369** — Free-form Description	0 .. 1	String	03	1 .. 45	
│ ├ **373** — Date	0 .. 1	Date	04	8 .. 8	
│ ├ **337** — Time	0 .. 1	Time	05	4 .. 8	
│ ├ **623** — Time Code	0 .. 1	Token	06	2 .. 2	623
│ └ **C040** — Reference Identifier	0 .. 1		07		
│ ├ **128** — Reference Identification Qualifier	1 .. 1	Token	01	2 .. 3	128
│ ├ **127** — Reference Identification	1 .. 1	String	02	1 .. 30	
│ ├ **128** — Reference Identification Qualifier	0 .. 1	Token	03	2 .. 3	128
│ ├ **127** — Reference Identification	0 .. 1	String	04	1 .. 30	
│ ├ **128** — Reference Identification Qualifier	0 .. 1	Token	05	2 .. 3	128
│ └ **127** — Reference Identification	0 .. 1	String	06	1 .. 30	
├ **K1** — Remarks	0 .. 10		100		
│ ├ **61** — Free-Form Message	1 .. 1	String	01	1 .. 30	
│ └ **61** — Free-Form Message	0 .. 1	String	02	1 .. 30	
├ **0400** — Loop 0400	0 .. 9999		120		
│ ├ **LX** — Assigned Number	1 .. 1		120		
│ │ └ **554** — Assigned Number	1 .. 1	Integer	01	1 .. 6	
│ ├ **L0** — Line Item - Quantity and Weight	0 .. 1		170		
│ │ ├ **221** — Billed/Rated-as Qualifier	0 .. 1	Token	03	2 .. 2	221
│ │ └ **380** — Quantity	0 .. 1	Decimal	13	1 .. 15	
│ └ **L1** — Rate and Charges	1 .. 1		180		
│ ├ **60** — Freight Rate	0 .. 1	Decimal	02	1 .. 9	
│ ├ **122** — Rate/Value Qualifier	0 .. 1	Token	03	2 .. 2	122
│ ├ **58** — Charge	1 .. 1	Decimal	04	1 .. 12	
│ ├ **150** — Special Charge or Allowance Code	0 .. 1	Token	08	3 .. 3	150
│ ├ **276** — Special Charge Description	1 .. 1	String	12	2 .. 25	
│ ├ **220** — Billed/Rated-as Quantity	0 .. 1	Decimal	17	1 .. 11	
│ ├ **221** — Billed/Rated-as Qualifier	0 .. 1	Token	18	2 .. 2	221
│ ├ **954** — Percent	0 .. 1	Decimal	19	1 .. 10	
│ ├ **100** — Currency Code	0 .. 1	Token	20	3 .. 3	ISO_4217
│ └ **610** — Amount	0 .. 1	Decimal	21	1 .. 15	
├ **L3** — Total Weight and Charges	0 .. 1		010		
│ ├ **58** — Charge	0 .. 1	Decimal	05	1 .. 12	
│ └ **150** — Special Charge or Allowance Code	0 .. 1	Token	08	3 .. 3	150
└ **SE** — Transaction Set Trailer	1 .. 1		020		
├ **96** — Number of Included Segments	1 .. 1	Integer	01	1 .. 10	
└ **329** — Transaction Set Control Number	1 .. 1	String	02	4 .. 9	

4 DETAILS MESSAGE

4.1 210 — Motor Carrier Freight Details and Invoice

Structure

Node	Card.	Prim.Type	Pos.	Length	Codelists
210 — Motor Carrier Freight Details and Invoice	1 .. 1				
├ **ST** — Transaction Set Header	1 .. 1		010		
├ **B3** — Beginning Segment for Carrier's Invoice	1 .. 1		020		
├ **C3** — Currency	1 .. 1		040		
├ **N9** — Reference Identification	3 .. 300		060		
├ **K1** — Remarks	0 .. 10		100		
├ **0400** — Loop 0400	0 .. 9999		120		
├ **L3** — Total Weight and Charges	0 .. 1		010		
└ **SE** — Transaction Set Trailer	1 .. 1		020		

Properties

Identifier 210

Name Motor Carrier Freight Details and Invoice

Cardinality min: 1 max: 1

4.2 ST — Transaction Set Header

Structure

Node	Card.	Prim.Type	Pos.	Length	Codelists
210 — Motor Carrier Freight Details and Invoice	1 .. 1				
├ **ST** — Transaction Set Header	1 .. 1		010		
│ ├ **143** — Transaction Set Identifier Code	1 .. 1	Token	01	3 .. 3	143
│ └ **329** — Transaction Set Control Number	1 .. 1	String	02	4 .. 9	

Documentation

Definition To indicate the start of a transaction set and to assign a control number

Properties

Identifier ST

Name Transaction Set Header

Cardinality min: 1 max: 1

Syntax Type Related

External Category Segment

Position 010

Level 2

Notes

Usage 1 The transaction set identifier (ST01) used by the translation routines of the interchange partners to select the appropriate transaction set definition (e.g., 810 selects the Invoice Transaction Set).

Leaf Elements

Identifier/Name	Description/Notes/Code Values	Properties
143 Transaction Set Identifier Code	Code uniquely identifying a Transaction Set **Selected Values** **Code** 210 **Name** Motor Carrier Freight Details and Invoice	**Cardinality** min: 1 max: 1 **Primitive Type** Token **Length** min: 3 max: 3 **External Category** Simple Data Element **Data Type** ID **Position** 01 **Fixed Value** 210 **Codelist Id** 143 **Type System** ASC_X12 **Version Mode** Current **Version** 004010
329 Transaction Set Control Number	Identifying control number that must be unique within the transaction set functional group assigned by the originator for a transaction set	**Cardinality** min: 1 max: 1 **Primitive Type** String **Length** min: 4 max: 9 **External Category** Simple Data Element **Data Type** AN **Position** 02

4.3 B3 — Beginning Segment for Carrier's Invoice

Structure

Node	Card.	Prim.Type	Pos.	Length	Codelists
210 — Motor Carrier Freight Details and Invoice	1 .. 1				
├ **B3** — Beginning Segment for Carrier's Invoice	1 .. 1		020		
│ ├ **76** — Invoice Number	1 .. 1	String	02	1 .. 22	
│ ├ **145** — Shipment Identification Number	1 .. 1	String	03	1 .. 30	
│ ├ **146** — Shipment Method of Payment	1 .. 1	Token	04	2 .. 2	146
│ ├ **373** — Date	1 .. 1	Date	06	8 .. 8	
│ ├ **193** — Net Amount Due	1 .. 1	Decimal	07	1 .. 12	
│ └ **140** — Standard Carrier Alpha Code	1 .. 1	Token	11	2 .. 4	

Documentation

Definition To transmit basic data relating to the carrier's invoice

Properties

Identifier B3

Name Beginning Segment for Carrier's Invoice

Cardinality min: 1 max: 1

Syntax Type Related

External Category Segment

Position 020

Level 2

Notes

Usage 1 B306 is the billing date.

Usage 2 On collect freight bills the data in B309 will be the actual delivery date. For the shipments invoiced prior to delivery, the B309 will be the estimated date of delivery.

Usage 3 If B314 is used, B304 will indicate the party or parties responsible for payment of the transportation terms identified in B314.

Constraint 1 P0910 Paired Multiple - If any are used, all must be used

Leaf Elements

Identifier/Name	Description/Notes/Code Values	Properties
76 Invoice Number	Identifying number assigned by issuer	**Cardinality** min: 1 max: 1 **Primitive Type** String **Length** min: 1 max: 22 **External Category** Simple Data Element **Data Type** AN **Position** 02
145 Shipment Identification Number	Identification number assigned to the shipment by the shipper that uniquely identifies the shipment from origin to ultimate destination and is not subject to modification; (Does not contain blanks or special characters)	**Cardinality** min: 1 max: 1 **Primitive Type** String **Length** min: 1 max: 30 **External Category** Simple Data Element **Data Type** AN **Position** 03
146 Shipment Method of Payment	Code identifying payment terms for transportation charges **Selected Values** All Values in Codelist	**Cardinality** min: 1 max: 1 **Primitive Type** Token **Length** min: 2 max: 2 **External Category** Simple Data Element **Data Type** ID **Position** 04 **Codelist Id** 146

		Type System ASC_X12 **Version Mode** Current **Version** 004010
373 Date	Date expressed as CCYYMMDD **Usage 1** The invoice date.	**Cardinality** **min:** 1 **max:** 1 **Primitive Type** Date **Length** **min:** 8 **max:** 8 **Date Time Format** CCYYMMDD **External Category** Simple Data Element **Data Type** DT **Position** 06
193 Net Amount Due	Total charges to be paid by the receiver of this transaction set expressed in the standard monetary denomination for the currency specified	**Cardinality** **min:** 1 **max:** 1 **Primitive Type** Decimal **Length** **min:** 1 **max:** 12 **Fraction Digits** 2 **Total Digits** 12 **External Category** Simple Data Element **Data Type** N2 **Position** 07
140 Standard Carrier Alpha Code	Standard Carrier Alpha Code **Usage 1** This field is not used.	**Cardinality** **min:** 1 **max:** 1 **Primitive Type** Token **Length** **min:** 2 **max:** 4 **External Category** Simple Data Element **Data Type** ID **Position** 11

4.4 C3 — Currency

Structure

Node	Card.	Prim.Type	Pos.	Length	Codelists
210 — Motor Carrier Freight Details and Invoice	1 .. 1				
├ **C3** — Currency	1 .. 1		040		
│ └ **100** — Currency Code	1 .. 1	Token	01	3 .. 3	ISO_4217

Documentation

Definition To specify the currency being used in the transaction set

Properties

Identifier C3

Name Currency

Cardinality min: 1 max: 1

Syntax Type Related

External Category Segment

Position 040

Level 2

Notes

Usage 1 C301 is the billing currency.

Usage 2 C303 is the payment currency.

Usage 3 C304 is the rated currency.

Usage 4 This is the currency of gross amount. This is a mandatory field for Business Network for Logistics.

Comment 1 Currency is implied by the code for the country in whose currency the monetary amounts are specified.

Leaf Elements

Identifier/Name	Description/Notes/Code Values	Properties
100 Currency Code	Code (Standard ISO) for country in whose currency the charges are specified **Selected Values** All Values in Codelist	**Cardinality** min: 1 max: 1 **Primitive Type** Token **Length** min: 3 max: 3 **External Category** Simple Data Element **Data Type** ID **Position** 01 **Codelist Id** ISO_4217 **Type System** ISO_CodelistsAndSchemes **Version Mode** Latest **Version** 2015