4.5 N9 — Reference Identification

Structure

Node	Card.	Prim.Type	Pos.	Length	Codelists
210 — Motor Carrier Freight Details and Invoice	1 .. 1				
├ **N9** — Reference Identification	3 .. 300		060		
│ ├ **128** — Reference Identification Qualifier	1 .. 1	Token	01	2 .. 3	128
│ ├ **127** — Reference Identification - System Number	1 .. 1	String	02	1 .. 30	
│ ├ **127** — Reference Identification - Billing Account	0 .. 1	String	02	1 .. 30	
│ ├ **127** — Reference Identification - Purchasing Party	0 .. 1	String	02	1 .. 30	
│ ├ **369** — Free-form Description	0 .. 1	String	03	1 .. 45	
│ ├ **373** — Date	0 .. 1	Date	04	8 .. 8	
│ ├ **337** — Time	0 .. 1	Time	05	4 .. 8	
│ ├ **623** — Time Code	0 .. 1	Token	06	2 .. 2	623
│ └ **C040** — Reference Identifier	0 .. 1		07		

Documentation

Definition To transmit identifying information as specified by the Reference Identification Qualifier

Properties

Identifier N9

Name Reference Identification

Cardinality min: 3 max: 300

Syntax Type Related

External Category Segment

Position 060

Level 2

Notes

Usage 1 N906 reflects the time zone which the time reflects.

Usage 2 N907 contains data relating to the value cited in N902.

Constraint 1 R0203 Required - At least one of those noted must be used

Constraint 2 C0605 Conditional - If the first element is present, then the others must be present

Leaf Elements

Identifier/Name	Description/Notes/Code Values	Properties
128 Reference Identification Qualifier	Code qualifying the Reference Identification **Selected Values** All Values in Codelist	**Cardinality** min: 1 max: 1 **Primitive Type** Token **Length** min: 2 max: 3 **External Category** Simple Data Element **Data Type** ID **Position** 01 **Codelist Id** 128 **Type System** ASC_X12 **Version Mode** Current **Version** 004010
127 [128 = "06"] Reference Identification - System Number	Reference information as defined for a particular Transaction Set or as specified by the Reference Identification Qualifier	**Cardinality** min: 1 max: 1 **Primitive Type** String **Length** min: 1 max: 30 **External Category** Simple Data Element **Data Type** AN **Position** 02
127 [128 = "12"] Reference Identification -	Reference information as defined for a particular Transaction Set or as specified by the Reference	**Cardinality** min: 0 max: 1 **Primitive Type** String

Billing Account	Identification Qualifier	**Length** min: 1 max: 30 **External Category** Simple Data Element **Data Type** AN **Position** 02
127 [128 = "CN"] Reference Identification - Purchasing Party	Reference information as defined for a particular Transaction Set or as specified by the Reference Identification Qualifier **Usage 1** The CN qualifier is used to identify the Purchasing Party	**Cardinality** min: 0 max: 1 **Primitive Type** String **Length** min: 1 max: 30 **External Category** Simple Data Element **Data Type** AN **Position** 02
369 Free-form Description	Free-form descriptive text	**Cardinality** min: 0 max: 1 **Primitive Type** String **Length** min: 1 max: 45 **External Category** Simple Data Element **Data Type** AN **Position** 03
373 Date	Date expressed as CCYYMMDD	**Cardinality** min: 0 max: 1 **Primitive Type** Date **Length** min: 8 max: 8 **Date Time Format** CCYYMMDD **External Category** Simple Data Element **Data Type** DT **Position** 04
337 Time	Time expressed in 24-hour clock time as follows: HHMM, or HHMMSS, or HHMMSSD, or HHMMSSDD, where H = hours (00-23), M = minutes (00-59), S = integer seconds (00-59) and DD = decimal seconds; decimal seconds are expressed as follows: D = tenths (0-9) and DD = hundredths (00-99)	**Cardinality** min: 0 max: 1 **Primitive Type** Time **Length** min: 4 max: 8 **Date Time Format** hhmm[ss[f[f]]] **External Category** Simple Data Element **Data Type** TM **Position** 05
623 Time Code	Code identifying the time. In accordance with International Standards Organization standard 8601, time can be specified by a + or - and an indication in hours in relation to Universal Time Coordinate (UTC) time; since + is a restricted character, + and - are substituted by P and M in the codes that follow **Selected Values** All Values in Codelist	**Cardinality** min: 0 max: 1 **Primitive Type** Token **Length** min: 2 max: 2 **External Category** Simple Data Element **Data Type** ID **Position** 06 **Codelist Id** 623 **Type System** ASC_X12 **Version Mode** Current **Version** 004010

4.6 C040 — Reference Identifier

Structure

Node	Card.	Prim.Type	Pos.	Length	Codelists
210 — Motor Carrier Freight Details and Invoice	1 .. 1				
├ **N9** — Reference Identification	3 .. 300		060		
│ └ **C040** — Reference Identifier	0 .. 1		07		
│ ├ **128** — Reference Identification Qualifier	1 .. 1	Token	01	2 .. 3	128
│ ├ **127** — Reference Identification	1 .. 1	String	02	1 .. 30	
│ ├ **128** — Reference Identification Qualifier	0 .. 1	Token	03	2 .. 3	128
│ ├ **127** — Reference Identification	0 .. 1	String	04	1 .. 30	
│ ├ **128** — Reference Identification Qualifier	0 .. 1	Token	05	2 .. 3	128
│ └ **127** — Reference Identification	0 .. 1	String	06	1 .. 30	

Documentation

Definition To identify one or more reference numbers or identification numbers as specified by the Reference Qualifier

Properties

Identifier C040

Name Reference Identifier

Cardinality min: 0 max: 1

Syntax Type Related

External Category Composite Data Structure

Position 07

Notes

Constraint 1 P0304 Paired Multiple - If any are used, all must be used

Constraint 2 P0506 Paired Multiple - If any are used, all must be used

Leaf Elements

Identifier/Name	Description/Notes/Code Values	Properties
128 Reference Identification Qualifier	Code qualifying the Reference Identification **Selected Values** All Values in Codelist	**Cardinality** min: 1 max: 1 **Primitive Type** Token **Length** min: 2 max: 3 **External Category** Simple Data Element **Data Type** ID **Position** 01 **Codelist Id** 128 **Type System** ASC_X12 **Version Mode** Current **Version** 004010
127 Reference Identification	Reference information as defined for a particular Transaction Set or as specified by the Reference Identification Qualifier	**Cardinality** min: 1 max: 1 **Primitive Type** String **Length** min: 1 max: 30 **External Category** Simple Data Element **Data Type** AN **Position** 02
128 Reference Identification Qualifier	Code qualifying the Reference Identification **Selected Values** All Values in Codelist	**Cardinality** min: 0 max: 1 **Primitive Type** Token **Length** min: 2 max: 3 **External Category** Simple Data Element **Data Type** ID **Position** 03 **Codelist Id** 128

		Type System ASC_X12 **Version Mode** Current **Version** 004010
127 Reference Identification	Reference information as defined for a particular Transaction Set or as specified by the Reference Identification Qualifier	**Cardinality** **min:** 0 **max:** 1 **Primitive Type** String **Length** **min:** 1 **max:** 30 **External Category** Simple Data Element **Data Type** AN **Position** 04
128 Reference Identification Qualifier	Code qualifying the Reference Identification **Selected Values** All Values in Codelist	**Cardinality** **min:** 0 **max:** 1 **Primitive Type** Token **Length** **min:** 2 **max:** 3 **External Category** Simple Data Element **Data Type** ID **Position** 05 **Codelist Id** 128 **Type System** ASC_X12 **Version Mode** Current **Version** 004010
127 Reference Identification	Reference information as defined for a particular Transaction Set or as specified by the Reference Identification Qualifier	**Cardinality** **min:** 0 **max:** 1 **Primitive Type** String **Length** **min:** 1 **max:** 30 **External Category** Simple Data Element **Data Type** AN **Position** 06

4.7 K1 — Remarks

Structure

Node	Card.	Prim.Type	Pos.	Length	Codelists
210 — Motor Carrier Freight Details and Invoice	1 .. 1				
├ **K1** — Remarks	0 .. 10		100		
│ ├ **61** — Free-Form Message	1 .. 1	String	01	1 .. 30	
│ └ **61** — Free-Form Message	0 .. 1	String	02	1 .. 30	

Documentation

Definition To transmit information in a free-form format for comment or special instruction

Properties

Identifier K1

Name Remarks

Cardinality min: 0 max: 10

Syntax Type Related

External Category Segment

Position 100

Level 2

Leaf Elements

Identifier/Name	Description/Notes/Code Values	Properties
61 Free-Form Message	Free-form information	**Cardinality** **min:** 1 **max:** 1 **Primitive Type** String **Length** **min:** 1 **max:** 30 **External Category** Simple Data Element **Data Type** AN **Position** 01
61 Free-Form Message	Free-form information	**Cardinality** **min:** 0 **max:** 1 **Primitive Type** String **Length** **min:** 1 **max:** 30 **External Category** Simple Data Element **Data Type** AN **Position** 02

4.8 0400 — Loop 0400

Structure

Node	Card.	Prim.Type	Pos.	Length	Codelists
210 — Motor Carrier Freight Details and Invoice	1 .. 1				
├ **0400** — Loop 0400	0 .. 9999		120		
│ ├ **LX** — Assigned Number	1 .. 1		120		
│ ├ **L0** — Line Item - Quantity and Weight	0 .. 1		170		
│ └ **L1** — Rate and Charges	1 .. 1		180		

Properties

Identifier 0400

Name Loop 0400

Cardinality min: 0 max: 9999

Syntax Type Related

External Category Loop

Position 120

Level 2

4.9 LX — Assigned Number

Structure

Node	Card.	Prim.Type	Pos.	Length	Codelists
210 — Motor Carrier Freight Details and Invoice	1 .. 1				
├ **0400** — Loop 0400	0 .. 9999		120		
│ ├ **LX** — Assigned Number	1 .. 1		120		
│ │ └ **554** — Assigned Number	1 .. 1	Integer	01	1 .. 6	

Documentation

Definition To reference a line number in a transaction set

Properties

Identifier LX

Name Assigned Number

Cardinality min: 1 max: 1

Syntax Type Related

External Category Segment

Position 120

Level 3

Leaf Elements

Identifier/Name	Description/Notes/Code Values	Properties
554 Assigned Number	Number assigned for differentiation within a transaction set	**Cardinality** min: 1 max: 1 **Primitive Type** Integer **Length** min: 1 max: 6 **Fraction Digits** 0 **Total Digits** 6 **External Category** Simple Data Element **Data Type** N0 **Position** 01

4.10 L0 — Line Item - Quantity and Weight

Structure

Node	Card.	Prim.Type	Pos.	Length	Codelists
210 — Motor Carrier Freight Details and Invoice	1 .. 1				
├ **0400** — Loop 0400	0 .. 9999		120		
│ ├ **L0** — Line Item - Quantity and Weight	0 .. 1		170		
│ │ ├ **221** — Billed/Rated-as Qualifier	0 .. 1	Token	03	2 .. 2	221
│ │ └ **380** — Quantity	0 .. 1	Decimal	13	1 .. 15	

Documentation

Definition To specify quantity, weight, volume, and type of service for a line item including applicable "quantity/rate-as" data

Properties

Identifier L0

Name Line Item - Quantity and Weight

Cardinality min: 0 max: 1

Syntax Type Related

External Category Segment

Position 170

Level 3

Notes

Usage 1 L008 is the number of handling units of the line item tendered to the carrier.

Usage 2 L013 can only be used if the code in L009 is PLT, SKD, or SLP.

Usage 3 L015 designates whether the carrier will be required to verify the number of units contained on a pallet, slip sheet or skid. Code "Y" indicates that the carrier will be required to verify. Code "N" indicates that the carrier will not be required to verify.

Constraint 1 P0203 Paired Multiple - If any are used, all must be used

Constraint 2 P0405 Paired Multiple - If any are used, all must be used

Constraint 3 P0607 Paired Multiple - If any are used, all must be used

Constraint 4 P0809 Paired Multiple - If any are used, all must be used

Constraint 5 C1104 Conditional - If the first element is present, then the others must be present

Constraint 6 P1315 Paired Multiple - If any are used, all must be used

Comment 1 L013 is used to convey the total number of boxes, cartons, or pieces contained on a pallet, skid, or slip sheet for the line item.

Leaf Elements

Identifier/Name	Description/Notes/Code Values	Properties
221 Billed/Rated-as Qualifier	Code identifying the type of quantity or value on which the rate or item pricing is based **Usage 1** The unit of measurement of the quantity. **Selected Values** All Values in Codelist	**Cardinality** min: 0 max: 1 **Primitive Type** Token **Length** min: 2 max: 2 **External Category** Simple Data Element **Data Type** ID **Position** 03 **Codelist Id** 221 **Type System** ASC_X12 **Version Mode** Current **Version** 004010
380	Numeric value of quantity	**Cardinality** min: 0 max: 1

Quantity		**Primitive Type** Decimal **Length** **min:** 1 **max:** 15 **Total Digits** 15 **External Category** Simple Data Element **Data Type** R **Position** 13

4.11 L1 — Rate and Charges

Structure

Node	Card.	Prim.Type	Pos.	Length	Codelists
210 — Motor Carrier Freight Details and Invoice	1 .. 1				
├ **0400** — Loop 0400	0 .. 9999		120		
│ └ **L1** — Rate and Charges	1 .. 1		180		
│ ├ **60** — Freight Rate	0 .. 1	Decimal	02	1 .. 9	
│ ├ **122** — Rate/Value Qualifier	0 .. 1	Token	03	2 .. 2	122
│ ├ **58** — Charge	1 .. 1	Decimal	04	1 .. 12	
│ ├ **150** — Special Charge or Allowance Code	0 .. 1	Token	08	3 .. 3	150
│ ├ **276** — Special Charge Description	1 .. 1	String	12	2 .. 25	
│ ├ **220** — Billed/Rated-as Quantity	0 .. 1	Decimal	17	1 .. 11	
│ ├ **221** — Billed/Rated-as Qualifier	0 .. 1	Token	18	2 .. 2	221
│ ├ **954** — Percent	0 .. 1	Decimal	19	1 .. 10	
│ ├ **100** — Currency Code	0 .. 1	Token	20	3 .. 3	ISO_4217
│ └ **610** — Amount	0 .. 1	Decimal	21	1 .. 15	

Documentation

Definition To specify rate and charges detail relative to a line item including freight charges, advances, special charges, and entitlements

Properties

Identifier L1

Name Rate and Charges

Cardinality min: 1 max: 1

Syntax Type Related

External Category Segment

Position 180

Level 3

Notes

Usage 1 If D_150 used only tax information in this L1 segment will be handled. In this case the fields D_954 and D_610 are mandatory. Additionally all fields beside D_150, D_954, D_610 and D_100 will be ignored.

Usage 2 If D_150 is not used, this L1 segment will be handled as either percentage, rate or flat rate charge depending on the value of D_122. See notes of D_122 for more detailed information.

Example 1 L1 segment used for a tax charge: L1****1234****TAX****VAT_DEST*******19*USD*42

Example 2 L1 segment used for a percentage rate charge: L1***PW*1234********FUEL_EMERGENCY*******19 or L1*2*123*PH*48534********FUEL_EMERGENCY*****1*CC***

Example 3 L1 segment used for a rate charge: L1**6*RC*1200********FUEL_PER_MILE*****1*DM**USD

Example 4 L1 segment used for a flat rate charge: L1***FR*15022********BASE_CHARGE or L1****15022********BASE_CHARGE

Leaf Elements

Identifier/Name	Description/Notes/Code Values	Properties
60 Freight Rate	Rate that applies to the specific commodity **Usage 1** If D_122 has value RC, this field contains the rate for the charge.	**Cardinality** min: 0 max: 1 **Primitive Type** Decimal **Length** min: 1 max: 9 **Total Digits** 9 **External Category** Simple Data Element **Data Type** R **Position** 02
122 Rate/Value Qualifier	Code qualifying how to extend charges or interpret value	**Cardinality** min: 0 max: 1 **Primitive Type** Token