		Data Type xsd:string
D_337 Time	Time expressed in 24-hour clock time as follows: HHMM, or HHMMSS, or HHMMSSD, or HHMMSSDD, where H = hours (00-23), M = minutes (00-59), S = integer seconds (00-59) and DD = decimal seconds; decimal seconds are expressed as follows: D = tenths (0-9) and DD = hundredths (00-99)	**Cardinality** **min:** 1 **max:** 1 **Primitive Type** String **Length** **min:** 6 **max:** 6 **External Category** Element **Data Type** xsd:string
D_28 Group Control Number	Assigned number originated and maintained by the sender	**Cardinality** **min:** 1 **max:** 1 **Primitive Type** String **Length** **min:** 9 **max:** 9 **External Category** Element **Data Type** xsd:string
D_455 Responsible Agency Code	Code identifying the issuer of the standard; this code is used in conjunction with Data Element 480 **Selected Values** All Values in Codelist	**Cardinality** **min:** 1 **max:** 1 **Primitive Type** String **Length** **min:** 1 **max:** 1 **External Category** Element **Data Type** xsd:string **Codelist Id** D_455 **Type System** Customer_TS **Version Mode** Local **Version** 1.1
D_480 Version / Release / Industry Identifier Code	Code indicating the version, release, subrelease, and industry identifier of the EDI standard being used, including the GS and GE segments; if code in DE455 in GS segment is X, then in DE 480 positions 1-3 are the version number; positions 4-6 are the release and subrelease, level of the version; and positions 7-12 are the industry or trade association identifiers (optionally assigned by user); if code in DE455 in GS segment is T, then other formats are allowed **Selected Values** All Values in Codelist	**Cardinality** **min:** 1 **max:** 1 **Primitive Type** String **Length** **min:** 6 **max:** 6 **External Category** Element **Data Type** xsd:string **Codelist Id** D_480 **Type System** Customer_TS **Version Mode** Local **Version** 1.1

2.5 S_GE — Functional Group Trailer

Structure

Node	Card.	Prim.Type	Pos.	Length	Codelists
Interchange — Interchange Structure	1 .. 1				
├ **FunctionalGroup** — Functional Group	1 .. 1				
│ └ **S_GE** — Functional Group Trailer	1 .. 1				
│ ├ **D_97** — Number of Transaction Sets Included	1 .. 1	String		1 .. 1	
│ └ **D_28** — Group Control Number	1 .. 1	String		9 .. 9	

Documentation

Definition To indicate the end of a functional group and to provide control information Comments 1. The use of identical data interchange control numbers in the associated functional group header and trailer is designed to maximize functional group integrity. The control number is the same as that used in the corresponding header. Semantic Notes: 1. The data interchange control number GE02 in this trailer must be identical to the same data element in the associated functional group header, GS06.

Properties

Identifier S_GE

Name Functional Group Trailer

Cardinality min: 1 max: 1

Syntax Type Related

External Category Element

Leaf Elements

Identifier/Name	Description/Notes/Code Values	Properties
D_97 Number of Transaction Sets Included	Total number of transaction sets included in the functional group or interchange (transmission) group terminated by the trailer containing this data element	**Cardinality** min: 1 max: 1 **Primitive Type** String **Length** min: 1 max: 1 **External Category** Element **Data Type** xsd:string
D_28 Group Control Number	Assigned number originated and maintained by the sender	**Cardinality** min: 1 max: 1 **Primitive Type** String **Length** min: 9 max: 9 **External Category** Element **Data Type** xsd:string

2.6 S_IEA — Interchange Control Trailer

Structure

Node	Card.	Prim.Type	Pos.	Length	Codelists
Interchange — Interchange Structure	1 .. 1				
└ **S_IEA** — Interchange Control Trailer	1 .. 1				
├ **D_I16** — Number of Included Functional Groups	1 .. 1	String		1 .. 1	
└ **D_I12** — Interchange Control Number	1 .. 1	String		9 .. 9	

Documentation

Definition To define the end of an interchange of zero or more functional groups and interchange-related control segments

Properties

Identifier S_IEA

Name Interchange Control Trailer

Cardinality min: 1 max: 1

Syntax Type Related

External Category Element

Leaf Elements

Identifier/Name	Description/Notes/Code Values	Properties
D_I16 Number of Included Functional Groups	A count of the number of functional groups included in an interchange	**Cardinality** min: 1 max: 1 **Primitive Type** String **Length** min: 1 max: 1 **External Category** Element **Data Type** xsd:string
D_I12 Interchange Control Number	A control number assigned by the interchange sender	**Cardinality** min: 1 max: 1 **Primitive Type** String **Length** min: 9 max: 9 **External Category** Element **Data Type** xsd:string

3 OVERVIEW MESSAGE

General Information

Name	ANSI_X12_213_GTT
Direction	In
Status	Active
Message Type	Motor Carrier Shipment Status Inquiry
Type System	ASC_X12
Version	004010
External Category	Transaction Set

Documentation

Definition

This Draft Standard for Trial Use contains the format and establishes the data contents of the Motor Carrier Shipment Status Inquiry Transaction Set (213) for use within the context of an Electronic Data Interchange (EDI) environment. The transaction set can be used to request shipment status from a motor carrier. The requestor may be a shipper or consignee.

As of now, the Messagetype is only available for the Global Track and Trace (GTT).

Notes

Example 1

```
ISA*00*          *00*          *02*”Carrier LBNID”*01*”Shipper
LBNID”*221130*1604*U*00401*000001102*0*T*>~
GS*QM*”Carrier LBNID”*”Shipper LBNID”*221130*1604*000001102*X*004010~
ST*213*11020001~
B11*0*FreightOrderId~
REF*”Sender System ID”*06~
REF*FreightOrderType*8X~
N1*00~
REF*”Location ID”*LU~
REF*”Location type”*4L~
REF*”Stop ID”*QN~
SE*9*0001~
GE*1*000001102~
IEA*1*000001102~
```

3.1 Structure

The following table shows the complete structure.

Node	Card.	Prim.Type	Pos.	Length	Codelists
213 — Motor Carrier Shipment Status Inquiry	1 .. 1				
├ **ST** — Transaction Set Header	1 .. 1		010		
│ ├ **143** — Transaction Set Identifier Code	1 .. 1	Token	01	3 .. 3	143
│ └ **329** — Transaction Set Control Number	1 .. 1	String	02	4 .. 9	
├ **B11** — Beginning Segment for Shipment Status Inquiry	1 .. 1		020		
│ ├ **66** — Identification Code Qualifier	1 .. 1	Token	01	1 .. 2	145
│ └ **67** — Identification Code	1 .. 1	String	02	2 .. 80	
├ **REF** — Reference Identification	1 .. 10		040		
│ ├ **128** — Reference Identification Qualifier	1 .. 1	Token	01	2 .. 3	128
│ └ **127** — Reference Identification	0 .. 1	String	02	1 .. 30	
├ **0100** — Loop 0100	0 .. 5		060		
│ ├ **N1** — Name	1 .. 1		060		
│ │ └ **98** — Entity Identifier Code	1 .. 1	Token	01	2 .. 3	98
│ └ **REF** — Reference Identification	1 .. 10		100		
│ ├ **128** — Reference Identification Qualifier	1 .. 1	Token	01	2 .. 3	128
│ └ **127** — Reference Identification	0 .. 1	String	02	1 .. 30	
└ **SE** — Transaction Set Trailer	1 .. 1		120		
├ **96** — Number of Included Segments	1 .. 1	Integer	01	1 .. 10	
└ **329** — Transaction Set Control Number	1 .. 1	String	02	4 .. 9	

4 DETAILS MESSAGE

4.1 213 — Motor Carrier Shipment Status Inquiry

Structure

Node	Card.	Prim.Type	Pos.	Length	Codelists
213 — Motor Carrier Shipment Status Inquiry	1 .. 1				
├ **ST** — Transaction Set Header	1 .. 1		010		
├ **B11** — Beginning Segment for Shipment Status Inquiry	1 .. 1		020		
├ **REF** — Reference Identification	1 .. 10		040		
├ **0100** — Loop 0100	0 .. 5		060		
└ **SE** — Transaction Set Trailer	1 .. 1		120		

Properties

Identifier 213

Name Motor Carrier Shipment Status Inquiry

Cardinality min: 1 max: 1

4.2 ST — Transaction Set Header

Structure

Node	Card.	Prim.Type	Pos.	Length	Codelists
213 — Motor Carrier Shipment Status Inquiry	1 .. 1				
├ **ST** — Transaction Set Header	1 .. 1		010		
│ ├ **143** — Transaction Set Identifier Code	1 .. 1	Token	01	3 .. 3	143
│ └ **329** — Transaction Set Control Number	1 .. 1	String	02	4 .. 9	

Documentation

Definition To indicate the start of a transaction set and to assign a control number

Properties

Identifier ST

Name Transaction Set Header

Cardinality min: 1 max: 1

Syntax Type Related

External Category Segment

Position 010

Level 2

Notes

Usage 1 The transaction set identifier (ST01) used by the translation routines of the interchange partners to select the appropriate transaction set definition (e.g., 810 selects the Invoice Transaction Set).

Leaf Elements

Identifier/Name	Description/Notes/Code Values	Properties
143 Transaction Set Identifier Code	Code uniquely identifying a Transaction Set **Selected Values** All Values in Codelist	**Cardinality** min: 1 max: 1 **Primitive Type** Token **Length** min: 3 max: 3 **External Category** Simple Data Element **Data Type** ID **Position** 01 **Codelist Id** 143 **Type System** ASC_X12 **Version Mode** Current **Version** 004010
329 Transaction Set Control Number	Identifying control number that must be unique within the transaction set functional group assigned by the originator for a transaction set	**Cardinality** min: 1 max: 1 **Primitive Type** String **Length** min: 4 max: 9 **External Category** Simple Data Element **Data Type** AN **Position** 02

4.3 B11 — Beginning Segment for Shipment Status Inquiry

Structure

Node	Card.	Prim.Type	Pos.	Length	Codelists
213 — Motor Carrier Shipment Status Inquiry	1 .. 1				
├ **B11** — Beginning Segment for Shipment Status Inquiry	1 .. 1		020		
│ ├ **66** — Identification Code Qualifier	1 .. 1	Token	01	1 .. 2	145
│ └ **67** — Identification Code	1 .. 1	String	02	2 .. 80	

Documentation

Definition To transmit identifying numbers, dates, and other basic data relating to the transaction set

Properties

Identifier B11

Name Beginning Segment for Shipment Status Inquiry

Cardinality min: 1 max: 1

Syntax Type Related

External Category Segment

Position 020

Level 2

Notes

Usage 1 B1103 is the pick-up date.

Constraint 1 P0405 Paired Multiple - If any are used, all must be used

Constraint 2 P0607 Paired Multiple - If any are used, all must be used

Constraint 3 P0809 Paired Multiple - If any are used, all must be used

Comment 1 B1101 identifies the requestor.

Leaf Elements

Identifier/Name	Description/Notes/Code Values	Properties
66 Identification Code Qualifier	Code designating the system/method of code structure used for Identification Code (67) **Selected Values** All Values in Codelist	**Cardinality** min: 1 max: 1 **Primitive Type** Token **Length** min: 1 max: 2 **External Category** Simple Data Element **Data Type** ID **Position** 01 **Codelist Id** 145 **Version Mode** Fixed
67 Identification Code	Code identifying a party or other code	**Cardinality** min: 1 max: 1 **Primitive Type** String **Length** min: 2 max: 80 **External Category** Simple Data Element **Data Type** AN **Position** 02

4.4 REF — Reference Identification

Structure

Node	Card.	Prim.Type	Pos.	Length	Codelists
213 — Motor Carrier Shipment Status Inquiry	1 .. 1				
├ **REF** — Reference Identification	1 .. 10		040		
│ ├ **128** — Reference Identification Qualifier	1 .. 1	Token	01	2 .. 3	128
│ └ **127** — Reference Identification	0 .. 1	String	02	1 .. 30	

Documentation

Definition To specify identifying information

Properties

Identifier REF

Name Reference Identification

Cardinality min: 1 max: 10

Syntax Type Related

External Category Segment

Position 040

Level 2

Notes

Usage 1 REF04 contains data relating to the value cited in REF02.

Constraint 1 R0203 Required - At least one of those noted must be used

Leaf Elements

Identifier/Name	Description/Notes/Code Values	Properties
128 Reference Identification Qualifier	Code qualifying the Reference Identification **Selected Values** **Code** 06 **Name** System Number **Code** 8X **Name** Transaction Category or Type **Code** CN **Name** Carrier's Reference Number (PRO/Invoice)	**Cardinality** min: 1 max: 1 **Primitive Type** Token **Length** min: 2 max: 3 **External Category** Simple Data Element **Data Type** ID **Position** 01 **Codelist Id** 128 **Type System** ASC_X12 **Version Mode** Current **Version** 004010
127 Reference Identification	Reference information as defined for a particular Transaction Set or as specified by the Reference Identification Qualifier	**Cardinality** min: 0 max: 1 **Primitive Type** String **Length** min: 1 max: 30 **External Category** Simple Data Element **Data Type** AN **Position** 02

4.5 0100 — Loop 0100

Structure

Node	Card.	Prim.Type	Pos.	Length	Codelists
213 — Motor Carrier Shipment Status Inquiry	1 .. 1				
├ **0100** — Loop 0100	0 .. 5		060		
│ ├ **N1** — Name	1 .. 1		060		
│ └ **REF** — Reference Identification	1 .. 10		100		

Properties

Identifier 0100

Name Loop 0100

Cardinality min: 0 max: 5

Syntax Type Related

External Category Loop

Position 060

Level 2