		Data Type xsd:string
D_337 Time	Time expressed in 24-hour clock time as follows: HHMM, or HHMMSS, or HHMMSSD, or HHMMSSDD, where H = hours (00-23), M = minutes (00-59), S = integer seconds (00-59) and DD = decimal seconds; decimal seconds are expressed as follows: D = tenths (0-9) and DD = hundredths (00-99)	**Cardinality** **min:** 1 **max:** 1 **Primitive Type** String **Length** **min:** 6 **max:** 6 **External Category** Element **Data Type** xsd:string
D_28 Group Control Number	Assigned number originated and maintained by the sender	**Cardinality** **min:** 1 **max:** 1 **Primitive Type** String **Length** **min:** 9 **max:** 9 **External Category** Element **Data Type** xsd:string
D_455 Responsible Agency Code	Code identifying the issuer of the standard; this code is used in conjunction with Data Element 480 **Selected Values** All Values in Codelist	**Cardinality** **min:** 1 **max:** 1 **Primitive Type** String **Length** **min:** 1 **max:** 1 **External Category** Element **Data Type** xsd:string **Codelist Id** D_455 **Type System** Customer_TS **Version Mode** Local **Version** 1.1
D_480 Version / Release / Industry Identifier Code	Code indicating the version, release, subrelease, and industry identifier of the EDI standard being used, including the GS and GE segments; if code in DE455 in GS segment is X, then in DE 480 positions 1-3 are the version number; positions 4-6 are the release and subrelease, level of the version; and positions 7-12 are the industry or trade association identifiers (optionally assigned by user); if code in DE455 in GS segment is T, then other formats are allowed **Selected Values** All Values in Codelist	**Cardinality** **min:** 1 **max:** 1 **Primitive Type** String **Length** **min:** 6 **max:** 6 **External Category** Element **Data Type** xsd:string **Codelist Id** D_480 **Type System** Customer_TS **Version Mode** Local **Version** 1.1

2.5 S_GE — Functional Group Trailer

Structure

Node	Card.	Prim.Type	Pos.	Length	Codelists
Interchange — Interchange Structure	1 .. 1				
├ **FunctionalGroup** — Functional Group	1 .. 1				
│ └ **S_GE** — Functional Group Trailer	1 .. 1				
│ ├ **D_97** — Number of Transaction Sets Included	1 .. 1	String		1 .. 1	
│ └ **D_28** — Group Control Number	1 .. 1	String		9 .. 9	

Documentation

Definition To indicate the end of a functional group and to provide control information Comments 1. The use of identical data interchange control numbers in the associated functional group header and trailer is designed to maximize functional group integrity. The control number is the same as that used in the corresponding header. Semantic Notes: 1. The data interchange control number GE02 in this trailer must be identical to the same data element in the associated functional group header, GS06.

Properties

Identifier S_GE

Name Functional Group Trailer

Cardinality min: 1 max: 1

Syntax Type Related

External Category Element

Leaf Elements

Identifier/Name	Description/Notes/Code Values	Properties
D_97 Number of Transaction Sets Included	Total number of transaction sets included in the functional group or interchange (transmission) group terminated by the trailer containing this data element	**Cardinality** min: 1 max: 1 **Primitive Type** String **Length** min: 1 max: 1 **External Category** Element **Data Type** xsd:string
D_28 Group Control Number	Assigned number originated and maintained by the sender	**Cardinality** min: 1 max: 1 **Primitive Type** String **Length** min: 9 max: 9 **External Category** Element **Data Type** xsd:string

2.6 S_IEA — Interchange Control Trailer

Structure

Node	Card.	Prim.Type	Pos.	Length	Codelists
Interchange — Interchange Structure	1 .. 1				
└ **S_IEA** — Interchange Control Trailer	1 .. 1				
├ **D_I16** — Number of Included Functional Groups	1 .. 1	String		1 .. 1	
└ **D_I12** — Interchange Control Number	1 .. 1	String		9 .. 9	

Documentation

Definition To define the end of an interchange of zero or more functional groups and interchange-related control segments

Properties

Identifier S_IEA

Name Interchange Control Trailer

Cardinality min: 1 max: 1

Syntax Type Related

External Category Element

Leaf Elements

Identifier/Name	Description/Notes/Code Values	Properties
D_I16 Number of Included Functional Groups	A count of the number of functional groups included in an interchange	**Cardinality** min: 1 max: 1 **Primitive Type** String **Length** min: 1 max: 1 **External Category** Element **Data Type** xsd:string
D_I12 Interchange Control Number	A control number assigned by the interchange sender	**Cardinality** min: 1 max: 1 **Primitive Type** String **Length** min: 9 max: 9 **External Category** Element **Data Type** xsd:string

3 OVERVIEW MESSAGE

General Information

Name	SAP_LBN_ANSI_X12_214
Direction	In
Status	Active
Message Type	Transportation Carrier Shipment Status Message
Type System	ASC_X12
Version	004010
External Category	Transaction Set

Documentation

Definition This Draft Standard for Trial Use contains the format and establishes the data contents of the Transportation Carrier Shipment Status Message Transaction Set (214) for use within the context of an Electronic Data Interchange (EDI) environment. This transaction set can be used by a transportation carrier to provide shippers, consignees, and their agents with the status of shipments in terms of dates, times, locations, route, identifying numbers, and conveyance. The structures shown in this document are reduced to the functionalities supported in the LBN.

Notes

Example 1

```
ISA*00*          *00*          *02*Carrier LBNID*01*Shipper
LBNID*211209*0759*U*00401*000006692*0*T*>~
GS*QM*Carrier LBNID*Shipper LBNID*20211209*075900*000006692*X*004010~
ST*214*66920001~
B10**Freightorder ID 1*MCUO~
L11*System ID*06~
LX*1~
AT7*SD*AF*CP**20211209*0759*UT~
L11*Container ID*OC~
L11*Location ID*LU~
L11*Location type*4L~
L11*Stop ID*QN~
SE*9*66920001~
ST*214*66920001~
B10**Freightorder ID 2*MCUO~
L11*System ID*06~
LX*2~
AT7*AF*BE***20211209*0759*LT~
AT7*SD*BC*X1**20211209*0850*LT~
AT7*X3*BE***20211209*1233*LT~
L11*Container ID*OC~
L11*Location ID*LU~
L11*Location type*4L~
L11*Stop ID*QN~
SE*11*66920001~
GE*2*000006692~
IEA*1*000006692~
```

3.1 Structure

The following table shows the complete structure.

Node	Card.	Prim.Type	Pos.	Length	Codelists
214 — Transportation Carrier Shipment Status Message	1 .. 1				
├ **ST** — Transaction Set Header	1 .. 1		010		
│ ├ **143** — Transaction Set Identifier Code	1 .. 1	Token	01	3 .. 3	143
│ └ **329** — Transaction Set Control Number	1 .. 1	String	02	4 .. 9	
├ **B10** — Beginning Segment for Transportation Carrier Shipment Status Message	1 .. 1		020		
│ ├ **145** — Shipment Identification Number	1 .. 1	String	02	1 .. 30	
│ └ **140** — Standard Carrier Alpha Code	1 .. 1	Token	03	2 .. 4	
├ **L11** — Business Instructions and Reference Number	1 .. 300		030		
│ ├ **127** — Reference Identification - System Number	1 .. 1	String	01	1 .. 30	
│ └ **128** — Reference Identification Qualifier	1 .. 1	Token	02	2 .. 3	128
├ **0200** — Loop 0200	1 .. 999999		130		
│ ├ **LX** — Assigned Number	1 .. 1		130		
│ │ └ **554** — Assigned Number	1 .. 1	Integer	01	1 .. 6	
│ ├ **0205** — Loop 0205	0 .. 10		140		
│ │ ├ **AT7** — Shipment Status Details	1 .. 1		140		
│ │ │ ├ **1650** — Shipment Status Code	1 .. 1	Token	01	2 .. 2	1650
│ │ │ ├ **1651** — Shipment Status or Appointment Reason Code	0 .. 1	Token	02	2 .. 2	1651
│ │ │ ├ **1652** — Shipment Appointment Status Code	0 .. 1	Token	03	2 .. 2	1652
│ │ │ ├ **373** — Date	1 .. 1	Date	05	8 .. 8	
│ │ │ ├ **337** — Time	1 .. 1	Time	06	4 .. 8	
│ │ │ └ **623** — Time Code	1 .. 1	Token	07	2 .. 2	623
│ │ └ **MS1** — Equipment, Shipment, or Real Property Location	0 .. 1		143		
│ │ ├ **19** — City Name	0 .. 1	String	01	2 .. 30	
│ │ ├ **156** — State or Province Code	0 .. 1	Token	02	2 .. 2	
│ │ ├ **26** — Country Code	0 .. 1	Token	03	2 .. 3	ISO_3166-1
│ │ ├ **1654** — Longitude Code	0 .. 1	Token	04	7 .. 7	
│ │ ├ **1655** — Latitude Code	0 .. 1	Token	05	7 .. 7	
│ │ ├ **1280** — Direction Identifier Code	0 .. 1	Token	06	1 .. 1	1280
│ │ └ **1280** — Direction Identifier Code	0 .. 1	Token	07	1 .. 1	1280
│ └ **L11** — Business Instructions and Reference Number	1 .. 10		150		
│ ├ **127** — Reference Identification - Location Number	0 .. 1	String	01	1 .. 30	
│ ├ **127** — Reference Identification - Location-specific Services Reference Number	0 .. 1	String	01	1 .. 30	
│ ├ **127** — Reference Identification - Stop Sequence Number	0 .. 1	String	01	1 .. 30	
│ └ **128** — Reference Identification Qualifier	1 .. 1	Token	02	2 .. 3	128
└ **SE** — Transaction Set Trailer	1 .. 1		610		
├ **96** — Number of Included Segments	1 .. 1	Integer	01	1 .. 10	
└ **329** — Transaction Set Control Number	1 .. 1	String	02	4 .. 9	

4 DETAILS MESSAGE

4.1 214 — Transportation Carrier Shipment Status Message

Structure

Node	Card.	Prim.Type	Pos.	Length	Codelists
214 — Transportation Carrier Shipment Status Message	1 .. 1				
├ **ST** — Transaction Set Header	1 .. 1		010		
├ **B10** — Beginning Segment for Transportation Carrier Shipment Status Message	1 .. 1		020		
├ **L11** — Business Instructions and Reference Number	1 .. 300		030		
├ **0200** — Loop 0200	1 .. 999999		130		
└ **SE** — Transaction Set Trailer	1 .. 1		610		

Properties

Identifier 214

Name Transportation Carrier Shipment Status Message

Cardinality min: 1 max: 1

4.2 ST — Transaction Set Header

Structure

Node	Card.	Prim.Type	Pos.	Length	Codelists
214 — Transportation Carrier Shipment Status Message	1 .. 1				
├ **ST** — Transaction Set Header	1 .. 1		010		
│ ├ **143** — Transaction Set Identifier Code	1 .. 1	Token	01	3 .. 3	143
│ └ **329** — Transaction Set Control Number	1 .. 1	String	02	4 .. 9	

Documentation

Definition To indicate the start of a transaction set and to assign a control number

Properties

Identifier ST

Name Transaction Set Header

Cardinality min: 1 max: 1

Syntax Type Related

External Category Segment

Position 010

Level 2

Notes

Leaf Elements

Identifier/Name	Description/Notes/Code Values	Properties
143 Transaction Set Identifier Code	Code uniquely identifying a Transaction Set **Selected Values** **Code** 214 **Name** Transportation Carrier Shipment Status Message	**Cardinality** min: 1 max: 1 **Primitive Type** Token **Length** min: 3 max: 3 **External Category** Simple Data Element **Data Type** ID **Position** 01 **Fixed Value** 214 **Codelist Id** 143 **Type System** ASC_X12 **Version Mode** Current **Version** 004010
329 Transaction Set Control Number	Identifying control number that must be unique within the transaction set functional group assigned by the originator for a transaction set	**Cardinality** min: 1 max: 1 **Primitive Type** String **Length** min: 4 max: 9 **External Category** Simple Data Element **Data Type** AN **Position** 02

4.3 B10 — Beginning Segment for Transportation Carrier Shipment Status Message

Structure

Node	Card.	Prim.Type	Pos.	Length	Codelists
214 — Transportation Carrier Shipment Status Message	1 .. 1				
├ **B10** — Beginning Segment for Transportation Carrier Shipment Status Message	1 .. 1		020		
│ ├ **145** — Shipment Identification Number	1 .. 1	String	02	1 .. 30	
│ └ **140** — Standard Carrier Alpha Code	1 .. 1	Token	03	2 .. 4	

Documentation

Definition To transmit identifying numbers and other basic data relating to the transaction set

Properties

Identifier B10

Name Beginning Segment for Transportation Carrier Shipment Status Message

Cardinality min: 1 max: 1

Syntax Type Related

External Category Segment

Position 020

Level 2

Notes

Leaf Elements

Identifier/Name	Description/Notes/Code Values	Properties
145 Shipment Identification Number	Identification number assigned to the shipment by the shipper that uniquely identifies the shipment from origin to ultimate destination and is not subject to modification; (Does not contain blanks or special characters)	**Cardinality** min: 1 max: 1 **Primitive Type** String **Length** min: 1 max: 30 **External Category** Simple Data Element **Data Type** AN **Position** 02
140 Standard Carrier Alpha Code	Standard Carrier Alpha Code (SCAC) **Comment 1** Not used in LBN	**Cardinality** min: 1 max: 1 **Primitive Type** Token **Length** min: 2 max: 4 **External Category** Simple Data Element **Data Type** ID **Position** 03

4.4 L11 — Business Instructions and Reference Number

Structure

Node	Card.	Prim.Type	Pos.	Length	Codelists
214 — Transportation Carrier Shipment Status Message	1 .. 1				
├ **L11** — Business Instructions and Reference Number	1 .. 300		030		
│ ├ **127** — Reference Identification - System Number	1 .. 1	String	01	1 .. 30	
│ └ **128** — Reference Identification Qualifier	1 .. 1	Token	02	2 .. 3	128

Documentation

Definition To specify instructions in this business relationship or a reference number

Properties

Identifier L11

Name Business Instructions and Reference Number

Cardinality min: 1 max: 300

Syntax Type Related

External Category Segment

Position 030

Level 2

Notes

Leaf Elements

Identifier/Name	Description/Notes/Code Values	Properties
127 [128 = "06"] Reference Identification - System Number	Reference information as defined for a particular Transaction Set or as specified by the Reference Identification Qualifier **Usage 1** The System of the sender.	**Cardinality** min: 1 max: 1 **Primitive Type** String **Length** min: 1 max: 30 **External Category** Simple Data Element **Data Type** AN **Position** 01
128 Reference Identification Qualifier	Code qualifying the Reference Identification **Selected Values** **Code** 06 **Name** System Number **Code** T7 **Name** Affected Subsystem Code **Code** 8X **Name** Transaction Category or Type	**Cardinality** min: 1 max: 1 **Primitive Type** Token **Length** min: 2 max: 3 **External Category** Simple Data Element **Data Type** ID **Position** 02 **Codelist Id** 128 **Type System** ASC_X12 **Version Mode** Current **Version** 004010

4.5 0200 — Loop 0200

Structure

Node	Card.	Prim.Type	Pos.	Length	Codelists
214 — Transportation Carrier Shipment Status Message	1 .. 1				
├ **0200** — Loop 0200	1 .. 999999		130		
│ ├ **LX** — Assigned Number	1 .. 1		130		
│ ├ **0205** — Loop 0205	0 .. 10		140		
│ └ **L11** — Business Instructions and Reference Number	1 .. 10		150		

Properties

Identifier 0200

Name Loop 0200

Cardinality min: 1 max: 999999

Syntax Type Related

External Category Loop

Position 130

Level 2