		Length min: 8 max: 8 **External Category** Element **Data Type** xsd:string
D_337 Time	Time expressed in 24-hour clock time as follows: HHMM, or HHMMSS, or HHMMSSD, or HHMMSSDD, where H = hours (00-23), M = minutes (00-59), S = integer seconds (00-59) and DD = decimal seconds; decimal seconds are expressed as follows: D = tenths (0-9) and DD = hundredths (00-99)	**Cardinality** min: 1 max: 1 **Primitive Type** String **Length** min: 6 max: 6 **External Category** Element **Data Type** xsd:string
D_28 Group Control Number	Assigned number originated and maintained by the sender	**Cardinality** min: 1 max: 1 **Primitive Type** String **Length** min: 9 max: 9 **External Category** Element **Data Type** xsd:string
D_455 Responsible Agency Code	Code identifying the issuer of the standard; this code is used in conjunction with Data Element 480 **Selected Values** All Values in Codelist	**Cardinality** min: 1 max: 1 **Primitive Type** String **Length** min: 1 max: 1 **External Category** Element **Data Type** xsd:string **Codelist Id** D_455 **Type System** Customer_TS **Version Mode** Local **Version** 1.1
D_480 Version / Release / Industry Identifier Code	Code indicating the version, release, subrelease, and industry identifier of the EDI standard being used, including the GS and GE segments; if code in DE455 in GS segment is X, then in DE 480 positions 1-3 are the version number; positions 4-6 are the release and subrelease, level of the version; and positions 7-12 are the industry or trade association identifiers (optionally assigned by user); if code in DE455 in GS segment is T, then other formats are allowed **Selected Values** All Values in Codelist	**Cardinality** min: 1 max: 1 **Primitive Type** String **Length** min: 6 max: 6 **External Category** Element **Data Type** xsd:string **Codelist Id** D_480 **Type System** Customer_TS **Version Mode** Local **Version** 1.1

2.5 S_GE — Functional Group Trailer

Structure

Node	Card.	Prim.Type	Pos.	Length	Codelists
Interchange — Interchange Structure	1 .. 1				
├ **FunctionalGroup** — Functional Group	1 .. 1				
│ └ **S_GE** — Functional Group Trailer	1 .. 1				
│ ├ **D_97** — Number of Transaction Sets Included	1 .. 1	String		1 .. 1	
│ └ **D_28** — Group Control Number	1 .. 1	String		9 .. 9	

Documentation

Definition To indicate the end of a functional group and to provide control information Comments 1. The use of identical data interchange control numbers in the associated functional group header and trailer is designed to maximize functional group integrity. The control number is the same as that used in the corresponding header. Semantic Notes: 1. The data interchange control number GE02 in this trailer must be identical to the same data element in the associated functional group header, GS06.

Properties

Tag S_GE

Name Functional Group Trailer

Cardinality min: 1 max: 1

Syntax Type Related

External Category Element

Leaf Elements

Tag/Name	Description/Notes/Code Values	Properties
D_97 Number of Transaction Sets Included	Total number of transaction sets included in the functional group or interchange (transmission) group terminated by the trailer containing this data element	**Cardinality** min: 1 max: 1 **Primitive Type** String **Length** min: 1 max: 1 **External Category** Element **Data Type** xsd:string
D_28 Group Control Number	Assigned number originated and maintained by the sender	**Cardinality** min: 1 max: 1 **Primitive Type** String **Length** min: 9 max: 9 **External Category** Element **Data Type** xsd:string

2.6 S_IEA — Interchange Control Trailer

Structure

Node	Card.	Prim.Type	Pos.	Length	Codelists
Interchange — Interchange Structure	1 .. 1				
└ **S_IEA** — Interchange Control Trailer	1 .. 1				
├ **D_I16** — Number of Included Functional Groups	1 .. 1	String		1 .. 1	
└ **D_I12** — Interchange Control Number	1 .. 1	String		9 .. 9	

Documentation

Definition To define the end of an interchange of zero or more functional groups and interchange-related control segments

Properties

Tag S_IEA

Name Interchange Control Trailer

Cardinality min: 1 max: 1

Syntax Type Related

External Category Element

Leaf Elements

Tag/Name	Description/Notes/Code Values	Properties
D_I16 Number of Included Functional Groups	A count of the number of functional groups included in an interchange	**Cardinality** min: 1 max: 1 **Primitive Type** String **Length** min: 1 max: 1 **External Category** Element **Data Type** xsd:string
D_I12 Interchange Control Number	A control number assigned by the interchange sender	**Cardinality** min: 1 max: 1 **Primitive Type** String **Length** min: 9 max: 9 **External Category** Element **Data Type** xsd:string

3 OVERVIEW MESSAGE

General Information

Name	SAP_LBN_ANSI_X12_300
Direction	Out
Status	Active
Message Type	Reservation (Booking Request) (Ocean)
Type System	ASC_X12
Version	004010
External Category	Transaction Set

Documentation

Definition This Draft Standard for Trial Use contains the format and establishes the data contents of the Reservation (Booking Request) (Ocean) Transaction Set (300) for use within the context of an Electronic Data Interchange (EDI) environment. The transaction set can be used by a shipper or a forwarder to reserve space, containers and equipment for transport by ocean vessel.

Notes

Usage 1

```
ISA*00*          *00*          *ZZ*10000034       *ZZ*10010003085
*230322*1330*U*00401*000000453*0*P*>~
GS*RO*10000034*10010003085*20230322*133005*000000453*X*004010~
ST*300*0001~
B1**BookingID**U~
Y1****S****DD~
Y2*1***20G0~
N9*06*QW9_170~
N9*TN*BookingID~
N9*EV*InternalID~
N1*OB*10000034**LBNE2EPO1~
N3*ABCStreet 1~
N4*DEFCity**68723*DE~
G61*FQ*Test Purchase Org. 1*TE*+49 06578 1234~
R4*L*OR*1*LBN-SD-BLR*IN~
DTM*369*20230309*2030*UT~
R4*E*DE*2*LBN-SD-MUM*IN~
DTM*371*20230221*1830*UT~
R4*A*KL*3*LBN-SD-MUM*IN~
R4*D*PD*4*LBN-SD-BLR*IN~
DTM*371*20230221*1830*UT~
R4*A*KL*5*LBN-SD-BLR*IN~
DTM*369*20230313*1830*UT~
R4*D*PD*6*LBN-SD-DL*IN~
DTM*371*20230315*1830*UT~
LX*2~
N7**1000010*******S**********20G0~
W09*CN*-1*CE*5*CE~
L0*2*******1~
H1*1095*4**DGItemId: 20; Text 1111~
H1*1090*3**DGItemId: 10; Text 2222~
V1****VESSEL_INFO*****S~
SE*29*0001~
GE*1*000000453~
IEA*1*000000453~
```

3.1 Structure

The following table shows only the root element and the group elements.

Node	Card.	Prim.Type	Pos.	Length	Codelists
300 — Reservation (Booking Request) (Ocean)	1 .. 1				
├ **ST** — Transaction Set Header - Reservation (Booking Request) (Ocean)	1 .. 1		010		
├ **B1** — Beginning Segment for Booking or Pick-up/Delivery	1 .. 1		020		
├ **Y1** — Space Reservation Request	1 .. 1		050		
├ **Y2** — Loop Y2	0 .. 10		060		
│ └ **Y2** — Container Details	1 .. 1		060		
├ **N9** — Reference Identification - System Number or Others	0 .. 100		069		
├ **N1** — Loop N1	1 .. 10		080		
│ ├ **N1** — Name - Consignee or Others	1 .. 1		080		
│ ├ **N3** — Address Information	0 .. 2		100		
│ ├ **N4** — Geographic Location	0 .. 1		110		
│ └ **G61** — Contact	0 .. 3		120		
├ **R4** — Loop R4	1 .. 20		130		
│ ├ **R4** — Port or Terminal	1 .. 1		130		
│ └ **DTM** — Date/Time Reference - Estimated Departure Date or Others	0 .. 1		140		
├ **LX** — Loop LX	1 .. 999		010		
│ ├ **LX** — Assigned Number	1 .. 1		010		
│ ├ **N7** — Equipment Details	0 .. 1		020		
│ ├ **W09** — Equipment and Temperature	0 .. 1		021		
│ ├ **L0** — Line Item - Quantity and Weight	0 .. 1		040		
│ ├ **L4** — Measurement	0 .. 1		060		
│ └ **H1** — Loop H1	0 .. 10		070		
│ └ **H1** — Hazardous Material	1 .. 1		070		
├ **V1** — Vessel Identification	0 .. 2		090		
└ **SE** — Transaction Set Trailer	1 .. 1		010		

4 DETAILS MESSAGE

4.1 300 — Reservation (Booking Request) (Ocean)

Structure

Node	Card.	Prim.Type	Pos.	Length	Codelists
300 — Reservation (Booking Request) (Ocean)	1 .. 1				
├ **ST** — Transaction Set Header - Reservation (Booking Request) (Ocean)	1 .. 1		010		
├ **B1** — Beginning Segment for Booking or Pick-up/Delivery	1 .. 1		020		
├ **Y1** — Space Reservation Request	1 .. 1		050		
├ **Y2** — Loop Y2	0 .. 10		060		
├ **N9** — Reference Identification - System Number or Others	0 .. 100		069		
├ **N1** — Loop N1	1 .. 10		080		
├ **R4** — Loop R4	1 .. 20		130		
├ **LX** — Loop LX	1 .. 999		010		
├ **V1** — Vessel Identification	0 .. 2		090		
└ **SE** — Transaction Set Trailer	1 .. 1		010		

Properties

Identifier 300

Name Reservation (Booking Request) (Ocean)

Cardinality min: 1 max: 1

4.2 ST [143 = “300”] — Transaction Set Header - Reservation (Booking Request) (Ocean)

Structure

Node	Card.	Prim.Type	Pos.	Length	Codelists
300 — Reservation (Booking Request) (Ocean)	1 .. 1				
├ **ST** — Transaction Set Header - Reservation (Booking Request) (Ocean)	1 .. 1		010		
│ ├ **143** — Transaction Set Identifier Code	1 .. 1	Token	01	3 .. 3	143
│ └ **329** — Transaction Set Control Number	1 .. 1	String	02	4 .. 9	

Documentation

Definition To indicate the start of a transaction set and to assign a control number

Properties

Identifier ST

Name Transaction Set Header - Reservation (Booking Request) (Ocean)

Cardinality min: 1 max: 1

Syntax Type Related

External Category Segment

Position 010

Level 2

Notes

Usage 1 The transaction set identifier (ST01) used by the translation routines of the interchange partners to select the appropriate transaction set definition (e.g., 810 selects the Invoice Transaction Set).

Leaf Elements

Identifier/Name	Description/Notes/Code Values	Properties
143 Transaction Set Identifier Code	Code uniquely identifying a Transaction Set **Selected Values** **Code** 300 **Name** Reservation (Booking Request) (Ocean)	**Cardinality** min: 1 max: 1 **Primitive Type** Token **Length** min: 3 max: 3 **External Category** Simple Data Element **Data Type** ID **Position** 01 **Codelist Id** 143 **Type System** ASC_X12 **Version Mode** Current **Version** 004010
329 Transaction Set Control Number	Identifying control number that must be unique within the transaction set functional group assigned by the originator for a transaction set	**Cardinality** min: 1 max: 1 **Primitive Type** String **Length** min: 4 max: 9 **External Category** Simple Data Element **Data Type** AN **Position** 02

4.3 B1 — Beginning Segment for Booking or Pick-up/Delivery

Structure

Node	Card.	Prim.Type	Pos.	Length	Codelists
300 — Reservation (Booking Request) (Ocean)	1 .. 1				
├ **B1** — Beginning Segment for Booking or Pick-up/Delivery	1 .. 1		020		
│ ├ **140** — Standard Carrier Alpha Code	0 .. 1	Token	01	2 .. 4	
│ ├ **145** — Shipment Identification Number	1 .. 1	String	02	1 .. 30	
│ └ **558** — Reservation Action Code	0 .. 1	Token	04	1 .. 1	558

Documentation

Definition To transmit identifying numbers, dates, and other basic data relating to the transaction set

Properties

Identifier B1

Name Beginning Segment for Booking or Pick-up/Delivery

Cardinality min: 1 max: 1

Syntax Type Related

External Category Segment

Position 020

Level 2

Notes

Usage 1 B101 is the Standard Carrier Alpha Code (SCAC) of the carrier sending the EDI transmission.

Usage 2 B103 is the booking date accepted by the carrier.

Leaf Elements

Identifier/Name	Description/Notes/Code Values	Properties
140 Standard Carrier Alpha Code	Standard Carrier Alpha Code	**Cardinality** min: 0 max: 1 **Primitive Type** Token **Length** min: 2 max: 4 **External Category** Simple Data Element **Data Type** ID **Position** 01
145 Shipment Identification Number	Identification number assigned to the shipment by the shipper that uniquely identifies the shipment from origin to ultimate destination and is not subject to modification; (Does not contain blanks or special characters)	**Cardinality** min: 1 max: 1 **Primitive Type** String **Length** min: 1 max: 30 **External Category** Simple Data Element **Data Type** AN **Position** 02
558 Reservation Action Code	Code identifying action on reservation or offering **Selected Values** **Code** N **Name** New **Code** U **Name** Change	**Cardinality** min: 0 max: 1 **Primitive Type** Token **Length** min: 1 max: 1 **External Category** Simple Data Element **Data Type** ID **Position** 04 **Codelist Id** 558 **Type System** ASC_X12 **Version Mode** Current **Version** 004010

4.4 Y1 — Space Reservation Request

Structure

Node	Card.	Prim.Type	Pos.	Length	Codelists
300 — Reservation (Booking Request) (Ocean)	1 .. 1				
├ **Y1** — Space Reservation Request	1 .. 1		050		
│ ├ **135** — Sailing/Flight Date Estimated	0 .. 1	Date	01	8 .. 8	
│ ├ **91** — Transportation Method/Type Code	0 .. 1	Token	04	1 .. 2	91
│ ├ **375** — Tariff Service Code	0 .. 1	Token	08	2 .. 2	375
│ └ **374** — Date/Time Qualifier	0 .. 1	Token	09	3 .. 3	374

Documentation

Definition To specify information used to make a reservation for space on an ocean vessel

Properties

Identifier Y1

Name Space Reservation Request

Cardinality min: 1 max: 1

Syntax Type Related

External Category Segment

Position 050

Level 2

Notes

Usage 1 Y102 is the date the shipment for which space reservation is requested to be available at the origin.

Constraint 1 P0209 Paired Multiple - If any are used, all must be used

Leaf Elements

Identifier/Name	Description/Notes/Code Values	Properties
135 Sailing/Flight Date Estimated	Date for reservation expressed in format CCYYMMDD **Usage 1** Expected time zone is UTC.	**Cardinality** min: 0 max: 1 **Primitive Type** Date **Length** min: 8 max: 8 **Date Time Format** CCYYMMDD **External Category** Simple Data Element **Data Type** DT **Position** 01
91 Transportation Method/Type Code	Code specifying the method or type of transportation for the shipment **Selected Values** **Code** S **Name** Ocean	**Cardinality** min: 0 max: 1 **Primitive Type** Token **Length** min: 1 max: 2 **External Category** Simple Data Element **Data Type** ID **Position** 04 **Codelist Id** 91 **Type System** ASC_X12 **Version Mode** Current **Version** 004010
375 Tariff Service Code	Code specifying the types of services for rating purposes **Selected Values** **Code** DD **Name** Door-to-Door Rate applies for shipments in door-to-door service **Code** DP **Name** Door-to-Pier Rate applies for shipments in	**Cardinality** min: 0 max: 1 **Primitive Type** Token **Length** min: 2 max: 2 **External Category** Simple Data Element **Data Type** ID **Position** 08 **Codelist Id** 375 **Type System** ASC_X12

	door-to-ocean carrier's port/terminal pier service **Code** PD **Name** Pier-to-Door Rate applies for shipments in pier-to-door service **Code** PP **Name** Pier-to-Pier All cargo other than that specified in codes HH, HP, or PH whether shipped in containers or otherwise	**Version Mode** Current **Version** 004010
374 Date/Time Qualifier	Code specifying type of date or time, or both date and time **Selected Values** **Code** 369 **Name** Estimated Departure Date **Code** 371 **Name** Estimated Arrival Date	**Cardinality** **min:** 0 **max:** 1 **Primitive Type** Token **Length** **min:** 3 **max:** 3 **External Category** Simple Data Element **Data Type** ID **Position** 09 **Codelist Id** 374 **Type System** ASC_X12 **Version Mode** Current **Version** 004010