4.5 Y2 — Loop Y2

Structure

Node	Card.	Prim.Type	Pos.	Length	Codelists
300 — Reservation (Booking Request) (Ocean)	1 .. 1				
├ **Y2** — Loop Y2	0 .. 10		060		
│ └ **Y2** — Container Details	1 .. 1		060		

Properties

Identifier Y2

Name Loop Y2

Cardinality min: 0 max: 10

Syntax Type Related

External Category Loop

Position 060

Level 2

4.6 Y2 — Container Details

Structure

Node	Card.	Prim.Type	Pos.	Length	Codelists
300 — Reservation (Booking Request) (Ocean)	1 .. 1				
├ **Y2** — Loop Y2	0 .. 10		060		
│ └ **Y2** — Container Details	1 .. 1		060		
│ ├ **95** — Number of Containers	1 .. 1	Integer	01	1 .. 4	
│ └ **24** — Equipment Type	1 .. 1	Token	04	4 .. 4	

Documentation

Definition To specify container information and transportation service to be used

Properties

Identifier Y2

Name Container Details

Cardinality min: 1 max: 1

Syntax Type Related

External Category Segment

Position 060

Level 3

Leaf Elements

Identifier/Name	Description/Notes/Code Values	Properties
95 Number of Containers	Number of shipping containers	**Cardinality** min: 1 max: 1 **Primitive Type** Integer **Length** min: 1 max: 4 **Fraction Digits** 0 **Total Digits** 4 **External Category** Simple Data Element **Data Type** N0 **Position** 01
24 Equipment Type	Code identifying equipment type	**Cardinality** min: 1 max: 1 **Primitive Type** Token **Length** min: 4 max: 4 **External Category** Simple Data Element **Data Type** ID **Position** 04

4.7 N9 [128 = “06” | “EV” | “TN”] — Reference Identification - System Number or Others

Structure

Node	Card.	Prim.Type	Pos.	Length	Codelists
300 — Reservation (Booking Request) (Ocean)	1 .. 1				
├ **N9** — Reference Identification - System Number or Others	0 .. 100		069		
│ ├ **128** — Reference Identification Qualifier	1 .. 1	Token	01	2 .. 3	128
│ └ **127** — Reference Identification	0 .. 1	String	02	1 .. 30	

Documentation

Definition To transmit identifying information as specified by the Reference Identification Qualifier

Properties

Identifier N9

Name Reference Identification - System Number or Others

Cardinality min: 0 max: 100

Qualification

Qualified By	Qualifying values	
	Code	Description
./128	06	System Number
	EV	Receiver Identification Number
	TN	Transaction Reference Number

Syntax Type Related

External Category Segment

Position 069

Level 2

Notes

Usage 1 N906 reflects the time zone which the time reflects.

Usage 2 N907 contains data relating to the value cited in N902.

Usage 3 If N901 is “EV”, N902 contains an internal-ID used to identify the technical document. The same fields with same values are expected in the corresponding 301 message.

Constraint 1 R0203 Required - At least one of those noted must be used

Constraint 2 C0605 Conditional - If the first element is present, then the others must be present

Leaf Elements

Identifier/Name	Description/Notes/Code Values	Properties
128 Reference Identification Qualifier	Code qualifying the Reference Identification **Selected Values** **Code** 06 **Name** System Number **Code** EV **Name** Receiver Identification Number A unique number identifying the organization/site location designated to receive the current transmitted transaction set **Code** TN **Name** Transaction Reference Number	**Cardinality** min: 1 max: 1 **Primitive Type** Token **Length** min: 2 max: 3 **External Category** Simple Data Element **Data Type** ID **Position** 01 **Codelist Id** 128 **Type System** ASC_X12 **Version Mode** Current **Version** 004010
127 Reference Identification	Reference information as defined for a particular Transaction Set or as specified by the Reference	**Cardinality** min: 0 max: 1 **Primitive Type** String

	Identification Qualifier	**Length** **min:** 1 **max:** 30 **External Category** Simple Data Element **Data Type** AN **Position** 02

4.8 N1 — Loop N1

Structure

Node	Card.	Prim.Type	Pos.	Length	Codelists
300 — Reservation (Booking Request) (Ocean)	1 .. 1				
├ **N1** — Loop N1	1 .. 10		080		
│ ├ **N1** — Name - Consignee or Others	1 .. 1		080		
│ ├ **N3** — Address Information	0 .. 2		100		
│ ├ **N4** — Geographic Location	0 .. 1		110		
│ └ **G61** — Contact	0 .. 3		120		

Properties

Identifier N1

Name Loop N1

Cardinality min: 1 max: 10

Syntax Type Related

External Category Loop

Position 080

Level 2

4.9 N1 [98 = “CN” | “OB” | “SH”] — Name - Consignee or Others

Structure

Node	Card.	Prim.Type	Pos.	Length	Codelists
300 — Reservation (Booking Request) (Ocean)	1 .. 1				
├ **N1** — Loop N1	1 .. 10		080		
│ ├ **N1** — Name - Consignee or Others	1 .. 1		080		
│ │ ├ **98** — Entity Identifier Code	1 .. 1	Token	01	2 .. 3	98
│ │ ├ **93** — Name	0 .. 1	String	02	1 .. 60	
│ │ ├ **66** — Identification Code Qualifier	0 .. 1	Token	03	1 .. 2	66
│ │ └ **67** — Identification Code - D-U-N-S Number, Dun & Bradstreet or Others	0 .. 1	String	04	2 .. 80	

Documentation

Definition To identify a party by type of organization, name, and code

Properties

Identifier N1

Name Name - Consignee or Others

Cardinality min: 1 max: 1

Qualification

Qualified By	Qualifying values	
	Code	**Description**
./98	CN	Consignee
	OB	Ordered By
	SH	Shipper

Syntax Type Related

External Category Segment

Position 080

Level 3

Notes

Constraint 1 R0203 Required - At least one of those noted must be used

Constraint 2 P0304 Paired Multiple - If any are used, all must be used

Comment 1 This segment, used alone, provides the most efficient method of providing organizational identification. To obtain this efficiency the “ID Code” (N104) must provide a key to the table maintained by the transaction processing party.

Comment 2 N105 and N106 further define the type of entity in N101.

Leaf Elements

Identifier/Name	Description/Notes/Code Values	Properties
98 Entity Identifier Code	Code identifying an organizational entity, a physical location, property or an individual **Selected Values** **Code** CN **Name** Consignee **Code** OB **Name** Ordered By **Code** SH **Name** Shipper	**Cardinality** min: 1 max: 1 **Primitive Type** Token **Length** min: 2 max: 3 **External Category** Simple Data Element **Data Type** ID **Position** 01 **Codelist Id** 98 **Type System** ASC_X12 **Version Mode** Current **Version** 004010

93 Name	Free-form name	**Cardinality** **min:** 0 **max:** 1 **Primitive Type** String **Length** **min:** 1 **max:** 60 **External Category** Simple Data Element **Data Type** AN **Position** 02
66 Identification Code Qualifier	Code designating the system/method of code structure used for Identification Code (67) **Selected Values** **Code** 1 **Name** D-U-N-S Number, Dun & Bradstreet **Code** 2 **Name** Standard Carrier Alpha Code (SCAC) **Code** 4 **Name** International Air Transport Association (IATA) **Code** 8 **Name** UCC/EAN Global Product Identification Prefix The first part of a UCC/EAN Product Identification Code within the Uniform Code Council (UCC) and International Article Number Association (EAN) numbering system; A globally unique 3 to 10 digit code for the identification of the company assigning the remainder of the ID code, such as U.P.C., EAN-13, SCC-14, EAN-14 or SSCC-18	**Cardinality** **min:** 0 **max:** 1 **Primitive Type** Token **Length** **min:** 1 **max:** 2 **External Category** Simple Data Element **Data Type** ID **Position** 03 **Codelist Id** 66 **Type System** ASC_X12 **Version Mode** Current **Version** 004010
67 [66 = “1” | “2” | “4” | “8”] Identification Code - D-U-N-S Number, Dun & Bradstreet or Others	Code identifying a party or other code	**Cardinality** **min:** 0 **max:** 1 **Primitive Type** String **Length** **min:** 2 **max:** 80 **External Category** Simple Data Element **Data Type** AN **Position** 04

4.10 N3 — Address Information

Structure

Node	Card.	Prim.Type	Pos.	Length	Codelists
300 — Reservation (Booking Request) (Ocean)	1 .. 1				
├ **N1** — Loop N1	1 .. 10		080		
│ ├ **N3** — Address Information	0 .. 2		100		
│ │ └ **166** — Address Information	1 .. 1	String	01	1 .. 55	

Documentation

Definition To specify the location of the named party

Properties

Identifier N3

Name Address Information

Cardinality min: 0 max: 2

Syntax Type Related

External Category Segment

Position 100

Level 3

Leaf Elements

Identifier/Name	Description/Notes/Code Values	Properties
166 Address Information	Address information	**Cardinality** **min:** 1 **max:** 1 **Primitive Type** String **Length** **min:** 1 **max:** 55 **External Category** Simple Data Element **Data Type** AN **Position** 01

4.11 N4 — Geographic Location

Structure

Node	Card.	Prim.Type	Pos.	Length	Codelists
300 — Reservation (Booking Request) (Ocean)	1 .. 1				
├ **N1** — Loop N1	1 .. 10		080		
│ ├ **N4** — Geographic Location	0 .. 1		110		
│ │ ├ **19** — City Name	0 .. 1	String	01	2 .. 30	
│ │ ├ **156** — State or Province Code	0 .. 1	Token	02	2 .. 2	
│ │ ├ **116** — Postal Code	0 .. 1	Token	03	3 .. 15	
│ │ └ **26** — Country Code	0 .. 1	Token	04	2 .. 3	ISO_3166-1

Documentation

Definition To specify the geographic place of the named party

Properties

Identifier N4

Name Geographic Location

Cardinality min: 0 max: 1

Syntax Type Related

External Category Segment

Position 110

Level 3

Notes

Constraint 1 C0605 Conditional - If the first element is present, then the others must be present

Comment 1 A combination of either N401 through N404, or N405 and N406 may be adequate to specify a location.

Comment 2 N402 is required only if city name (N401) is in the U.S. or Canada.

Leaf Elements

Identifier/Name	Description/Notes/Code Values	Properties
19 City Name	Free-form text for city name	**Cardinality** min: 0 max: 1 **Primitive Type** String **Length** min: 2 max: 30 **External Category** Simple Data Element **Data Type** AN **Position** 01
156 State or Province Code	Code (Standard State/Province) as defined by appropriate government agency	**Cardinality** min: 0 max: 1 **Primitive Type** Token **Length** min: 2 max: 2 **External Category** Simple Data Element **Data Type** ID **Position** 02
116 Postal Code	Code defining international postal zone code excluding punctuation and blanks (zip code for United States)	**Cardinality** min: 0 max: 1 **Primitive Type** Token **Length** min: 3 max: 15 **External Category** Simple Data Element **Data Type** ID **Position** 03
26 Country Code	Code identifying the country **Selected Values** All Values in Codelist	**Cardinality** min: 0 max: 1 **Primitive Type** Token **Length** min: 2 max: 3 **External Category** Simple Data Element **Data Type** ID **Position** 04

		Codelist Id ISO_3166-1 **Type System** ISO_CodelistsAndSchemes **Version Mode** Latest **Version** 2013