4.12 G61 — Contact

Structure

Node	Card.	Prim.Type	Pos.	Length	Codelists
300 — Reservation (Booking Request) (Ocean)	1 .. 1				
├ **N1** — Loop N1	1 .. 10		080		
│ └ **G61** — Contact	0 .. 3		120		
│ ├ **366** — Contact Function Code	1 .. 1	Token	01	2 .. 2	366
│ ├ **93** — Name	1 .. 1	String	02	1 .. 60	
│ ├ **365** — Communication Number Qualifier	0 .. 1	Token	03	2 .. 2	365
│ └ **364** — Communication Number - Electronic Mail or Others	0 .. 1	String	04	1 .. 80	

Documentation

Definition To identify a person or office to whom communications should be directed

Properties

Identifier G61

Name Contact

Cardinality min: 0 max: 3

Syntax Type Related

External Category Segment

Position 120

Level 3

Notes

Constraint 1 P0304 Paired Multiple - If any are used, all must be used

Comment 1 G6103 qualifies G6104.

Leaf Elements

Identifier/Name	Description/Notes/Code Values	Properties
366 Contact Function Code	Code identifying the major duty or responsibility of the person or group named **Selected Values** **Code** FQ **Name** Staff	**Cardinality** min: 1 max: 1 **Primitive Type** Token **Length** min: 2 max: 2 **External Category** Simple Data Element **Data Type** ID **Position** 01 **Codelist Id** 366 **Type System** ASC_X12 **Version Mode** Current **Version** 004010
93 Name	Free-form name	**Cardinality** min: 1 max: 1 **Primitive Type** String **Length** min: 1 max: 60 **External Category** Simple Data Element **Data Type** AN **Position** 02
365 Communication Number Qualifier	Code identifying the type of communication number **Selected Values** **Code** EM **Name** Electronic Mail **Code** FX **Name** Facsimile **Code** TE **Name** Telephone **Code** WC **Name** Work Cellular	**Cardinality** min: 0 max: 1 **Primitive Type** Token **Length** min: 2 max: 2 **External Category** Simple Data Element **Data Type** ID **Position** 03 **Codelist Id** 365

		Type System ASC_X12 **Version Mode** Current **Version** 004010
364 [365 = “EM” | “FX” | “TE” | “WC”] Communication Number - Electronic Mail or Others	Complete communications number including country or area code when applicable	**Cardinality** **min:** 0 **max:** 1 **Primitive Type** String **Length** **min:** 1 **max:** 80 **External Category** Simple Data Element **Data Type** AN **Position** 04

4.13 R4 — Loop R4

Structure

Node	Card.	Prim.Type	Pos.	Length	Codelists
300 — Reservation (Booking Request) (Ocean)	1 .. 1				
├ **R4** — Loop R4	1 .. 20		130		
│ ├ **R4** — Port or Terminal	1 .. 1		130		
│ └ **DTM** — Date/Time Reference - Estimated Departure Date or Others	0 .. 1		140		

Properties

Identifier R4

Name Loop R4

Cardinality min: 1 max: 20

Syntax Type Related

External Category Loop

Position 130

Level 2

4.14 R4 — Port or Terminal

Structure

Node	Card.	Prim.Type	Pos.	Length	Codelists
300 — Reservation (Booking Request) (Ocean)	1 .. 1				
├ **R4** — Loop R4	1 .. 20		130		
│ ├ **R4** — Port or Terminal	1 .. 1		130		
│ │ ├ **115** — Port or Terminal Function Code	1 .. 1	Token	01	1 .. 1	115
│ │ ├ **309** — Location Qualifier	0 .. 1	Token	02	1 .. 2	309
│ │ ├ **310** — Location Identifier - Destination (Shipping) or Others	0 .. 1	String	03	1 .. 30	
│ │ ├ **114** — Port Name	0 .. 1	String	04	2 .. 24	
│ │ └ **26** — Country Code	0 .. 1	Token	05	2 .. 3	ISO_3166-1

Documentation

Definition Contractual or operational port or point relevant to the movement of the cargo

Properties

Identifier R4

Name Port or Terminal

Cardinality min: 1 max: 1

Syntax Type Related

External Category Segment

Position 130

Level 3

Notes

Constraint 1 P0203 Paired Multiple - If any are used, all must be used

Comment 1 R4 is required for each port to be identified.

Leaf Elements

Identifier/Name	Description/Notes/Code Values	Properties
115 Port or Terminal Function Code	Code defining function performed at the port or terminal with respect to a shipment **Selected Values** **Code** A **Name** Place of Acceptance (Operational) Place at which carrier actually accepts cargo from shipper or his agent **Code** D **Name** Port of Discharge (Operational) Port at which cargo is unloaded from vessel **Code** E **Name** Place of Delivery (Contractual) Place at which cargo leaves its care and custody of carrier **Code** L **Name** Port of Loading (Operational) Port at which cargo is loaded on vessel	**Cardinality** min: 1 max: 1 **Primitive Type** Token **Length** min: 1 max: 1 **External Category** Simple Data Element **Data Type** ID **Position** 01 **Codelist Id** 115 **Type System** ASC_X12 **Version Mode** Current **Version** 004010
309 Location Qualifier	Code identifying type of location **Selected Values** **Code** DE **Name** Destination (Shipping) **Code** KL **Name** Port of Loading **Code** OR **Name** Origin (Shipping Point) **Code** PB **Name** Port of Discharge Port where shipment is unloaded	**Cardinality** min: 0 max: 1 **Primitive Type** Token **Length** min: 1 max: 2 **External Category** Simple Data Element **Data Type** ID **Position** 02 **Codelist Id** 309 **Type System** ASC_X12

		Version Mode Current **Version** 004010
310 [309 = “DE” | “KL” | “OR” | “PB”] Location Identifier - Destination (Shipping) or Others	Code which identifies a specific location	**Cardinality** **min:** 0 **max:** 1 **Primitive Type** String **Length** **min:** 1 **max:** 30 **External Category** Simple Data Element **Data Type** AN **Position** 03
114 Port Name	Free-form name for the place at which an offshore carrier originates or terminates (by transshipment or otherwise) its actual ocean carriage of property	**Cardinality** **min:** 0 **max:** 1 **Primitive Type** String **Length** **min:** 2 **max:** 24 **External Category** Simple Data Element **Data Type** AN **Position** 04
26 Country Code	Code identifying the country **Selected Values** All Values in Codelist	**Cardinality** **min:** 0 **max:** 1 **Primitive Type** Token **Length** **min:** 2 **max:** 3 **External Category** Simple Data Element **Data Type** ID **Position** 05 **Codelist Id** ISO_3166-1 **Type System** ISO_CodelistsAndSchemes **Version Mode** Latest **Version** 2013

4.15 DTM [374 = “369” | “371”] — Date/Time Reference - Estimated Departure Date or Others

Structure

Node	Card.	Prim.Type	Pos.	Length	Codelists
300 — Reservation (Booking Request) (Ocean)	1 .. 1				
├ **R4** — Loop R4	1 .. 20		130		
│ └ **DTM** — Date/Time Reference - Estimated Departure Date or Others	0 .. 1		140		
│ ├ **374** — Date/Time Qualifier	1 .. 1	Token	01	3 .. 3	374
│ ├ **373** — Date	0 .. 1	Date	02	8 .. 8	
│ ├ **337** — Time	0 .. 1	Time	03	4 .. 8	
│ ├ **623** — Time Code	0 .. 1	Token	04	2 .. 2	623
│ ├ **1250** — Date Time Period Format Qualifier	0 .. 1	Token	05	2 .. 3	1250
│ └ **1251** — Date Time Period - Range of Date and Time, Expressed in Format CCYYMMDDHHMM-CCYYMMDDHHMM	0 .. 1	String	06	1 .. 35	

Documentation

Definition To specify pertinent dates and times

Properties

Identifier DTM

Name Date/Time Reference - Estimated Departure Date or Others

Cardinality min: 0 max: 1

Qualification

Qualified By	Qualifying values	
	Code	Description
./374	369	Estimated Departure Date
	371	Estimated Arrival Date

Syntax Type Related

External Category Segment

Position 140

Level 3

Notes

Constraint 1 R020305 Required - At least one of those noted must be used

Constraint 2 C0403 Conditional - If the first element is present, then the others must be present

Constraint 3 P0506 Paired Multiple - If any are used, all must be used

Leaf Elements

Identifier/Name	Description/Notes/Code Values	Properties
374 Date/Time Qualifier	Code specifying type of date or time, or both date and time **Selected Values** **Code** 369 **Name** Estimated Departure Date **Code** 371 **Name** Estimated Arrival Date	**Cardinality** min: 1 max: 1 **Primitive Type** Token **Length** min: 3 max: 3 **External Category** Simple Data Element **Data Type** ID **Position** 01 **Codelist Id** 374 **Type System** ASC_X12 **Version Mode** Current **Version** 004010
373	Date expressed as CCYYMMDD	**Cardinality** min: 0 max: 1

Date		**Primitive Type** Date **Length** **min:** 8 **max:** 8 **Date Time Format** CCYYMMDD **External Category** Simple Data Element **Data Type** DT **Position** 02
337 Time	Time expressed in 24-hour clock time as follows: HHMM, or HHMMSS, or HHMMSSD, or HHMMSSDD, where H = hours (00-23), M = minutes (00-59), S = integer seconds (00-59) and DD = decimal seconds; decimal seconds are expressed as follows: D = tenths (0-9) and DD = hundredths (00-99)	**Cardinality** **min:** 0 **max:** 1 **Primitive Type** Time **Length** **min:** 4 **max:** 8 **Date Time Format** hhmm[ss[f[f]]] **External Category** Simple Data Element **Data Type** TM **Position** 03
623 Time Code	Code identifying the time. In accordance with International Standards Organization standard 8601, time can be specified by a + or - and an indication in hours in relation to Universal Time Coordinate (UTC) time; since + is a restricted character, + and - are substituted by P and M in the codes that follow **Selected Values** **Code** LT **Name** Local Time **Code** UT **Name** Universal Time Coordinate	**Cardinality** **min:** 0 **max:** 1 **Primitive Type** Token **Length** **min:** 2 **max:** 2 **External Category** Simple Data Element **Data Type** ID **Position** 04 **Codelist Id** 623 **Type System** ASC_X12 **Version Mode** Current **Version** 004010
1250 Date Time Period Format Qualifier	Code indicating the date format, time format, or date and time format **Selected Values** **Code** RDT **Name** Range of Date and Time, Expressed in Format CCYYMMDDHHMM-CCYYMMDDHHMM A range of dates and times expressed in the format CCYYMMDDHHMM-CCYYMMDDHHMM where CCYY is the numerical expression of the century CC and year YY, MM is the numerical expression of the month within the year, DD is the numerical expression of the day within the month, HH is the numerical expression of hours in the day based on a twenty-four hour clock, and MM is the numerical expression of minutes within an hour; the first occurrence of CCYYMMDDHHMM is the starting time and the second is the ending time	**Cardinality** **min:** 0 **max:** 1 **Primitive Type** Token **Length** **min:** 2 **max:** 3 **External Category** Simple Data Element **Data Type** ID **Position** 05 **Codelist Id** 1250 **Type System** ASC_X12 **Version Mode** Current **Version** 004010
1251 [1250 = “RDT”] Date Time Period - Range of Date and Time, Expressed in Format CCYYMMDDHHMM-CCYYMMDDHHMM	Expression of a date, a time, or range of dates, times or dates and times	**Cardinality** **min:** 0 **max:** 1 **Primitive Type** String **Length** **min:** 1 **max:** 35 **External Category** Simple Data Element **Data Type** AN **Position** 06

4.16 LX — Loop LX

Structure

Node	Card.	Prim.Type	Pos.	Length	Codelists
300 — Reservation (Booking Request) (Ocean)	1 .. 1				
├ **LX** — Loop LX	1 .. 999		010		
│ ├ **LX** — Assigned Number	1 .. 1		010		
│ ├ **N7** — Equipment Details	0 .. 1		020		
│ ├ **W09** — Equipment and Temperature	0 .. 1		021		
│ ├ **L0** — Line Item - Quantity and Weight	0 .. 1		040		
│ ├ **L4** — Measurement	0 .. 1		060		
│ └ **H1** — Loop H1	0 .. 10		070		

Properties

Identifier LX

Name Loop LX

Cardinality min: 1 max: 999

Syntax Type Related

External Category Loop

Position 010

Level 2

4.17 LX — Assigned Number

Structure

Node	Card.	Prim.Type	Pos.	Length	Codelists
300 — Reservation (Booking Request) (Ocean)	1 .. 1				
├ **LX** — Loop LX	1 .. 999		010		
│ ├ **LX** — Assigned Number	1 .. 1		010		
│ │ └ **554** — Assigned Number	1 .. 1	Integer	01	1 .. 6	

Documentation

Definition To reference a line number in a transaction set

Properties

Identifier LX

Name Assigned Number

Cardinality min: 1 max: 1

Syntax Type Related

External Category Segment

Position 010

Level 3

Leaf Elements

Identifier/Name	Description/Notes/Code Values	Properties
554 Assigned Number	Number assigned for differentiation within a transaction set	**Cardinality** min: 1 max: 1 **Primitive Type** Integer **Length** min: 1 max: 6 **Fraction Digits** 0 **Total Digits** 6 **External Category** Simple Data Element **Data Type** N0 **Position** 01

4.18 N7 — Equipment Details

Structure

Node	Card.	Prim.Type	Pos.	Length	Codelists
300 — Reservation (Booking Request) (Ocean)	1 .. 1				
├ **LX** — Loop LX	1 .. 999		010		
│ ├ **N7** — Equipment Details	0 .. 1		020		
│ │ ├ **207** — Equipment Number	1 .. 1	String	02	1 .. 10	
│ │ ├ **102** — Ownership Code	0 .. 1	Token	10	1 .. 1	102
│ │ └ **24** — Equipment Type	0 .. 1	Token	22	4 .. 4	

Documentation

Definition To identify the equipment

Properties

Identifier N7

Name Equipment Details

Cardinality min: 0 max: 1

Syntax Type Related

External Category Segment

Position 020

Level 3

Notes

Usage 1 N712 is the owner of the equipment.

Usage 2 N723 is the operator or carrier of the rights of the equipment.

Constraint 1 P0304 Paired Multiple - If any are used, all must be used

Constraint 2 P0516 Paired Multiple - If any are used, all must be used

Constraint 3 P0809 Paired Multiple - If any are used, all must be used

Comment 1 N701 is mandatory for rail transactions.

Comment 2 N720 and N721 are expressed in inches.

Leaf Elements

Identifier/Name	Description/Notes/Code Values	Properties
207 Equipment Number	Sequencing or serial part of an equipment unit's identifying number (pure numeric form for equipment number is preferred)	**Cardinality** min: 1 max: 1 **Primitive Type** String **Length** min: 1 max: 10 **External Category** Simple Data Element **Data Type** AN **Position** 02
102 Ownership Code	Code indicating the relationship of equipment to carrier or ownership of equipment **Selected Values** **Code** N **Name** Not Customer Owned or Leased **Code** S **Name** Customer Owned or Leased	**Cardinality** min: 0 max: 1 **Primitive Type** Token **Length** min: 1 max: 1 **External Category** Simple Data Element **Data Type** ID **Position** 10 **Codelist Id** 102 **Type System** ASC_X12 **Version Mode** Current **Version** 004010
24 Equipment Type	Code identifying equipment type	**Cardinality** min: 0 max: 1 **Primitive Type** Token