		Data Type xsd:string
D_337 Time	Time expressed in 24-hour clock time as follows: HHMM, or HHMMSS, or HHMMSSD, or HHMMSSDD, where H = hours (00-23), M = minutes (00-59), S = integer seconds (00-59) and DD = decimal seconds; decimal seconds are expressed as follows: D = tenths (0-9) and DD = hundredths (00-99)	**Cardinality** **min:** 1 **max:** 1 **Primitive Type** String **Length** **min:** 6 **max:** 6 **External Category** Element **Data Type** xsd:string
D_28 Group Control Number	Assigned number originated and maintained by the sender	**Cardinality** **min:** 1 **max:** 1 **Primitive Type** String **Length** **min:** 9 **max:** 9 **External Category** Element **Data Type** xsd:string
D_455 Responsible Agency Code	Code identifying the issuer of the standard; this code is used in conjunction with Data Element 480 **Selected Values** All Values in Codelist	**Cardinality** **min:** 1 **max:** 1 **Primitive Type** String **Length** **min:** 1 **max:** 1 **External Category** Element **Data Type** xsd:string **Codelist Id** D_455 **Type System** Customer_TS **Version Mode** Local **Version** 1.1
D_480 Version / Release / Industry Identifier Code	Code indicating the version, release, subrelease, and industry identifier of the EDI standard being used, including the GS and GE segments; if code in DE455 in GS segment is X, then in DE 480 positions 1-3 are the version number; positions 4-6 are the release and subrelease, level of the version; and positions 7-12 are the industry or trade association identifiers (optionally assigned by user); if code in DE455 in GS segment is T, then other formats are allowed **Selected Values** All Values in Codelist	**Cardinality** **min:** 1 **max:** 1 **Primitive Type** String **Length** **min:** 6 **max:** 6 **External Category** Element **Data Type** xsd:string **Codelist Id** D_480 **Type System** Customer_TS **Version Mode** Local **Version** 1.1

2.5 S_GE — Functional Group Trailer

Structure

Node	Card.	Prim.Type	Pos.	Length	Codelists
Interchange — Interchange Structure	1 .. 1				
├ **FunctionalGroup** — Functional Group	1 .. 1				
│ └ **S_GE** — Functional Group Trailer	1 .. 1				
│ ├ **D_97** — Number of Transaction Sets Included	1 .. 1	String		1 .. 1	
│ └ **D_28** — Group Control Number	1 .. 1	String		9 .. 9	

Documentation

Definition To indicate the end of a functional group and to provide control information Comments 1. The use of identical data interchange control numbers in the associated functional group header and trailer is designed to maximize functional group integrity. The control number is the same as that used in the corresponding header. Semantic Notes: 1. The data interchange control number GE02 in this trailer must be identical to the same data element in the associated functional group header, GS06.

Properties

Identifier S_GE

Name Functional Group Trailer

Cardinality min: 1 max: 1

Syntax Type Related

External Category Element

Leaf Elements

Identifier/Name	Description/Notes/Code Values	Properties
D_97 Number of Transaction Sets Included	Total number of transaction sets included in the functional group or interchange (transmission) group terminated by the trailer containing this data element	**Cardinality** min: 1 max: 1 **Primitive Type** String **Length** min: 1 max: 1 **External Category** Element **Data Type** xsd:string
D_28 Group Control Number	Assigned number originated and maintained by the sender	**Cardinality** min: 1 max: 1 **Primitive Type** String **Length** min: 9 max: 9 **External Category** Element **Data Type** xsd:string

2.6 S_IEA — Interchange Control Trailer

Structure

Node	Card.	Prim.Type	Pos.	Length	Codelists
Interchange — Interchange Structure	1 .. 1				
└ **S_IEA** — Interchange Control Trailer	1 .. 1				
├ **D_I16** — Number of Included Functional Groups	1 .. 1	String		1 .. 1	
└ **D_I12** — Interchange Control Number	1 .. 1	String		9 .. 9	

Documentation

Definition To define the end of an interchange of zero or more functional groups and interchange-related control segments

Properties

Identifier S_IEA

Name Interchange Control Trailer

Cardinality min: 1 max: 1

Syntax Type Related

External Category Element

Leaf Elements

Identifier/Name	Description/Notes/Code Values	Properties
D_I16 Number of Included Functional Groups	A count of the number of functional groups included in an interchange	**Cardinality** min: 1 max: 1 **Primitive Type** String **Length** min: 1 max: 1 **External Category** Element **Data Type** xsd:string
D_I12 Interchange Control Number	A control number assigned by the interchange sender	**Cardinality** min: 1 max: 1 **Primitive Type** String **Length** min: 9 max: 9 **External Category** Element **Data Type** xsd:string

3 OVERVIEW MESSAGE

General Information

Name	SAP_LBN_ANSI_X12_301
Direction	In
Status	Active
Message Type	Confirmation (Ocean)
Type System	ASC_X12
Version	004010
External Category	Transaction Set

Documentation

Definition This Draft Standard for Trial Use contains the format and establishes the data contents of the Confirmation (Ocean) Transaction Set (301) for use within the context of an Electronic Data Interchange (EDI) environment. The transaction set can be used to provide all the information necessary for an ocean carrier to confirm space, container, and equipment availability in response to the Reservation (Booking Request) (Ocean) Transaction Set (300); or to notify other parties such as terminal operators or other ocean carriers.

3.1 Structure

The following table shows the complete structure.

Node	Card.	Prim.Type	Pos.	Length	Codelists
301 — Confirmation (Ocean)	1 .. 1				
├ **ST** — Transaction Set Header	1 .. 1		010		
│ ├ **143** — Transaction Set Identifier Code	1 .. 1	Token	01	3 .. 3	143
│ └ **329** — Transaction Set Control Number	1 .. 1	String	02	4 .. 9	
├ **B1** — Beginning Segment for Booking or Pick-up/Delivery	1 .. 1		020		
│ ├ **145** — Shipment Identification Number	1 .. 1	String	02	1 .. 30	
│ └ **558** — Reservation Action Code	0 .. 1	Token	04	1 .. 1	558
├ **Y3** — Space Confirmation	1 .. 1		040		
│ └ **13** — Booking Number	1 .. 1	String	01	1 .. 17	
├ **N9** — Reference Identification	0 .. 100		054		
│ ├ **128** — Reference Identification Qualifier	1 .. 1	Token	01	2 .. 3	128
│ └ **127** — Reference Identification - System Number or Others	0 .. 1	String	02	1 .. 30	
├ **R4** — Loop R4	1 .. 20		110		
│ └ **R4** — Port or Terminal	1 .. 1		110		
│ └ **115** — Port or Terminal Function Code	1 .. 1	Token	01	1 .. 1	115
├ **LX** — Loop LX	1 .. 999		010		
│ └ **LX** — Assigned Number	1 .. 1		010		
│ └ **554** — Assigned Number	1 .. 1	Integer	01	1 .. 6	
└ **SE** — Transaction Set Trailer	1 .. 1		010		
├ **96** — Number of Included Segments	1 .. 1	Integer	01	1 .. 10	
└ **329** — Transaction Set Control Number	1 .. 1	String	02	4 .. 9	

4 DETAILS MESSAGE

4.1 301 — Confirmation (Ocean)

Structure

Node	Card.	Prim.Type	Pos.	Length	Codelists
301 — Confirmation (Ocean)	1 .. 1				
├ **ST** — Transaction Set Header	1 .. 1		010		
├ **B1** — Beginning Segment for Booking or Pick-up/Delivery	1 .. 1		020		
├ **Y3** — Space Confirmation	1 .. 1		040		
├ **N9** — Reference Identification	0 .. 100		054		
├ **R4** — Loop R4	1 .. 20		110		
├ **LX** — Loop LX	1 .. 999		010		
└ **SE** — Transaction Set Trailer	1 .. 1		010		

Properties

Identifier 301

Name Confirmation (Ocean)

Cardinality min: 1 max: 1

4.2 ST — Transaction Set Header

Structure

Node	Card.	Prim.Type	Pos.	Length	Codelists
301 — Confirmation (Ocean)	1 .. 1				
├ **ST** — Transaction Set Header	1 .. 1		010		
│ ├ **143** — Transaction Set Identifier Code	1 .. 1	Token	01	3 .. 3	143
│ └ **329** — Transaction Set Control Number	1 .. 1	String	02	4 .. 9	

Documentation

Definition To indicate the start of a transaction set and to assign a control number

Properties

Identifier ST

Name Transaction Set Header

Cardinality min: 1 max: 1

Syntax Type Related

External Category Segment

Position 010

Level 2

Notes

Usage 1 The transaction set identifier (ST01) used by the translation routines of the interchange partners to select the appropriate transaction set definition (e.g., 810 selects the Invoice Transaction Set).

Leaf Elements

Identifier/Name	Description/Notes/Code Values	Properties
143 Transaction Set Identifier Code	Code uniquely identifying a Transaction Set **Selected Values** **Code** 301 **Name** Confirmation (Ocean)	**Cardinality** min: 1 max: 1 **Primitive Type** Token **Length** min: 3 max: 3 **External Category** Simple Data Element **Data Type** ID **Position** 01 **Codelist Id** 143 **Type System** ASC_X12 **Version Mode** Current **Version** 004010
329 Transaction Set Control Number	Identifying control number that must be unique within the transaction set functional group assigned by the originator for a transaction set	**Cardinality** min: 1 max: 1 **Primitive Type** String **Length** min: 4 max: 9 **External Category** Simple Data Element **Data Type** AN **Position** 02

4.3 B1 — Beginning Segment for Booking or Pick-up/Delivery

Structure

Node	Card.	Prim.Type	Pos.	Length	Codelists
301 — Confirmation (Ocean)	1 .. 1				
├ **B1** — Beginning Segment for Booking or Pick-up/Delivery	1 .. 1		020		
│ ├ **145** — Shipment Identification Number	1 .. 1	String	02	1 .. 30	
│ └ **558** — Reservation Action Code	0 .. 1	Token	04	1 .. 1	558

Documentation

Definition To transmit identifying numbers, dates, and other basic data relating to the transaction set

Properties

Identifier B1

Name Beginning Segment for Booking or Pick-up/Delivery

Cardinality min: 1 max: 1

Syntax Type Related

External Category Segment

Position 020

Level 2

Notes

Usage 1 B101 is the Standard Carrier Alpha Code (SCAC) of the carrier sending the EDI transmission.

Usage 2 B103 is the booking date accepted by the carrier.

Leaf Elements

Identifier/Name	Description/Notes/Code Values	Properties
145 Shipment Identification Number	Identification number assigned to the shipment by the shipper that uniquely identifies the shipment from origin to ultimate destination and is not subject to modification; (Does not contain blanks or special characters)	**Cardinality** min: 1 max: 1 **Primitive Type** String **Length** min: 1 max: 30 **External Category** Simple Data Element **Data Type** AN **Position** 02
558 Reservation Action Code	Code identifying action on reservation or offering **Selected Values** **Code** A **Name** Reservation Accepted **Code** D **Name** Reservation Cancelled	**Cardinality** min: 0 max: 1 **Primitive Type** Token **Length** min: 1 max: 1 **External Category** Simple Data Element **Data Type** ID **Position** 04 **Codelist Id** 558 **Type System** ASC_X12 **Version Mode** Current **Version** 004010

4.4 Y3 — Space Confirmation

Structure

Node	Card.	Prim.Type	Pos.	Length	Codelists
301 — Confirmation (Ocean)	1 .. 1				
├ **Y3** — Space Confirmation	1 .. 1		040		
│ └ **13** — Booking Number	1 .. 1	String	01	1 .. 17	

Documentation

Definition To specify confirmation information for space booking including numbers, dates, and load time

Properties

Identifier Y3

Name Space Confirmation

Cardinality min: 1 max: 1

Syntax Type Related

External Category Segment

Position 040

Level 2

Notes

Usage 1 Y303 is the date of departure of the vessel.

Usage 2 Y304 is the estimated arrival date at the port of discharge.

Usage 3 Y307 is the required pier date.

Usage 4 Y308 is the load time.

Usage 5 Y311 is the time zone which the time reflects.

Constraint 1 C0908 Conditional - If the first element is present, then the others must be present

Comment 1 If space is available, all of the conditional data elements in segment Y3 are required. If the requested space is not available, Y301 is the booking number ‘decline’.

Leaf Elements

Identifier/Name	Description/Notes/Code Values	Properties
13 Booking Number	Number assigned by the carrier for space reservation	**Cardinality** min: 1 max: 1 **Primitive Type** String **Length** min: 1 max: 17 **External Category** Simple Data Element **Data Type** AN **Position** 01

4.5 N9 — Reference Identification

Structure

Node	Card.	Prim.Type	Pos.	Length	Codelists
301 — Confirmation (Ocean)	1 .. 1				
├ **N9** — Reference Identification	0 .. 100		054		
│ ├ **128** — Reference Identification Qualifier	1 .. 1	Token	01	2 .. 3	128
│ └ **127** — Reference Identification - System Number or Others	0 .. 1	String	02	1 .. 30	

Documentation

Definition To transmit identifying information as specified by the Reference Identification Qualifier

Properties

Identifier N9

Name Reference Identification

Cardinality min: 0 max: 100

Syntax Type Related

External Category Segment

Position 054

Level 2

Notes

Usage 1 N906 reflects the time zone which the time reflects.

Usage 2 N907 contains data relating to the value cited in N902.

Usage 3 If in 300 message there is a N9 segment with code “EV” in N901, the segment must be present in this message, so that the freight booking can be updated.

Constraint 1 R0203 Required - At least one of those noted must be used

Constraint 2 C0605 Conditional - If the first element is present, then the others must be present

Leaf Elements

Identifier/Name	Description/Notes/Code Values	Properties
128 Reference Identification Qualifier	Code qualifying the Reference Identification **Selected Values** All Values in Codelist	**Cardinality** min: 1 max: 1 **Primitive Type** Token **Length** min: 2 max: 3 **External Category** Simple Data Element **Data Type** ID **Position** 01 **Codelist Id** 128 **Type System** ASC_X12 **Version Mode** Current **Version** 004010
127 [128 = “06” | “EV”] Reference Identification - System Number or Others	Reference information as defined for a particular Transaction Set or as specified by the Reference Identification Qualifier	**Cardinality** min: 0 max: 1 **Primitive Type** String **Length** min: 1 max: 30 **External Category** Simple Data Element **Data Type** AN **Position** 02