		Data Type xsd:string
D_337 Time	Time expressed in 24-hour clock time as follows: HHMM, or HHMMSS, or HHMMSSD, or HHMMSSDD, where H = hours (00-23), M = minutes (00-59), S = integer seconds (00-59) and DD = decimal seconds; decimal seconds are expressed as follows: D = tenths (0-9) and DD = hundredths (00-99)	**Cardinality** **min:** 1 **max:** 1 **Primitive Type** String **Length** **min:** 6 **max:** 6 **External Category** Element **Data Type** xsd:string
D_28 Group Control Number	Assigned number originated and maintained by the sender	**Cardinality** **min:** 1 **max:** 1 **Primitive Type** String **Length** **min:** 9 **max:** 9 **External Category** Element **Data Type** xsd:string
D_455 Responsible Agency Code	Code identifying the issuer of the standard; this code is used in conjunction with Data Element 480 **Selected Values** All Values in Codelist	**Cardinality** **min:** 1 **max:** 1 **Primitive Type** String **Length** **min:** 1 **max:** 1 **External Category** Element **Data Type** xsd:string **Codelist Id** D_455 **Type System** Customer_TS **Version Mode** Local **Version** 1.1
D_480 Version / Release / Industry Identifier Code	Code indicating the version, release, subrelease, and industry identifier of the EDI standard being used, including the GS and GE segments; if code in DE455 in GS segment is X, then in DE 480 positions 1-3 are the version number; positions 4-6 are the release and subrelease, level of the version; and positions 7-12 are the industry or trade association identifiers (optionally assigned by user); if code in DE455 in GS segment is T, then other formats are allowed **Selected Values** All Values in Codelist	**Cardinality** **min:** 1 **max:** 1 **Primitive Type** String **Length** **min:** 6 **max:** 6 **External Category** Element **Data Type** xsd:string **Codelist Id** D_480 **Type System** Customer_TS **Version Mode** Local **Version** 1.1

2.5 S_GE — Functional Group Trailer

Structure

Node	Card.	Prim.Type	Pos.	Length	Codelists
Interchange — Interchange Structure	1 .. 1				
├ **FunctionalGroup** — Functional Group	1 .. 1				
│ └ **S_GE** — Functional Group Trailer	1 .. 1				
│ ├ **D_97** — Number of Transaction Sets Included	1 .. 1	String		1 .. 1	
│ └ **D_28** — Group Control Number	1 .. 1	String		9 .. 9	

Documentation

Definition To indicate the end of a functional group and to provide control information Comments 1. The use of identical data interchange control numbers in the associated functional group header and trailer is designed to maximize functional group integrity. The control number is the same as that used in the corresponding header. Semantic Notes: 1. The data interchange control number GE02 in this trailer must be identical to the same data element in the associated functional group header, GS06.

Properties

Identifier S_GE

Name Functional Group Trailer

Cardinality min: 1 max: 1

Syntax Type Related

External Category Element

Leaf Elements

Identifier/Name	Description/Notes/Code Values	Properties
D_97 Number of Transaction Sets Included	Total number of transaction sets included in the functional group or interchange (transmission) group terminated by the trailer containing this data element	**Cardinality** min: 1 max: 1 **Primitive Type** String **Length** min: 1 max: 1 **External Category** Element **Data Type** xsd:string
D_28 Group Control Number	Assigned number originated and maintained by the sender	**Cardinality** min: 1 max: 1 **Primitive Type** String **Length** min: 9 max: 9 **External Category** Element **Data Type** xsd:string

2.6 S_IEA — Interchange Control Trailer

Structure

Node	Card.	Prim.Type	Pos.	Length	Codelists
Interchange — Interchange Structure	1 .. 1				
└ **S_IEA** — Interchange Control Trailer	1 .. 1				
├ **D_I16** — Number of Included Functional Groups	1 .. 1	String		1 .. 1	
└ **D_I12** — Interchange Control Number	1 .. 1	String		9 .. 9	

Documentation

Definition To define the end of an interchange of zero or more functional groups and interchange-related control segments

Properties

Identifier S_IEA

Name Interchange Control Trailer

Cardinality min: 1 max: 1

Syntax Type Related

External Category Element

Leaf Elements

Identifier/Name	Description/Notes/Code Values	Properties
D_I16 Number of Included Functional Groups	A count of the number of functional groups included in an interchange	**Cardinality** min: 1 max: 1 **Primitive Type** String **Length** min: 1 max: 1 **External Category** Element **Data Type** xsd:string
D_I12 Interchange Control Number	A control number assigned by the interchange sender	**Cardinality** min: 1 max: 1 **Primitive Type** String **Length** min: 9 max: 9 **External Category** Element **Data Type** xsd:string

3 OVERVIEW MESSAGE

General Information

Name	SAP_LBN_ANSI_X12_303
Direction	Out
Status	Active
Message Type	Booking Cancellation (Ocean)
Type System	ASC_X12
Version	004010
External Category	Transaction Set

Documentation

Definition This Draft Standard for Trial Use contains the format and establishes the data contents of the Booking Cancellation (Ocean) Transaction Set (303) for use within the context of an Electronic Data Interchange (EDI) environment. The transaction set can be used to provide all the information necessary for a shipper or forwarder to cancel a previous booking request.

Notes

Example 1

```
ISA*00*          *00*          *ZZ*10020002156      *ZZ*10020002177
*251217*0659*U*00401*000002301*0*P*>~
GS*RO*10020002156*10020002177*20251217*065918*000002301*X*004010~
ST*303*0001~
B1**BookingID**N~
Y5*BookingID~
SE*4*0001~
GE*1*000002301~
IEA*1*000002301~
```

3.1 Structure

The following table shows the complete structure.

Node	Card.	Prim.Type	Pos.	Length	Codelists
303 — Booking Cancellation (Ocean)	1 .. 1				
├ **ST** — Transaction Set Header	1 .. 1		010		
│ ├ **143** — Transaction Set Identifier Code	1 .. 1	Token	01	3 .. 3	143
│ └ **329** — Transaction Set Control Number	1 .. 1	String	02	4 .. 9	
├ **B1** — Beginning Segment for Booking or Pick-up/Delivery	1 .. 1		020		
│ ├ **140** — Standard Carrier Alpha Code	0 .. 1	Token	01	2 .. 4	
│ ├ **145** — Shipment Identification Number	1 .. 1	String	02	1 .. 30	
│ └ **558** — Reservation Action Code	0 .. 1	Token	04	1 .. 1	558
├ **Y5** — Space Booking Cancellation	1 .. 1		040		
│ └ **13** — Booking Number	1 .. 1	String	01	1 .. 17	
└ **SE** — Transaction Set Trailer	1 .. 1		060		
├ **96** — Number of Included Segments	1 .. 1	Integer	01	1 .. 10	
└ **329** — Transaction Set Control Number	1 .. 1	String	02	4 .. 9	

4 DETAILS MESSAGE

4.1 303 — Booking Cancellation (Ocean)

Structure

Node	Card.	Prim.Type	Pos.	Length	Codelists
303 — Booking Cancellation (Ocean)	1 .. 1				
├ **ST** — Transaction Set Header	1 .. 1		010		
├ **B1** — Beginning Segment for Booking or Pick-up/Delivery	1 .. 1		020		
├ **Y5** — Space Booking Cancellation	1 .. 1		040		
└ **SE** — Transaction Set Trailer	1 .. 1		060		

Properties

Identifier 303

Name Booking Cancellation (Ocean)

Cardinality min: 1 max: 1

4.2 ST — Transaction Set Header

Structure

Node	Card.	Prim.Type	Pos.	Length	Codelists
303 — Booking Cancellation (Ocean)	1 .. 1				
├ **ST** — Transaction Set Header	1 .. 1		010		
│ ├ **143** — Transaction Set Identifier Code	1 .. 1	Token	01	3 .. 3	143
│ └ **329** — Transaction Set Control Number	1 .. 1	String	02	4 .. 9	

Documentation

Definition To indicate the start of a transaction set and to assign a control number

Properties

Identifier ST

Name Transaction Set Header

Cardinality min: 1 max: 1

Syntax Type Related

External Category Segment

Position 010

Level 2

Notes

Usage 1 The transaction set identifier (ST01) used by the translation routines of the interchange partners to select the appropriate transaction set definition (e.g., 810 selects the Invoice Transaction Set).

Leaf Elements

Identifier/Name	Description/Notes/Code Values	Properties
143 Transaction Set Identifier Code	Code uniquely identifying a Transaction Set **Selected Values** All Values in Codelist	**Cardinality** min: 1 max: 1 **Primitive Type** Token **Length** min: 3 max: 3 **External Category** Simple Data Element **Data Type** ID **Position** 01 **Codelist Id** 143 **Type System** ASC_X12 **Version Mode** Current **Version** 004010
329 Transaction Set Control Number	Identifying control number that must be unique within the transaction set functional group assigned by the originator for a transaction set	**Cardinality** min: 1 max: 1 **Primitive Type** String **Length** min: 4 max: 9 **External Category** Simple Data Element **Data Type** AN **Position** 02

4.3 B1 — Beginning Segment for Booking or Pick-up/Delivery

Structure

Node	Card.	Prim.Type	Pos.	Length	Codelists
303 — Booking Cancellation (Ocean)	1 .. 1				
├ **B1** — Beginning Segment for Booking or Pick-up/Delivery	1 .. 1		020		
│ ├ **140** — Standard Carrier Alpha Code	0 .. 1	Token	01	2 .. 4	
│ ├ **145** — Shipment Identification Number	1 .. 1	String	02	1 .. 30	
│ └ **558** — Reservation Action Code	0 .. 1	Token	04	1 .. 1	558

Documentation

Definition To transmit identifying numbers, dates, and other basic data relating to the transaction set

Properties

Identifier B1

Name Beginning Segment for Booking or Pick-up/Delivery

Cardinality min: 1 max: 1

Syntax Type Related

External Category Segment

Position 020

Level 2

Notes

Usage 1 B101 is the Standard Carrier Alpha Code (SCAC) of the carrier sending the EDI transmission.

Usage 2 B103 is the booking date accepted by the carrier.

Leaf Elements

Identifier/Name	Description/Notes/Code Values	Properties
140 Standard Carrier Alpha Code	Standard Carrier Alpha Code	**Cardinality** min: 0 max: 1 **Primitive Type** Token **Length** min: 2 max: 4 **External Category** Simple Data Element **Data Type** ID **Position** 01
145 Shipment Identification Number	Identification number assigned to the shipment by the shipper that uniquely identifies the shipment from origin to ultimate destination and is not subject to modification; (Does not contain blanks or special characters)	**Cardinality** min: 1 max: 1 **Primitive Type** String **Length** min: 1 max: 30 **External Category** Simple Data Element **Data Type** AN **Position** 02
558 Reservation Action Code	Code identifying action on reservation or offering **Selected Values** All Values in Codelist	**Cardinality** min: 0 max: 1 **Primitive Type** Token **Length** min: 1 max: 1 **External Category** Simple Data Element **Data Type** ID **Position** 04 **Codelist Id** 558 **Type System** ASC_X12 **Version Mode** Current **Version** 004010

4.4 Y5 — Space Booking Cancellation

Structure

Node	Card.	Prim.Type	Pos.	Length	Codelists
303 — Booking Cancellation (Ocean)	1 .. 1				
├ **Y5** — Space Booking Cancellation	1 .. 1		040		
│ └ **13** — Booking Number	1 .. 1	String	01	1 .. 17	

Documentation

Definition To specify booking number for cancellation

Properties

Identifier Y5

Name Space Booking Cancellation

Cardinality min: 1 max: 1

Syntax Type Related

External Category Segment

Position 040

Level 2

Leaf Elements

Identifier/Name	Description/Notes/Code Values	Properties
13 Booking Number	Number assigned by the carrier for space reservation	**Cardinality** min: 1 max: 1 **Primitive Type** String **Length** min: 1 max: 17 **External Category** Simple Data Element **Data Type** AN **Position** 01

4.5 SE — Transaction Set Trailer

Structure

Node	Card.	Prim.Type	Pos.	Length	Codelists
303 — Booking Cancellation (Ocean)	1 .. 1				
└ **SE** — Transaction Set Trailer	1 .. 1		060		
├ **96** — Number of Included Segments	1 .. 1	Integer	01	1 .. 10	
└ **329** — Transaction Set Control Number	1 .. 1	String	02	4 .. 9	

Documentation

Definition To indicate the end of the transaction set and provide the count of the transmitted segments (including the beginning (ST) and ending (SE) segments)

Properties

Identifier SE

Name Transaction Set Trailer

Cardinality min: 1 max: 1

Syntax Type Related

External Category Segment

Position 060

Level 2

Notes

Comment 1 SE is the last segment of each transaction set.

Leaf Elements

Identifier/Name	Description/Notes/Code Values	Properties
96 Number of Included Segments	Total number of segments included in a transaction set including ST and SE segments	**Cardinality** min: 1 max: 1 **Primitive Type** Integer **Length** min: 1 max: 10 **Fraction Digits** 0 **Total Digits** 10 **External Category** Simple Data Element **Data Type** N0 **Position** 01
329 Transaction Set Control Number	Identifying control number that must be unique within the transaction set functional group assigned by the originator for a transaction set	**Cardinality** min: 1 max: 1 **Primitive Type** String **Length** min: 4 max: 9 **External Category** Simple Data Element **Data Type** AN **Position** 02