4.4 N9 — Reference Identification

Structure

Node	Card.	Prim.Type	Pos.	Length	Codelists
310 — Freight Receipt and Invoice (Ocean)	1 .. 1				
├ **N9** — Reference Identification	3 .. 15		060		
│ ├ **128** — Reference Identification Qualifier	1 .. 1	Token	01	2 .. 3	128
│ ├ **127** — Reference Identification - System Number	1 .. 1	String	02	1 .. 30	
│ ├ **127** — Reference Identification - Billing Account	0 .. 1	String	02	1 .. 30	
│ ├ **127** — Reference Identification - Carrier's Reference Number (PRO/Invoice)	0 .. 1	String	02	1 .. 30	
│ ├ **369** — Free-form Description	0 .. 1	String	03	1 .. 45	
│ ├ **373** — Date	0 .. 1	Date	04	8 .. 8	
│ ├ **337** — Time	0 .. 1	Time	05	4 .. 8	
│ ├ **623** — Time Code	0 .. 1	Token	06	2 .. 2	623
│ └ **C040** — Reference Identifier	0 .. 1		07		

Documentation

Definition To transmit identifying information as specified by the Reference Identification Qualifier

Properties

Identifier N9

Name Reference Identification

Cardinality min: 3 max: 15

Syntax Type Related

External Category Segment

Position 060

Level 2

Notes

Usage 1 N906 reflects the time zone which the time reflects.

Usage 2 N907 contains data relating to the value cited in N902.

Constraint 1 R0203 Required - At least one of those noted must be used

Constraint 2 C0605 Conditional - If the first element is present, then the others must be present

Leaf Elements

Identifier/Name	Description/Notes/Code Values	Properties
128 Reference Identification Qualifier	Code qualifying the Reference Identification **Selected Values** All Values in Codelist	**Cardinality** min: 1 max: 1 **Primitive Type** Token **Length** min: 2 max: 3 **External Category** Simple Data Element **Data Type** ID **Position** 01 **Codelist Id** 128 **Type System** ASC_X12 **Version Mode** Current **Version** 004010
127 [128 = "06"] Reference Identification - System Number	Reference information as defined for a particular Transaction Set or as specified by the Reference Identification Qualifier	**Cardinality** min: 1 max: 1 **Primitive Type** String **Length** min: 1 max: 30 **External Category** Simple Data Element **Data Type** AN **Position** 02
127 [128 = "12"]	Reference information as defined for a particular	**Cardinality** min: 0 max: 1

Reference Identification - Billing Account	Transaction Set or as specified by the Reference Identification Qualifier	**Primitive Type** String **Length** **min:** 1 **max:** 30 **External Category** Simple Data Element **Data Type** AN **Position** 02
127 [128 = "CN"] Reference Identification - Carrier's Reference Number (PRO/Invoice)	Reference information as defined for a particular Transaction Set or as specified by the Reference Identification Qualifier	**Cardinality** **min:** 0 **max:** 1 **Primitive Type** String **Length** **min:** 1 **max:** 30 **External Category** Simple Data Element **Data Type** AN **Position** 02
369 Free-form Description	Free-form descriptive text	**Cardinality** **min:** 0 **max:** 1 **Primitive Type** String **Length** **min:** 1 **max:** 45 **External Category** Simple Data Element **Data Type** AN **Position** 03
373 Date	Date expressed as CCYYMMDD	**Cardinality** **min:** 0 **max:** 1 **Primitive Type** Date **Length** **min:** 8 **max:** 8 **Date Time Format** CCYYMMDD **External Category** Simple Data Element **Data Type** DT **Position** 04
337 Time	Time expressed in 24-hour clock time as follows: HHMM, or HHMMSS, or HHMMSSD, or HHMMSSDD, where H = hours (00-23), M = minutes (00-59), S = integer seconds (00-59) and DD = decimal seconds; decimal seconds are expressed as follows: D = tenths (0-9) and DD = hundredths (00-99)	**Cardinality** **min:** 0 **max:** 1 **Primitive Type** Time **Length** **min:** 4 **max:** 8 **Date Time Format** hhmm[ss[f[f]]] **External Category** Simple Data Element **Data Type** TM **Position** 05
623 Time Code	Code identifying the time. In accordance with International Standards Organization standard 8601, time can be specified by a + or - and an indication in hours in relation to Universal Time Coordinate (UTC) time; since + is a restricted character, + and - are substituted by P and M in the codes that follow **Selected Values** All Values in Codelist	**Cardinality** **min:** 0 **max:** 1 **Primitive Type** Token **Length** **min:** 2 **max:** 2 **External Category** Simple Data Element **Data Type** ID **Position** 06 **Codelist Id** 623 **Type System** ASC_X12 **Version Mode** Current **Version** 004010

4.5 C040 — Reference Identifier

Structure

Node	Card.	Prim.Type	Pos.	Length	Codelists
310 — Freight Receipt and Invoice (Ocean)	1 .. 1				
├ **N9** — Reference Identification	3 .. 15		060		
│ └ **C040** — Reference Identifier	0 .. 1		07		
│ ├ **128** — Reference Identification Qualifier	1 .. 1	Token	01	2 .. 3	128
│ ├ **127** — Reference Identification	1 .. 1	String	02	1 .. 30	
│ ├ **128** — Reference Identification Qualifier	0 .. 1	Token	03	2 .. 3	128
│ ├ **127** — Reference Identification	0 .. 1	String	04	1 .. 30	
│ ├ **128** — Reference Identification Qualifier	0 .. 1	Token	05	2 .. 3	128
│ └ **127** — Reference Identification	0 .. 1	String	06	1 .. 30	

Documentation

Definition To identify one or more reference numbers or identification numbers as specified by the Reference Qualifier

Properties

Identifier C040

Name Reference Identifier

Cardinality min: 0 max: 1

Syntax Type Related

External Category Composite Data Structure

Position 07

Notes

Constraint 1 P0304 Paired Multiple - If any are used, all must be used

Constraint 2 P0506 Paired Multiple - If any are used, all must be used

Leaf Elements

Identifier/Name	Description/Notes/Code Values	Properties
128 Reference Identification Qualifier	Code qualifying the Reference Identification **Selected Values** All Values in Codelist	**Cardinality** min: 1 max: 1 **Primitive Type** Token **Length** min: 2 max: 3 **External Category** Simple Data Element **Data Type** ID **Position** 01 **Codelist Id** 128 **Type System** ASC_X12 **Version Mode** Current **Version** 004010
127 Reference Identification	Reference information as defined for a particular Transaction Set or as specified by the Reference Identification Qualifier	**Cardinality** min: 1 max: 1 **Primitive Type** String **Length** min: 1 max: 30 **External Category** Simple Data Element **Data Type** AN **Position** 02
128 Reference Identification Qualifier	Code qualifying the Reference Identification **Selected Values** All Values in Codelist	**Cardinality** min: 0 max: 1 **Primitive Type** Token **Length** min: 2 max: 3 **External Category** Simple Data Element **Data Type** ID **Position** 03

		Codelist Id 128 **Type System** ASC_X12 **Version Mode** Current **Version** 004010
127 Reference Identification	Reference information as defined for a particular Transaction Set or as specified by the Reference Identification Qualifier	**Cardinality** **min:** 0 **max:** 1 **Primitive Type** String **Length** **min:** 1 **max:** 30 **External Category** Simple Data Element **Data Type** AN **Position** 04
128 Reference Identification Qualifier	Code qualifying the Reference Identification **Selected Values** All Values in Codelist	**Cardinality** **min:** 0 **max:** 1 **Primitive Type** Token **Length** **min:** 2 **max:** 3 **External Category** Simple Data Element **Data Type** ID **Position** 05 **Codelist Id** 128 **Type System** ASC_X12 **Version Mode** Current **Version** 004010
127 Reference Identification	Reference information as defined for a particular Transaction Set or as specified by the Reference Identification Qualifier	**Cardinality** **min:** 0 **max:** 1 **Primitive Type** String **Length** **min:** 1 **max:** 30 **External Category** Simple Data Element **Data Type** AN **Position** 06

4.6 V1 — Vessel Identification

Structure

Node	Card.	Prim.Type	Pos.	Length	Codelists
310 — Freight Receipt and Invoice (Ocean)	1 .. 1				
├ **V1** — Vessel Identification	1 .. 2		070		

Documentation

Definition To provide vessel details and voyage number

Properties

Identifier V1

Name Vessel Identification

Cardinality min: 1 max: 2

Syntax Type Related

External Category Segment

Position 070

Level 2

Notes

Usage 1 V103 is the code identifying the country in which the ship (vessel) is registered.

Usage 2 V105 identifies the ocean carrier.

Constraint 1 R0102 Required - At least one of those noted must be used

Constraint 2 C0801 Conditional - If the first element is present, then the others must be present

4.7 C3 — Currency

Structure

Node	Card.	Prim.Type	Pos.	Length	Codelists
310 — Freight Receipt and Invoice (Ocean)	1 .. 1				
├ **C3** — Currency	0 .. 1		110		
│ └ **100** — Currency Code	1 .. 1	Token	01	3 .. 3	ISO_4217

Documentation

Definition To specify the currency being used in the transaction set

Properties

Identifier C3

Name Currency

Cardinality min: 0 max: 1

Syntax Type Related

External Category Segment

Position 110

Level 2

Notes

Usage 1 C301 is the billing currency.

Usage 2 C303 is the payment currency.

Usage 3 C304 is the rated currency.

Comment 1 Currency is implied by the code for the country in whose currency the monetary amounts are specified.

Leaf Elements

Identifier/Name	Description/Notes/Code Values	Properties
100 Currency Code	Code (Standard ISO) for country in whose currency the charges are specified **Selected Values** All Values in Codelist	**Cardinality** min: 1 max: 1 **Primitive Type** Token **Length** min: 3 max: 3 **External Category** Simple Data Element **Data Type** ID **Position** 01 **Codelist Id** ISO_4217 **Type System** ISO_CodelistsAndSchemes **Version Mode** Latest **Version** 2015

4.8 N1 — Loop N1

Structure

Node	Card.	Prim.Type	Pos.	Length	Codelists
310 — Freight Receipt and Invoice (Ocean)	1 .. 1				
├ **N1** — Loop N1	1 .. 10		130		
│ └ **N1** — Name	1 .. 1		130		

Properties

Identifier N1

Name Loop N1

Cardinality min: 1 max: 10

Syntax Type Related

External Category Loop

Position 130

Level 2

4.9 N1 — Name

Structure

Node	Card.	Prim.Type	Pos.	Length	Codelists
310 — Freight Receipt and Invoice (Ocean)	1 .. 1				
├ **N1** — Loop N1	1 .. 10		130		
│ └ **N1** — Name	1 .. 1		130		
│ └ **98** — Entity Identifier Code	1 .. 1	Token	01	2 .. 3	98

Documentation

Definition To identify a party by type of organization, name, and code

Properties

Identifier N1

Name Name

Cardinality min: 1 max: 1

Syntax Type Related

External Category Segment

Position 130

Level 3

Notes

Constraint 1 R0203 Required - At least one of those noted must be used

Constraint 2 P0304 Paired Multiple - If any are used, all must be used

Comment 1 This segment, used alone, provides the most efficient method of providing organizational identification. To obtain this efficiency the “ID Code” (N104) must provide a key to the table maintained by the transaction processing party.

Comment 2 N105 and N106 further define the type of entity in N101.

Leaf Elements

Identifier/Name	Description/Notes/Code Values	Properties
98 Entity Identifier Code	Code identifying an organizational entity, a physical location, property or an individual **Selected Values** All Values in Codelist	**Cardinality** min: 1 max: 1 **Primitive Type** Token **Length** min: 2 max: 3 **External Category** Simple Data Element **Data Type** ID **Position** 01 **Codelist Id** 98 **Type System** ASC_X12 **Version Mode** Current **Version** 004010

4.10 R4 — Loop R4

Structure

Node	Card.	Prim.Type	Pos.	Length	Codelists
310 — Freight Receipt and Invoice (Ocean)	1 .. 1				
├ **R4** — Loop R4	1 .. 20		180		
│ └ **R4** — Port or Terminal	1 .. 1		180		

Properties

Identifier R4

Name Loop R4

Cardinality min: 1 max: 20

Syntax Type Related

External Category Loop

Position 180

Level 2

4.11 R4 — Port or Terminal

Structure

Node	Card.	Prim.Type	Pos.	Length	Codelists
310 — Freight Receipt and Invoice (Ocean)	1 .. 1				
├ **R4** — Loop R4	1 .. 20		180		
│ └ **R4** — Port or Terminal	1 .. 1		180		
│ └ **115** — Port or Terminal Function Code	1 .. 1	Token	01	1 .. 1	115

Documentation

Definition Contractual or operational port or point relevant to the movement of the cargo

Properties

Identifier R4

Name Port or Terminal

Cardinality min: 1 max: 1

Syntax Type Related

External Category Segment

Position 180

Level 3

Notes

Constraint 1 P0203 Paired Multiple - If any are used, all must be used

Comment 1 R4 is required for each port to be identified.

Leaf Elements

Identifier/Name	Description/Notes/Code Values	Properties
115 Port or Terminal Function Code	Code defining function performed at the port or terminal with respect to a shipment **Selected Values** All Values in Codelist	**Cardinality** min: 1 max: 1 **Primitive Type** Token **Length** min: 1 max: 1 **External Category** Simple Data Element **Data Type** ID **Position** 01 **Codelist Id** 115 **Type System** ASC_X12 **Version Mode** Current **Version** 004010