		Data Type xsd:string
D_337 Time	Time expressed in 24-hour clock time as follows: HHMM, or HHMMSS, or HHMMSSD, or HHMMSSDD, where H = hours (00-23), M = minutes (00-59), S = integer seconds (00-59) and DD = decimal seconds; decimal seconds are expressed as follows: D = tenths (0-9) and DD = hundredths (00-99)	**Cardinality** **min:** 1 **max:** 1 **Primitive Type** String **Length** **min:** 6 **max:** 6 **External Category** Element **Data Type** xsd:string
D_28 Group Control Number	Assigned number originated and maintained by the sender	**Cardinality** **min:** 1 **max:** 1 **Primitive Type** String **Length** **min:** 9 **max:** 9 **External Category** Element **Data Type** xsd:string
D_455 Responsible Agency Code	Code identifying the issuer of the standard; this code is used in conjunction with Data Element 480 **Selected Values** All Values in Codelist	**Cardinality** **min:** 1 **max:** 1 **Primitive Type** String **Length** **min:** 1 **max:** 1 **External Category** Element **Data Type** xsd:string **Codelist Id** D_455 **Type System** Customer_TS **Version Mode** Local **Version** 1.1
D_480 Version / Release / Industry Identifier Code	Code indicating the version, release, subrelease, and industry identifier of the EDI standard being used, including the GS and GE segments; if code in DE455 in GS segment is X, then in DE 480 positions 1-3 are the version number; positions 4-6 are the release and subrelease, level of the version; and positions 7-12 are the industry or trade association identifiers (optionally assigned by user); if code in DE455 in GS segment is T, then other formats are allowed **Selected Values** All Values in Codelist	**Cardinality** **min:** 1 **max:** 1 **Primitive Type** String **Length** **min:** 6 **max:** 6 **External Category** Element **Data Type** xsd:string **Codelist Id** D_480 **Type System** Customer_TS **Version Mode** Local **Version** 1.1

2.5 S_GE — Functional Group Trailer

Structure

Node	Card.	Prim.Type	Pos.	Length	Codelists
Interchange — Interchange Structure	1 .. 1				
├ **FunctionalGroup** — Functional Group	1 .. 1				
│ └ **S_GE** — Functional Group Trailer	1 .. 1				
│ ├ **D_97** — Number of Transaction Sets Included	1 .. 1	String		1 .. 1	
│ └ **D_28** — Group Control Number	1 .. 1	String		9 .. 9	

Documentation

Definition To indicate the end of a functional group and to provide control information Comments 1. The use of identical data interchange control numbers in the associated functional group header and trailer is designed to maximize functional group integrity. The control number is the same as that used in the corresponding header. Semantic Notes: 1. The data interchange control number GE02 in this trailer must be identical to the same data element in the associated functional group header, GS06.

Properties

Identifier S_GE

Name Functional Group Trailer

Cardinality min: 1 max: 1

Syntax Type Related

External Category Element

Leaf Elements

Identifier/Name	Description/Notes/Code Values	Properties
D_97 Number of Transaction Sets Included	Total number of transaction sets included in the functional group or interchange (transmission) group terminated by the trailer containing this data element	**Cardinality** min: 1 max: 1 **Primitive Type** String **Length** min: 1 max: 1 **External Category** Element **Data Type** xsd:string
D_28 Group Control Number	Assigned number originated and maintained by the sender	**Cardinality** min: 1 max: 1 **Primitive Type** String **Length** min: 9 max: 9 **External Category** Element **Data Type** xsd:string

2.6 S_IEA — Interchange Control Trailer

Structure

Node	Card.	Prim.Type	Pos.	Length	Codelists
Interchange — Interchange Structure	1 .. 1				
└ **S_IEA** — Interchange Control Trailer	1 .. 1				
├ **D_I16** — Number of Included Functional Groups	1 .. 1	String		1 .. 1	
└ **D_I12** — Interchange Control Number	1 .. 1	String		9 .. 9	

Documentation

Definition To define the end of an interchange of zero or more functional groups and interchange-related control segments

Properties

Identifier S_IEA

Name Interchange Control Trailer

Cardinality min: 1 max: 1

Syntax Type Related

External Category Element

Leaf Elements

Identifier/Name	Description/Notes/Code Values	Properties
D_I16 Number of Included Functional Groups	A count of the number of functional groups included in an interchange	**Cardinality** min: 1 max: 1 **Primitive Type** String **Length** min: 1 max: 1 **External Category** Element **Data Type** xsd:string
D_I12 Interchange Control Number	A control number assigned by the interchange sender	**Cardinality** min: 1 max: 1 **Primitive Type** String **Length** min: 9 max: 9 **External Category** Element **Data Type** xsd:string

3 OVERVIEW MESSAGE

General Information

Name	SAP_LBN_ANSI_X12_315
Direction	In
Status	Active
Message Type	Status Details (Ocean)
Type System	ASC_X12
Version	004010
External Category	Transaction Set

Documentation

Definition This Draft Standard for Trial Use contains the format and establishes the data contents of the Status Details (Ocean) Transaction Set (315) for use within the context of an Electronic Data Interchange (EDI) environment. The transaction set can be used to provide all the information necessary to report status or event details for selected shipments or containers. It is intended to accommodate the details for one status or event associated with many shipments or containers, as well as more than one status or event for one shipment or container.

Notes

Constraint 1 Latitude and longitude reporting is not supported.

Constraint 2 referenceEventType is not supported in EDI 315.

Constraint 3 R4/DTM/371 and R4/DTM/369 are mapped to estimated events (ARRIV_DEST and DEPARTURE). All such DTM segments within the same EDI message must use a shared location. Per-DTM location mapping is not supported. Separate EDI messages are required when different locations are needed.

Example 1

```
ISA*00*          *00*          *02*Carrier LBNID      *01*Shipper LBNID
*221115*0847*U*00401*000006693*0*P*>~
GS*QO*Carrier LBNID*Shipper LBNID*20250109*075900*000006693*X*004010~
ST*315*0001~
N9*BN*Freight Order ID~
N9*OC*Container ID~
N9*4L*Location Type~
N9*06*System ID~
N9*T7*GTT~
N9*8X*Document Type~
Q2*********Voyage Number****Vessel Name***~
SG*X1*B14~
R4*5*EA*Location ID*Port Name*Country Code*Terminal Name~
DTM*140*20241231*180000*UT~
SE*12*66930002~
GE*1*000006693~
IEA*1*000006693~
```

3.1 Structure

The following table shows the complete structure.

Node	Card.	Prim.Type	Pos.	Length	Codelists
315 — Status Details (Ocean)	1 .. 1				
├ **ST** — Transaction Set Header	1 .. 1		010		
│ ├ **143** — Transaction Set Identifier Code	1 .. 1	Token	01	3 .. 3	143
│ └ **329** — Transaction Set Control Number	1 .. 1	String	02	4 .. 9	
├ **N9** — Reference Identification	0 .. 30		030		
│ ├ **128** — Reference Identification Qualifier	1 .. 1	Token	01	2 .. 3	128
│ └ **127** — Reference Identification	0 .. 1	String	02	1 .. 30	
├ **Q2** — Status Details (Ocean)	0 .. 1		040		
│ ├ **597** — Vessel Code	0 .. 1	Token	01	1 .. 8	
│ ├ **26** — Country Code	0 .. 1	Token	02	2 .. 3	ISO_3166-1
│ ├ **373** — Date	0 .. 1	Date	03	8 .. 8	
│ ├ **373** — Date	0 .. 1	Date	04	8 .. 8	
│ ├ **373** — Date	0 .. 1	Date	05	8 .. 8	
│ ├ **80** — Lading Quantity	0 .. 1	Integer	06	1 .. 7	
│ ├ **81** — Weight	0 .. 1	Decimal	07	1 .. 10	
│ ├ **187** — Weight Qualifier	0 .. 1	Token	08	1 .. 2	187
│ ├ **55** — Flight/Voyage Number	0 .. 1	String	09	2 .. 10	
│ ├ **128** — Reference Identification Qualifier	0 .. 1	Token	10	2 .. 3	128
│ ├ **127** — Reference Identification	0 .. 1	String	11	1 .. 30	
│ ├ **897** — Vessel Code Qualifier	0 .. 1	Token	12	1 .. 1	897
│ └ **182** — Vessel Name	0 .. 1	String	13	2 .. 28	
├ **SG** — Shipment Status	0 .. 15		050		
│ ├ **157** — Shipment Status Code	0 .. 1	Token	01	1 .. 2	157
│ └ **641** — Status Reason Code	0 .. 1	Token	02	3 .. 3	641
├ **R4** — Loop R4	1 .. 20		060		
│ ├ **R4** — Port or Terminal	1 .. 1		060		
│ │ ├ **115** — Port or Terminal Function Code	1 .. 1	Token	01	1 .. 1	115
│ │ ├ **309** — Location Qualifier	0 .. 1	Token	02	1 .. 2	309
│ │ ├ **310** — Location Identifier	0 .. 1	String	03	1 .. 30	
│ │ ├ **114** — Port Name	0 .. 1	String	04	2 .. 24	
│ │ ├ **26** — Country Code	0 .. 1	Token	05	2 .. 3	ISO_3166-1
│ │ ├ **174** — Terminal Name	0 .. 1	String	06	2 .. 30	
│ │ ├ **113** — Pier Number	0 .. 1	String	07	1 .. 4	
│ │ └ **156** — State or Province Code	0 .. 1	Token	08	2 .. 2	
│ └ **DTM** — Date/Time Reference	0 .. 15		070		
│ ├ **374** — Date/Time Qualifier	1 .. 1	Token	01	3 .. 3	374
│ ├ **373** — Date	0 .. 1	Date	02	8 .. 8	
│ ├ **337** — Time	0 .. 1	Time	03	4 .. 8	
│ └ **623** — Time Code	0 .. 1	Token	04	2 .. 2	623
└ **SE** — Transaction Set Trailer	1 .. 1		090		
├ **96** — Number of Included Segments	1 .. 1	Integer	01	1 .. 10	
└ **329** — Transaction Set Control Number	1 .. 1	String	02	4 .. 9	

4 DETAILS MESSAGE

4.1 315 — Status Details (Ocean)

Structure

Node	Card.	Prim.Type	Pos.	Length	Codelists
315 — Status Details (Ocean)	1 .. 1				
├ **ST** — Transaction Set Header	1 .. 1		010		
├ **N9** — Reference Identification	0 .. 30		030		
├ **Q2** — Status Details (Ocean)	0 .. 1		040		
├ **SG** — Shipment Status	0 .. 15		050		
├ **R4** — Loop R4	1 .. 20		060		
└ **SE** — Transaction Set Trailer	1 .. 1		090		

Properties

Identifier 315

Name Status Details (Ocean)

Cardinality min: 1 max: 1

4.2 ST — Transaction Set Header

Structure

Node	Card.	Prim.Type	Pos.	Length	Codelists
315 — Status Details (Ocean)	1 .. 1				
├ **ST** — Transaction Set Header	1 .. 1		010		
│ ├ **143** — Transaction Set Identifier Code	1 .. 1	Token	01	3 .. 3	143
│ └ **329** — Transaction Set Control Number	1 .. 1	String	02	4 .. 9	

Documentation

Definition To indicate the start of a transaction set and to assign a control number

Properties

Identifier ST

Name Transaction Set Header

Cardinality min: 1 max: 1

Syntax Type Related

External Category Segment

Position 010

Level 2

Notes

Usage 1 The transaction set identifier (ST01) used by the translation routines of the interchange partners to select the appropriate transaction set definition (e.g., 810 selects the Invoice Transaction Set).

Leaf Elements

Identifier/Name	Description/Notes/Code Values	Properties
143 Transaction Set Identifier Code	Code uniquely identifying a Transaction Set **Selected Values** All Values in Codelist	**Cardinality** min: 1 max: 1 **Primitive Type** Token **Length** min: 3 max: 3 **External Category** Simple Data Element **Data Type** ID **Position** 01 **Codelist Id** 143 **Type System** ASC_X12 **Version Mode** Current **Version** 004010
329 Transaction Set Control Number	Identifying control number that must be unique within the transaction set functional group assigned by the originator for a transaction set	**Cardinality** min: 1 max: 1 **Primitive Type** String **Length** min: 4 max: 9 **External Category** Simple Data Element **Data Type** AN **Position** 02

4.3 N9 — Reference Identification

Structure

Node	Card.	Prim.Type	Pos.	Length	Codelists
315 — Status Details (Ocean)	1 .. 1				
├ **N9** — Reference Identification	0 .. 30		030		
│ ├ **128** — Reference Identification Qualifier	1 .. 1	Token	01	2 .. 3	128
│ └ **127** — Reference Identification	0 .. 1	String	02	1 .. 30	

Documentation

Definition To transmit identifying information as specified by the Reference Identification Qualifier

Properties

Identifier N9

Name Reference Identification

Cardinality min: 0 max: 30

Syntax Type Related

External Category Segment

Position 030

Level 2

Notes

Usage 1 N906 reflects the time zone which the time reflects.

Usage 2 N907 contains data relating to the value cited in N902.

Constraint 1 R0203 Required - At least one of those noted must be used

Constraint 2 C0605 Conditional - If the first element is present, then the others must be present

Leaf Elements

Identifier/Name	Description/Notes/Code Values	Properties
128 Reference Identification Qualifier	Code qualifying the Reference Identification **Selected Values** **Code** QN **Name** Stop Sequence Number **Code** OC **Name** Ocean Container Number **Code** 4L **Name** Location-specific Services Reference Number **Code** BN **Name** Booking Number **Code** 06 **Name** System Number **Code** T7 **Name** Affected Subsystem Code **Code** 8X **Name** Transaction Category or Type	**Cardinality** min: 1 max: 1 **Primitive Type** Token **Length** min: 2 max: 3 **External Category** Simple Data Element **Data Type** ID **Position** 01 **Codelist Id** 128 **Type System** ASC_X12 **Version Mode** Current **Version** 004010
127 Reference Identification	Reference information as defined for a particular Transaction Set or as specified by the Reference Identification Qualifier	**Cardinality** min: 0 max: 1 **Primitive Type** String **Length** min: 1 max: 30 **External Category** Simple Data Element **Data Type** AN **Position** 02

4.4 Q2 — Status Details (Ocean)

Structure

Node	Card.	Prim.Type	Pos.	Length	Codelists
315 — Status Details (Ocean)	1 .. 1				
├ **Q2** — Status Details (Ocean)	0 .. 1		040		
│ ├ **597** — Vessel Code	0 .. 1	Token	01	1 .. 8	
│ ├ **26** — Country Code	0 .. 1	Token	02	2 .. 3	ISO_3166-1
│ ├ **373** — Date	0 .. 1	Date	03	8 .. 8	
│ ├ **373** — Date	0 .. 1	Date	04	8 .. 8	
│ ├ **373** — Date	0 .. 1	Date	05	8 .. 8	
│ ├ **80** — Lading Quantity	0 .. 1	Integer	06	1 .. 7	
│ ├ **81** — Weight	0 .. 1	Decimal	07	1 .. 10	
│ ├ **187** — Weight Qualifier	0 .. 1	Token	08	1 .. 2	187
│ ├ **55** — Flight/Voyage Number	0 .. 1	String	09	2 .. 10	
│ ├ **128** — Reference Identification Qualifier	0 .. 1	Token	10	2 .. 3	128
│ ├ **127** — Reference Identification	0 .. 1	String	11	1 .. 30	
│ ├ **897** — Vessel Code Qualifier	0 .. 1	Token	12	1 .. 1	897
│ └ **182** — Vessel Name	0 .. 1	String	13	2 .. 28	

Documentation

Definition To transmit identifying information relative to identification of vessel, transportation dates, lading quantity, weight, and cube

Properties

Identifier Q2

Name Status Details (Ocean)

Cardinality min: 0 max: 1

Syntax Type Related

External Category Segment

Position 040

Level 2

Notes

Usage 1 Q202 is the code identifying the country in which the ship (vessel) is registered.

Usage 2 Q203 is the required pier date.

Usage 3 Q204 is the date of departure of the vessel.

Usage 4 Q205 is the date the shipment was unloaded from the vessel.

Constraint 1 P070816 Paired Multiple - If any are used, all must be used

Constraint 2 C1011 Conditional - If the first element is present, then the others must be present

Constraint 3 P1415 Paired Multiple - If any are used, all must be used

Leaf Elements

Identifier/Name	Description/Notes/Code Values	Properties
597 Vessel Code	Code identifying vessel	**Cardinality** min: 0 max: 1 **Primitive Type** Token **Length** min: 1 max: 8 **External Category** Simple Data Element **Data Type** ID **Position** 01
26 Country Code	Code identifying the country **Selected Values**	**Cardinality** min: 0 max: 1 **Primitive Type** Token **Length** min: 2 max: 3

	All Values in Codelist	**External Category** Simple Data Element **Data Type** ID **Position** 02 **Codelist Id** ISO_3166-1 **Type System** ISO_CodelistsAndSchemes **Version Mode** Latest **Version** 2013
373 Date	Date expressed as CCYYMMDD	**Cardinality** **min:** 0 **max:** 1 **Primitive Type** Date **Length** **min:** 8 **max:** 8 **Date Time Format** CCYYMMDD **External Category** Simple Data Element **Data Type** DT **Position** 03
373 Date	Date expressed as CCYYMMDD	**Cardinality** **min:** 0 **max:** 1 **Primitive Type** Date **Length** **min:** 8 **max:** 8 **Date Time Format** CCYYMMDD **External Category** Simple Data Element **Data Type** DT **Position** 04
373 Date	Date expressed as CCYYMMDD	**Cardinality** **min:** 0 **max:** 1 **Primitive Type** Date **Length** **min:** 8 **max:** 8 **Date Time Format** CCYYMMDD **External Category** Simple Data Element **Data Type** DT **Position** 05
80 Lading Quantity	Number of units (pieces) of the lading commodity	**Cardinality** **min:** 0 **max:** 1 **Primitive Type** Integer **Length** **min:** 1 **max:** 7 **Fraction Digits** 0 **Total Digits** 7 **External Category** Simple Data Element **Data Type** N0 **Position** 06
81 Weight	Numeric value of weight	**Cardinality** **min:** 0 **max:** 1 **Primitive Type** Decimal **Length** **min:** 1 **max:** 10 **Total Digits** 10 **External Category** Simple Data Element **Data Type** R **Position** 07
187 Weight Qualifier	Code defining the type of weight **Selected Values** All Values in Codelist	**Cardinality** **min:** 0 **max:** 1 **Primitive Type** Token **Length** **min:** 1 **max:** 2 **External Category** Simple Data Element **Data Type** ID **Position** 08 **Codelist Id** 187 **Type System** ASC_X12 **Version Mode** Current **Version** 004010
55 Flight/Voyage Number	Identifying designator for the particular flight or voyage on which the cargo travels	**Cardinality** **min:** 0 **max:** 1 **Primitive Type** String **Length** **min:** 2 **max:** 10 **External Category** Simple Data Element **Data Type** AN **Position** 09
128 Reference Identification Qualifier	Code qualifying the Reference Identification **Selected Values**	**Cardinality** **min:** 0 **max:** 1 **Primitive Type** Token **Length** **min:** 2 **max:** 3