	Code FA **Name** Fahrenheit **Code** KV **Name** Kelvin **Code** NB **Name** Barge **Code** CC **Name** Cubic Centimeter **Code** 8C **Name** Cord **Code** CF **Name** Cubic Feet **Code** GA **Name** Gallon **Code** NL **Name** Load **Code** DM **Name** Decimeter **Code** CI **Name** Cubic Inches **Code** NC **Name** Car **Code** CH **Name** Container **Code** LT **Name** Liter **Code** CR **Name** Cubic Meter **Code** CY **Name** Cubic Yard **Code** FC **Name** 1000 Cubic Feet **Code** LY **Name** Linear Yard **Code** LM **Name** Linear Meter **Code** LF **Name** Linear Foot **Code** C8 **Name** Cubic Decimeter **Code** MP **Name** Metric Ton **Code** LG **Name** Long Ton 2240 pounds as used in the U.K.	

4.10 TD5 — Carrier Details (Routing Sequence/Transit Time)

Structure

Node	Card.	Prim.Type	Pos.	Length	Codelists
840 — Request for Quotation	1 .. 1				
├ **TD5** — Carrier Details (Routing Sequence/Transit Time)	0 .. 12		240		
│ ├ **133** — Routing Sequence Code	0 .. 1	Token	01	1 .. 2	133
│ ├ **66** — Identification Code Qualifier	0 .. 1	Token	02	1 .. 2	66
│ ├ **67** — Identification Code	0 .. 1	String	03	2 .. 80	
│ └ **91** — Transportation Method/Type Code	0 .. 1	Token	04	1 .. 2	91

Documentation

Definition To specify the carrier and sequence of routing and provide transit time information

Properties

Identifier TD5

Name Carrier Details (Routing Sequence/Transit Time)

Cardinality min: 0 max: 12

Syntax Type Related

External Category Segment

Position 240

Level 2

Notes

Usage 1 TD515 is the country where the service is to be performed.

Constraint 1 R0204050612 Required - At least one of those noted must be used

Constraint 2 C0203 Conditional - If the first element is present, then the others must be present

Constraint 3 C0708 Conditional - If the first element is present, then the others must be present

Constraint 4 C1011 Conditional - If the first element is present, then the others must be present

Constraint 5 C1312 Conditional - If the first element is present, then the others must be present

Constraint 6 C1413 Conditional - If the first element is present, then the others must be present

Constraint 7 C1512 Conditional - If the first element is present, then the others must be present

Comment 1 When specifying a routing sequence to be used for the shipment movement in lieu of specifying each carrier within the movement, use TD502 to identify the party responsible for defining the routing sequence, and use TD503 to identify the actual routing sequence, specified by the party identified in TD502.

Leaf Elements

Identifier/Name	Description/Notes/Code Values	Properties
133 Routing Sequence Code	Code describing the relationship of a carrier to a specific shipment movement **Selected Values** All Values in Codelist	**Cardinality** min: 0 max: 1 **Primitive Type** Token **Length** min: 1 max: 2 **External Category** Simple Data Element **Data Type** ID **Position** 01 **Codelist Id** 133 **Type System** ASC_X12 **Version Mode** Current **Version** 004010
66 Identification Code Qualifier	Code designating the system/method of code structure used for Identification Code (67) **Selected Values**	**Cardinality** min: 0 max: 1 **Primitive Type** Token **Length** min: 1 max: 2 **External Category** Simple Data Element

	All Values in Codelist	**Data Type** ID **Position** 02 **Codelist Id** 66 **Type System** ASC_X12 **Version Mode** Current **Version** 004010
67 Identification Code	Code identifying a party or other code	**Cardinality** **min:** 0 **max:** 1 **Primitive Type** String **Length** **min:** 2 **max:** 80 **External Category** Simple Data Element **Data Type** AN **Position** 03
91 Transportation Method/Type Code	Code specifying the method or type of transportation for the shipment **Selected Values** **Code** S **Name** Ocean **Code** R **Name** Rail **Code** M **Name** Motor (Common Carrier) **Code** A **Name** Air **Code** U **Name** Private Parcel Service	**Cardinality** **min:** 0 **max:** 1 **Primitive Type** Token **Length** **min:** 1 **max:** 2 **External Category** Simple Data Element **Data Type** ID **Position** 04 **Codelist Id** 91 **Type System** ASC_X12 **Version Mode** Current **Version** 004010

4.11 RRA — Required Response

Structure

Node	Card.	Prim.Type	Pos.	Length	Codelists
840 — Request for Quotation	1 .. 1				
├ **RRA** — Required Response	0 .. 100		280		
│ └ **701** — Information Type	1 .. 1	Token	01	2 .. 2	701

Documentation

Definition To indicate information that is required to be included in the response

Properties

Identifier RRA

Name Required Response

Cardinality min: 0 max: 100

Syntax Type Related

External Category Segment

Position 280

Level 2

Notes

Usage 1 Use RRA02 only to specify applicable regulatory or contractual clause.

Leaf Elements

Identifier/Name	Description/Notes/Code Values	Properties
701 Information Type	Code specifying the information required in the response **Selected Values** **Code** 16 **Name** All Information	**Cardinality** min: 1 max: 1 **Primitive Type** Token **Length** min: 2 max: 2 **External Category** Simple Data Element **Data Type** ID **Position** 01 **Codelist Id** 701 **Type System** ASC_X12 **Version Mode** Current **Version** 004010

4.12 N9 — Loop N9

Structure

Node	Card.	Prim.Type	Pos.	Length	Codelists
840 — Request for Quotation	1 .. 1				
├ **N9** — Loop N9	0 .. 1000		290		
│ ├ **N9** — Reference Identification	1 .. 1		290		
│ ├ **DTM** — Date/Time Reference	0 .. *		295		
│ └ **MSG** — Message Text	0 .. 1000		300		

Properties

Identifier N9

Name Loop N9

Cardinality min: 0 max: 1000

Syntax Type Related

External Category Loop

Position 290

Level 2

4.13 N9 — Reference Identification

Structure

Node	Card.	Prim.Type	Pos.	Length	Codelists
840 — Request for Quotation	1 .. 1				
├ **N9** — Loop N9	0 .. 1000		290		
│ ├ **N9** — Reference Identification	1 .. 1		290		
│ │ ├ **128** — Reference Identification Qualifier	1 .. 1	Token	01	2 .. 3	128
│ │ ├ **127** — Reference Identification	0 .. 1	String	02	1 .. 30	
│ │ └ **369** — Free-form Description	0 .. 1	String	03	1 .. 45	

Documentation

Definition To transmit identifying information as specified by the Reference Identification Qualifier

Properties

Identifier N9

Name Reference Identification

Cardinality min: 1 max: 1

Syntax Type Related

External Category Segment

Position 290

Level 3

Notes

Usage 1 N906 reflects the time zone which the time reflects.

Usage 2 N907 contains data relating to the value cited in N902.

Constraint 1 R0203 Required - At least one of those noted must be used

Constraint 2 C0605 Conditional - If the first element is present, then the others must be present

Leaf Elements

Identifier/Name	Description/Notes/Code Values	Properties
128 Reference Identification Qualifier	Code qualifying the Reference Identification **Selected Values** **Code** L1 **Name** Letters or Notes **Code** 55 **Name** Sequence Number **Code** ZZ **Name** Mutually Defined	**Cardinality** min: 1 max: 1 **Primitive Type** Token **Length** min: 2 max: 3 **External Category** Simple Data Element **Data Type** ID **Position** 01 **Codelist Id** 128 **Type System** ASC_X12 **Version Mode** Current **Version** 004010
127 Reference Identification	Reference information as defined for a particular Transaction Set or as specified by the Reference Identification Qualifier	**Cardinality** min: 0 max: 1 **Primitive Type** String **Length** min: 1 max: 30 **External Category** Simple Data Element **Data Type** AN **Position** 02
369 Free-form Description	Free-form descriptive text	**Cardinality** min: 0 max: 1 **Primitive Type** String **Length** min: 1 max: 45 **External Category** Simple Data Element **Data Type** AN **Position** 03

4.14 DTM — Date/Time Reference

Structure

Node	Card.	Prim.Type	Pos.	Length	Codelists
840 — Request for Quotation	1 .. 1				
├ **N9** — Loop N9	0 .. 1000		290		
│ ├ **DTM** — Date/Time Reference	0 .. *		295		
│ │ ├ **374** — Date/Time Qualifier	1 .. 1	Token	01	3 .. 3	374
│ │ ├ **373** — Date	0 .. 1	Date	02	8 .. 8	
│ │ ├ **337** — Time	0 .. 1	Time	03	4 .. 8	
│ │ └ **623** — Time Code	0 .. 1	Token	04	2 .. 2	623

Documentation

Definition To specify pertinent dates and times

Properties

Identifier DTM

Name Date/Time Reference

Cardinality min: 0 max: *

Syntax Type Related

External Category Segment

Position 295

Level 3

Notes

Constraint 1 R020305 Required - At least one of those noted must be used

Constraint 2 C0403 Conditional - If the first element is present, then the others must be present

Constraint 3 P0506 Paired Multiple - If any are used, all must be used

Leaf Elements

Identifier/Name	Description/Notes/Code Values	Properties
374 Date/Time Qualifier	Code specifying type of date or time, or both date and time **Selected Values** **Code** 010 **Name** Requested Ship **Code** 017 **Name** Estimated Delivery **Code** 037 **Name** Ship Not Before **Code** 038 **Name** Ship No Later **Code** 064 **Name** Do Not Deliver Before **Code** 071 **Name** Requested for Delivery (After and Including) **Code** 074 **Name** Requested for Delivery (Prior to and Including) **Code** 063 **Name** Do Not Deliver After **Code** 081 **Name** Requested for Shipment (After and Including) **Code** 083 **Name** Scheduled for Shipment (Prior to and Including)	**Cardinality** min: 1 max: 1 **Primitive Type** Token **Length** min: 3 max: 3 **External Category** Simple Data Element **Data Type** ID **Position** 01 **Codelist Id** 374 **Type System** ASC_X12 **Version Mode** Current **Version** 004010
373 Date	Date expressed as CCYYMMDD	**Cardinality** min: 0 max: 1 **Primitive Type** Date **Length** min: 8 max: 8 **Date Time Format** CCYYMMDD **External Category** Simple Data Element **Data Type** DT **Position** 02

337 Time	Time expressed in 24-hour clock time as follows: HHMM, or HHMMSS, or HHMMSSD, or HHMMSSDD, where H = hours (00-23), M = minutes (00-59), S = integer seconds (00-59) and DD = decimal seconds; decimal seconds are expressed as follows: D = tenths (0-9) and DD = hundredths (00-99)	**Cardinality** min: 0 max: 1 **Primitive Type** Time **Length** min: 4 max: 8 **Date Time Format** hhmm[ss[f[f]]] **External Category** Simple Data Element **Data Type** TM **Position** 03
623 Time Code	Code identifying the time. In accordance with International Standards Organization standard 8601, time can be specified by a + or - and an indication in hours in relation to Universal Time Coordinate (UTC) time; since + is a restricted character, + and - are substituted by P and M in the codes that follow **Selected Values** All Values in Codelist	**Cardinality** min: 0 max: 1 **Primitive Type** Token **Length** min: 2 max: 2 **External Category** Simple Data Element **Data Type** ID **Position** 04 **Codelist Id** 623 **Type System** ASC_X12 **Version Mode** Current **Version** 004010

4.15 MSG — Message Text

Structure

Node	Card.	Prim.Type	Pos.	Length	Codelists
840 — Request for Quotation	1 .. 1				
├ **N9** — Loop N9	0 .. 1000		290		
│ └ **MSG** — Message Text	0 .. 1000		300		
│ └ **933** — Free-Form Message Text	1 .. 1	String	01	1 .. 264	

Documentation

Definition To provide a free-form format that allows the transmission of text information

Properties

Identifier MSG

Name Message Text

Cardinality min: 0 max: 1000

Syntax Type Related

External Category Segment

Position 300

Level 3

Notes

Usage 1 MSG03 is the number of lines to advance before printing.

Constraint 1 C0302 Conditional - If the first element is present, then the others must be present

Comment 1 MSG02 is not related to the specific characteristics of a printer, but identifies top of page, advance a line, etc.

Comment 2 If MSG02 is “AA - Advance the specified number of lines before print” then MSG03 is required.

Leaf Elements

Identifier/Name	Description/Notes/Code Values	Properties
933 Free-Form Message Text	Free-form message text	**Cardinality** min: 1 max: 1 **Primitive Type** String **Length** min: 1 max: 264 **External Category** Simple Data Element **Data Type** AN **Position** 01

4.16 N1 — Loop N1

Structure

Node	Card.	Prim.Type	Pos.	Length	Codelists
840 — Request for Quotation	1 .. 1				
├ **N1** — Loop N1	0 .. 10000		310		
│ ├ **N1** — Name	1 .. 1		310		
│ ├ **N3** — Address Information	0 .. 2		330		
│ ├ **N4** — Geographic Location	0 .. *		340		
│ ├ **REF** — Reference Identification	0 .. 12		350		
│ └ **PER** — Administrative Communications Contact	0 .. *		360		

Properties

Identifier N1

Name Loop N1

Cardinality min: 0 max: 10000

Syntax Type Related

External Category Loop

Position 310

Level 2