4.17 N1 — Name

Structure

Node	Card.	Prim.Type	Pos.	Length	Codelists
840 — Request for Quotation	1 .. 1				
├ **N1** — Loop N1	0 .. 10000		310		
│ ├ **N1** — Name	1 .. 1		310		
│ │ ├ **98** — Entity Identifier Code	1 .. 1	Token	01	2 .. 3	98
│ │ └ **93** — Name	0 .. 1	String	02	1 .. 60	

Documentation

Definition To identify a party by type of organization, name, and code

Properties

Identifier N1

Name Name

Cardinality min: 1 max: 1

Syntax Type Related

External Category Segment

Position 310

Level 3

Notes

Constraint 1 R0203 Required - At least one of those noted must be used

Constraint 2 P0304 Paired Multiple - If any are used, all must be used

Comment 1 This segment, used alone, provides the most efficient method of providing organizational identification. To obtain this efficiency the “ID Code” (N104) must provide a key to the table maintained by the transaction processing party.

Comment 2 N105 and N106 further define the type of entity in N101.

Leaf Elements

Identifier/Name	Description/Notes/Code Values	Properties
98 Entity Identifier Code	Code identifying an organizational entity, a physical location, property or an individual **Selected Values** **Code** SF **Name** Ship From **Code** ST **Name** Ship To **Code** BY **Name** Buying Party (Purchaser) **Code** CA **Name** Carrier	**Cardinality** min: 1 max: 1 **Primitive Type** Token **Length** min: 2 max: 3 **External Category** Simple Data Element **Data Type** ID **Position** 01 **Codelist Id** 98 **Type System** ASC_X12 **Version Mode** Current **Version** 004010
93 Name	Free-form name	**Cardinality** min: 0 max: 1 **Primitive Type** String **Length** min: 1 max: 60 **External Category** Simple Data Element **Data Type** AN **Position** 02

4.18 N3 — Address Information

Structure

Node	Card.	Prim.Type	Pos.	Length	Codelists
840 — Request for Quotation	1 .. 1				
├ **N1** — Loop N1	0 .. 10000		310		
│ ├ **N3** — Address Information	0 .. 2		330		
│ │ ├ **166** — Address Information	1 .. 1	String	01	1 .. 55	
│ │ └ **166** — Address Information	0 .. 1	String	02	1 .. 55	

Documentation

Definition To specify the location of the named party

Properties

Identifier N3

Name Address Information

Cardinality min: 0 max: 2

Syntax Type Related

External Category Segment

Position 330

Level 3

Leaf Elements

Identifier/Name	Description/Notes/Code Values	Properties
166 Address Information	Address information	**Cardinality** min: 1 max: 1 **Primitive Type** String **Length** min: 1 max: 55 **External Category** Simple Data Element **Data Type** AN **Position** 01
166 Address Information	Address information	**Cardinality** min: 0 max: 1 **Primitive Type** String **Length** min: 1 max: 55 **External Category** Simple Data Element **Data Type** AN **Position** 02

4.19 N4 — Geographic Location

Structure

Node	Card.	Prim.Type	Pos.	Length	Codelists
840 — Request for Quotation	1 .. 1				
├ **N1** — Loop N1	0 .. 10000		310		
│ ├ **N4** — Geographic Location	0 .. *		340		
│ │ ├ **19** — City Name	0 .. 1	String	01	2 .. 30	
│ │ ├ **156** — State or Province Code	0 .. 1	Token	02	2 .. 2	
│ │ ├ **116** — Postal Code	0 .. 1	Token	03	3 .. 15	
│ │ └ **26** — Country Code	0 .. 1	Token	04	2 .. 3	ISO_3166-1

Documentation

Definition To specify the geographic place of the named party

Properties

Identifier N4

Name Geographic Location

Cardinality min: 0 max: *

Syntax Type Related

External Category Segment

Position 340

Level 3

Notes

Constraint 1 C0605 Conditional - If the first element is present, then the others must be present

Comment 1 A combination of either N401 through N404, or N405 and N406 may be adequate to specify a location.

Comment 2 N402 is required only if city name (N401) is in the U.S. or Canada.

Leaf Elements

Identifier/Name	Description/Notes/Code Values	Properties
19 City Name	Free-form text for city name	**Cardinality** min: 0 max: 1 **Primitive Type** String **Length** min: 2 max: 30 **External Category** Simple Data Element **Data Type** AN **Position** 01
156 State or Province Code	Code (Standard State/Province) as defined by appropriate government agency	**Cardinality** min: 0 max: 1 **Primitive Type** Token **Length** min: 2 max: 2 **External Category** Simple Data Element **Data Type** ID **Position** 02
116 Postal Code	Code defining international postal zone code excluding punctuation and blanks (zip code for United States)	**Cardinality** min: 0 max: 1 **Primitive Type** Token **Length** min: 3 max: 15 **External Category** Simple Data Element **Data Type** ID **Position** 03
26 Country Code	Code identifying the country **Selected Values** All Values in Codelist	**Cardinality** min: 0 max: 1 **Primitive Type** Token **Length** min: 2 max: 3 **External Category** Simple Data Element **Data Type** ID

		Position 04 **Codelist Id** ISO_3166-1 **Type System** ISO_CodelistsAndSchemes **Version Mode** Latest **Version** 2013

4.20 REF — Reference Identification

Structure

Node	Card.	Prim.Type	Pos.	Length	Codelists
840 — Request for Quotation	1 .. 1				
├ **N1** — Loop N1	0 .. 10000		310		
│ ├ **REF** — Reference Identification	0 .. 12		350		
│ │ ├ **128** — Reference Identification Qualifier	1 .. 1	Token	01	2 .. 3	128
│ │ ├ **127** — Reference Identification	0 .. 1	String	02	1 .. 30	
│ │ └ **352** — Description	0 .. 1	String	03	1 .. 80	

Documentation

Definition To specify identifying information

Properties

Identifier REF

Name Reference Identification

Cardinality min: 0 max: 12

Syntax Type Related

External Category Segment

Position 350

Level 3

Notes

Usage 1 REF04 contains data relating to the value cited in REF02.

Constraint 1 R0203 Required - At least one of those noted must be used

Leaf Elements

Identifier/Name	Description/Notes/Code Values	Properties
128 Reference Identification Qualifier	Code qualifying the Reference Identification **Selected Values** **Code** 55 **Name** Sequence Number **Code** CN **Name** Carrier's Reference Number (PRO/Invoice) **Code** 12 **Name** Billing Account Account number under which billing is rendered	**Cardinality** min: 1 max: 1 **Primitive Type** Token **Length** min: 2 max: 3 **External Category** Simple Data Element **Data Type** ID **Position** 01 **Codelist Id** 128 **Type System** ASC_X12 **Version Mode** Current **Version** 004010
127 Reference Identification	Reference information as defined for a particular Transaction Set or as specified by the Reference Identification Qualifier	**Cardinality** min: 0 max: 1 **Primitive Type** String **Length** min: 1 max: 30 **External Category** Simple Data Element **Data Type** AN **Position** 02
352 Description	A free-form description to clarify the related data elements and their content	**Cardinality** min: 0 max: 1 **Primitive Type** String **Length** min: 1 max: 80 **External Category** Simple Data Element **Data Type** AN **Position** 03

4.21 PER — Administrative Communications Contact

Structure

Node	Card.	Prim.Type	Pos.	Length	Codelists
840 — Request for Quotation	1 .. 1				
├ **N1** — Loop N1	0 .. 10000		310		
│ └ **PER** — Administrative Communications Contact	0 .. *		360		
│ ├ **366** — Contact Function Code	1 .. 1	Token	01	2 .. 2	366
│ ├ **93** — Name	0 .. 1	String	02	1 .. 60	
│ ├ **365** — Communication Number Qualifier	0 .. 1	Token	03	2 .. 2	365
│ ├ **364** — Communication Number	0 .. 1	String	04	1 .. 80	
│ ├ **365** — Communication Number Qualifier	0 .. 1	Token	05	2 .. 2	365
│ └ **364** — Communication Number	0 .. 1	String	06	1 .. 80	

Documentation

Definition To identify a person or office to whom administrative communications should be directed

Properties

Identifier PER

Name Administrative Communications Contact

Cardinality min: 0 max: *

Syntax Type Related

External Category Segment

Position 360

Level 3

Notes

Constraint 1 P0304 Paired Multiple - If any are used, all must be used

Constraint 2 P0506 Paired Multiple - If any are used, all must be used

Constraint 3 P0708 Paired Multiple - If any are used, all must be used

Leaf Elements

Identifier/Name	Description/Notes/Code Values	Properties
366 Contact Function Code	Code identifying the major duty or responsibility of the person or group named **Selected Values** **Code** IC **Name** Information Contact	**Cardinality** min: 1 max: 1 **Primitive Type** Token **Length** min: 2 max: 2 **External Category** Simple Data Element **Data Type** ID **Position** 01 **Codelist Id** 366 **Type System** ASC_X12 **Version Mode** Current **Version** 004010
93 Name	Free-form name	**Cardinality** min: 0 max: 1 **Primitive Type** String **Length** min: 1 max: 60 **External Category** Simple Data Element **Data Type** AN **Position** 02
365 Communication Number Qualifier	Code identifying the type of communication number **Selected Values** **Code** TE **Name** Telephone	**Cardinality** min: 0 max: 1 **Primitive Type** Token **Length** min: 2 max: 2 **External Category** Simple Data Element **Data Type** ID

	Code EM **Name** Electronic Mail	**Position** 03 **Codelist Id** 365 **Type System** ASC_X12 **Version Mode** Current **Version** 004010
364 Communication Number	Complete communications number including country or area code when applicable	**Cardinality** **min:** 0 **max:** 1 **Primitive Type** String **Length** **min:** 1 **max:** 80 **External Category** Simple Data Element **Data Type** AN **Position** 04
365 Communication Number Qualifier	Code identifying the type of communication number **Selected Values** **Code** TE **Name** Telephone **Code** EM **Name** Electronic Mail	**Cardinality** **min:** 0 **max:** 1 **Primitive Type** Token **Length** **min:** 2 **max:** 2 **External Category** Simple Data Element **Data Type** ID **Position** 05 **Codelist Id** 365 **Type System** ASC_X12 **Version Mode** Current **Version** 004010
364 Communication Number	Complete communications number including country or area code when applicable	**Cardinality** **min:** 0 **max:** 1 **Primitive Type** String **Length** **min:** 1 **max:** 80 **External Category** Simple Data Element **Data Type** AN **Position** 06

4.22 PO1 — Loop PO1

Structure

Node	Card.	Prim.Type	Pos.	Length	Codelists
840 — Request for Quotation	1 .. 1				
├ **PO1** — Loop PO1	1 .. 100000		010		
│ ├ **PO1** — Baseline Item Data	1 .. 1		010		
│ ├ **MEA** — Measurements	0 .. 40		049		
│ ├ **PID** — Loop PID	0 .. 1000		050		
│ ├ **REF** — Reference Identification	0 .. *		100		
│ └ **TD4** — Carrier Details (Special Handling, or Hazardous Materials, or Both)	0 .. 5		270		

Properties

Identifier PO1

Name Loop PO1

Cardinality min: 1 max: 100000

Syntax Type Related

External Category Loop

Position 010

Level 2

4.23 PO1 — Baseline Item Data

Structure

Node	Card.	Prim.Type	Pos.	Length	Codelists
840 — Request for Quotation	1 .. 1				
├ **PO1** — Loop PO1	1 .. 100000		010		
│ ├ **PO1** — Baseline Item Data	1 .. 1		010		
│ │ ├ **350** — Assigned Identification	0 .. 1	String	01	1 .. 20	
│ │ ├ **330** — Quantity Ordered	0 .. 1	Decimal	02	1 .. 15	
│ │ └ **355** — Unit or Basis for Measurement Code	0 .. 1	Token	03	2 .. 2	355

Documentation

Definition To specify basic and most frequently used line item data

Properties

Identifier PO1

Name Baseline Item Data

Cardinality min: 1 max: 1

Syntax Type Related

External Category Segment

Position 010

Level 3

Notes

Constraint 1 C0302 Conditional - If the first element is present, then the others must be present

Constraint 2 C0504 Conditional - If the first element is present, then the others must be present

Constraint 3 P0607 Paired Multiple - If any are used, all must be used

Constraint 4 P0809 Paired Multiple - If any are used, all must be used

Constraint 5 P1011 Paired Multiple - If any are used, all must be used

Constraint 6 P1213 Paired Multiple - If any are used, all must be used

Constraint 7 P1415 Paired Multiple - If any are used, all must be used

Constraint 8 P1617 Paired Multiple - If any are used, all must be used

Constraint 9 P1819 Paired Multiple - If any are used, all must be used

Constraint 10 P2021 Paired Multiple - If any are used, all must be used

Constraint 11 P2223 Paired Multiple - If any are used, all must be used

Constraint 12 P2425 Paired Multiple - If any are used, all must be used

Comment 1 See the Data Element Dictionary for a complete list of IDs.

Comment 2 PO101 is the line item identification.

Comment 3 PO106 through PO125 provide for ten different product/service IDs per each item. For example: Case, Color, Drawing No., U.P.C. No., ISBN No., Model No., or SKU.

Leaf Elements

Identifier/Name	Description/Notes/Code Values	Properties
350 Assigned Identification	Alphanumeric characters assigned for differentiation within a transaction set	**Cardinality** min: 0 max: 1 **Primitive Type** String **Length** min: 1 max: 20 **External Category** Simple Data Element **Data Type** AN **Position** 01

330 Quantity Ordered	Quantity ordered	**Cardinality** min: 0 max: 1 **Primitive Type** Decimal **Length** min: 1 max: 15 **Total Digits** 15 **External Category** Simple Data Element **Data Type** R **Position** 02
355 Unit or Basis for Measurement Code	Code specifying the units in which a value is being expressed, or manner in which a measurement has been taken **Selected Values** **Code** BI **Name** Bar A centimeter-gram-second unit of pressure, equal to one million dynes per square centimeter **Code** B8 **Name** Board **Code** BD **Name** Bundle **Code** BG **Name** Bag **Code** BC **Name** Bucket **Code** BA **Name** Bale **Code** BO **Name** Bottle **Code** BU **Name** Bushel 32 dry quarts **Code** CP **Name** Crate **Code** CN **Name** Can **Code** CH **Name** Container **Code** CX **Name** Coil **Code** CB **Name** Carboy **Code** CQ **Name** Cartridge **Code** CA **Name** Case **Code** CT **Name** Carton **Code** CL **Name** Cylinder **Code** CS **Name** Cassette **Code** DC **Name** Disk (Disc) **Code** DR **Name** Drum **Code** DZ **Name** Dozen **Code** NT **Name** Trailer **Code** EA **Name** Each **Code** PC **Name** Piece **Code** JR **Name** Jar **Code** NB **Name** Barge **Code** PK **Name** Package **Code** PL **Name** Pallet/Unit Load **Code** PH **Name** Pack (PAK) **Code** PA **Name** Pail **Code** PR **Name** Pair **Code** SO **Name** Spool **Code** SH **Name** Sheet **Code** TE **Name** Tote **Code** TB **Name** Tube **Code** BN **Name** Bulk **Code** UL **Name** Unitless Unit of Measure for properties or test results without units of measure **Code** LT **Name** Liter	**Cardinality** min: 0 max: 1 **Primitive Type** Token **Length** min: 2 max: 2 **External Category** Simple Data Element **Data Type** ID **Position** 03 **Codelist Id** 355 **Type System** ASC_X12 **Version Mode** Current **Version** 004010