4.4 CUR — Currency

Structure

Node	Card.	Prim.Type	Pos.	Length	Codelists
843 — Response to Request for Quotation	1 .. 1				
├ **CUR** — Currency	0 .. 1		040		
│ ├ **98** — Entity Identifier Code	1 .. 1	Token	01	2 .. 3	98
│ └ **100** — Currency Code	1 .. 1	Token	02	3 .. 3	ISO_4217

Documentation

Definition To specify the currency (dollars, pounds, francs, etc.) used in a transaction

Properties

Identifier CUR

Name Currency

Cardinality min: 0 max: 1

Syntax Type Related

External Category Segment

Position 040

Level 2

Notes

Constraint 1 C0807 Conditional - If the first element is present, then the others must be present

Constraint 2 C0907 Conditional - If the first element is present, then the others must be present

Constraint 3 L101112 List Conditional - If the first element is present, then at least one of the others must be present

Constraint 4 C1110 Conditional - If the first element is present, then the others must be present

Constraint 5 C1210 Conditional - If the first element is present, then the others must be present

Constraint 6 L131415 List Conditional - If the first element is present, then at least one of the others must be present

Constraint 7 C1413 Conditional - If the first element is present, then the others must be present

Constraint 8 C1513 Conditional - If the first element is present, then the others must be present

Constraint 9 L161718 List Conditional - If the first element is present, then at least one of the others must be present

Constraint 10 C1716 Conditional - If the first element is present, then the others must be present

Constraint 11 C1816 Conditional - If the first element is present, then the others must be present

Constraint 12 L192021 List Conditional - If the first element is present, then at least one of the others must be present

Constraint 13 C2019 Conditional - If the first element is present, then the others must be present

Constraint 14 C2119 Conditional - If the first element is present, then the others must be present

Comment 1 See Figures Appendix for examples detailing the use of the CUR segment.

Leaf Elements

Identifier/Name	Description/Notes/Code Values	Properties
98 Entity Identifier Code	Code identifying an organizational entity, a physical location, property or an individual **Selected Values** **Code** BY **Name** Buying Party (Purchaser)	**Cardinality** min: 1 max: 1 **Primitive Type** Token **Length** min: 2 max: 3 **External Category** Simple Data Element **Data Type** ID **Position** 01 **Codelist Id** 98 **Type System** ASC_X12 **Version Mode** Current **Version** 004010

100 Currency Code	Code (Standard ISO) for country in whose currency the charges are specified **Selected Values** All Values in Codelist	**Cardinality** min: 1 max: 1 **Primitive Type** Token **Length** min: 3 max: 3 **External Category** Simple Data Element **Data Type** ID **Position** 02 **Codelist Id** ISO_4217 **Type System** ISO_CodelistsAndSchemes **Version Mode** Latest **Version** 2015

4.5 REF — Reference Identification

Structure

Node	Card.	Prim.Type	Pos.	Length	Codelists
843 — Response to Request for Quotation	1 .. 1				
├ **REF** — Reference Identification	0 .. *		050		
│ ├ **128** — Reference Identification Qualifier	1 .. 1	Token	01	2 .. 3	128
│ ├ **127** — Reference Identification	0 .. 1	String	02	1 .. 30	
│ └ **352** — Description	0 .. 1	String	03	1 .. 80	

Documentation

Definition To specify identifying information

Properties

Identifier REF

Name Reference Identification

Cardinality min: 0 max: *

Syntax Type Related

External Category Segment

Position 050

Level 2

Notes

Usage 1 REF04 contains data relating to the value cited in REF02.

Constraint 1 R0203 Required - At least one of those noted must be used

Leaf Elements

Identifier/Name	Description/Notes/Code Values	Properties
128 Reference Identification Qualifier	Code qualifying the Reference Identification **Selected Values** **Code** 06 **Name** System Number **Code** KT **Name** Request for Quotation Reference A discrete number assigned for identification purposes to a request for quotation **Code** ZZ **Name** Mutually Defined	**Cardinality** min: 1 max: 1 **Primitive Type** Token **Length** min: 2 max: 3 **External Category** Simple Data Element **Data Type** ID **Position** 01 **Codelist Id** 128 **Type System** ASC_X12 **Version Mode** Current **Version** 004010
127 Reference Identification	Reference information as defined for a particular Transaction Set or as specified by the Reference Identification Qualifier	**Cardinality** min: 0 max: 1 **Primitive Type** String **Length** min: 1 max: 30 **External Category** Simple Data Element **Data Type** AN **Position** 02
352 Description	A free-form description to clarify the related data elements and their content	**Cardinality** min: 0 max: 1 **Primitive Type** String **Length** min: 1 max: 80 **External Category** Simple Data Element **Data Type** AN **Position** 03

4.6 CTP — Pricing Information

Structure

Node	Card.	Prim.Type	Pos.	Length	Codelists
843 — Response to Request for Quotation	1 .. 1				
├ **CTP** — Pricing Information	0 .. *		090		
│ ├ **687** — Class of Trade Code	0 .. 1	Token	01	2 .. 2	687
│ ├ **236** — Price Identifier Code	0 .. 1	Token	02	3 .. 3	236
│ └ **212** — Unit Price	0 .. 1	Decimal	03	1 .. 17	

Documentation

Definition To specify pricing information

Properties

Identifier CTP

Name Pricing Information

Cardinality min: 0 max: *

Syntax Type Related

External Category Segment

Position 090

Level 2

Notes

Usage 1 CTP07 is a multiplier factor to arrive at a final discounted price. A multiplier of .90 would be the factor if a 10% discount is given.

Usage 2 CTP08 is the rebate amount.

Constraint 1 P0405 Paired Multiple - If any are used, all must be used

Constraint 2 C0607 Conditional - If the first element is present, then the others must be present

Constraint 3 C0902 Conditional - If the first element is present, then the others must be present

Constraint 4 C1002 Conditional - If the first element is present, then the others must be present

Constraint 5 C1103 Conditional - If the first element is present, then the others must be present

Comment 1 See Figures Appendix for an example detailing the use of CTP03 and CTP04. See Figures Appendix for an example detailing the use of CTP03, CTP04 and CTP07.

Leaf Elements

Identifier/Name	Description/Notes/Code Values	Properties
687 Class of Trade Code	Code indicating class of trade **Selected Values** All Values in Codelist	**Cardinality** min: 0 max: 1 **Primitive Type** Token **Length** min: 2 max: 2 **External Category** Simple Data Element **Data Type** ID **Position** 01 **Codelist Id** 687 **Type System** ASC_X12 **Version Mode** Current **Version** 004010
236 Price Identifier Code	Code identifying pricing specification **Selected Values** All Values in Codelist	**Cardinality** min: 0 max: 1 **Primitive Type** Token **Length** min: 3 max: 3 **External Category** Simple Data Element **Data Type** ID **Position** 02

		Codelist Id 236 **Type System** ASC_X12 **Version Mode** Current **Version** 004010
212 Unit Price	Price per unit of product, service, commodity, etc.	**Cardinality** **min:** 0 **max:** 1 **Primitive Type** Decimal **Length** **min:** 1 **max:** 17 **Total Digits** 17 **External Category** Simple Data Element **Data Type** R **Position** 03

4.7 N9 — Loop N9

Structure

Node	Card.	Prim.Type	Pos.	Length	Codelists
843 — Response to Request for Quotation	1 .. 1				
├ **N9** — Loop N9	0 .. 1000		290		
│ ├ **N9** — Reference Identification	1 .. 1		290		
│ ├ **DTM** — Date/Time Reference	0 .. *		295		
│ └ **MSG** — Message Text	0 .. 1000		300		

Properties

Identifier N9

Name Loop N9

Cardinality min: 0 max: 1000

Syntax Type Related

External Category Loop

Position 290

Level 2

4.8 N9 — Reference Identification

Structure

Node	Card.	Prim.Type	Pos.	Length	Codelists
843 — Response to Request for Quotation	1 .. 1				
├ **N9** — Loop N9	0 .. 1000		290		
│ ├ **N9** — Reference Identification	1 .. 1		290		
│ │ ├ **128** — Reference Identification Qualifier	1 .. 1	Token	01	2 .. 3	128
│ │ └ **127** — Reference Identification	0 .. 1	String	02	1 .. 30	

Documentation

Definition To transmit identifying information as specified by the Reference Identification Qualifier

Properties

Identifier N9

Name Reference Identification

Cardinality min: 1 max: 1

Syntax Type Related

External Category Segment

Position 290

Level 3

Notes

Usage 1 N906 reflects the time zone which the time reflects.

Usage 2 N907 contains data relating to the value cited in N902.

Constraint 1 R0203 Required - At least one of those noted must be used

Constraint 2 C0605 Conditional - If the first element is present, then the others must be present

Leaf Elements

Identifier/Name	Description/Notes/Code Values	Properties
128 Reference Identification Qualifier	Code qualifying the Reference Identification **Selected Values** **Code** 55 **Name** Sequence Number **Code** L1 **Name** Letters or Notes	**Cardinality** min: 1 max: 1 **Primitive Type** Token **Length** min: 2 max: 3 **External Category** Simple Data Element **Data Type** ID **Position** 01 **Codelist Id** 128 **Type System** ASC_X12 **Version Mode** Current **Version** 004010
127 Reference Identification	Reference information as defined for a particular Transaction Set or as specified by the Reference Identification Qualifier	**Cardinality** min: 0 max: 1 **Primitive Type** String **Length** min: 1 max: 30 **External Category** Simple Data Element **Data Type** AN **Position** 02

4.9 DTM — Date/Time Reference

Structure

Node	Card.	Prim.Type	Pos.	Length	Codelists
843 — Response to Request for Quotation	1 .. 1				
├ **N9** — Loop N9	0 .. 1000		290		
│ ├ **DTM** — Date/Time Reference	0 .. *		295		
│ │ ├ **374** — Date/Time Qualifier	1 .. 1	Token	01	3 .. 3	374
│ │ ├ **373** — Date	0 .. 1	Date	02	8 .. 8	
│ │ ├ **337** — Time	0 .. 1	Time	03	4 .. 8	
│ │ └ **623** — Time Code	0 .. 1	Token	04	2 .. 2	623

Documentation

Definition To specify pertinent dates and times

Properties

Identifier DTM

Name Date/Time Reference

Cardinality min: 0 max: *

Syntax Type Related

External Category Segment

Position 295

Level 3

Notes

Constraint 1 R020305 Required - At least one of those noted must be used

Constraint 2 C0403 Conditional - If the first element is present, then the others must be present

Constraint 3 P0506 Paired Multiple - If any are used, all must be used

Leaf Elements

Identifier/Name	Description/Notes/Code Values	Properties
374 Date/Time Qualifier	Code specifying type of date or time, or both date and time **Selected Values** **Code** 073 **Name** Scheduled for Delivery (Prior to and Including) **Code** 070 **Name** Scheduled for Delivery (After and Including) **Code** 080 **Name** Scheduled for Shipment (After and Including) **Code** 083 **Name** Scheduled for Shipment (Prior to and Including)	**Cardinality** min: 1 max: 1 **Primitive Type** Token **Length** min: 3 max: 3 **External Category** Simple Data Element **Data Type** ID **Position** 01 **Codelist Id** 374 **Type System** ASC_X12 **Version Mode** Current **Version** 004010
373 Date	Date expressed as CCYYMMDD	**Cardinality** min: 0 max: 1 **Primitive Type** Date **Length** min: 8 max: 8 **Date Time Format** CCYYMMDD **External Category** Simple Data Element **Data Type** DT **Position** 02
337 Time	Time expressed in 24-hour clock time as follows: HHMM, or HHMMSS, or HHMMSSD, or HHMMSSDD, where H = hours (00-23), M = minutes (00-59), S = integer seconds (00-59) and DD = decimal seconds; decimal seconds are	**Cardinality** min: 0 max: 1 **Primitive Type** Time **Length** min: 4 max: 8 **Date Time Format** hhmm[ss[f[f]]] **External Category** Simple Data Element

	expressed as follows: D = tenths (0-9) and DD = hundredths (00-99)	**Data Type** TM **Position** 03
623 Time Code	Code identifying the time. In accordance with International Standards Organization standard 8601, time can be specified by a + or - and an indication in hours in relation to Universal Time Coordinate (UTC) time; since + is a restricted character, + and - are substituted by P and M in the codes that follow **Selected Values** **Code** 01 **Name** Equivalent to ISO P01 **Code** 02 **Name** Equivalent to ISO P02 **Code** 03 **Name** Equivalent to ISO P03 **Code** 04 **Name** Equivalent to ISO P04 **Code** 05 **Name** Equivalent to ISO P05 **Code** 06 **Name** Equivalent to ISO P06 **Code** 07 **Name** Equivalent to ISO P07 **Code** 08 **Name** Equivalent to ISO P08 **Code** 09 **Name** Equivalent to ISO P09 **Code** 10 **Name** Equivalent to ISO P10 **Code** 11 **Name** Equivalent to ISO P11 **Code** 12 **Name** Equivalent to ISO P12 **Code** 13 **Name** Equivalent to ISO M12 **Code** 14 **Name** Equivalent to ISO M11 **Code** 15 **Name** Equivalent to ISO M10 **Code** 16 **Name** Equivalent to ISO M09 **Code** 17 **Name** Equivalent to ISO M08 **Code** 18 **Name** Equivalent to ISO M07 **Code** 19 **Name** Equivalent to ISO M06 **Code** 20 **Name** Equivalent to ISO M05 **Code** 21 **Name** Equivalent to ISO M04 **Code** 22 **Name** Equivalent to ISO M03 **Code** 23 **Name** Equivalent to ISO M02 **Code** 24 **Name** Equivalent to ISO M01 **Code** AD **Name** Alaska Daylight Time **Code** AS **Name** Alaska Standard Time **Code** CD **Name** Central Daylight Time **Code** ED **Name** Eastern Daylight Time **Code** ES **Name** Eastern Standard Time **Code** LT **Name** Local Time **Code** MD **Name** Mountain Daylight Time **Code** MS **Name** Mountain Standard Time **Code** PD **Name** Pacific Daylight Time **Code** PS **Name** Pacific Standard Time **Code** UT **Name** Universal Time Coordinate	**Cardinality** **min:** 0 **max:** 1 **Primitive Type** Token **Length** **min:** 2 **max:** 2 **External Category** Simple Data Element **Data Type** ID **Position** 04 **Codelist Id** 623 **Type System** ASC_X12 **Version Mode** Current **Version** 004010

4.10 MSG — Message Text

Structure

Node	Card.	Prim.Type	Pos.	Length	Codelists
843 — Response to Request for Quotation	1 .. 1				
├ **N9** — Loop N9	0 .. 1000		290		
│ └ **MSG** — Message Text	0 .. 1000		300		
│ └ **933** — Free-Form Message Text	1 .. 1	String	01	1 .. 264	

Documentation

Definition To provide a free-form format that allows the transmission of text information

Properties

Identifier MSG

Name Message Text

Cardinality min: 0 max: 1000

Syntax Type Related

External Category Segment

Position 300

Level 3

Notes

Usage 1 MSG03 is the number of lines to advance before printing.

Constraint 1 C0302 Conditional - If the first element is present, then the others must be present

Comment 1 MSG02 is not related to the specific characteristics of a printer, but identifies top of page, advance a line, etc.

Comment 2 If MSG02 is “AA - Advance the specified number of lines before print” then MSG03 is required.

Leaf Elements

Identifier/Name	Description/Notes/Code Values	Properties
933 Free-Form Message Text	Free-form message text	**Cardinality** min: 1 max: 1 **Primitive Type** String **Length** min: 1 max: 264 **External Category** Simple Data Element **Data Type** AN **Position** 01