		Data Type xsd:string
D_337 Time	Time expressed in 24-hour clock time as follows: HHMM, or HHMMSS, or HHMMSSD, or HHMMSSDD, where H = hours (00-23), M = minutes (00-59), S = integer seconds (00-59) and DD = decimal seconds; decimal seconds are expressed as follows: D = tenths (0-9) and DD = hundredths (00-99)	**Cardinality** **min:** 1 **max:** 1 **Primitive Type** String **Length** **min:** 6 **max:** 6 **External Category** Element **Data Type** xsd:string
D_28 Group Control Number	Assigned number originated and maintained by the sender	**Cardinality** **min:** 1 **max:** 1 **Primitive Type** String **Length** **min:** 9 **max:** 9 **External Category** Element **Data Type** xsd:string
D_455 Responsible Agency Code	Code identifying the issuer of the standard; this code is used in conjunction with Data Element 480 **Selected Values** All Values in Codelist	**Cardinality** **min:** 1 **max:** 1 **Primitive Type** String **Length** **min:** 1 **max:** 1 **External Category** Element **Data Type** xsd:string **Codelist Id** D_455 **Type System** Customer_TS **Version Mode** Local **Version** 1.1
D_480 Version / Release / Industry Identifier Code	Code indicating the version, release, subrelease, and industry identifier of the EDI standard being used, including the GS and GE segments; if code in DE455 in GS segment is X, then in DE 480 positions 1-3 are the version number; positions 4-6 are the release and subrelease, level of the version; and positions 7-12 are the industry or trade association identifiers (optionally assigned by user); if code in DE455 in GS segment is T, then other formats are allowed **Selected Values** All Values in Codelist	**Cardinality** **min:** 1 **max:** 1 **Primitive Type** String **Length** **min:** 6 **max:** 6 **External Category** Element **Data Type** xsd:string **Codelist Id** D_480 **Type System** Customer_TS **Version Mode** Local **Version** 1.1

2.5 S_GE — Functional Group Trailer

Structure

Node	Card.	Prim.Type	Pos.	Length	Codelists
Interchange — Interchange Structure	1 .. 1				
├ **FunctionalGroup** — Functional Group	1 .. 1				
│ └ **S_GE** — Functional Group Trailer	1 .. 1				
│ ├ **D_97** — Number of Transaction Sets Included	1 .. 1	String		1 .. 1	
│ └ **D_28** — Group Control Number	1 .. 1	String		9 .. 9	

Documentation

Definition To indicate the end of a functional group and to provide control information Comments 1. The use of identical data interchange control numbers in the associated functional group header and trailer is designed to maximize functional group integrity. The control number is the same as that used in the corresponding header. Semantic Notes: 1. The data interchange control number GE02 in this trailer must be identical to the same data element in the associated functional group header, GS06.

Properties

Identifier S_GE

Name Functional Group Trailer

Cardinality min: 1 max: 1

Syntax Type Related

External Category Element

Leaf Elements

Identifier/Name	Description/Notes/Code Values	Properties
D_97 Number of Transaction Sets Included	Total number of transaction sets included in the functional group or interchange (transmission) group terminated by the trailer containing this data element	**Cardinality** min: 1 max: 1 **Primitive Type** String **Length** min: 1 max: 1 **External Category** Element **Data Type** xsd:string
D_28 Group Control Number	Assigned number originated and maintained by the sender	**Cardinality** min: 1 max: 1 **Primitive Type** String **Length** min: 9 max: 9 **External Category** Element **Data Type** xsd:string

2.6 S_IEA — Interchange Control Trailer

Structure

Node	Card.	Prim.Type	Pos.	Length	Codelists
Interchange — Interchange Structure	1 .. 1				
└ **S_IEA** — Interchange Control Trailer	1 .. 1				
├ **D_I16** — Number of Included Functional Groups	1 .. 1	String		1 .. 1	
└ **D_I12** — Interchange Control Number	1 .. 1	String		9 .. 9	

Documentation

Definition To define the end of an interchange of zero or more functional groups and interchange-related control segments

Properties

Identifier S_IEA

Name Interchange Control Trailer

Cardinality min: 1 max: 1

Syntax Type Related

External Category Element

Leaf Elements

Identifier/Name	Description/Notes/Code Values	Properties
D_I16 Number of Included Functional Groups	A count of the number of functional groups included in an interchange	**Cardinality** min: 1 max: 1 **Primitive Type** String **Length** min: 1 max: 1 **External Category** Element **Data Type** xsd:string
D_I12 Interchange Control Number	A control number assigned by the interchange sender	**Cardinality** min: 1 max: 1 **Primitive Type** String **Length** min: 9 max: 9 **External Category** Element **Data Type** xsd:string

3 OVERVIEW MESSAGE

General Information

Name	SAP_LBN_ANSI_X12_864
Direction	Out
Status	Active
Message Type	Text Message
Type System	ASC_X12
Version	004010
External Category	Transaction Set

Documentation

Definition

This Draft Standard for Trial Use contains the format and establishes the data content of the Text Message Transaction Set (864) for use within the context of an Electronic Data Interchange (EDI) environment.
In the SAP LBN Tendering scenario, this EDI 864 message is specifically used for quotation notification between shipper and carrier systems, including quotation awarded and quotation rejected outcomes. The transaction set is used to communicate this business notification in a human-readable form.

Notes

Usage 1

MIT carries the RFQ document ID from the original request for quotation.

Example:
MIT*RFQ20252886~

Usage 2

MSG/933 uses a fixed business format instead of arbitrary free text:
SHIPPING_TYPE={ VALUE}
Allowed values for { VALUE} :
LTL
FTL
PARCEL
BULK
LOOSE
ULD
LCL
FCL

Example:
MIT*RFQ20252886~
MSG*SHIPPING_TYPE=LTL~

Example 1

Award Example:

ISA*00* *00* *ZZ*Shipper LBNID *ZZ*Carrier LBNID *260331*0829*U*00401*000003100*0*P*>~
GS*TX*Shipper LBNID*Carrier LBNID*20260331*082933*000003100*X*004010~
ST*864*0001~
BMG*00*Quotation Awarded*65~
DTM*007*20260331~
N1*CA*Carrier*92*Carrier LBNID~
MIT*RFQ20252886~
MSG*SHIPPING_TYPE=LTL~
SE*7*0001~
GE*1*000003100~
IEA*1*000003100~

Example 2

Rejection Example:

ISA*00* *00* *ZZ*Shipper LBNID *ZZ*Carrier LBNID *260331*0829*U*00401*000003100*0*P*>~
GS*TX*Shipper LBNID*Carrier LBNID*20260331*082933*000003100*X*004010~
ST*864*0001~
BMG*00*Quotation Rejected*69~
DTM*007*20260331~
N1*CA*Carrier*92*Carrier LBNID~
MIT*RFQ20252886~
MSG*SHIPPING_TYPE=LTL~
SE*7*0001~
GE*1*000003100~
IEA*1*000003100~

3.1 Structure

The following table shows the complete structure.

Node	Card.	Prim.Type	Pos.	Length	Codelists
864 — Text Message	1 .. 1				
├ **ST** — Transaction Set Header	1 .. 1		010		
│ ├ **143** — Transaction Set Identifier Code	1 .. 1	Token	01	3 .. 3	143
│ └ **329** — Transaction Set Control Number	1 .. 1	String	02	4 .. 9	
├ **BMG** — Beginning Segment For Text Message	1 .. 1		020		
│ ├ **353** — Transaction Set Purpose Code	1 .. 1	Token	01	2 .. 2	353
│ ├ **352** — Description	0 .. 1	String	02	1 .. 80	
│ └ **640** — Transaction Type Code	0 .. 1	Token	03	2 .. 2	640
├ **DTM** — Date/Time Reference	0 .. 10		030		
│ ├ **374** — Date/Time Qualifier	1 .. 1	Token	01	3 .. 3	374
│ ├ **373** — Date	0 .. 1	Date	02	8 .. 8	
│ └ **337** — Time	0 .. 1	Time	03	4 .. 8	
├ **N1** — Loop N1	0 .. 200		040		
│ └ **N1** — Name	1 .. 1		040		
│ ├ **98** — Entity Identifier Code	1 .. 1	Token	01	2 .. 3	98
│ ├ **93** — Name	0 .. 1	String	02	1 .. 60	
│ ├ **66** — Identification Code Qualifier	0 .. 1	Token	03	1 .. 2	66
│ └ **67** — Identification Code	0 .. 1	String	04	2 .. 80	
├ **MIT** — Loop MIT	1 .. *		010		
│ ├ **MIT** — Message Identification	1 .. 1		010		
│ │ └ **127** — Reference Identification	1 .. 1	String	01	1 .. 30	
│ └ **MSG** — Message Text	1 .. 100000		080		
│ └ **933** — Free-Form Message Text	1 .. 1	String	01	1 .. 264	
└ **SE** — Transaction Set Trailer	1 .. 1		010		
├ **96** — Number of Included Segments	1 .. 1	Integer	01	1 .. 10	
└ **329** — Transaction Set Control Number	1 .. 1	String	02	4 .. 9	

4 DETAILS MESSAGE

4.1 864 — Text Message

Structure

Node	Card.	Prim.Type	Pos.	Length	Codelists
864 — Text Message	1 .. 1				
├ **ST** — Transaction Set Header	1 .. 1		010		
├ **BMG** — Beginning Segment For Text Message	1 .. 1		020		
├ **DTM** — Date/Time Reference	0 .. 10		030		
├ **N1** — Loop N1	0 .. 200		040		
├ **MIT** — Loop MIT	1 .. *		010		
└ **SE** — Transaction Set Trailer	1 .. 1		010		

Properties

Identifier 864

Name Text Message

Cardinality min: 1 max: 1

4.2 ST — Transaction Set Header

Structure

Node	Card.	Prim.Type	Pos.	Length	Codelists
864 — Text Message	1 .. 1				
├ **ST** — Transaction Set Header	1 .. 1		010		
│ ├ **143** — Transaction Set Identifier Code	1 .. 1	Token	01	3 .. 3	143
│ └ **329** — Transaction Set Control Number	1 .. 1	String	02	4 .. 9	

Documentation

Definition To indicate the start of a transaction set and to assign a control number

Properties

Identifier ST

Name Transaction Set Header

Cardinality min: 1 max: 1

Syntax Type Related

External Category Segment

Position 010

Level 2

Notes

Usage 1 The transaction set identifier (ST01) used by the translation routines of the interchange partners to select the appropriate transaction set definition (e.g., 810 selects the Invoice Transaction Set).

Leaf Elements

Identifier/Name	Description/Notes/Code Values	Properties
143 Transaction Set Identifier Code	Code uniquely identifying a Transaction Set **Selected Values** All Values in Codelist	**Cardinality** min: 1 max: 1 **Primitive Type** Token **Length** min: 3 max: 3 **External Category** Simple Data Element **Data Type** ID **Position** 01 **Codelist Id** 143 **Type System** ASC_X12 **Version Mode** Current **Version** 004010
329 Transaction Set Control Number	Identifying control number that must be unique within the transaction set functional group assigned by the originator for a transaction set	**Cardinality** min: 1 max: 1 **Primitive Type** String **Length** min: 4 max: 9 **External Category** Simple Data Element **Data Type** AN **Position** 02

4.3 BMG — Beginning Segment For Text Message

Structure

Node	Card.	Prim.Type	Pos.	Length	Codelists
864 — Text Message	1 .. 1				
├ **BMG** — Beginning Segment For Text Message	1 .. 1		020		
│ ├ **353** — Transaction Set Purpose Code	1 .. 1	Token	01	2 .. 2	353
│ ├ **352** — Description	0 .. 1	String	02	1 .. 80	
│ └ **640** — Transaction Type Code	0 .. 1	Token	03	2 .. 2	640

Documentation

Definition To indicate the beginning of a Text Message Transaction Set

Properties

Identifier BMG

Name Beginning Segment For Text Message

Cardinality min: 1 max: 1

Syntax Type Related

External Category Segment

Position 020

Level 2

Notes

Comment 1 BMG02 contains the message subject.

Leaf Elements

Identifier/Name	Description/Notes/Code Values	Properties
353 Transaction Set Purpose Code	Code identifying purpose of transaction set **Selected Values** **Code** 00 **Name** Original	**Cardinality** min: 1 max: 1 **Primitive Type** Token **Length** min: 2 max: 2 **External Category** Simple Data Element **Data Type** ID **Position** 01 **Codelist Id** 353 **Type System** ASC_X12 **Version Mode** Current **Version** 004010
352 Description	A free-form description to clarify the related data elements and their content	**Cardinality** min: 0 max: 1 **Primitive Type** String **Length** min: 1 max: 80 **External Category** Simple Data Element **Data Type** AN **Position** 02
640 Transaction Type Code	Code specifying the type of transaction **Selected Values** **Code** 65 **Name** Award Notification **Code** 69 **Name** Bid Rejection Notice	**Cardinality** min: 0 max: 1 **Primitive Type** Token **Length** min: 2 max: 2 **External Category** Simple Data Element **Data Type** ID **Position** 03 **Codelist Id** 640 **Type System** ASC_X12 **Version Mode** Current **Version** 004010

4.4 DTM — Date/Time Reference

Structure

Node	Card.	Prim.Type	Pos.	Length	Codelists
864 — Text Message	1 .. 1				
├ **DTM** — Date/Time Reference	0 .. 10		030		
│ ├ **374** — Date/Time Qualifier	1 .. 1	Token	01	3 .. 3	374
│ ├ **373** — Date	0 .. 1	Date	02	8 .. 8	
│ └ **337** — Time	0 .. 1	Time	03	4 .. 8	

Documentation

Definition To specify pertinent dates and times

Properties

Identifier DTM

Name Date/Time Reference

Cardinality min: 0 max: 10

Syntax Type Related

External Category Segment

Position 030

Level 2

Notes

Constraint 1 R020305 Required - At least one of those noted must be used

Constraint 2 C0403 Conditional - If the first element is present, then the others must be present

Constraint 3 P0506 Paired Multiple - If any are used, all must be used

Leaf Elements

Identifier/Name	Description/Notes/Code Values	Properties
374 Date/Time Qualifier	Code specifying type of date or time, or both date and time **Selected Values** **Code** 007 **Name** Effective	**Cardinality** min: 1 max: 1 **Primitive Type** Token **Length** min: 3 max: 3 **External Category** Simple Data Element **Data Type** ID **Position** 01 **Codelist Id** 374 **Type System** ASC_X12 **Version Mode** Current **Version** 004010
373 Date	Date expressed as CCYYMMDD	**Cardinality** min: 0 max: 1 **Primitive Type** Date **Length** min: 8 max: 8 **Date Time Format** CCYYMMDD **External Category** Simple Data Element **Data Type** DT **Position** 02
337 Time	Time expressed in 24-hour clock time as follows: HHMM, or HHMMSS, or HHMMSSD, or HHMMSSDD, where H = hours (00-23), M = minutes (00-59), S = integer seconds (00-59) and DD = decimal seconds; decimal seconds are expressed as follows: D = tenths (0-9) and DD = hundredths (00-99)	**Cardinality** min: 0 max: 1 **Primitive Type** Time **Length** min: 4 max: 8 **Date Time Format** hhmm[ss[f[f]]] **External Category** Simple Data Element **Data Type** TM **Position** 03

4.5 N1 — Loop N1

Structure

Node	Card.	Prim.Type	Pos.	Length	Codelists
864 — Text Message	1 .. 1				
├ **N1** — Loop N1	0 .. 200		040		
│ └ **N1** — Name	1 .. 1		040		

Properties

Identifier N1

Name Loop N1

Cardinality min: 0 max: 200

Syntax Type Related

External Category Loop

Position 040

Level 2