| | | |
|---|---|---|
| | | **Data Type** xsd:string |
| **D_337**<br>Time | Time expressed in 24-hour clock time as follows: HHMM, or HHMMSS, or HHMMSSD, or HHMMSSDD, where H = hours (00-23), M = minutes (00-59), S = integer seconds (00-59) and DD = decimal seconds; decimal seconds are expressed as follows: D = tenths (0-9) and DD = hundredths (00-99) | **Cardinality** **min:** 1 **max:** 1<br>**Primitive Type** String<br>**Length** **min:** 6 **max:** 6<br>**External Category** Element<br>**Data Type** xsd:string |
| **D_28**<br>Group Control Number | Assigned number originated and maintained by the sender | **Cardinality** **min:** 1 **max:** 1<br>**Primitive Type** String<br>**Length** **min:** 9 **max:** 9<br>**External Category** Element<br>**Data Type** xsd:string |
| **D_455**<br>Responsible Agency Code | Code identifying the issuer of the standard; this code is used in conjunction with Data Element 480<br><br>**Selected Values**<br>All Values in Codelist | **Cardinality** **min:** 1 **max:** 1<br>**Primitive Type** String<br>**Length** **min:** 1 **max:** 1<br>**External Category** Element<br>**Data Type** xsd:string<br><br>**Codelist Id** D_455<br>**Type System** Customer_TS<br>**Version Mode** Local<br>**Version** 1.1 |
| **D_480**<br>Version / Release / Industry Identifier Code | Code indicating the version, release, subrelease, and industry identifier of the EDI standard being used, including the GS and GE segments; if code in DE455 in GS segment is X, then in DE 480 positions 1-3 are the version number; positions 4-6 are the release and subrelease, level of the version; and positions 7-12 are the industry or trade association identifiers (optionally assigned by user); if code in DE455 in GS segment is T, then other formats are allowed<br><br>**Selected Values**<br>All Values in Codelist | **Cardinality** **min:** 1 **max:** 1<br>**Primitive Type** String<br>**Length** **min:** 6 **max:** 6<br>**External Category** Element<br>**Data Type** xsd:string<br><br>**Codelist Id** D_480<br>**Type System** Customer_TS<br>**Version Mode** Local<br>**Version** 1.1 |

## 2.5 S_GE — Functional Group Trailer

### Structure

| Node | Card. | Prim.Type | Pos. | Length | Codelists |
|---|---|---|---|---|---|
| **Interchange** — Interchange Structure | 1 .. 1 | | | | |
| ├ **FunctionalGroup** — Functional Group | 1 .. 1 | | | | |
| │ └ **S_GE** — Functional Group Trailer | 1 .. 1 | | | | |
| │ ├ **D_97** — Number of Transaction Sets Included | 1 .. 1 | String | | 1 .. 1 | |
| │ └ **D_28** — Group Control Number | 1 .. 1 | String | | 9 .. 9 | |

### Documentation

**Definition** To indicate the end of a functional group and to provide control information Comments 1. The use of identical data interchange control numbers in the associated functional group header and trailer is designed to maximize functional group integrity. The control number is the same as that used in the corresponding header. Semantic Notes: 1. The data interchange control number GE02 in this trailer must be identical to the same data element in the associated functional group header, GS06.

### Properties

**Identifier** S_GE

**Name** Functional Group Trailer

**Cardinality** min: 1 max: 1

### Syntax Type Related

**External Category** Element

### Leaf Elements

| Identifier/Name | Description/Notes/Code Values | Properties |
|---|---|---|
| **D_97**<br>Number of Transaction Sets Included | Total number of transaction sets included in the functional group or interchange (transmission) group terminated by the trailer containing this data element | **Cardinality** min: 1 max: 1<br>**Primitive Type** String<br>**Length** min: 1 max: 1<br>**External Category** Element<br>**Data Type** xsd:string |
| **D_28**<br>Group Control Number | Assigned number originated and maintained by the sender | **Cardinality** min: 1 max: 1<br>**Primitive Type** String<br>**Length** min: 9 max: 9<br>**External Category** Element<br>**Data Type** xsd:string |

## 2.6 S_IEA — Interchange Control Trailer

### Structure

| Node | Card. | Prim.Type | Pos. | Length | Codelists |
|---|---|---|---|---|---|
| **Interchange** — Interchange Structure | 1 .. 1 | | | | |
| └ **S_IEA** — Interchange Control Trailer | 1 .. 1 | | | | |
| ├ **D_I16** — Number of Included Functional Groups | 1 .. 1 | String | | 1 .. 1 | |
| └ **D_I12** — Interchange Control Number | 1 .. 1 | String | | 9 .. 9 | |

### Documentation

**Definition** To define the end of an interchange of zero or more functional groups and interchange-related control segments

### Properties

**Identifier** S_IEA

**Name** Interchange Control Trailer

**Cardinality** min: 1 max: 1

### Syntax Type Related

**External Category** Element

### Leaf Elements

| Identifier/Name | Description/Notes/Code Values | Properties |
|---|---|---|
| **D_I16**<br>Number of Included Functional Groups | A count of the number of functional groups included in an interchange | **Cardinality** min: 1 max: 1<br>**Primitive Type** String<br>**Length** min: 1 max: 1<br>**External Category** Element<br>**Data Type** xsd:string |
| **D_I12**<br>Interchange Control Number | A control number assigned by the interchange sender | **Cardinality** min: 1 max: 1<br>**Primitive Type** String<br>**Length** min: 9 max: 9<br>**External Category** Element<br>**Data Type** xsd:string |

# 3 OVERVIEW MESSAGE

## General Information

| | |
|---|---|
| **Name** | SAP_LBN_ANSI_X12_990 |
| **Direction** | In |
| **Status** | Active |
| **Message Type** | Response to a Load Tender |
| **Type System** | ASC_X12 |
| **Version** | 004010 |
| **External Category** | Transaction Set |

## Documentation

**Definition** This Draft Standard for Trial Use contains the format and establishes the data contents of the Response to a Load Tender Transaction Set (990) for use within the context of an Electronic Data Interchange (EDI) environment. The transaction set can be used to provide general information relative to a specific shipment. The Response to a Load Tender is used as the response to a Motor Carrier Shipment Information Transaction Set (204) which has been used as a load tender.

## Notes

**Example 1**

```
ISA*00*          *00*          *02*”Carrier LBNID”*01*”Shipper
LBNID”*211209*0841*U*00401*000000515*0*T*>~
GS*GF*”Carrier LBNID”*”Shipper LBNID”*20211209*084100*000000515*X*004010~
ST*990*5150001~
B1**”Freightorder ID 1”**A~
N9*06*”Sender System ID”*****IX>”Item ID”~
N7**”Equipment ID”~
K1*free text~
SE*6*5150001~
ST*990*5150002~
B1**”Freightorder ID 2”**D~
N9*06*”Sender System ID”~
K1*free text*optional free text~
SE*5*5150002~
GE*2*000000515~
IEA*2*000000515~
```

### 3.1 Structure

The following table shows the complete structure.

| Node | Card. | Prim.Type | Pos. | Length | Codelists |
|---|---|---|---|---|---|
| **990** — Response to a Load Tender | 1 .. 1 | | | | |
| ├ **ST** — Transaction Set Header - Response To a Load Tender | 1 .. 1 | | 010 | | |
| │ ├ **143** — Transaction Set Identifier Code | 1 .. 1 | Token | 01 | 3 .. 3 | 143 |
| │ └ **329** — Transaction Set Control Number | 1 .. 1 | String | 02 | 4 .. 9 | |
| ├ **B1** — Beginning Segment for Booking or Pick-up/Delivery | 1 .. 1 | | 020 | | |
| │ ├ **145** — Shipment Identification Number | 1 .. 1 | String | 02 | 1 .. 30 | |
| │ └ **558** — Reservation Action Code | 1 .. 1 | Token | 04 | 1 .. 1 | 558 |
| ├ **N9** — Reference Identification | 1 .. 1 | | 030 | | |
| │ ├ **128** — Reference Identification Qualifier | 1 .. 1 | Token | 01 | 2 .. 3 | 128 |
| │ ├ **127** — Reference Identification - System Number | 1 .. 1 | String | 02 | 1 .. 30 | |
| │ └ **C040** — Reference Identifier | 0 .. 1 | | 07 | | |
| │ ├ **128** — Reference Identification Qualifier | 1 .. 1 | Token | 01 | 2 .. 3 | 128 |
| │ └ **127** — Reference Identification | 1 .. 1 | String | 02 | 1 .. 30 | |
| ├ **N7** — Equipment Details | 0 .. 1 | | 036 | | |
| │ └ **207** — Equipment Number | 1 .. 1 | String | 02 | 1 .. 10 | |
| ├ **K1** — Remarks | 0 .. 10 | | 060 | | |
| │ └ **61** — Free-Form Message | 1 .. 1 | String | 01 | 1 .. 30 | |
| └ **SE** — Transaction Set Trailer | 1 .. 1 | | 070 | | |
| ├ **96** — Number of Included Segments | 1 .. 1 | Integer | 01 | 1 .. 10 | |
| └ **329** — Transaction Set Control Number | 1 .. 1 | String | 02 | 4 .. 9 | |

# 4 DETAILS MESSAGE

## 4.1 990 — Response to a Load Tender

### Structure

| Node | Card. | Prim.Type | Pos. | Length | Codelists |
|---|---|---|---|---|---|
| **990** — Response to a Load Tender | 1 .. 1 | | | | |
| ├ **ST** — Transaction Set Header - Response To a Load Tender | 1 .. 1 | | 010 | | |
| ├ **B1** — Beginning Segment for Booking or Pick-up/Delivery | 1 .. 1 | | 020 | | |
| ├ **N9** — Reference Identification | 1 .. 1 | | 030 | | |
| ├ **N7** — Equipment Details | 0 .. 1 | | 036 | | |
| ├ **K1** — Remarks | 0 .. 10 | | 060 | | |
| └ **SE** — Transaction Set Trailer | 1 .. 1 | | 070 | | |

### Properties

**Identifier** 990

**Name** Response to a Load Tender

**Cardinality** min: 1 max: 1

## 4.2 ST [143 = “990”] — Transaction Set Header - Response To a Load Tender

### Structure

| Node | Card. | Prim.Type | Pos. | Length | Codelists |
|---|---|---|---|---|---|
| **990** — Response to a Load Tender | 1 .. 1 | | | | |
| ├ **ST** — Transaction Set Header - Response To a Load Tender | 1 .. 1 | | 010 | | |
| │ ├ **143** — Transaction Set Identifier Code | 1 .. 1 | Token | 01 | 3 .. 3 | 143 |
| │ └ **329** — Transaction Set Control Number | 1 .. 1 | String | 02 | 4 .. 9 | |

### Documentation

**Definition** To indicate the start of a transaction set and to assign a control number.

### Properties

**Identifier** ST

**Name** Transaction Set Header - Response To a Load Tender

**Cardinality** min: 1 max: 1

### Syntax Type Related

**External Category** Segment

**Position** 010

**Level** 2

### Notes

**Usage 1** The transaction set identifier (ST01) used by the translation routines of the interchange partners to select the appropriate transaction set definition (e.g., 990 selects the Response to a Load Tender).

### Leaf Elements

| Identifier/Name | Description/Notes/Code Values | Properties |
|---|---|---|
| **143**<br>Transaction Set Identifier Code | Code uniquely identifying a Transaction Set.<br><br>**Selected Values**<br>**Code** 990 **Name** Response To a Load Tender | **Cardinality** min: 1 max: 1<br>**Primitive Type** Token<br>**Length** min: 3 max: 3<br>**External Category** Simple Data Element<br>**Data Type** ID<br>**Position** 01<br>**Fixed Value** 990<br><br>**Codelist Id** 143<br>**Type System** ASC_X12<br>**Version Mode** Current<br>**Version** 004010 |
| **329**<br>Transaction Set Control Number | Identifying control number that must be unique within the transaction set functional group assigned by the originator for a transaction set. | **Cardinality** min: 1 max: 1<br>**Primitive Type** String<br>**Length** min: 4 max: 9<br>**External Category** Simple Data Element<br>**Data Type** AN<br>**Position** 02 |

## 4.3 B1 — Beginning Segment for Booking or Pick-up/Delivery

### Structure

| Node | Card. | Prim.Type | Pos. | Length | Codelists |
|---|---|---|---|---|---|
| **990** — Response to a Load Tender | 1 .. 1 | | | | |
| ├ **B1** — Beginning Segment for Booking or Pick-up/Delivery | 1 .. 1 | | 020 | | |
| │ ├ **145** — Shipment Identification Number | 1 .. 1 | String | 02 | 1 .. 30 | |
| │ └ **558** — Reservation Action Code | 1 .. 1 | Token | 04 | 1 .. 1 | 558 |

### Documentation

**Definition** To transmit identifying numbers, dates, and other basic data relating to the transaction set.

### Properties

**Identifier** B1

**Name** Beginning Segment for Booking or Pick-up/Delivery

**Cardinality** min: 1 max: 1

### Syntax Type Related

**External Category** Segment

**Position** 020

**Level** 2

### Notes

### Leaf Elements

| Identifier/Name | Description/Notes/Code Values | Properties |
|---|---|---|
| **145**<br>Shipment Identification Number | Identification number assigned to the shipment by the shipper that uniquely identifies the shipment from origin to ultimate destination and is not subject to modification; (Does not contain blanks or special characters).<br><br>**Comment 1**<br>Not used in LBN | **Cardinality** min: 1 max: 1<br>**Primitive Type** String<br>**Length** min: 1 max: 30<br>**External Category** Simple Data Element<br>**Data Type** AN<br>**Position** 02 |
| **558**<br>Reservation Action Code | Code identifying action on reservation or offering.<br><br>**Selected Values**<br>**Code** A **Name** Reservation Accepted<br>**Code** D **Name** Reservation Cancelled | **Cardinality** min: 1 max: 1<br>**Primitive Type** Token<br>**Length** min: 1 max: 1<br>**External Category** Simple Data Element<br>**Data Type** ID<br>**Position** 04<br><br>**Codelist Id** 558<br>**Type System** ASC_X12<br>**Version Mode** Current<br>**Version** 004010 |

## 4.4 N9 — Reference Identification

### Structure

| Node | Card. | Prim.Type | Pos. | Length | Codelists |
|---|---|---|---|---|---|
| **990** — Response to a Load Tender | 1 .. 1 | | | | |
| ├ **N9** — Reference Identification | 1 .. 1 | | 030 | | |
| │ ├ **128** — Reference Identification Qualifier | 1 .. 1 | Token | 01 | 2 .. 3 | 128 |
| │ ├ **127** — Reference Identification - System Number | 1 .. 1 | String | 02 | 1 .. 30 | |
| │ └ **C040** — Reference Identifier | 0 .. 1 | | 07 | | |

### Documentation

**Definition** To transmit identifying information as specified by the Reference Identification Qualifier.

### Properties

**Identifier** N9

**Name** Reference Identification

**Cardinality** min: 1 max: 1

### Syntax Type Related

**External Category** Segment

**Position** 030

**Level** 2

### Notes

### Leaf Elements

| Identifier/Name | Description/Notes/Code Values | Properties |
|---|---|---|
| **128**<br>Reference Identification Qualifier | Code qualifying the Reference Identification.<br><br>**Usage 1**<br>The Item ID<br><br>**Selected Values**<br>**Code** 06 **Name** System Number<br>**Code** CN **Name** Carrier's Reference Number (PRO/Invoice) | **Cardinality** min: 1 max: 1<br>**Primitive Type** Token<br>**Length** min: 2 max: 3<br>**External Category** Simple Data Element<br>**Data Type** ID<br>**Position** 01<br>**Fixed Value** 06<br><br>**Codelist Id** 128<br>**Type System** ASC_X12<br>**Version Mode** Current<br>**Version** 004010 |
| **127 [128 = "06"]**<br>Reference Identification - System Number | Reference information as defined for a particular Transaction Set or as specified by the Reference Identification Qualifier.<br><br>**Comment 1**<br>Sender system ID as given in ANSI X12 204 message, position L1101. | **Cardinality** min: 1 max: 1<br>**Primitive Type** String<br>**Length** min: 1 max: 30<br>**External Category** Simple Data Element<br>**Data Type** AN<br>**Position** 02 |

## 4.5 C040 — Reference Identifier

### Structure

| Node | Card. | Prim.Type | Pos. | Length | Codelists |
|---|---|---|---|---|---|
| **990** — Response to a Load Tender | 1 .. 1 | | | | |
| ├ **N9** — Reference Identification | 1 .. 1 | | 030 | | |
| │ └ **C040** — Reference Identifier | 0 .. 1 | | 07 | | |
| │ ├ **128** — Reference Identification Qualifier | 1 .. 1 | Token | 01 | 2 .. 3 | 128 |
| │ └ **127** — Reference Identification | 1 .. 1 | String | 02 | 1 .. 30 | |

### Documentation

**Definition** To identify one or more reference numbers or identification numbers as specified by the Reference Qualifier

### Properties

**Identifier** C040

**Name** Reference Identifier

**Cardinality** min: 0 max: 1

### Syntax Type Related

**External Category** Composite Data Structure

**Position** 07

### Notes

**Constraint 1** P0304 Paired Multiple - If any are used, all must be used

**Constraint 2** P0506 Paired Multiple - If any are used, all must be used

### Leaf Elements

| Identifier/Name | Description/Notes/Code Values | Properties |
|---|---|---|
| **128**<br>Reference Identification Qualifier | Code qualifying the Reference Identification<br><br>**Usage 1**<br>The Item ID<br><br>**Selected Values**<br>**Code** IX **Name** Item Number | **Cardinality** min: 1 max: 1<br>**Primitive Type** Token<br>**Length** min: 2 max: 3<br>**External Category** Simple Data Element<br>**Data Type** ID<br>**Position** 01<br><br>**Codelist Id** 128<br>**Type System** ASC_X12<br>**Version Mode** Current<br>**Version** 004010 |
| **127**<br>Reference Identification | Reference information as defined for a particular Transaction Set or as specified by the Reference Identification Qualifier | **Cardinality** min: 1 max: 1<br>**Primitive Type** String<br>**Length** min: 1 max: 30<br>**External Category** Simple Data Element<br>**Data Type** AN<br>**Position** 02 |