2.7 FunctionalGroup — Functional Group

Structure

Node	Card.	Prim.Type	Pos.	Length	Codelists
Interchange — Interchange Structure	1 .. 1				
┣ **FunctionalGroup** — Functional Group	1 .. *				

Properties

Identifier FunctionalGroup

Name Functional Group

Cardinality min: 1 max: *

Syntax Type Related

External Category Element

Notes

Tech. Info. 0 Choice : (FunctionalGroup) (maxOccurs : 1) (minOccurs : 1)

2.8 S_UNZ — S UNZ

Structure

Node	Card.	Prim.Type	Pos.	Length	Codelists
Interchange — Interchange Structure	1 .. 1				
└ **S_UNZ** — S UNZ	1 .. 1				
├ **D_0036** — Interchange control count	1 .. 1	Decimal			
└ **D_0020** — Interchange control reference	1 .. 1	String		1 .. 14	

Properties

Identifier S_UNZ

Name S UNZ

Cardinality min: 1 max: 1

Syntax Type Related

External Category Element

Leaf Elements

Identifier/Name	Description/Notes/Code Values	Properties
D_0036 Interchange control count	The count either of the number of messages or, if used, of the number of functional groups in an interchange. One of these counts shall appear.	**Cardinality** **min:** 1 **max:** 1 **Primitive Type** Decimal **Length** **min:** 0 **Total Digits** 6 **External Category** Element **Data Type** xsd:decimal
D_0020 Interchange control reference	Unique reference assigned by the sender to an interchange. **Usage 1** Shall be identical in UNB and UNZ.	**Cardinality** **min:** 1 **max:** 1 **Primitive Type** String **Length** **min:** 1 **max:** 14 **External Category** Element **Data Type** xsd:string

3 OVERVIEW MESSAGE

General Information

Name	SAP_LBN_EDIFACT_IFTMIN
Direction	Out
Status	Active
Message Type	Instruction message
Type System	UNEDIFACT
Version	D.96A S3
External Category	Message Type

Documentation

Summary Documentation Summary comes here.

Definition

0. Introduction
This specification provides the definition of the Instruction message (IFTMIN) to be used in Electronic Data Interchange (EDI) between trading partners involved in administration, commerce and transport.

1 Scope
This paper provides the definition of the Instruction Message to be used in fulfilling the requirements of trading partners in the transport chain worldwide, in the interchange of cargo and transport related information using Electronic Data Interchange (EDI).
This message is a single consignment based message, being aligned with other single consignment based messages such as the booking messages (IFTMBP, IFTMBF and IFTMBC), the Instruction Contract Status Message (IFTMCS) and the Arrival Notice Message (IFTMAN).
The single consignment based messages can be used by all modes of transport for the forwarding and transport of goods from any origin to any destination, regardless of route or prevailing commercial practice.
These messages are suitable for the arrangement of the transport of goods between all parties to the movement of the consignment (including the consignor/shipper and consignee as well as the forwarders, brokers, and carriers involved) as well as providing the information necessary to perform that transport and delivery of the goods.
They should be used in the same way by each mode of transport when the requirements are common even if functionally similar information is known by different names.

1.1 Functional Definition
A message from the party issuing an instruction regarding forwarding/transport services for a consignment under conditions agreed, to the party arranging the forwarding and/or transport services. This message may be applied for both national and international trade. It is based on universal practice and is not dependent on the type of business or industry.

1.2 Principles
The instruction results in a transport contract for a consignment and is primarily meant for administrative purposes. It will be the message from shipper to carrier or forwarder containing the final details of the consignment for which services are provided. The instruction message is the one and only message which results in the actual contract which can either be a document or an electronic contract.
If only one message will suffice in an exchange between a shipper and a carrier/forwarder the instruction message should be the one as this message is the only message that results in a contract. The receiving party is to ascertain whether the Instruction message is preceded by a Booking Firm message, to be able to interpret the function as being an administrative message only or an administrative and operational message.
- A consignment may contain several goods items.
- Goods items may or may not be containerized.
- A goods item may be transported in one or more containers, and a single container may contain one or more goods items.
- One goods item may be related to one or more customs tariff codes.
- Goods items related to one customs tariff code may be carried in one or more containers.
- Goods items may reflect either the contractual or operational description of the goods.
- A party to the movement of the consignment may book or order transport for one or more goods items.
- A party to the movement of the consignment may book or issue instructions of transport to be arranged for several goods items by means of one or several of the following messages: IFTMBP, IFTMBF, IFTMBC, IFTMIN, IFTMCS, IFTMAN.
- Pre-carriage (advanced haulage) and/or on-carriage (destination haulage) of goods items or equipment within one booking or instruction may take place in different steps, each step specified with its own transport details group.
- Equipment may have other types of equipment attached to it, e.g. a temperature control unit attached to a container.
- Equipment and/or goods items may be attached to or transported on another load or transport device, which as such may be attached to or transported on yet another load or transport device, e.g. a container on a chassis on a rail-car.
- Transport devices, which have the ability of powered movement on their own, are specified in the

transport details group. Other load or transport devices are specified as equipment.
- The expression of packaging for goods items can be expressed at up to three levels.
A number of generic transport terms are used in this specification, to be described as:
* MODE OF TRANSPORT: The method of transport used for the conveyance of goods or persons, e.g. by rail, by road, by sea.
* MEANS OF TRANSPORT: The vehicle used for the transport of goods or persons, e.g. aircraft, truck, vessel.
* TYPE OF MEANS OF TRANSPORT: The type of vehicle used in the transport process, e.g. wide body, tank truck, passenger vessel.
* EQUIPMENT: Material resources necessary to facilitate the transport and handling of cargo. Transport equipment does under the given circumstances not have the ability to move by its own propulsion (e.g. sea container, trailer, unit load device, pallet).
* TYPE OF EQUIPMENT: The type of material used, e.g. 40 feet container, four way pallet, mafi trailer.

Examples:
Annex A Example (Details of transport)
1.
TDT+20+HL12345+1:MARITIME+:CONTAINER VESSEL+:::HAPAG LLOYD+++PHXXX:::FAITHFUL'
Notes: 20 indicates 'main transport' (d.e. 8051); HL12345 is assigned by the carrier (d.e. 8028; is the 'flight number' in the air mode); PHXXX is the radio call sign (d.e. 8213); 'FAITHFUL' is the name of the vessel
2.
TDT+20+91/05/0021+3:ROAD++:::INT. TRUCKING CO.+++BB-10-XX::::NL' Note: BB-10-XX represents the (Dutch) truck registration no.
Source: Western European EDIFACT Board

Notes

Constraint 1 Service Level will be provided on header level.

Constraint 2 Some of the DG data are part of the B2B message. If Product compliance is activated, the dangerous goods information is missing.

Constraint 3 Actually TM does not support sending information for dangerous goods items if they are related to limited or excepted quantities.

3.1 Structure

The following table shows only the root element and the group elements.

Node	Card.	Prim.Type	Pos.	Length	Codelists
IFTMIN — Instruction message	1 .. 1				
├ **UNH** — MESSAGE HEADER	1 .. 1		0010		
│ └ **S009** — MESSAGE IDENTIFIER	1 .. 1		020		
├ **BGM** — Beginning of message	1 .. 1		0020		
│ └ **C002** — Document/message name	1 .. 1		010		
├ **DTM** — Date/time/period - Document/message date/time	1 .. 1		0050		
│ └ **C507** — Date/time/period	1 .. 1		010		
├ **DTM** — Date/time/period - Delivery date/time, requested	1 .. 1		0050		
│ └ **C507** — Date/time/period	1 .. 1		010		
├ **DTM** — Date/time/period - Collection date/time, earliest	1 .. 1		0050		
│ └ **C507** — Date/time/period	1 .. 1		010		
├ **DTM** — Date/time/period - Delivery date/time, latest	0 .. 1		0050		
│ └ **C507** — Date/time/period	1 .. 1		010		
├ **TSR** — Transport service requirements	0 .. 9		0060		
│ ├ **C537** — Transport priority	1 .. 1		030		
│ └ **C703** — Nature of cargo	0 .. 1		040		
├ **MOA** — Monetary amount	0 .. 3		0080		
│ └ **C516** — Monetary amount	1 .. 1		010		
├ **FTX** — Free text	0 .. 99		0090		
│ └ **C108** — Text literal	1 .. 1		040		
├ **SG2** — Segment Group 2: TOD-LOC	0 .. 1		0150		
│ ├ **TOD** — Terms of delivery or transport	1 .. 1		0160		
│ │ └ **C100** — Terms of delivery or transport	1 .. 1		030		
│ └ **LOC** — Place/location identification	0 .. 1		0170		
│ └ **C517** — Location identification	1 .. 1		020		
├ **SG3** — Segment Group 3: RFF-DTM	1 .. 99		0180		
│ └ **RFF** — Reference	1 .. 1		0190		
│ └ **C506** — Reference	1 .. 1		010		
├ **SG11** — Segment Group 11: NAD-LOC-MOA-SG12-SG13-SG14-SG15-SG16-SG17	0 .. 3		0560		
│ └ **NAD** — Name and address	1 .. 1		0570		
│ ├ **C082** — Party identification details	0 .. 1		020		
│ ├ **C080** — Party name	0 .. 1		040		
│ └ **C059** — Street	0 .. 1		050		
├ **SG18** — Segment Group 18: GID-HAN-TMP-RNG-TMD-LOC-MOA-PIA-FTX-SG19-GDS-SG20-SG21-SG22-SG32	0 .. 999		0880		
│ ├ **GID** — Goods item details	1 .. 1		0890		
│ │ └ **C213** — Number and type of packages	0 .. 1		020		
│ ├ **FTX** — Free text	0 .. 9		0970		
│ │ └ **C108** — Text literal	1 .. 1		040		
│ ├ **SG20** — Segment Group 20: MEA-EQN	0 .. 3		1020		
│ │ └ **MEA** — Measurements	1 .. 1		1030		
│ │ ├ **C502** — Measurement details	1 .. 1		020		
│ │ └ **C174** — Value/range	1 .. 1		030		
│ ├ **SG23** — Segment Group 23: PCI-RFF-DTM-GIN	0 .. 1		111		

			0		
├ **PCI** — Package identification - Marked with serial shipping container code	1 .. 1		1120		
└ **GIN** — Goods identity number	1 .. 1		1150		
└ **C208** — Identity number range	1 .. 1		020		
└ **SG32** — Segment Group 32: DGS-FTX-SG33-SG34-SG35	0 .. 9		1470		
├ **DGS** — Dangerous goods	1 .. 1		1480		
├ **C205** — Hazard code	1 .. 1		020		
├ **C234** — Undg information	0 .. 1		030		
├ **C223** — Dangerous goods shipment flashpoint	0 .. 1		040		
└ **C236** — Dangerous goods label	0 .. 1		100		
├ **FTX** — Free text	0 .. 99		1490		
├ **C107** — Text reference	0 .. 1		030		
└ **C108** — Text literal	1 .. 1		040		
└ **SG34** — Segment Group 34: MEA-EQN	0 .. 9		1530		
└ **MEA** — Measurements	1 .. 1		1540		
├ **C502** — Measurement details	1 .. 1		020		
└ **C174** — Value/range	1 .. 1		030		
└ **UNT** — MESSAGE TRAILER	1 .. 1		1880		

4 DETAILS MESSAGE

4.1 IFTMIN — Instruction message

Structure

Node	Card.	Prim.Type	Pos.	Length	Codelists
IFTMIN — Instruction message	1 .. 1				
├ **UNH** — MESSAGE HEADER	1 .. 1		0010		
├ **BGM** — Beginning of message	1 .. 1		0020		
├ **DTM** — Date/time/period - Document/message date/time	1 .. 1		0050		
├ **DTM** — Date/time/period - Delivery date/time, requested	1 .. 1		0050		
├ **DTM** — Date/time/period - Collection date/time, earliest	1 .. 1		0050		
├ **DTM** — Date/time/period - Delivery date/time, latest	0 .. 1		0050		
├ **TSR** — Transport service requirements	0 .. 9		0060		
├ **MOA** — Monetary amount	0 .. 3		0080		
├ **FTX** — Free text	0 .. 99		0090		
├ **SG2** — Segment Group 2: TOD-LOC	0 .. 1		0150		
├ **SG3** — Segment Group 3: RFF-DTM	1 .. 99		0180		
├ **SG11** — Segment Group 11: NAD-LOC-MOA-SG12-SG13-SG14-SG15-SG16-SG17	0 .. 3		0560		
├ **SG18** — Segment Group 18: GID-HAN-TMP-RNG-TMD-LOC-MOA-PIA-FTX-SG19-GDS-SG20-SG21-SG22-SG32	0 .. 999		0880		
└ **UNT** — MESSAGE TRAILER	1 .. 1		1880		

Properties

Identifier IFTMIN

Name Instruction message

Cardinality min: 1 max: 1

Notes

Example 1

UNA:+.?
‘ UNB+UNOC:3+shipper-id:14:shipper-lbn-id+carrier-id:14:carrier-lbn-id+210218:1152+00100++IFTMIN’
UNH+1+IFTMIN:D:96A:UN’ BGM+340::9+freight-order-id#loading-stop-id#unloading-stop-id+9’
DTM+63:20211220:102’ DTM+2:20211220:102’ DTM+137:202111161743:203’
DTM+234:202112160142:203’ TSR+++6’ RFF+DQ:123456789’ RFF+ZZ1:sender-system-id’
RFF+ZZ2:freight-order-id’ RFF+ZZ3:loading-location-id’ RFF+ZZ4:unloading-location-id’
RFF+ZZ5:shipper-lbn-id’ RFF+ZZ6:carrier-lbn-id’ RFF+ZZ7:loading-stop--id’ RFF+ZZ8:unloading-stop-id’
NAD+CZ+shipper-id++company name+Street 111+City++12345+DE’
GID+1+1:DD:::000000000130000016’ FTX+AAA+++NAT-ORANGE-FLAVOURIN’
MEA+WT+AAE+KGM:58.78’ MEA+WT+AAF+KGM:57.00’ MEA+VOL+AAW+MTQ:1.884’
PCI+28+freight-order-id’ GIN+BJ+140459973028819358’ FTX+AAE++15:ZZZ+d-Limonene::2’
MEA+WT+AAE+KGM:50.0’ UNT+24+1’ UNZ+1+00100’

Example 2

UNA:+.?
‘ UNB+UNOC:3+shipper-id:14:shipper-lbn-id+carrier-id:14:carrier-lbn-id+210218:1152+00101++IFTMIN’
UNH+1+IFTMIN:D:96A:UN’ BGM+610::9+freight-order-id#loading-stop-id#unloading-stop-id+4’
DTM+63:202112200840:203’ DTM+2:20211220:102’ DTM+137:202111161743:203’
DTM+234:202112160142:203’ TSR+++20+HAZ’ MOA+123:1000:EUR’ FTX+DEL+++some free text’
TOD+6++DDP’ LOC+1+MACON’ RFF+DQ:123456789’ RFF+ZZ1:sender-system-id’
RFF+ZZ2:freight-order-id’ RFF+ZZ3:loading-location-id’ RFF+ZZ4:unloading-location-id’
RFF+ZZ5:shipper-lbn-id’ RFF+ZZ6:carrier-lbn-id’ RFF+ZZ7:loading-stop--id’ RFF+ZZ8:unloading-stop-id’
NAD+CZ+shipper-id++company name+Street 111+City++12345+DE’
GID+1+1:DD:::000000000130000016’ FTX+AAA+++NAT-ORANGE-FLAVOURIN’
MEA+WT+AAE+KGM:58.78’ MEA+WT+AAF+KGM:57.00’ MEA+VOL+AAW+MTQ:1.884’
PCI+28+freight-order-id’ GIN+BJ+140459973028819358’

DGS+ADR+9:M6+3082+099:CEL+III+++++9:X:X' FTX+AAE++15:ZZZ+d-Limonene::2'
MEA+WT+AAE+KGM:50.0' UNT+30+1' UNZ+1+00101'

Example 3

UNA:+.?
' UNB+UNOC:3+shipper-id:14:shipper-lbn-id+carrier-id:14:carrier-lbn-id+210218:1152+00102++IFTMIN'
UNH+1+IFTMIN:D:96A:UN' BGM+610::9+freight-order-id#loading-stop-id#unloading-stop-id+1'
DTM+63:202112200840:203' DTM+2:20211220:102' DTM+137:202111161743:203'
DTM+234:202112160142:203' TSR+++6+HAZ' TOD+6++DDP' LOC+1+MACON' RFF+DQ:123456789'
RFF+ZZ1:sender-system-id' RFF+ZZ2:freight-order-id' RFF+ZZ3:loading-location-id'
RFF+ZZ4:unloading-location-id' RFF+ZZ5:shipper-lbn-id' RFF+ZZ6:carrier-lbn-id'
RFF+ZZ7:loading-stop--id' RFF+ZZ8:unloading-stop-id' NAD+CZ+shipper-id++company name+Street
111+City++12345+DE' GID+1+1:DD:::000000000130000016' FTX+AAA+++NAT-ORANGE-FLAVOURIN'
MEA+WT+AAE+KGM:58.78' MEA+WT+AAF+KGM:57.00' MEA+VOL+AAW+MTQ:1.884'
PCI+28+freight-order-id' GIN+BJ+140459973028819358'
DGS+ADR+9:M6+3082+099:CEL+III+++++9:X:X' FTX+AAE++15:ZZZ+d-Limonene::2'
MEA+WT+AAE+KGM:50.0' UNT+25+1' UNZ+1+00102'

4.2 UNH — MESSAGE HEADER

Structure

Node	Card.	Prim.Type	Pos.	Length	Codelists
IFTMIN — Instruction message	1 .. 1				
├ **UNH** — MESSAGE HEADER	1 .. 1		0010		
│ ├ **0062** — Message reference number	1 .. 1	String	010	1 .. 14	
│ └ **S009** — MESSAGE IDENTIFIER	1 .. 1		020		

Documentation

Definition A service segment starting and uniquely identifying a message. The message type code for the Instruction message is IFTMIN. Note: Instruction messages conforming to this document must contain the following data in segment UNH, composite S009: Data element 0065 IFTMIN 0052 D 0054 96A 0051 UN

Properties

Identifier UNH

Name MESSAGE HEADER

Cardinality min: 1 max: 1

Syntax Type Related

External Category Segment

Position 0010

Level 2

Notes

Example 1 UNH+1+IFTMIN:D:96A:UN’

Leaf Elements

Identifier/Name	Description/Notes/Code Values	Properties
0062 Message reference number	Unique message reference assigned by the sender.	**Cardinality** min: 1 max: 1 **Primitive Type** String **Length** min: 1 max: 14 **External Category** Data Element **Data Type** an **Position** 010

4.3 S009 — MESSAGE IDENTIFIER

Structure

Node	Card.	Prim.Type	Pos.	Length	Codelists
IFTMIN — Instruction message	1 .. 1				
├ **UNH** — MESSAGE HEADER	1 .. 1		0010		
│ └ **S009** — MESSAGE IDENTIFIER	1 .. 1		020		
│ ├ **0065** — Message type identifier	1 .. 1	String	010	1 .. 6	0065
│ ├ **0052** — Message type version number	1 .. 1	String	020	1 .. 3	0052
│ ├ **0054** — Message type release number	1 .. 1	String	030	1 .. 3	0054
│ └ **0051** — Controlling agency	1 .. 1	String	040	1 .. 2	0051

Documentation

Definition Identification of the type, version etc. of the message being interchanged.

Properties

Identifier S009

Name MESSAGE IDENTIFIER

Cardinality min: 1 max: 1

Syntax Type Related

External Category Composite Data Element

Position 020

Leaf Elements

Identifier/Name	Description/Notes/Code Values	Properties
0065 Message type identifier	Code identifying a type of message and assigned by its controlling agency. **Selected Values** **Code** IFTMIN	**Cardinality** min: 1 max: 1 **Primitive Type** String **Length** min: 1 max: 6 **External Category** Data Element **Data Type** an **Position** 010 **Fixed Value** IFTMIN **Codelist Id** 0065 **Type System** UNEDIFACT **Version Mode** Current **Version** D.96A S3
0052 Message type version number	Version number of a message type. **Selected Values** All Values in Codelist	**Cardinality** min: 1 max: 1 **Primitive Type** String **Length** min: 1 max: 3 **External Category** Data Element **Data Type** an **Position** 020 **Fixed Value** D **Codelist Id** 0052 **Type System** UNEDIFACT **Version Mode** Current **Version** D.96A S3
0054 Message type release number	Release number within the current message type version number (0052). **Selected Values** All Values in Codelist	**Cardinality** min: 1 max: 1 **Primitive Type** String **Length** min: 1 max: 3 **External Category** Data Element **Data Type** an **Position** 030 **Fixed Value** 96A