		Codelist Id 0054 **Type System** UNEDIFACT **Version Mode** Current **Version** D.96A S3
0051 Controlling agency	Code identifying the agency controlling the specification, maintenance and publication of the message type. **Selected Values** **Code** UN	**Cardinality** **min:** 1 **max:** 1 **Primitive Type** String **Length** **min:** 1 **max:** 2 **External Category** Data Element **Data Type** an **Position** 040 **Fixed Value** UN **Codelist Id** 0051 **Type System** UNEDIFACT **Version Mode** Current **Version** D.96A S3

4.4 BGM — Beginning of message

Structure

Node	Card.	Prim.Type	Pos.	Length	Codelists
IFTMIN — Instruction message	1 .. 1				
├ **BGM** — Beginning of message	1 .. 1		0020		
│ ├ **C002** — Document/message name	1 .. 1		010		
│ ├ **1004** — Document/message number	1 .. 1	String	020	1 .. 35	
│ └ **1225** — Message function, coded	1 .. 1	String	030	1 .. 3	1225

Documentation

Definition A segment to indicate the beginning of a message and to transmit identifying number and type of the message.

Properties

Identifier BGM

Name Beginning of message

Cardinality min: 1 max: 1

Syntax Type Related

External Category Segment

Position 0020

Level 2

Notes

Example 1 BGM+610::9+5000154024#0000054387+9

Leaf Elements

Identifier/Name	Description/Notes/Code Values	Properties
1004 Document/message number	Reference number assigned to the document/message by the issuer. **Usage 1** The shipping number, which is a concatenation of the freight order identifier, a hash sign as separator and the internal location identifier of the ship-to location of the consignee. It is used to identify the original document for status updates via an IFTSTA message during execution of the transport by the carrier.	**Cardinality** min: 1 max: 1 **Primitive Type** String **Length** min: 1 max: 35 **External Category** Data Element **Data Type** an **Position** 020
1225 Message function, coded	Code indicating the function of the message. **Usage 1** Code 4 corresponds to the pre-advice (340) message, code 9 to the final (610) message. **Selected Values** **Code** 1 **Code** 4 **Code** 9	**Cardinality** min: 1 max: 1 **Primitive Type** String **Length** min: 1 max: 3 **External Category** Data Element **Data Type** an **Position** 030 **Codelist Id** 1225 **Type System** UNEDIFACT **Version Mode** Current **Version** D.96A S3

4.5 C002 — Document/message name

Structure

Node	Card.	Prim.Type	Pos.	Length	Codelists
IFTMIN — Instruction message	1 .. 1				
├ **BGM** — Beginning of message	1 .. 1		0020		
│ ├ **C002** — Document/message name	1 .. 1		010		
│ │ ├ **1001** — Document/message name, coded	1 .. 1	String	010	1 .. 3	1001
│ │ └ **3055** — Code list responsible agency, coded	1 .. 1	String	030	1 .. 3	3055

Documentation

Definition Identification of a type of document/message by code or name. Code preferred.

Properties

Identifier C002

Name Document/message name

Cardinality min: 1 max: 1

Syntax Type Related

External Category Composite Data Element

Position 010

Leaf Elements

Identifier/Name	Description/Notes/Code Values	Properties
1001 Document/message name, coded	Document/message identifier expressed in code. Note: Users should note that code values marked as additions or changes are included pending approval by the 1001 Maintenance Agency and may be disapproved or changed. The results of this review will be reflected in a future version of the draft directory. **Usage 1** Code 340 is used for a pre-advice message, which can be sent multiple times with changed content, i.e. items or dates. **Usage 2** Code 610 is used for the final message, when the freight order was finalized and no changes are expected anymore. **Selected Values** **Code** 340 **Code** 610	**Cardinality** min: 1 max: 1 **Primitive Type** String **Length** min: 1 max: 3 **External Category** Data Element **Data Type** an **Position** 010 **Codelist Id** 1001 **Type System** UNEDIFACT **Version Mode** Current **Version** D.96A S3
3055 Code list responsible agency, coded	Code identifying the agency responsible for a code list. **Selected Values** **Code** 9	**Cardinality** min: 1 max: 1 **Primitive Type** String **Length** min: 1 max: 3 **External Category** Data Element **Data Type** an **Position** 030 **Fixed Value** 9 **Codelist Id** 3055 **Type System** UNEDIFACT **Version Mode** Current **Version** D.96A S3

4.6 DTM [2005 = “137”] — Date/time/period - Document/message date/time

Structure

Node	Card.	Prim.Type	Pos.	Length	Codelists
IFTMIN — Instruction message	1 .. 1				
┣ **DTM** — Date/time/period - Document/message date/time	1 .. 1		0050		
┃ ┗ **C507** — Date/time/period	1 .. 1		010		

Documentation

Definition A segment to indicate a date and time applying to the whole message, e.g., date and time of document issue.

Properties

Identifier DTM

Name Date/time/period - Document/message date/time

Cardinality min: 1 max: 1

Syntax Type Related

External Category Segment

Position 0050

Level 2

Notes

Usage 1 This segment will be used to transmit the order date.

Usage 2 There is no timezone transmitted, because in logistics many carriers expect the date/time values in the local timezone of the corresponding location. This means the time is in the local timezone of the consignor’s location, specified in the NAD+CZ segment.

Example 1 DTM+137:202102181152:203’

4.7 C507 — Date/time/period

Structure

Node	Card.	Prim.Type	Pos.	Length	Codelists
IFTMIN — Instruction message	1 .. 1				
├ **DTM** — Date/time/period - Document/message date/time	1 .. 1		0050		
│ └ **C507** — Date/time/period	1 .. 1		010		
│ ├ **2005** — Date/time/period qualifier	1 .. 1	String	010	1 .. 3	2005
│ ├ **2380** — Date/time/period	1 .. 1	String	020	1 .. 35	
│ └ **2379** — Date/time/period format qualifier	1 .. 1	String	030	1 .. 3	2379

Documentation

Definition Date and/or time, or period relevant to the specified date/time/period type.

Properties

Identifier C507

Name Date/time/period

Cardinality min: 1 max: 1

Syntax Type Related

External Category Composite Data Element

Position 010

Leaf Elements

Identifier/Name	Description/Notes/Code Values	Properties
2005 Date/time/period qualifier	Code giving specific meaning to a date, time or period. **Selected Values** **Code** 137	**Cardinality** min: 1 max: 1 **Primitive Type** String **Length** min: 1 max: 3 **External Category** Data Element **Data Type** an **Position** 010 **Fixed Value** 137 **Codelist Id** 2005 **Type System** UNEDIFACT **Version Mode** Current **Version** D.96A S3
2380 Date/time/period	The value of a date, a date and time, a time or of a period in a specified representation.	**Cardinality** min: 1 max: 1 **Primitive Type** String **Length** min: 1 max: 35 **External Category** Data Element **Data Type** an **Position** 020
2379 Date/time/period format qualifier	Specification of the representation of a date, a date and time or of a period. **Selected Values** **Code** 203	**Cardinality** min: 1 max: 1 **Primitive Type** String **Length** min: 1 max: 3 **External Category** Data Element **Data Type** an **Position** 030 **Fixed Value** 203 **Codelist Id** 2379 **Type System** UNEDIFACT **Version Mode** Current **Version** D.96A S3

4.8 DTM [2005 = “2”] — Date/time/period - Delivery date/time, requested

Structure

Node	Card.	Prim.Type	Pos.	Length	Codelists
IFTMIN — Instruction message	1 .. 1				
├ **DTM** — Date/time/period - Delivery date/time, requested	1 .. 1		0050		
│ └ **C507** — Date/time/period	1 .. 1		010		

Documentation

Definition A segment to indicate a date and time applying to the whole message, e.g., date and time of document issue.

Properties

Identifier DTM

Name Date/time/period - Delivery date/time, requested

Cardinality min: 1 max: 1

Syntax Type Related

External Category Segment

Position 0050

Level 2

Notes

Usage 1 There is no timezone transmitted, because in logistics many carriers expect the date/time values in the local timezone of the corresponding location. This means the time is in the local timezone of the consignee’s location, specified in the NAD+CN segment.

Example 1 DTM+2:20210224:102’

4.9 C507 — Date/time/period

Structure

Node	Card.	Prim.Type	Pos.	Length	Codelists
IFTMIN — Instruction message	1 .. 1				
├ **DTM** — Date/time/period - Delivery date/time, requested	1 .. 1		0050		
│ └ **C507** — Date/time/period	1 .. 1		010		
│ ├ **2005** — Date/time/period qualifier	1 .. 1	String	010	1 .. 3	2005
│ ├ **2380** — Date/time/period	1 .. 1	String	020	1 .. 35	
│ └ **2379** — Date/time/period format qualifier	1 .. 1	String	030	1 .. 3	2379

Documentation

Definition Date and/or time, or period relevant to the specified date/time/period type.

Properties

Identifier C507

Name Date/time/period

Cardinality min: 1 max: 1

Syntax Type Related

External Category Composite Data Element

Position 010

Leaf Elements

Identifier/Name	Description/Notes/Code Values	Properties
2005 Date/time/period qualifier	Code giving specific meaning to a date, time or period. **Selected Values** **Code** 2	**Cardinality** min: 1 max: 1 **Primitive Type** String **Length** min: 1 max: 3 **External Category** Data Element **Data Type** an **Position** 010 **Fixed Value** 2 **Codelist Id** 2005 **Type System** UNEDIFACT **Version Mode** Current **Version** D.96A S3
2380 Date/time/period	The value of a date, a date and time, a time or of a period in a specified representation.	**Cardinality** min: 1 max: 1 **Primitive Type** String **Length** min: 1 max: 35 **External Category** Data Element **Data Type** an **Position** 020
2379 Date/time/period format qualifier	Specification of the representation of a date, a date and time or of a period. **Selected Values** **Code** 102	**Cardinality** min: 1 max: 1 **Primitive Type** String **Length** min: 1 max: 3 **External Category** Data Element **Data Type** an **Position** 030 **Fixed Value** 102 **Codelist Id** 2379 **Type System** UNEDIFACT **Version Mode** Current **Version** D.96A S3

4.10 DTM [2005 = “234”] — Date/time/period - Collection date/time, earliest

Structure

Node	Card.	Prim.Type	Pos.	Length	Codelists
IFTMIN — Instruction message	1 .. 1				
├ **DTM** — Date/time/period - Collection date/time, earliest	1 .. 1		0050		
│ └ **C507** — Date/time/period	1 .. 1		010		

Documentation

Definition A segment to indicate a date and time applying to the whole message, e.g., date and time of document issue.

Properties

Identifier DTM

Name Date/time/period - Collection date/time, earliest

Cardinality min: 1 max: 1

Syntax Type Related

External Category Segment

Position 0050

Level 2

Notes

Usage 1 This segment will be used to transmit the earliest pickup date/time.

Usage 2 There is no timezone transmitted, because in logistics many carriers expect the date/time values in the local timezone of the corresponding location. This means the time is in the local timezone of the consignor’s location, specified in the NAD+CZ segment.

Example 1 DTM+234:202102181000:203’

4.11 C507 — Date/time/period

Structure

Node	Card.	Prim.Type	Pos.	Length	Codelists
IFTMIN — Instruction message	1 .. 1				
├ **DTM** — Date/time/period - Collection date/time, earliest	1 .. 1		0050		
│ └ **C507** — Date/time/period	1 .. 1		010		
│ ├ **2005** — Date/time/period qualifier	1 .. 1	String	010	1 .. 3	2005
│ ├ **2380** — Date/time/period	1 .. 1	String	020	1 .. 35	
│ └ **2379** — Date/time/period format qualifier	1 .. 1	String	030	1 .. 3	2379

Documentation

Definition Date and/or time, or period relevant to the specified date/time/period type.

Properties

Identifier C507

Name Date/time/period

Cardinality min: 1 max: 1

Syntax Type Related

External Category Composite Data Element

Position 010

Leaf Elements

Identifier/Name	Description/Notes/Code Values	Properties
2005 Date/time/period qualifier	Code giving specific meaning to a date, time or period. **Selected Values** **Code** 234	**Cardinality** min: 1 max: 1 **Primitive Type** String **Length** min: 1 max: 3 **External Category** Data Element **Data Type** an **Position** 010 **Fixed Value** 234 **Codelist Id** 2005 **Type System** UNEDIFACT **Version Mode** Current **Version** D.96A S3
2380 Date/time/period	The value of a date, a date and time, a time or of a period in a specified representation.	**Cardinality** min: 1 max: 1 **Primitive Type** String **Length** min: 1 max: 35 **External Category** Data Element **Data Type** an **Position** 020
2379 Date/time/period format qualifier	Specification of the representation of a date, a date and time or of a period. **Selected Values** **Code** 203	**Cardinality** min: 1 max: 1 **Primitive Type** String **Length** min: 1 max: 3 **External Category** Data Element **Data Type** an **Position** 030 **Fixed Value** 203 **Codelist Id** 2379 **Type System** UNEDIFACT **Version Mode** Current **Version** D.96A S3

4.12 DTM [2005 = “63”] — Date/time/period - Delivery date/time, latest

Structure

Node	Card.	Prim.Type	Pos.	Length	Codelists
IFTMIN — Instruction message	1 .. 1				
├ **DTM** — Date/time/period - Delivery date/time, latest	0 .. 1		0050		
│ └ **C507** — Date/time/period	1 .. 1		010		

Documentation

Definition A segment to indicate a date and time applying to the whole message, e.g., date and time of document issue.

Properties

Identifier DTM

Name Date/time/period - Delivery date/time, latest

Cardinality min: 0 max: 1

Syntax Type Related

External Category Segment

Position 0050

Level 2

Notes

Usage 1 This segment is only present for a pre-advice message and will be used to transmit the latest delivery date/time.

Usage 2 The used date/time format qualifier depends on the transport priority code 4219 in the TSR segment. For priority code 20 the format code 203 is used, for all other codes the format code 102 is used.

Usage 3 There is no timezone transmitted, because in logistics many carriers expect the date/time values in the local timezone of the corresponding location. This means the time is in the local timezone of the consignee’s location, specified in the NAD+CN segment.