## 4.21 SG2 — Segment Group 2: TOD-LOC

### Structure

| Node | Card. | Prim.Type | Pos. | Length | Codelists |
|---|---|---|---|---|---|
| **IFTMIN** — Instruction message | 1 .. 1 | | | | |
| ├ **SG2** — Segment Group 2: TOD-LOC | 0 .. 1 | | 0150 | | |
| │ ├ **TOD** — Terms of delivery or transport | 1 .. 1 | | 0160 | | |
| │ └ **LOC** — Place/location identification | 0 .. 1 | | 0170 | | |

### Documentation

**Definition** A group of segments to specify terms of delivery and related locations.

### Properties

**Identifier** SG2

**Name** Segment Group 2: TOD-LOC

**Cardinality** min: 0 max: 1

### Syntax Type Related

**External Category** Segment Group

**Position** 0150

**Level** 2

## 4.22 TOD — Terms of delivery or transport

### Structure

| Node | Card. | Prim.Type | Pos. | Length | Codelists |
|---|---|---|---|---|---|
| **IFTMIN** — Instruction message | 1 .. 1 | | | | |
| ├ **SG2** — Segment Group 2: TOD-LOC | 0 .. 1 | | 0150 | | |
| │ ├ **TOD** — Terms of delivery or transport | 1 .. 1 | | 0160 | | |
| │ │ ├ **4055** — Terms of delivery or transport function, coded | 1 .. 1 | String | 010 | 1 .. 3 | 4055 |
| │ │ └ **C100** — Terms of delivery or transport | 1 .. 1 | | 030 | | |

### Documentation

**Definition** A segment to specify the applicable terms of delivery.

### Properties

**Identifier** TOD

**Name** Terms of delivery or transport

**Cardinality** min: 1 max: 1

### Syntax Type Related

**External Category** Segment

**Position** 0160

**Level** 3

### Notes

**Example 1** TOD+6++DDP'

### Leaf Elements

| Identifier/Name | Description/Notes/Code Values | Properties |
|---|---|---|
| **4055**<br>Terms of delivery or transport function, coded | Indication whether the terms relate to e.g. price conditions, delivery conditions, transport conditions, or a combination of these.<br><br>**Selected Values**<br>**Code** 6 | **Cardinality** min: 1 max: 1<br>**Primitive Type** String<br>**Length** min: 1 max: 3<br>**External Category** Data Element<br>**Data Type** an<br>**Position** 010<br>**Fixed Value** 6<br><br>**Codelist Id** 4055<br>**Type System** UNEDIFACT<br>**Version Mode** Current<br>**Version** D.96A S3 |

## 4.23 C100 — Terms of delivery or transport

### Structure

| Node | Card. | Prim.Type | Pos. | Length | Codelists |
|---|---|---|---|---|---|
| **IFTMIN** — Instruction message | 1 .. 1 | | | | |
| ├ **SG2** — Segment Group 2: TOD-LOC | 0 .. 1 | | 0150 | | |
| │ ├ **TOD** — Terms of delivery or transport | 1 .. 1 | | 0160 | | |
| │ │ └ **C100** — Terms of delivery or transport | 1 .. 1 | | 030 | | |
| │ │ └ **4053** — Terms of delivery or transport, coded | 1 .. 1 | String | 010 | 1 .. 3 | Rec_5_custom |

### Documentation

**Definition** Terms of delivery or transport code from a specified source.

### Properties

**Identifier** C100

**Name** Terms of delivery or transport

**Cardinality** min: 1 max: 1

### Syntax Type Related

**External Category** Composite Data Element

**Position** 030

### Leaf Elements

| Identifier/Name | Description/Notes/Code Values | Properties |
|---|---|---|
| **4053**<br>Terms of delivery or transport, coded | Identification of the terms agreed between two parties (e.g. seller/buyer, shipper/carrier) under which a product or service is provided. Note: Use UN/ECE Recommendation No. 5 Incoterms 1990. If not applicable, use appropriate code set in combination with 1131/3055.<br><br>**Usage 1**<br>Contains the Incoterm code.<br><br>**Selected Values**<br>**Code** CFR **Name** Costs and Freight<br>**Code** CIF **Name** Costs,Insurance & Freight<br>**Code** CIP **Name** Carriage and Insurance Paid to<br>**Code** CPT **Name** Carriage Paid to<br>**Code** DAT **Name** Delivered at Terminal<br>**Code** DAP **Name** Delivered at Place<br>**Code** DAF **Name** Delivered at Frontier<br>**Code** DDP **Name** Delivered Duty Paid<br>**Code** DDU **Name** Delivered Duty Unpaid<br>**Code** DEQ **Name** Delivered Ex Quay (Duty Paid)<br>**Code** DES **Name** Delivered Ex Ship<br>**Code** EXW **Name** Ex Works<br>**Code** FAS **Name** Free Alongside Ship<br>**Code** FCA **Name** Free Carrier<br>**Code** FH **Name** Free House<br>**Code** FOB **Name** Free on Board<br>**Code** UN **Name** Not Free | **Cardinality** min: 1 max: 1<br>**Primitive Type** String<br>**Length** min: 1 max: 3<br>**External Category** Data Element<br>**Data Type** an<br>**Position** 010<br><br>**Codelist Id** Rec_5_custom<br>**Version Mode** Fixed |

## 4.24 LOC — Place/location identification

### Structure

| Node | Card. | Prim.Type | Pos. | Length | Codelists |
|---|---|---|---|---|---|
| **IFTMIN** — Instruction message | 1 .. 1 | | | | |
| ├ **SG2** — Segment Group 2: TOD-LOC | 0 .. 1 | | 0150 | | |
| │ └ **LOC** — Place/location identification | 0 .. 1 | | 0170 | | |
| │ ├ **3227** — Place/location qualifier | 1 .. 1 | String | 010 | 1 .. 3 | 3227 |
| │ └ **C517** — Location identification | 1 .. 1 | | 020 | | |

### Documentation

**Definition** A segment to specify a location related to the terms of delivery.

### Properties

**Identifier** LOC

**Name** Place/location identification

**Cardinality** min: 0 max: 1

### Syntax Type Related

**External Category** Segment

**Position** 0170

**Level** 3

### Notes

**Example 1** LOC+1+MACON'

### Leaf Elements

| Identifier/Name | Description/Notes/Code Values | Properties |
|---|---|---|
| **3227**<br>Place/location qualifier | Code identifying the function of a location.<br><br>**Selected Values**<br>**Code** 1 | **Cardinality** min: 1 max: 1<br>**Primitive Type** String<br>**Length** min: 1 max: 3<br>**External Category** Data Element<br>**Data Type** an<br>**Position** 010<br>**Fixed Value** 1<br><br>**Codelist Id** 3227<br>**Type System** UNEDIFACT<br>**Version Mode** Current<br>**Version** D.96A S3 |

## 4.25 C517 — Location identification

### Structure

| Node | Card. | Prim.Type | Pos. | Length | Codelists |
|---|---|---|---|---|---|
| **IFTMIN** — Instruction message | 1 .. 1 | | | | |
| ┣ **SG2** — Segment Group 2: TOD-LOC | 0 .. 1 | | 0150 | | |
| ┃ ┗ **LOC** — Place/location identification | 0 .. 1 | | 0170 | | |
| ┃ ┗ **C517** — Location identification | 1 .. 1 | | 020 | | |
| ┃ ┗ **3225** — Place/location identification | 1 .. 1 | String | 010 | 1 .. 25 | |

### Documentation

**Definition** Identification of a location by code or name.

### Properties

**Identifier** C517

**Name** Location identification

**Cardinality** min: 1 max: 1

### Syntax Type Related

**External Category** Composite Data Element

**Position** 020

### Leaf Elements

| Identifier/Name | Description/Notes/Code Values | Properties |
|---|---|---|
| **3225**<br>Place/location identification | Identification of the name of place/location, other than 3164 City name. Note: Use UN/ECE Recommendation No. 16: UNLOCODE. If not applicable, use appropriate code set in combination with 1131/3055.<br><br>**Usage 1**<br>The corresponding Incoterm location as free-text. Not all Incoterm codes need to specify a location. | **Cardinality** min: 1 max: 1<br>**Primitive Type** String<br>**Length** min: 1 max: 25<br>**External Category** Data Element<br>**Data Type** an<br>**Position** 010 |

## 4.26 SG3 — Segment Group 3: RFF-DTM

### Structure

| Node | Card. | Prim.Type | Pos. | Length | Codelists |
|---|---|---|---|---|---|
| **IFTMIN** — Instruction message | 1 .. 1 | | | | |
| ┣ **SG3** — Segment Group 3: RFF-DTM | 1 .. 99 | | 0180 | | |
| ┃ ┗ **RFF** — Reference | 1 .. 1 | | 0190 | | |

### Documentation

**Definition** A group of segments containing a reference and constants which apply to the entire message.

### Properties

**Identifier** SG3

**Name** Segment Group 3: RFF-DTM

**Cardinality** min: 1 max: 99

### Syntax Type Related

**External Category** Segment Group

**Position** 0180

**Level** 2

## 4.27 RFF — Reference

### Structure

| Node | Card. | Prim.Type | Pos. | Length | Codelists |
|---|---|---|---|---|---|
| **IFTMIN** — Instruction message | 1 .. 1 | | | | |
| ├ **SG3** — Segment Group 3: RFF-DTM | 1 .. 99 | | 0180 | | |
| │ └ **RFF** — Reference | 1 .. 1 | | 0190 | | |
| │ └ **C506** — Reference | 1 .. 1 | | 010 | | |

### Documentation

**Definition** A segment to express a reference which applies to the entire message such as: the document/message number that is to be updated by this very message (according to data element 1225 Message Function, Coded in segment BGM), booking reference, order number, insurance contract, etc.

### Properties

**Identifier** RFF

**Name** Reference

**Cardinality** min: 1 max: 1

### Syntax Type Related

**External Category** Segment

**Position** 0190

**Level** 3

### Notes

**Usage 1** RFF+ZZ1, ZZ2, ZZ7 and ZZ8 fields contain Sendersystem-ID, Freightorder-ID, Loadingstop-ID and Unloadingstop-ID. The same fields are expected in corresponding IFTSTA messages.

**Example 1** RFF+DQ:801250912’ RFF+ZZ1:QM7_910’ RFF+ZZ2:500167201’ RFF+ZZ7:1’ RFF+ZZ8:3’

## 4.28 C506 — Reference

### Structure

| Node | Card. | Prim.Type | Pos. | Length | Codelists |
|---|---|---|---|---|---|
| **IFTMIN** — Instruction message | 1 .. 1 | | | | |
| ├ **SG3** — Segment Group 3: RFF-DTM | 1 .. 99 | | 0180 | | |
| │ └ **RFF** — Reference | 1 .. 1 | | 0190 | | |
| │ └ **C506** — Reference | 1 .. 1 | | 010 | | |
| │ ├ **1153** — Reference qualifier | 1 .. 1 | String | 010 | 1 .. 3 | 1153_custom |
| │ └ **1154** — Reference number | 1 .. 1 | String | 020 | 1 .. 35 | |

### Documentation

**Definition** Identification of a reference.

### Properties

**Identifier** C506

**Name** Reference

**Cardinality** min: 1 max: 1

### Syntax Type Related

**External Category** Composite Data Element

**Position** 010

### Leaf Elements

| Identifier/Name | Description/Notes/Code Values | Properties |
|---|---|---|
| **1153**<br>Reference qualifier | Code giving specific meaning to a reference segment or a reference number.<br><br>**Constraint 1**<br>RFF+ZZ1-6 needed for updating the status of the original freight order after receiving IFTSTA message. It is mandatory that the corresponding IFTSTA message contains the same RFF+ZZ1-6 segments.<br><br>**Selected Values**<br>**Code** DQ **Name** Delivery note number<br>Reference number assigned by the issuer to a delivery note.<br>**Code** ON **Name** Order number (purchase)<br>[1022] Reference number assigned by the buyer to an order.<br>**Code** ZZ1 **Name** Originator ID<br>Sender system ID<br>**Code** ZZ2 **Name** Freight order ID<br>**Code** ZZ3 **Name** Loading location ID<br>**Code** ZZ4 **Name** Unloading location ID<br>**Code** ZZ5 **Name** Ordering party LBN ID<br>**Code** ZZ6 **Name** Carrier LBN ID<br>**Code** ZZ7 **Name** Loading stop ID<br>**Code** ZZ8 **Name** Unloading stop ID | **Cardinality** min: 1 max: 1<br>**Primitive Type** String<br>**Length** min: 1 max: 3<br>**External Category** Data Element<br>**Data Type** an<br>**Position** 010<br><br>**Codelist Id** 1153_custom<br>**Version Mode** Fixed |
| **1154**<br>Reference number | Identification number the nature and function of which can be qualified by an entry in data element 1153 Reference qualifier. | **Cardinality** min: 1 max: 1<br>**Primitive Type** String<br>**Length** min: 1 max: 35<br>**External Category** Data Element<br>**Data Type** an<br>**Position** 020 |

## 4.29 SG11 — Segment Group 11: NAD-LOC-MOA-SG12-SG13-SG14-SG15-SG16-SG17

### Structure

| Node | Card. | Prim.Type | Pos. | Length | Codelists |
|---|---|---|---|---|---|
| **IFTMIN** — Instruction message | 1 .. 1 | | | | |
| ├ **SG11** — Segment Group 11: NAD-LOC-MOA-SG12-SG13-SG14-SG15-SG16-SG17 | 0 .. 3 | | 0560 | | |
| │ └ **NAD** — Name and address | 1 .. 1 | | 0570 | | |

### Documentation

**Definition** A group of segments to identify a party, related references, locations contacts, required documents, and charges to be paid by the party.

### Properties

**Identifier** SG11

**Name** Segment Group 11: NAD-LOC-MOA-SG12-SG13-SG14-SG15-SG16-SG17

**Cardinality** min: 0 max: 3

### Syntax Type Related

**External Category** Segment Group

**Position** 0560

**Level** 2

## 4.30 NAD — Name and address

### Structure

| Node | Card. | Prim.Type | Pos. | Length | Codelists |
|---|---|---|---|---|---|
| **IFTMIN** — Instruction message | 1 .. 1 | | | | |
| ├ **SG11** — Segment Group 11: NAD-LOC-MOA-SG12-SG13-SG14-SG15-SG16-SG17 | 0 .. 3 | | 0560 | | |
| │ └ **NAD** — Name and address | 1 .. 1 | | 0570 | | |
| │ ├ **3035** — Party qualifier | 1 .. 1 | String | 010 | 1 .. 3 | 3035 |
| │ ├ **C082** — Party identification details | 0 .. 1 | | 020 | | |
| │ ├ **C080** — Party name | 0 .. 1 | | 040 | | |
| │ ├ **C059** — Street | 0 .. 1 | | 050 | | |
| │ ├ **3164** — City name | 0 .. 1 | String | 060 | 1 .. 35 | |
| │ ├ **3251** — Postcode identification | 0 .. 1 | String | 080 | 1 .. 9 | |
| │ └ **3207** — Country, coded | 0 .. 1 | String | 090 | 1 .. 3 | ISO_3166-1 |

### Documentation

**Definition** A segment to identify the party's name, address, and function.

### Properties

**Identifier** NAD

**Name** Name and address

**Cardinality** min: 1 max: 1

### Syntax Type Related

**External Category** Segment

**Position** 0570

**Level** 3

### Notes

**Usage 1** In SAP LBN the street name and house ID are separate fields and can be longer than 35 characters when concatenated. The street name will be shortened in case it exceeds the maximum length, so that it fits with the unshortened house ID into the data element.

**Example 1** NAD+CZ+1234567890000++ABCDEFGHIJKLMN GmbH+Straße 111+STADT++12345+DE'

### Leaf Elements

| Identifier/Name | Description/Notes/Code Values | Properties |
|---|---|---|
| **3035**<br>Party qualifier | Code giving specific meaning to a party.<br><br>**Selected Values**<br>**Code** CZ **Name** Consignor<br>(3336) Party which, by contract with a carrier, consigns or sends goods with the carrier, or has them conveyed by him. Synonym: shipper, sender.<br>**Code** FW **Name** Freight forwarder<br>Party arranging forwarding of goods.<br>**Code** CN **Name** Consignee<br>(3132) Party to which goods are consigned.<br>**Code** II **Name** Issuer of invoice<br>(3028) Party issuing an invoice.<br>**Code** IV **Name** Invoicee<br>(3006) Party to whom an invoice is issued.<br>**Code VN Name** Vendor Party vending goods or services. | **Cardinality** min: 1 max: 1<br>**Primitive Type** String<br>**Length** min: 1 max: 3<br>**External Category** Data Element<br>**Data Type** an<br>**Position** 010<br><br>**Codelist Id** 3035<br>**Type System** UNEDIFACT<br>**Version Mode** Current<br>**Version** D.96A S3 |
| **3164**<br>City name | Name of a city (a town, a village) for addressing purposes. | **Cardinality** min: 0 max: 1<br>**Primitive Type** String<br>**Length** min: 1 max: 35 |