4.5 SG4 — Segment Group 4: CNI-LOC-CNT-SG5

Structure

Node	Card.	Prim.Type	Pos.	Length	Codelists
IFTSTA — International multimodal status report message	1 .. 1				
├ **SG4** — Segment Group 4: CNI-LOC-CNT-SG5	0 .. 99999		0160		
│ ├ **CNI** — Consignment information	1 .. 1		0170		
│ └ **SG5** — Segment Group 5: STS-RFF-DTM-DOC-FTX-SG6-LOC-PCI-SG8-SG10-SG14	1 .. 99		0200		

Documentation

Definition A group of segments to identify a consignment and status details relating to it.

Properties

Identifier SG4

Name Segment Group 4: CNI-LOC-CNT-SG5

Cardinality min: 0 max: 99999

Syntax Type Related

External Category Segment Group

Position 0160

Level 2

4.6 CNI — Consignment information

Structure

Node	Card.	Prim.Type	Pos.	Length	Codelists
IFTSTA — International multimodal status report message	1 .. 1				
├ **SG4** — Segment Group 4: CNI-LOC-CNT-SG5	0 .. 99999		0160		
│ ├ **CNI** — Consignment information	1 .. 1		0170		

Documentation

Definition A segment to identify a consignment for which status details are given.

Properties

Identifier CNI

Name Consignment information

Cardinality min: 1 max: 1

Syntax Type Related

External Category Segment

Position 0170

Level 3

Notes

Comment 2 None of the information in CNI is used in SAP LBN. Hence there is no validation of numbers and identifiers transmitted in this segment.

Example 1 CNI+6+04441458664'

4.7 SG5 — Segment Group 5: STS-RFF-DTM-DOC-FTX-SG6-LOC-PCI-SG8-SG10-SG14

Structure

Node	Card.	Prim.Type	Pos.	Length	Codelists
IFTSTA — International multimodal status report message	1 .. 1				
├ **SG4** — Segment Group 4: CNI-LOC-CNT-SG5	0 .. 99999		0160		
│ └ **SG5** — Segment Group 5: STS-RFF-DTM-DOC-FTX-SG6-LOC-PCI-SG8-SG10-SG14	1 .. 99		0200		
│ ├ **STS** — Status	1 .. 1		0210		
│ ├ **RFF** — Reference - originatorId	1 .. 1		0220		
│ ├ **RFF** — Reference - freightOrderId	1 .. 1		0220		
│ ├ **RFF** — Reference - orderingPartyLbnId	1 .. 1		0220		
│ ├ **RFF** — Reference - unloadingStopId	1 .. 1		0220		
│ ├ **RFF** — Reference - lbnSourceSystemId	1 .. 1		0220		
│ ├ **RFF** — Reference - trackingType	1 .. 1		0220		
│ ├ **RFF** — Reference - locationType	1 .. 1		0220		
│ ├ **RFF** — Reference - locationId	1 .. 1		0220		
│ ├ **RFF** — Reference - ordinalNo	1 .. 1		0220		
│ ├ **RFF** — Reference - latitude	1 .. 1		0220		
│ ├ **RFF** — Reference - longitude	1 .. 1		0220		
│ └ **DTM** — Date/time/period	1 .. 1		0230		

Documentation

Definition A group of segments indicating the status and/or identifying an event and specifying relevant details.

Properties

Identifier SG5

Name Segment Group 5: STS-RFF-DTM-DOC-FTX-SG6-LOC-PCI-SG8-SG10-SG14

Cardinality min: 1 max: 99

Syntax Type Related

External Category Segment Group

Position 0200

Level 3

Notes

Tech. Info. 1 The structures can differ. Currently the following scenarios of IFTSTA messages are supported: - 1 Event* per Interchange UNB - UNZ - 1 Event per Message** - n Events per Message - n Events per CNI-STS-RFF * 1 Event = CNI/STS ** 1 Message = UNH-UNT

4.8 STS — Status

Structure

Node	Card.	Prim.Type	Pos.	Length	Codelists
IFTSTA — International multimodal status report message	1 .. 1				
├ **SG4** — Segment Group 4: CNI-LOC-CNT-SG5	0 .. 99999		0160		
│ └ **SG5** — Segment Group 5: STS-RFF-DTM-DOC-FTX-SG6-LOC-PCI-SG8-SG10-SG14	1 .. 99		0200		
│ ├ **STS** — Status	1 .. 1		0210		
│ │ └ **C555** — Status	1 .. 1		020		

Documentation

Definition A segment specifying the status relating to a consignment (e.g. loaded).

Properties

Identifier STS

Name Status

Cardinality min: 1 max: 1

Syntax Type Related

External Category Segment

Position 0210

Level 4

Notes

Usage 1 SG5 is a split criteria for message processing in SAP LBN, if an IFTSTA contains bulk status updates. This allows to transmit multiple status events either as multiple IFTSTA messages within an interchange, multiple SG5 groups in a single IFTSTA message, or any combination of these.

Comment 1 SAP LBN currently only processes status updates related to delivery events, i.e. SG4/SG5/STS/C555/4405 equals code 21. Any other STS with a different code value will be ignored.

Comment 2 The status codes 21 correspond to the Destination Location Arrival Event in SAP LBN.

Comment 3 A freight order can have multiple shipments in SAP LBN.

Example 1 STS+1+21+108:::ZUGESTELLT

4.9 C555 — Status

Structure

Node	Card.	Prim.Type	Pos.	Length	Codelists
IFTSTA — International multimodal status report message	1 .. 1				
├ **SG4** — Segment Group 4: CNI-LOC-CNT-SG5	0 .. 99999		0160		
│ └ **SG5** — Segment Group 5: STS-RFF-DTM-DOC-FTX-SG6-LOC-PCI-SG8-SG10-SG14	1 .. 99		0200		
│ ├ **STS** — Status	1 .. 1		0210		
│ │ └ **C555** — Status	1 .. 1		020		
│ │ └ **4405** — Status description code	1 .. 1	String	010	1 .. 3	Rec_24

Documentation

Definition To specify a status.

Properties

Identifier C555

Name Status

Cardinality min: 1 max: 1

Syntax Type Related

External Category Composite Data Element

Position 020

Leaf Elements

Identifier/Name	Description/Notes/Code Values	Properties
4405 Status description code	Code specifying a status. **Constraint 1** If any not supported code is sent, the whole message will be ignored. **Tech. Info. 1** Please find the mapping from EDI to LBN codelists - Event Status Code Descriptions. 1 -> ARRIV_DEST 21 -> ARRIV_DEST 24 -> DEPARTURE 20 -> DELAYED 25 -> DELAYED 29 -> UNLOAD_END 31 -> OUT_FOR_DELIVERY 48 -> LOAD_END LBN Event Status Code Descriptions for reference - https://help.sap.com/docs/business-network-freight-collaboration/code-lists/event-code-descriptions **Selected Values** **Code** 21 **Name** Delivery, completed The goods/consignment/equipment has been delivered. **Code** 1 **Name** Arrival, completed The goods/consignment/equipment/means of transport has arrived. **Code** 20 **Name** Delayed, in the course of transportation The goods/consignment/equipment/means of transport has been delayed in the course of transportation. **Code** 25 **Name** Departure, delayed The means of transport has been delayed	**Cardinality** min: 1 max: 1 **Primitive Type** String **Length** min: 1 max: 3 **External Category** Data Element **Data Type** an **Position** 010 **Codelist Id** Rec_24 **Type System** UNCEFACT_TFR **Version Mode** Latest **Version** 2017

	in departure. **Code** 31 **Name** En route The goods/consignment/equipment/means of transport is moving to destination. **Code** 48 **Name** Loading, completed onto a means of transport The goods/consignment/equipment has been loaded onto a means of transport. **Code** 24 **Name** Departure, completed The means of transport has departed. **Code** 29 **Name** Unloaded The goods/consignment/equipment has been unloaded from a means of transport.	

4.10 RFF [1153 = “ZZ1”] — Reference - originatorId

Structure

Node	Card.	Prim.Type	Pos.	Length	Codelists
IFTSTA — International multimodal status report message	1 .. 1				
├ **SG4** — Segment Group 4: CNI-LOC-CNT-SG5	0 .. 99999		0160		
│ └ **SG5** — Segment Group 5: STS-RFF-DTM-DOC-FTX-SG6-LOC-PCI-SG8-SG10-SG14	1 .. 99		0200		
│ ├ **RFF** — Reference - originatorId	1 .. 1		0220		
│ │ └ **C506** — Reference	1 .. 1		010		

Documentation

Definition A segment identifying a reference relating to the status (e.g House Bill of Lading number).

Properties

Identifier RFF

Name Reference - originatorId

Cardinality min: 1 max: 1

Syntax Type Related

External Category Segment

Position 0220

Level 4

Notes

Usage 1 RFF+ZZ1, ZZ2, ZZ8 and ZZA fields are mandatory. They contain Sendersystem-ID, Freightorder-ID, Unloadingstop-ID and Trackingtype. The same fields are provided in the corresponding outbound IFTSTA message.

Comment 1 A freight order can have multiple shipments in SAP LBN.

Example 1 RFF+ZZ1:QM7_910’ RFF+ZZ2:9899301234’ RFF+ZZ8:98993012340001’ RFF+ZZA:FT1_SHIPMENT’

4.11 C506 — Reference

Structure

Node	Card.	Prim.Type	Pos.	Length	Codelists
IFTSTA — International multimodal status report message	1 .. 1				
├ **SG4** — Segment Group 4: CNI-LOC-CNT-SG5	0 .. 99999		0160		
│ └ **SG5** — Segment Group 5: STS-RFF-DTM-DOC-FTX-SG6-LOC-PCI-SG8-SG10-SG14	1 .. 99		0200		
│ ├ **RFF** — Reference - originatorId	1 .. 1		0220		
│ │ └ **C506** — Reference	1 .. 1		010		
│ │ ├ **1153** — Reference code qualifier	1 .. 1	String	010	1 .. 3	1
│ │ └ **1154** — Reference identifier	1 .. 1	String	020	1 .. 70	

Documentation

Definition Identification of a reference.

Properties

Identifier C506

Name Reference

Cardinality min: 1 max: 1

Syntax Type Related

External Category Composite Data Element

Position 010

Leaf Elements

Identifier/Name	Description/Notes/Code Values	Properties
1153 Reference code qualifier	Code qualifying a reference. **Tech. Info. 1** Retrieved from headerNotes in the IFTMIN-Message: S_RFF - C_C506 - D_1153 **Selected Values** **Code** ZZ1 **Name** originatorId	**Cardinality** min: 1 max: 1 **Primitive Type** String **Length** min: 1 max: 3 **External Category** Data Element **Data Type** an **Position** 010 **Codelist Id** 1 **Version Mode** Fixed
1154 Reference identifier	Identifies a reference. **Example 1** 10000290#ALE	**Cardinality** min: 1 max: 1 **Primitive Type** String **Length** min: 1 max: 70 **External Category** Data Element **Data Type** an **Position** 020

4.12 RFF [1153 = “ZZ2”] — Reference - freightOrderId

Structure

Node	Card.	Prim.Type	Pos.	Length	Codelists
IFTSTA — International multimodal status report message	1 .. 1				
├ **SG4** — Segment Group 4: CNI-LOC-CNT-SG5	0 .. 99999		0160		
│ └ **SG5** — Segment Group 5: STS-RFF-DTM-DOC-FTX-SG6-LOC-PCI-SG8-SG10-SG14	1 .. 99		0200		
│ ├ **RFF** — Reference - freightOrderId	1 .. 1		0220		
│ │ └ **C506** — Reference	1 .. 1		010		

Documentation

Definition A segment identifying a reference relating to the status (e.g House Bill of Lading number).

Properties

Identifier RFF

Name Reference - freightOrderId

Cardinality min: 1 max: 1

Syntax Type Related

External Category Segment

Position 0220

Level 4

Notes

Usage 1 RFF+ZZ1, ZZ2, ZZ8 and ZZA fields are mandatory. They contain Sendersystem-ID, Freightorder-ID, Unloadingstop-ID and Trackingtype. The same fields are provided in the corresponding outbound IFTSTA message.

Comment 1 A freight order can have multiple shipments in SAP LBN.

Example 1 RFF+ZZ1:QM7_910’ RFF+ZZ2:9899301234’ RFF+ZZ8:98993012340001’ RFF+ZZA:FT1_SHIPMENT’

4.13 C506 — Reference

Structure

Node	Card.	Prim.Type	Pos.	Length	Codelists
IFTSTA — International multimodal status report message	1 .. 1				
├ **SG4** — Segment Group 4: CNI-LOC-CNT-SG5	0 .. 99999		0160		
│ └ **SG5** — Segment Group 5: STS-RFF-DTM-DOC-FTX-SG6-LOC-PCI-SG8-SG10-SG14	1 .. 99		0200		
│ ├ **RFF** — Reference - freightOrderId	1 .. 1		0220		
│ │ └ **C506** — Reference	1 .. 1		010		
│ │ ├ **1153** — Reference code qualifier	1 .. 1	String	010	1 .. 3	1
│ │ └ **1154** — Reference identifier	1 .. 1	String	020	1 .. 70	

Documentation

Definition Identification of a reference.

Properties

Identifier C506

Name Reference

Cardinality min: 1 max: 1

Syntax Type Related

External Category Composite Data Element

Position 010

Leaf Elements

Identifier/Name	Description/Notes/Code Values	Properties
1153 Reference code qualifier	Code qualifying a reference. **Tech. Info. 1** Retrieved from headerNotes in the IFTMIN-Message: S_RFF - C_C506 - D_1153 **Selected Values** **Code** ZZ2 **Name** freightOrderId	**Cardinality** min: 1 max: 1 **Primitive Type** String **Length** min: 1 max: 3 **External Category** Data Element **Data Type** an **Position** 010 **Codelist Id** 1 **Version Mode** Fixed
1154 Reference identifier	Identifies a reference. **Example 1** 10000290#ALE	**Cardinality** min: 1 max: 1 **Primitive Type** String **Length** min: 1 max: 70 **External Category** Data Element **Data Type** an **Position** 020