4.14 RFF [1153 = “ZZ5”] — Reference - orderingPartyLbnId

Structure

Node	Card.	Prim.Type	Pos.	Length	Codelists
IFTSTA — International multimodal status report message	1 .. 1				
├ **SG4** — Segment Group 4: CNI-LOC-CNT-SG5	0 .. 99999		0160		
│ └ **SG5** — Segment Group 5: STS-RFF-DTM-DOC-FTX-SG6-LOC-PCI-SG8-SG10-SG14	1 .. 99		0200		
│ ├ **RFF** — Reference - orderingPartyLbnId	1 .. 1		0220		
│ │ └ **C506** — Reference	1 .. 1		010		

Documentation

Definition A segment identifying a reference relating to the status (e.g House Bill of Lading number).

Properties

Identifier RFF

Name Reference - orderingPartyLbnId

Cardinality min: 1 max: 1

Syntax Type Related

External Category Segment

Position 0220

Level 4

Notes

Usage 1 RFF+ZZ5 is not mandatory. It conatins orderingPartyLbnId, and ordering party LBN ID will be derived from the message header.

Comment 1 A freight order can have multiple shipments in SAP LBN.

Example 1 RFF+ZZ5:10000040’

4.15 C506 — Reference

Structure

Node	Card.	Prim.Type	Pos.	Length	Codelists
IFTSTA — International multimodal status report message	1 .. 1				
├ **SG4** — Segment Group 4: CNI-LOC-CNT-SG5	0 .. 99999		0160		
│ └ **SG5** — Segment Group 5: STS-RFF-DTM-DOC-FTX-SG6-LOC-PCI-SG8-SG10-SG14	1 .. 99		0200		
│ ├ **RFF** — Reference - orderingPartyLbnId	1 .. 1		0220		
│ │ └ **C506** — Reference	1 .. 1		010		
│ │ ├ **1153** — Reference code qualifier	1 .. 1	String	010	1 .. 3	1
│ │ └ **1154** — Reference identifier	1 .. 1	String	020	1 .. 70	

Documentation

Definition Identification of a reference.

Properties

Identifier C506

Name Reference

Cardinality min: 1 max: 1

Syntax Type Related

External Category Composite Data Element

Position 010

Leaf Elements

Identifier/Name	Description/Notes/Code Values	Properties
1153 Reference code qualifier	Code qualifying a reference. **Tech. Info. 1** Retrieved from headerNotes in the IFTMIN-Message: S_RFF - C_C506 - D_1153 **Selected Values** **Code** ZZ5 **Name** orderingPartyLbnId	**Cardinality** min: 1 max: 1 **Primitive Type** String **Length** min: 1 max: 3 **External Category** Data Element **Data Type** an **Position** 010 **Codelist Id** 1 **Version Mode** Fixed
1154 Reference identifier	Identifies a reference. **Example 1** 10000290#ALE	**Cardinality** min: 1 max: 1 **Primitive Type** String **Length** min: 1 max: 70 **External Category** Data Element **Data Type** an **Position** 020

4.16 RFF [1153 = “ZZ8”] — Reference - unloadingStopId

Structure

Node	Card.	Prim.Type	Pos.	Length	Codelists
IFTSTA — International multimodal status report message	1 .. 1				
├ **SG4** — Segment Group 4: CNI-LOC-CNT-SG5	0 .. 99999		0160		
│ └ **SG5** — Segment Group 5: STS-RFF-DTM-DOC-FTX-SG6-LOC-PCI-SG8-SG10-SG14	1 .. 99		0200		
│ ├ **RFF** — Reference - unloadingStopId	1 .. 1		0220		
│ │ └ **C506** — Reference	1 .. 1		010		

Documentation

Definition A segment identifying a reference relating to the status (e.g House Bill of Lading number).

Properties

Identifier RFF

Name Reference - unloadingStopId

Cardinality min: 1 max: 1

Syntax Type Related

External Category Segment

Position 0220

Level 4

Notes

Usage 1 RFF+ZZ1, ZZ2, ZZ8 and ZZA fields are mandatory. They contain Sendersystem-ID, Freightorder-ID, Unloadingstop-ID and Trackingtype. The same fields are provided in the corresponding outbound IFTSTA message.

Comment 1 A freight order can have multiple shipments in SAP LBN.

Example 1 RFF+ZZ1:QM7_910’ RFF+ZZ2:9899301234’ RFF+ZZ8:98993012340001’ RFF+ZZA:FT1_SHIPMENT

4.17 C506 — Reference

Structure

Node	Card.	Prim.Type	Pos.	Length	Codelists
IFTSTA — International multimodal status report message	1 .. 1				
├ **SG4** — Segment Group 4: CNI-LOC-CNT-SG5	0 .. 99999		0160		
│ └ **SG5** — Segment Group 5: STS-RFF-DTM-DOC-FTX-SG6-LOC-PCI-SG8-SG10-SG14	1 .. 99		0200		
│ ├ **RFF** — Reference - unloadingStopId	1 .. 1		0220		
│ │ └ **C506** — Reference	1 .. 1		010		
│ │ ├ **1153** — Reference code qualifier	1 .. 1	String	010	1 .. 3	1
│ │ └ **1154** — Reference identifier	1 .. 1	String	020	1 .. 70	

Documentation

Definition Identification of a reference.

Properties

Identifier C506

Name Reference

Cardinality min: 1 max: 1

Syntax Type Related

External Category Composite Data Element

Position 010

Leaf Elements

Identifier/Name	Description/Notes/Code Values	Properties
1153 Reference code qualifier	Code qualifying a reference. **Tech. Info. 1** Retrieved from headerNotes in the IFTMIN-Message: S_RFF - C_C506 - D_1153 **Selected Values** **Code** ZZ8 **Name** unloadingStopId	**Cardinality** min: 1 max: 1 **Primitive Type** String **Length** min: 1 max: 3 **External Category** Data Element **Data Type** an **Position** 010 **Codelist Id** 1 **Version Mode** Fixed
1154 Reference identifier	Identifies a reference. **Example 1** 10000290#ALE	**Cardinality** min: 1 max: 1 **Primitive Type** String **Length** min: 1 max: 70 **External Category** Data Element **Data Type** an **Position** 020

4.18 RFF [1153 = “ZZ9”] — Reference - IbnSourceSystemId

Structure

Node	Card.	Prim.Type	Pos.	Length	Codelists
IFTSTA — International multimodal status report message	1 .. 1				
├ **SG4** — Segment Group 4: CNI-LOC-CNT-SG5	0 .. 99999		0160		
│ └ **SG5** — Segment Group 5: STS-RFF-DTM-DOC-FTX-SG6-LOC-PCI-SG8-SG10-SG14	1 .. 99		0200		
│ ├ **RFF** — Reference - IbnSourceSystemId	1 .. 1		0220		
│ │ └ **C506** — Reference	1 .. 1		010		

Documentation

Definition A segment identifying a reference relating to the status (e.g House Bill of Lading number).

Properties

Identifier RFF

Name Reference - IbnSourceSystemId

Cardinality min: 1 max: 1

Syntax Type Related

External Category Segment

Position 0220

Level 4

Notes

Usage 1 RFF+ZZ9 field is mandatory in the inbound message. You must set its value to GTT. The same field is provided in the corresponding outbound IFTSTA message.

Example 1 RFF+ZZ9:GTT’

4.19 C506 — Reference

Structure

Node	Card.	Prim.Type	Pos.	Length	Codelists
IFTSTA — International multimodal status report message	1 .. 1				
├ **SG4** — Segment Group 4: CNI-LOC-CNT-SG5	0 .. 99999		0160		
│ └ **SG5** — Segment Group 5: STS-RFF-DTM-DOC-FTX-SG6-LOC-PCI-SG8-SG10-SG14	1 .. 99		0200		
│ ├ **RFF** — Reference - lbnSourceSystemId	1 .. 1		0220		
│ │ └ **C506** — Reference	1 .. 1		010		
│ │ ├ **1153** — Reference code qualifier	1 .. 1	String	010	1 .. 3	1
│ │ └ **1154** — Reference identifier	1 .. 1	String	020	1 .. 70	

Documentation

Definition Identification of a reference.

Properties

Identifier C506

Name Reference

Cardinality min: 1 max: 1

Syntax Type Related

External Category Composite Data Element

Position 010

Leaf Elements

Identifier/Name	Description/Notes/Code Values	Properties
1153 Reference code qualifier	Code qualifying a reference. **Tech. Info. 1** Retrieved from headerNotes in the IFTMIN-Message: S_RFF - C_C506 - D_1153 **Selected Values** **Code** ZZ9 **Name** lbnSourceSystemId	**Cardinality** min: 1 max: 1 **Primitive Type** String **Length** min: 1 max: 3 **External Category** Data Element **Data Type** an **Position** 010 **Codelist Id** 1 **Version Mode** Fixed
1154 Reference identifier	Identifies a reference. **Example 1** 10000290#ALE	**Cardinality** min: 1 max: 1 **Primitive Type** String **Length** min: 1 max: 70 **External Category** Data Element **Data Type** an **Position** 020

4.20 RFF [1153 = “ZZA”] — Reference - trackingType

Structure

Node	Card.	Prim.Type	Pos.	Length	Codelists
IFTSTA — International multimodal status report message	1 .. 1				
├ **SG4** — Segment Group 4: CNI-LOC-CNT-SG5	0 .. 99999		0160		
│ └ **SG5** — Segment Group 5: STS-RFF-DTM-DOC-FTX-SG6-LOC-PCI-SG8-SG10-SG14	1 .. 99		0200		
│ ├ **RFF** — Reference - trackingType	1 .. 1		0220		
│ │ └ **C506** — Reference	1 .. 1		010		

Documentation

Definition A segment identifying a reference relating to the status (e.g House Bill of Lading number).

Properties

Identifier RFF

Name Reference - trackingType

Cardinality min: 1 max: 1

Syntax Type Related

External Category Segment

Position 0220

Level 4

Notes

Usage 1 RFF+ZZ1, ZZ2, ZZ8 and ZZA fields are mandatory. They contain Sendersystem-ID, Freightorder-ID, Unloadingstop-ID and Trackingtype. The same fields are provided in the corresponding outbound IFTSTA message.

Comment 1 A freight order can have multiple shipments in SAP LBN.

Example 1 RFF+ZZ1:QM7_910’ RFF+ZZ2:9899301234’ RFF+ZZ8:98993012340001’ RFF+ZZA:FT1_SHIPMENT

4.21 C506 — Reference

Structure

Node	Card.	Prim.Type	Pos.	Length	Codelists
IFTSTA — International multimodal status report message	1 .. 1				
├ **SG4** — Segment Group 4: CNI-LOC-CNT-SG5	0 .. 99999		0160		
│ └ **SG5** — Segment Group 5: STS-RFF-DTM-DOC-FTX-SG6-LOC-PCI-SG8-SG10-SG14	1 .. 99		0200		
│ ├ **RFF** — Reference - trackingType	1 .. 1		0220		
│ │ └ **C506** — Reference	1 .. 1		010		
│ │ ├ **1153** — Reference code qualifier	1 .. 1	String	010	1 .. 3	1
│ │ └ **1154** — Reference identifier	1 .. 1	String	020	1 .. 70	

Documentation

Definition Identification of a reference.

Properties

Identifier C506

Name Reference

Cardinality min: 1 max: 1

Syntax Type Related

External Category Composite Data Element

Position 010

Leaf Elements

Identifier/Name	Description/Notes/Code Values	Properties
1153 Reference code qualifier	Code qualifying a reference. **Tech. Info. 1** Retrieved from headerNotes in the IFTMIN-Message: S_RFF - C_C506 - D_1153 **Selected Values** **Code** ZZA **Name** trackingType	**Cardinality** min: 1 max: 1 **Primitive Type** String **Length** min: 1 max: 3 **External Category** Data Element **Data Type** an **Position** 010 **Codelist Id** 1 **Version Mode** Fixed
1154 Reference identifier	Identifies a reference. **Example 1** 10000290#ALE	**Cardinality** min: 1 max: 1 **Primitive Type** String **Length** min: 1 max: 70 **External Category** Data Element **Data Type** an **Position** 020

4.22 RFF [1153 = “ZZB”] — Reference - locationType

Structure

Node	Card.	Prim.Type	Pos.	Length	Codelists
IFTSTA — International multimodal status report message	1 .. 1				
├ **SG4** — Segment Group 4: CNI-LOC-CNT-SG5	0 .. 99999		0160		
│ └ **SG5** — Segment Group 5: STS-RFF-DTM-DOC-FTX-SG6-LOC-PCI-SG8-SG10-SG14	1 .. 99		0200		
│ ├ **RFF** — Reference - locationType	1 .. 1		0220		
│ │ └ **C506** — Reference	1 .. 1		010		

Documentation

Definition A segment identifying a reference relating to the status (e.g House Bill of Lading number).

Properties

Identifier RFF

Name Reference - locationType

Cardinality min: 1 max: 1

Syntax Type Related

External Category Segment

Position 0220

Level 4

Notes

Usage 1 RFF+ZZB and ZZC fields are not mandatory. They contain LocationType and LocationId.

Example 1 RFF+ZZB:ShippingPoint’ RFF+ZZC:SP_ZS96’

4.23 C506 — Reference

Structure

Node	Card.	Prim.Type	Pos.	Length	Codelists
IFTSTA — International multimodal status report message	1 .. 1				
├ **SG4** — Segment Group 4: CNI-LOC-CNT-SG5	0 .. 99999		0160		
│ └ **SG5** — Segment Group 5: STS-RFF-DTM-DOC-FTX-SG6-LOC-PCI-SG8-SG10-SG14	1 .. 99		0200		
│ ├ **RFF** — Reference - locationType	1 .. 1		0220		
│ │ └ **C506** — Reference	1 .. 1		010		
│ │ ├ **1153** — Reference code qualifier	1 .. 1	String	010	1 .. 3	1
│ │ └ **1154** — Reference identifier	1 .. 1	String	020	1 .. 70	

Documentation

Definition Identification of a reference.

Properties

Identifier C506

Name Reference

Cardinality min: 1 max: 1

Syntax Type Related

External Category Composite Data Element

Position 010

Leaf Elements

Identifier/Name	Description/Notes/Code Values	Properties
1153 Reference code qualifier	Code qualifying a reference. **Tech. Info. 1** Retrieved from headerNotes in the IFTMIN-Message: S_RFF - C_C506 - D_1153 **Selected Values** **Code** ZZB **Name** locationType	**Cardinality** min: 1 max: 1 **Primitive Type** String **Length** min: 1 max: 3 **External Category** Data Element **Data Type** an **Position** 010 **Codelist Id** 1 **Version Mode** Fixed
1154 Reference identifier	Identifies a reference. **Example 1** 10000290#ALE	**Cardinality** min: 1 max: 1 **Primitive Type** String **Length** min: 1 max: 70 **External Category** Data Element **Data Type** an **Position** 020