2.7 FunctionalGroup — Functional Group

Structure

Node	Card.	Prim.Type	Pos.	Length	Codelists
Interchange — Interchange Structure	1 .. 1				
├ **FunctionalGroup** — Functional Group	1 .. *				

Properties

Identifier FunctionalGroup

Name Functional Group

Cardinality min: 1 max: *

Syntax Type Related

External Category Element

Notes

Tech. Info. 0 Choice : (FunctionalGroup) (maxOccurs : 1) (minOccurs : 1)

2.8 S_UNZ — S UNZ

Structure

Node	Card.	Prim.Type	Pos.	Length	Codelists
Interchange — Interchange Structure	1 .. 1				
└ **S_UNZ** — S UNZ	1 .. 1				
├ **D_0036** — Interchange control count	1 .. 1	Decimal			
└ **D_0020** — Interchange control reference	1 .. 1	String		1 .. 14	

Properties

Identifier S_UNZ

Name S UNZ

Cardinality min: 1 max: 1

Syntax Type Related

External Category Element

Leaf Elements

Identifier/Name	Description/Notes/Code Values	Properties
D_0036 Interchange control count	The count either of the number of messages or, if used, of the number of functional groups in an interchange. One of these counts shall appear.	**Cardinality** min: 1 max: 1 **Primitive Type** Decimal **Length** min: 0 **Total Digits** 6 **External Category** Element **Data Type** xsd:decimal
D_0020 Interchange control reference	Unique reference assigned by the sender to an interchange. **Usage 1** Shall be identical in UNB and UNZ.	**Cardinality** min: 1 max: 1 **Primitive Type** String **Length** min: 1 max: 14 **External Category** Element **Data Type** xsd:string

3 OVERVIEW MESSAGE

General Information

Name	SAP_LBN_EDIFACT_INVOIC
Direction	In
Status	Active
Message Type	Invoice message
Type System	UNEDIFACT
Version	D.96A S3
External Category	Message Type

Documentation

Definition

0. Introduction
This specification provides the definition of the Invoice message (INVOIC) to be used in Electronic Data Interchange (EDI) between trading partners involved in administration, commerce and transport.
1.1 Functional Definition
A message claiming payment for goods or services supplied under conditions agreed between the seller and the buyer.
The United Nations Standard Invoice Message, with correct data qualification, serves also as the specification for Debit Note and Credit Note messages. Throughout this document, the reference to 'Invoice' may be interpreted as conveying the wider meaning of 'Invoice/Credit Note/Debit Note'.
The UN Standard Invoice Message may be applied for both national and international trade. It is based on universal commercial practice and is not dependent on the type of business or industry.
1.3 Principles
- A seller may invoice for one or more transactions
- An invoice may refer to goods, items or services related to one or more orders, delivery instructions, call-offs, etc.
- An invoice may contain references to payment terms
- An invoice for cross border transactions may contain additional information for customs and/or statistical purposes/services
- An invoice may contain transport details.
4.1 Data Segment Clarification
The following guidelines and principles apply to the whole message and are intended to facilitate the understanding and implementation of the message:
All specified dates/times should be in the format 'yymmdd'/'hhmm' unless all parties involved in the transaction agree that there is a functional requirement for an alternative format. Periods should be specified as whole numbers representing the required period as indicated in the format qualifier (weeks, months, etc.)
Where a choice of code or text is given only the code element should be used wherever possible.
Conditional data that is not required in the message should not be included.
Care must be taken that the segment qualifier in dependent segments do not conflict with the segment qualifier of the trigger segment of a group.
Free text information within the message should be avoided as this inhibits automatic processing.
Source: To be provided

Notes

Example 1

```
UNA:+.? '
UNB+UNOC:3+4023083000008:14+gln-111:14+190228:1456+50'
UNH+1+INVOIC:D:96A:UN'
BGM++invoice-id'
DTM+137:20220905:102'
RFF+ZZ1:sender-system-id'
NAD+II+billing-account'
NAD+IV+carriers-reference-number'
CUX+1:GBP'
LIN+1+++0'
PIA+1+T:'
RFF+ZZ2:freight-order-id'
LIN+2++1+1:1'
PIA+5+lbn-charge-code-1'
MOA+66:65.00'
LIN+3++1+1:2'
PIA+5+lbn-charge-code-2'
MOA+66:4.80'
UNS+S'
MOA+77:69.80'
TAX+7'
MOA+124:81.56'
UNT+41+1'
```

UNZ+1+50'

3.1 Structure

The following table shows only the root element and the group elements.

Node	Card.	Prim.Type	Pos.	Length	Codelists
INVOIC — Invoice message	1 .. 1				
├ **UNH** — MESSAGE HEADER	1 .. 1		0010		
│ └ **S009** — MESSAGE IDENTIFIER	1 .. 1		020		
├ **BGM** — Beginning of message	1 .. 1		0020		
├ **DTM** — Date/time/period - Document/message date/time	1 .. 1		0030		
│ └ **C507** — Date/time/period	1 .. 1		010		
├ **FTX** — Free text	0 .. 10		0070		
│ └ **C108** — Text literal	0 .. 1		040		
├ **SG1** — Segment Group 1: RFF-DTM - Originator ID	1 .. 1		0080		
│ └ **RFF** — Reference	1 .. 1		0090		
│ └ **C506** — Reference	1 .. 1		010		
├ **SG2** — Segment Group 2: NAD-LOC-FII-SG3-SG4-SG5	0 .. 99		0110		
│ ├ **NAD** — Name and address - Issuer of invoice	1 .. 1		0120		
│ │ └ **C082** — Party identification details	1 .. 1		020		
│ └ **NAD** — Name and address - Invoicee	1 .. 1		0120		
│ └ **C082** — Party identification details	1 .. 1		020		
├ **SG7** — Segment Group 7: CUX-DTM	0 .. 1		0280		
│ └ **CUX** — Currencies	1 .. 1		0290		
│ └ **C504** — Currency details - Charge payment currency	1 .. 1		010		
├ **SG25** — Segment Group 25: LIN-PIA-IMD-MEA-QTY-PCD-ALI-DTM-GIN-GIR-QVR-EQD-FTX-SG26-SG46-SG47	0 .. 9999999		0890		
│ ├ **LIN** — Line item	1 .. 1		0900		
│ │ └ **C829** — Sub-line information	0 .. 1		040		
│ ├ **PIA** — Additional product id	0 .. 1		0910		
│ │ └ **C212** — Item number identification	1 .. 1		020		
│ ├ **QTY** — Quantity	0 .. 5		0940		
│ │ └ **C186** — Quantity details	1 .. 1		010		
│ ├ **SG26** — Segment Group 26: MOA-CUX	0 .. 1		1030		
│ │ └ **MOA** — Monetary amount	1 .. 1		1040		
│ │ └ **C516** — Monetary amount	1 .. 1		010		
│ ├ **SG27** — Segment Group 27: PAT-DTM-PCD-MOA	0 .. 10		1060		
│ │ ├ **PAT** — Payment terms basis	1 .. 1		1070		
│ │ └ **PCD** — Percentage details	0 .. 1		1090		
│ │ └ **C501** — Percentage details	1 .. 1		010		
│ ├ **SG28** — Segment Group 28: PRI-APR-RNG-DTM	0 .. 25		1110		
│ │ └ **PRI** — Price details	1 .. 1		1120		
│ │ └ **C509** — Price information	0 .. 1		010		
│ └ **SG29** — Segment Group 29: RFF-DTM - Freight order ID	1 .. 1		1160		
│ └ **RFF** — Reference	1 .. 1		1170		
│ └ **C506** — Reference	1 .. 1		010		
├ **UNS** — SECTION CONTROL	1 .. 1		179		

			0		
├ **SG48** — Segment Group 48: MOA-SG49 - Invoice amount	1 .. 1		1810		
│ └ **MOA** — Monetary amount	1 .. 1		1820		
│ └ **C516** — Monetary amount	1 .. 1		010		
├ **SG50** — Segment Group 50: TAX-MOA	1 .. 1		1860		
│ ├ **TAX** — Duty/tax/fee details	1 .. 1		1870		
│ └ **MOA** — Monetary amount - Tax amount	1 .. 1		1880		
│ └ **C516** — Monetary amount	1 .. 1		010		
└ **UNT** — MESSAGE TRAILER	1 .. 1		1930		

4 DETAILS MESSAGE

4.1 INVOIC — Invoice message

Structure

Node	Card.	Prim.Type	Pos.	Length	Codelists
INVOIC — Invoice message	1 .. 1				
├ **UNH** — MESSAGE HEADER	1 .. 1		0010		
├ **BGM** — Beginning of message	1 .. 1		0020		
├ **DTM** — Date/time/period - Document/message date/time	1 .. 1		0030		
├ **FTX** — Free text	0 .. 10		0070		
├ **SG1** — Segment Group 1: RFF-DTM - Originator ID	1 .. 1		0080		
├ **SG2** — Segment Group 2: NAD-LOC-FII-SG3-SG4-SG5	0 .. 99		0110		
├ **SG7** — Segment Group 7: CUX-DTM	0 .. 1		0280		
├ **SG25** — Segment Group 25: LIN-PIA-IMD-MEA-QTY-PCD-ALI-DTM-GIN-GIR-QVR-EQD-FTX-SG26-SG46-SG47	0 .. 9999999		0890		
├ **UNS** — SECTION CONTROL	1 .. 1		1790		
├ **SG48** — Segment Group 48: MOA-SG49 - Invoice amount	1 .. 1		1810		
├ **SG50** — Segment Group 50: TAX-MOA	1 .. 1		1860		
└ **UNT** — MESSAGE TRAILER	1 .. 1		1930		

Properties

Identifier INVOIC

Name Invoice message

Cardinality min: 1 max: 1

Notes

Example 1

UNA:+.? ' UNB+UNOC:3+4023083000008:14+4054429000000:14+190228:1456+50'
UNH+1+INVOIC:D:96A:UN' BGM+380::9+1232366478+9' DTM+137:20140905:102'
DTM+155:20140901:102' DTM+156:20140901:102' DTM+140:20140901:102'
FTX+PQ+++26076024106607100002' NAD+II+8799999000001++DACHSER+Sample Street 3+Sample City++99999+DE' NAD+IV+53178452++NAME INVOICE RECIPIENT+STREET+CITY++POSTAL+GB'
CUX+1:GBP:4' LIN+1++1+0' PIA+1+T:TG' PIA+5+Z:TG' IMD+A++PIA?+1:::T:European Logistics'
IMD+A++PIA?+5:::Z:targospeed' MEA+WT+AAE+KGM:147' MEA+WT+ACG+KGM:38'
RFF+FF:04037711769' RFF+CR:123456' TOD+++031:::free delivered' LIN+2++1+1:1'
PIA+5+107:SA+EUGB13' IMD+A++:::107:freight ex works' QTY+1:00240:Kg' QTY+1:00030:Zo'
MOA+66:65.00:::1' RFF+TR:1' LIN+3++1+1:2' PIA+5+283:SA+7,40%' IMD+A++:::283:fuel surcharge'
QTY+1:00203:Nk' QTY+1:00000000' MOA+66:4.80:::1' RFF+TR:1' UNS+S' MOA+77:489.36'
TAX+7+VAT+++:::20.00+1' MOA+125:407.80' MOA+124:81.56' UNT+40+1' UNZ+1+50'

4.2 UNH — MESSAGE HEADER

Structure

Node	Card.	Prim.Type	Pos.	Length	Codelists
INVOIC — Invoice message	1 .. 1				
├ **UNH** — MESSAGE HEADER	1 .. 1		0010		
│ ├ **0062** — Message reference number	1 .. 1	String	010	1 .. 14	
│ └ **S009** — MESSAGE IDENTIFIER	1 .. 1		020		

Documentation

Definition A service segment starting and uniquely identifying a message. The message type code for the Invoice message is INVOIC. Note: Invoice messages conforming to this document must contain the following data in segment UNH, composite S009: Data element 0065 INVOIC 0052 D 0054 96A 0051 UN

Properties

Identifier UNH

Name MESSAGE HEADER

Cardinality min: 1 max: 1

Syntax Type Related

External Category Segment

Position 0010

Level 2

Leaf Elements

Identifier/Name	Description/Notes/Code Values	Properties
0062 Message reference number	Unique message reference assigned by the sender.	**Cardinality** min: 1 max: 1 **Primitive Type** String **Length** min: 1 max: 14 **External Category** Data Element **Data Type** an **Position** 010

4.3 S009 — MESSAGE IDENTIFIER

Structure

Node	Card.	Prim.Type	Pos.	Length	Codelists
INVOIC — Invoice message	1 .. 1				
├ **UNH** — MESSAGE HEADER	1 .. 1		0010		
│ └ **S009** — MESSAGE IDENTIFIER	1 .. 1		020		
│ ├ **0065** — Message type identifier	1 .. 1	String	010	1 .. 6	0065
│ ├ **0052** — Message type version number	1 .. 1	String	020	1 .. 3	0052
│ ├ **0054** — Message type release number	1 .. 1	String	030	1 .. 3	0054
│ └ **0051** — Controlling agency	1 .. 1	String	040	1 .. 2	0051

Documentation

Definition Identification of the type, version etc. of the message being interchanged.

Properties

Identifier S009

Name MESSAGE IDENTIFIER

Cardinality min: 1 max: 1

Syntax Type Related

External Category Composite Data Element

Position 020

Leaf Elements

Identifier/Name	Description/Notes/Code Values	Properties
0065 Message type identifier	Code identifying a type of message and assigned by its controlling agency. **Selected Values** All Values in Codelist	**Cardinality** min: 1 max: 1 **Primitive Type** String **Length** min: 1 max: 6 **External Category** Data Element **Data Type** an **Position** 010 **Codelist Id** 0065 **Type System** UNEDIFACT **Version Mode** Current **Version** D.96A S3
0052 Message type version number	Version number of a message type. **Selected Values** All Values in Codelist	**Cardinality** min: 1 max: 1 **Primitive Type** String **Length** min: 1 max: 3 **External Category** Data Element **Data Type** an **Position** 020 **Codelist Id** 0052 **Type System** UNEDIFACT **Version Mode** Current **Version** D.96A S3
0054 Message type release number	Release number within the current message type version number (0052). **Selected Values** All Values in Codelist	**Cardinality** min: 1 max: 1 **Primitive Type** String **Length** min: 1 max: 3 **External Category** Data Element **Data Type** an **Position** 030 **Codelist Id** 0054 **Type System** UNEDIFACT **Version Mode** Current

		Version D.96A S3
0051 Controlling agency	Code identifying the agency controlling the specification, maintenance and publication of the message type. **Selected Values** All Values in Codelist	**Cardinality** **min:** 1 **max:** 1 **Primitive Type** String **Length** **min:** 1 **max:** 2 **External Category** Data Element **Data Type** an **Position** 040 **Codelist Id** 0051 **Type System** UNEDIFACT **Version Mode** Current **Version** D.96A S3