4.4 BGM — Beginning of message

Structure

Node	Card.	Prim.Type	Pos.	Length	Codelists
INVOIC — Invoice message	1 .. 1				
├ **BGM** — Beginning of message	1 .. 1		0020		
│ └ **1004** — Document/message number	0 .. 1	String	020	1 .. 35	

Documentation

Definition A segment by which the sender must uniquely identify the invoice by means of its type and number and when necessary its function.

Properties

Identifier BGM

Name Beginning of message

Cardinality min: 1 max: 1

Syntax Type Related

External Category Segment

Position 0020

Level 2

Leaf Elements

Identifier/Name	Description/Notes/Code Values	Properties
1004 Document/message number	Reference number assigned to the document/message by the issuer. **Usage 1** The invoice ID.	**Cardinality** min: 0 max: 1 **Primitive Type** String **Length** min: 1 max: 35 **External Category** Data Element **Data Type** an **Position** 020

4.5 DTM [2005 = “137”] — Date/time/period - Document/message date/time

Structure

Node	Card.	Prim.Type	Pos.	Length	Codelists
INVOIC — Invoice message	1 .. 1				
├ **DTM** — Date/time/period - Document/message date/time	1 .. 1		0030		
│ └ **C507** — Date/time/period	1 .. 1		010		

Documentation

Definition A segment specifying general dates and, when relevant, times related to the whole message. The segment must be specified at least once to identify the invoice date. Examples of the use of this DTM segment is: “shipped on date” or “delivery date”. The Date/time/period segment within other Segment groups should be used whenever the date/time/period requires to be logically related to another specified data item e.g. Payment due date is specified within the PAT Segment group.

Properties

Identifier DTM

Name Date/time/period - Document/message date/time

Cardinality min: 1 max: 1

Syntax Type Related

External Category Segment

Position 0030

Level 2

4.6 C507 — Date/time/period

Structure

Node	Card.	Prim.Type	Pos.	Length	Codelists
INVOIC — Invoice message	1 .. 1				
├ **DTM** — Date/time/period - Document/message date/time	1 .. 1		0030		
│ └ **C507** — Date/time/period	1 .. 1		010		
│ ├ **2005** — Date/time/period qualifier	1 .. 1	String	010	1 .. 3	2005
│ ├ **2380** — Date/time/period	1 .. 1	String	020	1 .. 35	
│ └ **2379** — Date/time/period format qualifier	1 .. 1	String	030	1 .. 3	2379

Documentation

Definition Date and/or time, or period relevant to the specified date/time/period type.

Properties

Identifier C507

Name Date/time/period

Cardinality min: 1 max: 1

Syntax Type Related

External Category Composite Data Element

Position 010

Leaf Elements

Identifier/Name	Description/Notes/Code Values	Properties
2005 Date/time/period qualifier	Code giving specific meaning to a date, time or period. **Selected Values** **Code** 137 **Name** Document/message date/time (2006) Date/time when a document/message is issued. This may include authentication.	**Cardinality** min: 1 max: 1 **Primitive Type** String **Length** min: 1 max: 3 **External Category** Data Element **Data Type** an **Position** 010 **Codelist Id** 2005 **Type System** UNEDIFACT **Version Mode** Current **Version** D.96A S3
2380 Date/time/period	The value of a date, a date and time, a time or of a period in a specified representation.	**Cardinality** min: 1 max: 1 **Primitive Type** String **Length** min: 1 max: 35 **External Category** Data Element **Data Type** an **Position** 020
2379 Date/time/period format qualifier	Specification of the representation of a date, a date and time or of a period. **Selected Values** **Code** 102 **Name** CCYYMMDD Calendar date: C = Century ; Y = Year ; M = Month ; D = Day. **Code** 203 **Name** CCYYMMDDHHMM Calendar date including time with minutes: C=Century; Y=Year; M=Month; D=Day; H=Hour; M=Minutes. **Code** 204 **Name** CCYYMMDDHHMMSS Calendar date including time with seconds: C=Century;Y=Year; M=Month;D=Day;H=Hour;M=Minute;S=Second.	**Cardinality** min: 1 max: 1 **Primitive Type** String **Length** min: 1 max: 3 **External Category** Data Element **Data Type** an **Position** 030 **Codelist Id** 2379 **Type System** UNEDIFACT **Version Mode** Current **Version** D.96A S3

4.7 FTX — Free text

Structure

Node	Card.	Prim.Type	Pos.	Length	Codelists
INVOIC — Invoice message	1 .. 1				
├ **FTX** — Free text	0 .. 10		0070		
│ ├ **4451** — Text subject qualifier	1 .. 1	String	010	1 .. 3	4451
│ ├ **C108** — Text literal	0 .. 1		040		
│ └ **3453** — Language, coded	0 .. 1	String	050	1 .. 3	ISO_639-1

Documentation

Definition A segment with free text information, in coded or clear form, used when additional information is needed but cannot be accommodated within other segments. In computer to computer exchanges such text will normally require the receiver to process this segment manually.

Properties

Identifier FTX

Name Free text

Cardinality min: 0 max: 10

Syntax Type Related

External Category Segment

Position 0070

Level 2

Leaf Elements

Identifier/Name	Description/Notes/Code Values	Properties
4451 Text subject qualifier	Code specifying subject of a free text. **Selected Values** **Code** INV **Name** Invoice instruction Note contains invoice instructions.	**Cardinality** min: 1 max: 1 **Primitive Type** String **Length** min: 1 max: 3 **External Category** Data Element **Data Type** an **Position** 010 **Fixed Value** INV **Codelist Id** 4451 **Type System** UNEDIFACT **Version Mode** Current **Version** D.96A S3
3453 Language, coded	Code of language (ISO 639-1988). Note: Use ISO 639-1988. **Selected Values** All Values in Codelist	**Cardinality** min: 0 max: 1 **Primitive Type** String **Length** min: 1 max: 3 **External Category** Data Element **Data Type** an **Position** 050 **Codelist Id** ISO_639-1 **Type System** ISO_CodelistsAndSchemes **Version Mode** Latest **Version** 2002

4.8 C108 — Text literal

Structure

Node	Card.	Prim.Type	Pos.	Length	Codelists
INVOIC — Invoice message	1 .. 1				
├ **FTX** — Free text	0 .. 10		0070		
│ ├ **C108** — Text literal	0 .. 1		040		
│ │ ├ **4440** — Free text	1 .. 1	String	010	1 .. 70	
│ │ ├ **4440_2** — Free text	0 .. 1	String	020	1 .. 70	
│ │ └ **4440_3** — Free text	0 .. 1	String	030	1 .. 70	

Documentation

Definition Free text; one to five lines.

Properties

Identifier C108

Name Text literal

Cardinality min: 0 max: 1

Syntax Type Related

External Category Composite Data Element

Position 040

Leaf Elements

Identifier/Name	Description/Notes/Code Values	Properties
4440 Free text	Free text field available to the message sender for information.	**Cardinality** min: 1 max: 1 **Primitive Type** String **Length** min: 1 max: 70 **External Category** Data Element **Data Type** an **Position** 010
4440_2 Free text	Free text field available to the message sender for information.	**Cardinality** min: 0 max: 1 **Primitive Type** String **Length** min: 1 max: 70 **External Category** Data Element **Data Type** an **Position** 020
4440_3 Free text	Free text field available to the message sender for information.	**Cardinality** min: 0 max: 1 **Primitive Type** String **Length** min: 1 max: 70 **External Category** Data Element **Data Type** an **Position** 030

4.9 SG1 [1153 = “ZZ1”] — Segment Group 1: RFF-DTM - Originator ID

Structure

Node	Card.	Prim.Type	Pos.	Length	Codelists
INVOIC — Invoice message	1 .. 1				
├ **SG1** — Segment Group 1: RFF-DTM - Originator ID	1 .. 1		0080		
│ └ **RFF** — Reference	1 .. 1		0090		

Documentation

Definition A group of segments for giving references and where necessary, their dates, relating to the whole message, e.g. contract number, import/export license number, despatch advice number.

Properties

Identifier SG1

Name Segment Group 1: RFF-DTM - Originator ID

Cardinality min: 1 max: 1

Syntax Type Related

External Category Segment Group

Position 0080

Level 2

4.10 RFF — Reference

Structure

Node	Card.	Prim.Type	Pos.	Length	Codelists
INVOIC — Invoice message	1 .. 1				
├ **SG1** — Segment Group 1: RFF-DTM - Originator ID	1 .. 1		0080		
│ └ **RFF** — Reference	1 .. 1		0090		
│ └ **C506** — Reference	1 .. 1		010		

Documentation

Definition A segment identifying the reference by its number and where appropriate a line number within a document.

Properties

Identifier RFF

Name Reference

Cardinality min: 1 max: 1

Syntax Type Related

External Category Segment

Position 0090

Level 3

4.11 C506 — Reference

Structure

Node	Card.	Prim.Type	Pos.	Length	Codelists
INVOIC — Invoice message	1 .. 1				
├ **SG1** — Segment Group 1: RFF-DTM - Originator ID	1 .. 1		0080		
│ └ **RFF** — Reference	1 .. 1		0090		
│ └ **C506** — Reference	1 .. 1		010		
│ ├ **1153** — Reference qualifier	1 .. 1	String	010	1 .. 3	1153_custom
│ └ **1154** — Reference number	1 .. 1	String	020	1 .. 35	

Documentation

Definition Identification of a reference.

Properties

Identifier C506

Name Reference

Cardinality min: 1 max: 1

Syntax Type Related

External Category Composite Data Element

Position 010

Leaf Elements

Identifier/Name	Description/Notes/Code Values	Properties
1153 Reference qualifier	Code giving specific meaning to a reference segment or a reference number. **Selected Values** **Code** ZZ1 **Name** Originator ID Sender system ID	**Cardinality** min: 1 max: 1 **Primitive Type** String **Length** min: 1 max: 3 **External Category** Data Element **Data Type** an **Position** 010 **Fixed Value** ZZ1 **Codelist Id** 1153_custom **Version Mode** Fixed
1154 Reference number	Identification number the nature and function of which can be qualified by an entry in data element 1153 Reference qualifier.	**Cardinality** min: 1 max: 1 **Primitive Type** String **Length** min: 1 max: 35 **External Category** Data Element **Data Type** an **Position** 020

4.12 SG2 — Segment Group 2: NAD-LOC-FII-SG3-SG4-SG5

Structure

Node	Card.	Prim.Type	Pos.	Length	Codelists
INVOIC — Invoice message	1 .. 1				
├ **SG2** — Segment Group 2: NAD-LOC-FII-SG3-SG4-SG5	0 .. 99		0110		
│ ├ **NAD** — Name and address - Issuer of invoice	1 .. 1		0120		
│ └ **NAD** — Name and address - Invoicee	1 .. 1		0120		

Documentation

Definition A group of segments identifying the parties with associated information.

Properties

Identifier SG2

Name Segment Group 2: NAD-LOC-FII-SG3-SG4-SG5

Cardinality min: 0 max: 99

Syntax Type Related

External Category Segment Group

Position 0110

Level 2

4.13 NAD [3035 = “II”] — Name and address - Issuer of invoice

Structure

Node	Card.	Prim.Type	Pos.	Length	Codelists
INVOIC — Invoice message	1 .. 1				
├ **SG2** — Segment Group 2: NAD-LOC-FII-SG3-SG4-SG5	0 .. 99		0110		
│ ├ **NAD** — Name and address - Issuer of invoice	1 .. 1		0120		
│ │ ├ **3035** — Party qualifier	1 .. 1	String	010	1 .. 3	3035
│ │ └ **C082** — Party identification details	1 .. 1		020		

Documentation

Definition A segment identifying names and addresses of the parties, in coded or clear form, and their functions relevant to the invoice. Identification of the seller and buyer parties is mandatory for the invoice message. It is recommended that where possible only the coded form of the party ID should be specified e.g. The Buyer and Seller are known to each other, thus only the coded ID is required, but the Consignee or Delivery address may vary and would have to be clearly specified, preferably in structured format.

Properties

Identifier NAD

Name Name and address - Issuer of invoice

Cardinality min: 1 max: 1

Syntax Type Related

External Category Segment

Position 0120

Level 3

Leaf Elements

Identifier/Name	Description/Notes/Code Values	Properties
3035 Party qualifier	Code giving specific meaning to a party. **Selected Values** **Code** II **Name** Issuer of invoice (3028) Party issuing an invoice.	**Cardinality** min: 1 max: 1 **Primitive Type** String **Length** min: 1 max: 3 **External Category** Data Element **Data Type** an **Position** 010 **Codelist Id** 3035 **Type System** UNEDIFACT **Version Mode** Current **Version** D.96A S3