You can navigate to the worklist pages of the fulfillment tracking apps from external systems with filtered results. In the navigation URLs, the filtering settings should be defined as the URL parameters,and the filtered results would be automatically displayed as you navigate to these pages.

Typically, the pattern of this navigation URL is: *<URL to the worklist page of the app>?<key>=<value>*

If you want to specify multiple filters or multiple values for one filter, the navigation URL patterns are as follows:

- For multiple filters: *<URL to the worklist page of the app>?<key_1>=<value_1>&<key_2>=<value_2>*
- For one filter with multiple values: *<URL to the worklist page of the app>?<key_1>=<value_1>&<key_1>=<value_2>*

For detailed instructions on how to define the URL parameters for the navigation, see Define the URL Parameters for Filtering the Worklists of Fulfillment Tracking Apps. You can also find some URL Parameters examples in List of URL Parameters Examples.

# Define the URL Parameters for Filtering the Worklists of Fulfillment Tracking Apps

## Context

To define the URL parameters for filtering the worklists of fulfillment tracking apps, do the following:

## Procedure

1. Decide on a filter to be defined in the navigation URL.
2. Define the key of the parameter. It is the field name of the filter. Generally, each filter in the apps corresponds to one user model field, standard model field or core model field in the standard model “gttft1”. To find the field name, do the following:
    - Go to the standard model in the Manage Models app.
    - Click the target tracked process or field type and find the corresponding field in the **User Model Fields**, **Standard Model Fields** or **Core Model Fields** sections.
    - Use the field name, not the description. The type of the field may influence the name of the key. For details, see List of URL Parameters Examples.
3. Define the value of the parameter. It consists of the operator and the field value, for example, “>2021”. The type of the field supports different operators. For details, see List of URL Parameters Examples.

# List of URL Parameters Examples

The examples of the URL parameters are sorted according to the types of the fields and listed as follows:

## UUID

For this type, the key is the field name.

| Example Filter | Field Name | Operator | Operator Description | URL |
|---|---|---|---|---|
| ID | id | = | equal to | *<GTT Fiori Launchpad URL>*/cp.portal/site#InboundASN- |

| Example Filter | Field Name | Operator | Operator Description | URL |
|---|---|---|---|---|
| | | | | monitor?id=e426761f-c1e4-5187-b2f5-ac4e03fc4650 |

## Boolean

For this type, the key is the field name. Typically, the field value is "true" or "false". But there is an exception:

- For Delay Status filter in the fulfillment tracking apps, the field value can only be "Yes" or "No".

| Example Filter | Field Name | Operator | Operator Description | URL |
|---|---|---|---|---|
| Dangerous Goods Relevant | dangerousGoods | = | equal to | *<GTT Fiori Launchpad URL>*/cp.portal/site#Shipment-track?dangerousGoods=true |
| | | | | *<GTT Fiori Launchpad URL>*/cp.portal/site#Shipment-track?dangerousGoods=false |
| Delay Status | delayStatus | = | equal to | *<GTT Fiori Launchpad URL>*/cp.portal/site#InboundASN-monitor?delayStatus=yes |
| Delay Status | delayStatus | = | equal to | *<GTT Fiori Launchpad URL>*/cp.portal/site#Shipment-track?delayStatus=no |

## Integer

For this type, the key is the field name.

| Example Filter | Field Name | Operator | Operator Description | URL |
|---|---|---|---|---|
| Version | version | = | equal to | *<GTT Fiori Launchpad URL>*/cp.portal/site#InboundASN-monitor?version=2 |

## Decimals

For this type, the key is the field name.

| Example Filter | Field Name | Operator | Operator Description | URL |
|---|---|---|---|---|
| Net Weight | netWeight | = | equal to | *<GTT Fiori Launchpad URL>*/cp.portal/site#Shipment-track?netWeight=3500.000 |

## String

Normally, the key is the field name for this type, but there are several exceptions in each app. You can find them in the second table.

| Example Filter | Field Name | Operator | Operator Description | URL |
|---|---|---|---|---|
| Inbound Delivery No. | inboundDeliveryNo | = | equal to | *<GTT Fiori Launchpad URL>*/cp.portal/site#InboundASN-monitor?inboundDeliveryNo=1372702164 |

Exceptions:

| App | Filter | Key |
|---|---|---|
| TS | Tracked Object ID | trackedObjectIdForSearch |
| | Carrier Reference Document ID | carrierRefDocIdForSearch |
| | Shipper Reference Document ID | shipperRefDocIdForSearch |
| MIA | Material ID | materialNumberForSearch |
| | Material Description | itemDescriptionForSearch |
| | Shipment No. | shipmentNoForSearch |
| MOD | Material ID | materialNoForSearch |
| | Material Description | materialDescriptionForSearch |
| | Shipment No. | shipmentNoForSearch |
| TSOF | Material No. | materialNoForSearch |
| | Material Description | materialDescriptionForSearch |
| | Delivery No. | deliveryNoForSearch |
| TPOF | Material ID | purchaseOrder.materialIdForSearch |
| | Material Description | purchaseOrder.materialDescriptionForSearch |
| | Delivery No. | purchaseOrder.deliveryNoForSearch |
| | Shipment No. | purchaseOrder.shipmentNoForSearch |

For OTIF Delivery Status filter in the TSOF and TPOF apps, you cannot find the exact field in the standard model. The parameter key and value for this filter are as follows:

| Example Filter | Key | Operator | Operator Description | Value | URL |
|---|---|---|---|---|---|
| OTIF Delivery Status | otifStatus | = | equal to | onTimeAndInFull | *<GTT Fiori Launchpad URL>*/cp.portal/site#SalesOrder-track?otifStatus=onTimeAndInFull |
| | | | | onTimeAndNotInFull | *<GTT Fiori Launchpad URL>*/cp.portal/site#SalesOrder- |

| Example Filter | Key | Operator | Operator Description | Value | URL |
|---|---|---|---|---|---|
| | | | | | track?otifStatus=onTimeAndNotInFull |
| | | | | notOnTimeAndInFull | *<GTT Fiori Launchpad URL>*/cp.portal/site#SalesOrder-track?otifStatus=notOnTimeAndInFull |
| | | | | notOnTimeAndNotInFull | *<GTT Fiori Launchpad URL>*/cp.portal/site#POFulfillment-track?otifStatus=notOnTimeAndNotInFull |
| | | | | none | *<GTT Fiori Launchpad URL>*/cp.portal/site#POFulfillment-track?otifStatus=none |

When you configure the location-relevant filters in the following table as parameters in the navigation URLs, in addition to the location ID, you can also use the location alternative key as the parameter value.

| App | Filter | Key | Value | URL |
|---|---|---|---|---|
| MIA | Supplier | supplierId | *<supplier location ID>* | *<GTT Fiori Launchpad URL>*/cp.portal/site#InboundASN-monitor?supplierId=*<supplier location ID>* |
| | | | *<location alternative key>* | *<GTT Fiori Launchpad URL>*/cp.portal/site#InboundASN-monitor?supplierId=*<location alternative key>* |
| | Receiving Location | receivingLocationId | *<receiving location ID>* | *<GTT Fiori Launchpad URL>*/cp.portal/site#InboundASN-monitor?receivingLocationId=*<receiving location ID>* |
| | | | *<location alternative key>* | *<GTT Fiori Launchpad URL>*/cp.portal/site#InboundASN-monitor?receivingLocationId=*<location alternative key>* |
| MOD | Shipping Point | shippingPointId | *<shipping point Location ID>* | <GTT Fiori Launchpad URL>/cp.portal/site#OutboundDelivery-monitor?shippingPointId=*<shipping point Location ID>* |
| | | | *<location alternative key>* | <GTT Fiori Launchpad URL>/cp.portal/site#OutboundDelivery-monitor?shippingPointId=*<location alternative key>* |
| | Ship-to Party | Ship-to Party shipToPartyId | *<ship-to party location ID>* | <GTT Fiori Launchpad URL>/cp.portal/site#OutboundDelivery-monitor?shipToPartyId=*<ship-to party location ID>* |

| App | Filter | Key | Value | URL |
|---|---|---|---|---|
| | | | *<location alternative key>* | <GTT Fiori Launchpad URL>/cp.portal/site#OutboundDelivery-monitor?shipToPartyId=*<location alternative key>* |
| TSOF | Ship-To Party | shipToPartyId | *<ship-to party location ID>* | *<GTT Fiori Launchpad URL>*/cp.portal/site#SalesOrder-track?shipToPartyId=*<ship-to party location ID>* |
| | | | *<location alternative key>* | *<GTT Fiori Launchpad URL>*/cp.portal/site#SalesOrder-track?shipToPartyId=*<location alternative key>* |
| | Sold-To Party | soldToPartyId | *<sold-to party location ID>* | *<GTT Fiori Launchpad URL>*/cp.portal/site#SalesOrder-track?soldToPartyId=*<sold-to party location ID>* |
| | | | *<location alternative key>* | *<GTT Fiori Launchpad URL>*/cp.portal/site#SalesOrder-track?soldToPartyId=*<location alternative key>* |
| TPOF | Supplier | supplierId | *<supplier location ID>* | *<GTT Fiori Launchpad URL>*/cp.portal/site#POFulfillment-track?supplierId=*<supplier location ID>* |
| | | | *<location alternative key>* | *<GTT Fiori Launchpad URL>*/cp.portal/site#POFulfillment-track?supplierId=*<location alternative key>* |
| | Receiving Location | receivingLocationId | *<receiving location ID>* | *<GTT Fiori Launchpad URL>*/cp.portal/site#POFulfillment-track?receivingLocationId=*<receiving location ID>* |
| | | | *<location alternative key>* | *<GTT Fiori Launchpad URL>*/cp.portal/site#POFulfillment-track?receivingLocationId=*<location alternative key>* |

## Date and Timestamps

For this type, the key is the field name.

| Example Filter | Field Name | Operator | Operator Description | URL |
|---|---|---|---|---|
| Creation Date Time | creationDateTime | = | equal to | *<GTT Fiori Launchpad URL>*/cp.portal/site#InboundASN-monitor?creationDateTime=2022-05-01T12:00:00.808Z |

| Example Filter | Field Name | Operator | Operator Description | URL |
|---|---|---|---|---|
| | | ... | between | *<GTT Fiori Launchpad URL>*/cp.portal/site#InboundASN-monitor?creationDateTime=2022-05-01...2022-05-02 |
| | | "<=" or "!>" | before or on/not after | *<GTT Fiori Launchpad URL>*/cp.portal/site#InboundASN-monitor?creationDateTime=<=2022-05-01 |
| | | ">=" or "!<" | after or on/not before | *<GTT Fiori Launchpad URL>*/cp.portal/site#InboundASN-monitor?creationDateTime=!<2022-05-01 |

### ℹ Note

The following formats of the field value are supported:

| Field Value | Example |
|---|---|
| yyyy-MM-dd'T'HH:mm:ss.SSSZ | 2022-05-01T12:00:00.808Z |
| yyyy | 2022 |
| yyyy-MM | 2022-05 |
| yyyy-MM-dd | 2022-05-01 |

## Code List

For this type, the format of the key is "<fieldName>_code". The field value is the corresponding model code that you can find in the Code Lists tab of the standard model “gttft1”.

| Example Filter | Field Name | Key | Operator | Operator Description | URL |
|---|---|---|---|---|---|
| Execution Status | executionStatus | executionStatus_code | = | equal to | *<GTT Fiori Launchpad URL>*/cp.portal/site#POFulfillment-track?executionStatus_code=NOT_STARTED |

## Association to One

For this type, the format of the key is "<fieldName_1>.<fieldName_2>". "<fieldName_1>" is the field name of the filter, and "<fieldName_2>" is the field name of the field in the associated tracked process.

| Example Filter | Field Name | Key | Operator | Operator Description | URL |
|---|---|---|---|---|---|
| zzResource | zzResource | zzResource.altKey | = | equal to | *<GTT Fiori Launchpad URL>*/cp.portal/site#Shipment-track?zzResource.altKey=12345 |

# Navigate to Detail Pages of Fulfillment Tracking Apps from External Systems

You can navigate from external systems to detail pages of fulfillment tracking apps directly with the tracking ID and logical system. The base navigation URLs to the detail pages are listed by each app as follows:

## Track Shipments

**Shipment Details** page: *<Global Track and Trace Fiori Launchpad URL>*/cp.portal/site#Shipment-track&/Shipment?trackingId=*<Shipment's tracking ID>*&systemId=*<Shipment's logical system>*

**Freight Unit Details** page: *<Global Track and Trace Fiori Launchpad URL>*/cp.portal/site#Shipment-track&/FreightUnit?trackingId=*<FU's tracking ID>*&systemId=*<FU's logical system>*

## Monitor Inbound ASNs

**Inbound Delivery Details** page: *<Global Track and Trace Fiori Launchpad URL>*/cp.portal/site#InboundASN-monitor&/deliveryDetail?systemId=*<Inbound Delivery's logical system>*&trackingId=*<Inbound Delivery's tracking ID>*

## Monitor Outbound Deliveries

**Outbound Delivery Details** page: *<Global Track and Trace Fiori Launchpad URL>*/cp.portal/site#OutboundDelivery-monitor&/deliveryDetail?systemId=*<Outbound Delivery's logical system>*&trackingId=*<Outbound Delivery's tracking ID>*

## Track SO Fulfillment

**Sales Order Details** page: *<Global Track and Trace Fiori Launchpad URL>*/cp.portal/site#SalesOrder-track&/SalesOrder?trackingId=*<SO's tracking ID>*&systemId=*<SO's logical system>*

**Sales Order Item Details** page: *<Global Track and Trace Fiori Launchpad URL>*/cp.portal/site#SalesOrder-track&/SalesOrderItem?trackingId=*<SO item's tracking ID>*&systemId=*<SO item's logical system>*

## Track PO Fulfillment

**Purchase Order Details** page: *<Global Track and Trace Fiori Launchpad URL>*/cp.portal/site#POFulfillment-track&/PurchaseOrder?systemId=*<PO's logical system>*&trackingId=*<PO's tracking ID>*

**Purchase Order Item Details** page: *<Global Track and Trace Fiori Launchpad URL>*/cp.portal/site#POFulfillment-track&/PurchaseOrderItem?trackingId=*<PO item's tracking ID>*&systemId=*<PO item's logical system>*

# Define My Tracking Status

## Context

“My Tracking Status” is a non-standard field that can reflect how your tracking process goes. You can display it in the Track Shipments, Monitor Inbound ASNs and Monitor Outbound Deliveries apps to identify shipments, inbound and outbound deliveries with exceptional tracking status. You can define it in a way that better meets your individual business needs.

## Procedure

1. Open the **Manage Models** app.
2. Go to the standard model “gttft1”.
3. In the **Code List** tab, click one of the following code lists:
    - “`ShipmentCustomTrackingStatus`” code list for the shipment.
    - "`TrackingUnitCustomTrackingStatus`" code list for the tracking unit.
    - “`InbDlvCustomTrackingStatus`” code list for the inbound delivery.
    - “`OutbDlvCustomTrackingStatus`” code list for the outbound delivery.
4. Click the Add button above the table. A new row with two empty inputs will be added on the bottom of the table.
5. Fill in code and name. If the code is left empty, this line will not be saved to model.

    ### ℹ Note

    The code must be in the format of “<prefix><status description>”, such as “ZZ_SUCCESS_ACTIVE”. The prefix indicates the status category, which determines the color of the status displayed in the apps. The categories with assigned colors are listed in the following table:

    | Category | Prefix | Color |
    |---|---|---|
    | Success | ZZ_SUCCESS_ | Green |
    | Inactive | ZZ_INACTIVE_ | Grey |
    | Error | ZZ_ERROR_ | Red |
    | Warning | ZZ_WARNING_ | Yellow |
    | Information | ZZ_INFO_ | Blue |

    For example, if you add the code “ZZ_ERROR_INTEGRATION” with the name as “Integration Error” to the code lists, then the tracking status “Integration Error” is available in red in the apps.

    If your codes do not follow the above format, the status will be shown in blue.

6. In the **Event to Action** tab, add your own script in the **User Script After Standard Script** section to set the tracking status value of your shipment or outbound delivery. For more, see Manage Models.
7. Click the **Save** button to save changes to model.

## Results

On the worklist pages of the Track Shipments, Monitor Inbound ASNs, Monitor Outbound Deliveries apps, you can display the **My Tracking Status** filter with the statuses available in its dropdown list for selection. After filtering, the color-coded statuses are displayed in the corresponding column of the worklist.

On the header of the following pages, you can add the tracking status tag in a color-coded box beside the shipment number or delivery number with the flexible UI function:

- **Shipment Details**
- **Tracking Unit Details**
- **Inbound Delivery Details**
- **Outbound Delivery Details**.

# Define My Execution Status

## Context

Apart from the standard execution status designed by SAP Business Network Global Track and Trace, “My Execution Status” is a non-standard field provided for you to define the execution status in a way that can better meet your individual business needs. You can display it in the fulfillment tracking apps to monitor tracked processes.

## Procedure

1. Open the Manage Models app.
2. Go to the standard model “gttft1”.
3. In the **Code List** tab, click one of the following code lists depending on your needs:
    - "`ShipmentCustomExecutionStatus`" code list for the shipment.
    - "`FreightUnitCustomExecutionStatus`" code list for the freight unit.
    - "`TrackingUnitCustomExecutionStatus`" code list for the tracking unit.
    - "`InbDlvCustomExecutionStatus`" code list for the inbound delivery
    - "`OutDlvCustomExecutionStatus`" code list for the outbound delivery
4. Click the Add button above the table. A new row with two empty inputs will be added on the bottom of the table.

### ℹ Note

The code must be in the format of “<prefix><status description>”, such as “ZZ_SUCCESS_ACTIVE”. The prefix indicates the status category, which determines the color of the status displayed in the app. The categories with assigned colors are listed in the following table:

| Category | Prefix | Color |
|---|---|---|
| Success | ZZ_SUCCESS_ | Green |
| Inactive | ZZ_INACTIVE_ | Grey |
| Error | ZZ_ERROR_ | Red |
| Warning | ZZ_WARNING_ | Yellow |
| Information | ZZ_INFO_ | Blue |

For example, if you add the code “ZZ_ERROR_INTEGRATION” with the name as “Integration Error” to the code lists, then the status “Integration Error” is available in red in the app.

If your codes do not follow the above format, the status will be shown in blue.

5. Fill in code and name. If the code is left empty, this line will not be saved to model.
6. In the **Event to Action** tab, add your own script in the **User Script After Standard Script** section to set the execution status value. For more, see Manage Models.
7. Save your changes.

## Results

On the worklist pages of the Track Shipments, Monitor Inbound ASNs, Monitor Outbound Deliveries apps, you can display the **My Execution Status** filter with the statuses available in its dropdown list for selection. After filtering, the color-coded statuses are displayed in the corresponding column of the worklist.

On the header of the following pages, you can add the my execution status tag in a color-coded box with Adapt UI:

- **Shipment Details** page
- **Freight Unit Details** page
- **Tracking Unit Details** page
- **Inbound Delivery Details** page
- **Outbound Delivery Details** page.

### ! Restriction

On the header of details pages, the appearance of custom execution status in "Other" and "Inactive" categories is identical. It's not possible to differentiate between the two from there, although they can be distinguished in the worklist.

# “In Execution” Status Customization

In the GTT standard model "gttft1", the following variable is available in the **Standard Declaration** of the “Event to Action” section:

- `GTT_TS_EVENT_TYPES_IN_EXEC`

This variable defines the list of event types that can trigger the execution status update. When any event of these event types, no matter planned or unplanned, is reported, the execution status changes to "In Execution" from "Not Started". For a complete list of event types defined for this variable by default, see Supported Event Types. It applies to the following tracked processes:

- Shipment
- Freight Unit
- Tracking Unit

You can customize the list of event types that better meets your business needs, for example, reducing the list, or enriching it by adding more event types. The custom list will override the default list. To do this, perform the steps below.

## Procedure