

Ch-07_08 R Codes

Ping-Yang Chen

2024-05-26

Textbook: Montgomery, D. C. (2012). *Design and analysis of experiments*, 8th Edition. John Wiley & Sons.

Online handouts: https://github.com/PingYangChen/ANOVA_Course_R_Code

7.21

By the defining contrast, to confound eight blocks with $ABCD$, ACE and $ABEF$, let

$$L_1 = x_1 + x_2 + x_3 + x_4$$

$$L_2 = x_1 + x_3 + x_5$$

$$L_3 = x_1 + x_2 + x_5 + x_6$$

```
designMat <- data.frame(
  A = rep(0:1, 32),
  B = rep(rep(0:1, each = 2), 16),
  C = rep(rep(0:1, each = 4), 8),
  D = rep(rep(0:1, each = 8), 4),
  E = rep(rep(0:1, each = 16), 2),
  F = rep(0:1, each = 32)
)
#print(head(designMat, 6))

letterMat <- sapply(1:ncol(designMat), function(j) {
  ifelse(designMat[,j] == 1, letters[j], "")
})
#print(head(letterMat, 6))

effectNames <- sapply(1:nrow(letterMat), function(i) {
  ifelse(all(letterMat[i,] == ""), "(1) ", paste0(letterMat[i,], collapse = ""))
})
rownames(designMat) <- effectNames
print(head(designMat, 6))
```

```
##      A B C D E F
## (1)  0 0 0 0 0 0
## a    1 0 0 0 0 0
## b    0 1 0 0 0 0
## ab   1 1 0 0 0 0
## c    0 0 1 0 0 0
## ac   1 0 1 0 0 0
```

Compute the linear combinations $L_1(i)$, $L_2(i)$ and $L_3(i)$, and take (mod 2) for each of them, $i = 1, 2, \dots, 64$.

```
attach(designMat)
assignBlock <- data.frame(
  L1 = (A + B + C + D) %% 2,
  L2 = (A + C + E) %% 2,
  L3 = (A + B + E + F) %% 2
)
detach(designMat)
```

Get the block IDs for each run.

```
blockId <- as.matrix(assignBlock) %*% c(2^2, 2, 1) + 1
```

Present the runs in each block.

```
result <- matrix("", 8, 8)
for (i in 1:8) {
  result[,i] <- effectNames[which(blockId == i)]
}
colnames(result) <- sprintf("Block %d", 1:8)
print(data.frame(result))
```

##	Block.1	Block.2	Block.3	Block.4	Block.5	Block.6	Block.7	Block.8
## 1	(1)	ac	ab	bc	abc	b	c	a
## 2	abcd	bd	cd	ad	d	acd	abd	bcd
## 3	bce	abe	ace	e	ae	ce	be	abce
## 4	ade	cde	bde	abcde	bcde	abde	acde	de
## 5	acf	f	bcf	abf	bf	abcf	af	cf
## 6	bdf	abcdf	adf	cdf	acdf	df	bcdf	abdf
## 7	abef	bcef	ef	acef	cef	aef	abcef	bef
## 8	cdef	adef	abcdef	bdef	abdef	bcdef	def	acdef

The other effects confounded with blocks:

$$\begin{aligned}
 (ABCD)(ACE) &= A^2BC^2DE = BDE \\
 (ABCD)(ABEF) &= A^2B^2CDEF = CDEF \\
 (ACE)(ABEF) &= A^2BCE^2F = BCF \\
 (ABCD)(BCF) &= AB^2C^2DF = ADF
 \end{aligned}$$

8.11

2^{5-2} fractional factorial design with defining relation

$$I = ACE \text{ and } I = BDE$$

1. generate the 2^3 full factorial design

```
lv1 <- c(-1, 1)
FF3 <- data.frame(
  A = rep(lv1, 4),
  B = rep(rep(lv1, each = 2), 2),
  C = rep(lv1, each = 4)
)
print(FF3)
```

```
##      A  B  C
## 1 -1 -1 -1
## 2  1 -1 -1
## 3 -1  1 -1
## 4  1  1 -1
## 5 -1 -1  1
## 6  1 -1  1
## 7 -1  1  1
## 8  1  1  1
```

2. add two columns D and E to form the 2^{5-2} by the defining relation

$$I = ACE \implies E = AC$$

$$I = BDE \implies D = BE \implies D = BAC$$

```
attach(FF3)
augmentFrF <- data.frame(
  D = A * B * C,
  E = A * C
)
detach(FF3)

FrF5_2 <- cbind(FF3, augmentFrF)
# Get letters of each effect
letterMat <- sapply(1:ncol(FrF5_2), function(j) {
  ifelse(FrF5_2[,j] == 1, letters[j], "")
})
# Combine letters
effectNames <- sapply(1:nrow(letterMat), function(i) {
  ifelse(all(letterMat[i,] == ""), "(1) ", paste0(letterMat[i,], collapse = ""))
})
rownames(FrF5_2) <- effectNames
print(FrF5_2)
```

```
##      A  B  C  D  E
## e    -1 -1 -1 -1  1
## ad    1 -1 -1  1 -1
## bde   -1  1 -1  1  1
## ab     1  1 -1 -1 -1
## cd    -1 -1  1  1 -1
## ace    1 -1  1 -1  1
## bc    -1  1  1 -1 -1
## abcde  1  1  1  1  1
```

Complete defining relation is

$$I = ACE = BDE = ABCD$$

All aliases are

$$\begin{aligned}
A &= CE = BCD \\
B &= DE = ACD \\
C &= AE = ABD \\
D &= BE = ABC \\
E &= AC \\
AB &= CD \\
AD &= BC \\
AC &= BD
\end{aligned}$$

Add column of the response variable.

```

y <- numeric(8)
y[effectNames == "e"]      <- 23.2
y[effectNames == "ad"]     <- 16.9
y[effectNames == "cd"]     <- 23.8
y[effectNames == "bde"]    <- 16.8
y[effectNames == "ab"]     <- 15.5
y[effectNames == "bc"]     <- 16.2
y[effectNames == "ace"]    <- 23.4
y[effectNames == "abcde"]  <- 18.1
frfData <- cbind(FrF5_2, y = y)

```

The estimation of main effects are:

```

# Compute the model matrix of all effect terms without intercept
mmat5 <- model.matrix( ~ A+B+C+D+E - 1, data = frfData)
# Calculate the effect sizes using the +/- signs of the model matrix
eff5 <- numeric(ncol(mmat5))
for (i in 1:ncol(mmat5)) {
  eff5[i] <- 2*mean(frfData$y*mmat5[,i])
}
names(eff5) <- colnames(mmat5)

```

```

##   Factor Est.Effect
## 1      A      -1.525
## 2      B      -5.175
## 3      C       2.275
## 4      D      -0.675
## 5      E       2.275

```

```

# Half Normal Plot
halfqqnorm <- function(input, tol = 0.5) {
  y <- sort(abs(input))
  nq <- qnorm(seq(0.5, 0.99, length = length(y)))
  plot(y, nq, yaxt = "n", pch = 15,
       xlab = "|Effects|", ylab = "Half Normal Probability")
  title("Half Normal Plot")
  # choose anchor point to draw a straight line
  s <- min(which(diff(y)/diff(range(y)) > 1/(length(y)-1)))
  abline(a = -y[1]*(nq[s]-nq[1])/(y[s]-y[1]), b = (nq[s]-nq[1])/(y[s]-y[1]))
  axis(2, at = qnorm(seq(0.5, 0.9999, length = 5)),

```

```

      labels = round(seq(0, 1, length = 5), 2))
loc <- sqrt((nq - (y - y[1])*(nq[s]-nq[1])/(y[s]-y[1]))^2) > tol
if (is.null(names(y))) {
  text(y[loc], nq[loc], order(abs(input))[loc], pos = 2)
} else {
  text(y[loc], nq[loc], names(abs(input))[order(abs(input))[loc]], pos = 2)
}
}

```

(d) Project the 2^{5-2} design to only considering factors A , B and D . The estimation of the effects are:

```

# Compute the model matrix of all effect terms without intercept
mmat_proj <- model.matrix( ~ A*B*D - 1, data = frfData)
# Calculate the effect sizes using the +/- signs of the model matrix
eff_proj <- numeric(ncol(mmat_proj))
for (i in 1:ncol(mmat_proj)) {
  eff_proj[i] <- 2*mean(frfData$y*mmat_proj[,i])
}
names(eff_proj) <- colnames(mmat_proj)

```


```

##   Factor Est.Effect
## 1      A      -1.525
## 2      B      -5.175
## 3      D      -0.675
## 4     A:B       1.825
## 5     A:D      -1.275
## 6     B:D       2.275
## 7    A:B:D       2.275

```

```
halfqqnorm(eff_proj)
```

Half Normal Plot



```
fitProj <- aov(y ~ A+B+D+B:D+A:B:D, data = frfData)
summary(fitProj)
```

```
##           Df Sum Sq Mean Sq F value Pr(>F)
## A           1   4.65    4.65    0.938 0.4349
## B           1  53.56   53.56   10.807 0.0814 .
## D           1   0.91    0.91    0.184 0.7098
## B:D          1  10.35   10.35    2.089 0.2853
## A:B:D          1  10.35   10.35    2.089 0.2853
## Residuals    2   9.91    4.96
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
```