

Ch-07__08 R Codes

Ping-Yang Chen

2024-05-26

Textbook: Montgomery, D. C. (2012). *Design and analysis of experiments*, 8th Edition. John Wiley & Sons.

Online handouts: https://github.com/PingYangChen/ANOVA_Course_R_Code

7.21

By the defining contrast, to confound eight blocks with $ABCD$, ACE and $ABEF$, let

$$L_1 = x_1 + x_2 + x_3 + x_4$$

$$L_2 = x_1 + x_3 + x_5$$

$$L_3 = x_1 + x_2 + x_5 + x_6$$

```
designMat <- data.frame(
  A = rep(0:1, 32),
  B = rep(rep(0:1, each = 2), 16),
  C = rep(rep(0:1, each = 4), 8),
  D = rep(rep(0:1, each = 8), 4),
  E = rep(rep(0:1, each = 16), 2),
  F = rep(0:1, each = 32)
)
#print(head(designMat, 6))

letterMat <- sapply(1:ncol(designMat), function(j) {
  ifelse(designMat[,j] == 1, letters[j], "")
})
#print(head(letterMat, 6))

effectNames <- sapply(1:nrow(letterMat), function(i) {
  ifelse(all(letterMat[i,] == ""), "(1) ", paste0(letterMat[i,], collapse = ""))
})
rownames(designMat) <- effectNames
print(head(designMat, 6))
```

```
##      A B C D E F
## (1)  0 0 0 0 0 0
## a    1 0 0 0 0 0
## b    0 1 0 0 0 0
```

```
## ab  1 1 0 0 0 0
## c   0 0 1 0 0 0
## ac  1 0 1 0 0 0
```

Compute the linear combinations $L_1(i)$, $L_2(i)$ and $L_3(i)$, and take (mod 2) for each of them, $i = 1, 2, \dots, 64$.

```
attach(designMat)
assignBlock <- data.frame(
  L1 = (A + B + C + D) %% 2,
  L2 = (A + C + E) %% 2,
  L3 = (A + B + E + F) %% 2
)
detach(designMat)
```

Get the block IDs for each run.

```
blockId <- as.matrix(assignBlock) %*% c(2^2, 2, 1) + 1
```

Present the runs in each block.

```
result <- matrix("", 8, 8)
for (i in 1:8) {
  result[,i] <- effectNames[which(blockId == i)]
}
colnames(result) <- sprintf("Block %d", 1:8)
print(data.frame(result))
```

```
##   Block.1 Block.2 Block.3 Block.4 Block.5 Block.6 Block.7 Block.8
## 1   (1)      ac      ab      bc      abc      b      c      a
## 2   abcd     bd      cd      ad      d      acd     abd     bcd
## 3    bce     abe     ace      e      ae      ce      be     abce
## 4    ade     cde     bde     abcde    bcde     abde     acde     de
## 5    acf      f      bcf     abf      bf     abcf     af      cf
## 6    bdf     abcdf    adf     cdf     acdf     df     bcdf     abdf
## 7    abef     bcef     ef     acef     cef     aef     abcef     bef
## 8    cdef     adef    abcdef    bdef    abdef    bcdef     def     acdef
```

The other effects confounded with blocks:

$$\begin{aligned}
 (ABCD)(ACE) &= A^2BC^2DE = BDE \\
 (ABCD)(ABEF) &= A^2B^2CDEF = CDEF \\
 (ACE)(ABEF) &= A^2BCE^2F = BCF \\
 (ABCD)(BCF) &= AB^2C^2DF = ADF
 \end{aligned}$$

8.11

2^{5-2} fractional factorial design with defining relation

$$I = ACE \text{ and } I = BDE$$

1. generate the 2^3 full factorial design

```
lvl <- c(-1, 1)
FF3 <- data.frame(
  A = rep(lvl, 4),
  B = rep(rep(lvl, each = 2), 2),
  C = rep(lvl, each = 4)
)
print(FF3)
```

```
##      A  B  C
## 1 -1 -1 -1
## 2  1 -1 -1
## 3 -1  1 -1
## 4  1  1 -1
## 5 -1 -1  1
## 6  1 -1  1
## 7 -1  1  1
## 8  1  1  1
```

2. add two columns D and E to form the 2^{5-2} by the defining relation

$$I = ACE \implies E = AC$$
$$I = BDE \implies D = BE \implies D = BAC$$

```
attach(FF3)
augmentFrF <- data.frame(
  D = A * B * C,
  E = A * C
)
detach(FF3)

FrF5_2 <- cbind(FF3, augmentFrF)
# Get letters of each effect
letterMat <- sapply(1:ncol(FrF5_2), function(j) {
  ifelse(FrF5_2[,j] == 1, letters[j], "")
})
# Combine letters
effectNames <- sapply(1:nrow(letterMat), function(i) {
  ifelse(all(letterMat[i,] == ""), "(1) ", paste0(letterMat[i,], collapse = ""))
})
rownames(FrF5_2) <- effectNames
print(FrF5_2)
```

```
##      A  B  C  D  E
## e    -1 -1 -1 -1  1
## ad     1 -1 -1  1 -1
## bde    -1  1 -1  1  1
## ab     1  1 -1 -1 -1
```

```
## cd      -1 -1  1  1 -1
## ace      1 -1  1 -1  1
## bc       -1  1  1 -1 -1
## abcde    1  1  1  1  1
```

Complete defining relation is

$$I = ACE = BDE = ABCD$$

All aliases are

$$\begin{aligned} A &= CE = BCDAB = CD \\ B &= DE = ACDAD = BC \\ C &= AE = ABDAC = BD \\ D &= BE = ABC \\ E &= AC \end{aligned}$$

Add column of the response variable.

```
y <- numeric(8)
y[effectNames == "e"]      <- 23.2
y[effectNames == "ad"]     <- 16.9
y[effectNames == "cd"]     <- 23.8
y[effectNames == "bde"]    <- 16.8
y[effectNames == "ab"]     <- 15.5
y[effectNames == "bc"]     <- 16.2
y[effectNames == "ace"]    <- 23.4
y[effectNames == "abcde"]  <- 18.1
frfData <- cbind(FrF5_2, y = y)
```

The estimation of factor effects are:

```
# Compute the model matrix of all effect terms without intercept
mmat5 <- model.matrix( ~ A+B+C+D+E+A:B+A:D - 1, data = frfData)
# Calculate the effect sizes using the +/- signs of the model matrix
eff5 <- numeric(ncol(mmat5))
for (i in 1:ncol(mmat5)) {
  eff5[i] <- 2*mean(frfData$y*mmat5[,i])
}
names(eff5) <- colnames(mmat5)
```


```
##      Factor Est.Effect
## 1         A      -1.525
## 2         B      -5.175
## 3         C       2.275
## 4         D      -0.675
## 5         E       2.275
## 6        A:B       1.825
## 7        A:D      -1.275
```

```

# Half Normal Plot
halfqqnorm <- function(input, tol = 0.5) {
  y <- sort(abs(input))
  nq <- qnorm(seq(0.5, 0.99, length = length(y)))
  plot(y, nq, yaxt = "n", pch = 15,
       xlab = "|Effects|", ylab = "Half Normal Probability")
  title("Half Normal Plot")
  # choose anchor point to draw a straight line
  s <- min(which(diff(y)/diff(range(y)) > 1/(length(y)-1)))
  abline(a = -y[1]*(nq[s]-nq[1])/(y[s]-y[1]), b = (nq[s]-nq[1])/(y[s]-y[1]))
  axis(2, at = qnorm(seq(0.5, 0.9999, length = 5)),
       labels = round(seq(0, 1, length = 5), 2))
  loc <- sqrt((nq - (y - y[1])*(nq[s]-nq[1])/(y[s]-y[1]))^2) > tol
  if (is.null(names(y))) {
    text(y[loc], nq[loc], order(abs(input))[loc], pos = 2)
  } else {
    text(y[loc], nq[loc], names(abs(input))[order(abs(input))[loc]], pos = 2)
  }
}

```

```
halfqqnorm(eff5)
```



```

fit2 <- aov(y ~ B, data = frfData)
summary(fit2)

```

```
##           Df Sum Sq Mean Sq F value Pr(>F)
## B           1  53.56   53.56   8.883 0.0246 *
## Residuals    6  36.18    6.03
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
```