



S HTML Syntax	Tag structure
HTML TAG/ATTRIBUTE SYNTAX	
<code><tag attribute="value"> content </tag></code>	
D Document tags	HTML main structure
MAIN TAGS	
<code><!DOCTYPE html></code> HTML5 document	
<code><html></code> document content root tag	
<code><head></code> metadata header related docs	
<code><body></code> page content visible content	
G Global Attributes	for all elements
DOM / STYLE ATTRIBUTES	
<code>id</code> element identifier unique per page	
<code>class</code> element class multiple per page	
<code>slot</code> element slot reference to <code><slot></code>	
<code>style</code> inline CSS styles css properties	
GLOBAL ATTRIBUTES	
<code>accesskey</code> shortcut key to focus	
<code>contenteditable</code> allow edit element	
<code>dir</code> <code>ltr</code> <code>rtl</code> <code>auto</code> text direction	
<code>draggable</code> <code>auto</code> enable drag and drop	
<code>hidden</code> hide element not relevant	
<code>is</code> <code>custom-elem</code> custom built-in elem	
<code>lang</code> <code>code</code> set content lang en, es, fr...	
<code>nonce</code> <code>hash</code> whitelist script/style [CSP]	
<code>spellcheck</code> disable grammar check	
<code>tabindex</code> <code>num</code> set element order	
<code>title</code> set tooltip text mouse hover	
<code>translate</code> <code>yes</code> <code>no</code> disable translation	
<code>data-*</code> custom metadata on element	
HINT TO BROWSER	
<code>enterkeyhint</code> <code>enter</code> <code>done</code> <code>go</code> <code>search</code>	
<code>next</code> <code>previous</code> <code>send</code> virtual keyb label	
<code>inputmode</code> <code>none</code> <code>text</code> <code>tel</code> <code>url</code> <code>email</code>	
<code>numeric</code> <code>decimal</code> <code>search</code>	
MICRODATA ATTRIBUTES	
<code>itemid</code> set global urn unique identifier	
<code>itemscope</code> new metadata item	
<code>itemtype</code> set microdata genre url	
<code>itemref</code> <code>id list</code> set reference to "id"	
<code>itemprop</code> <code>token</code> set property & value	
S Inline Styling	CSS inline
INLINE STYLES	
<code><style></code> embed css style in a document	
<code>title</code> set title to stylesheet set	
<code>type</code> <code>mime</code> hint type for browser	
ONLY FOR <LINK> PICTURE <SOURCE> & <STYLE>	
<code>media</code> apply to specific devices	
<code>all</code> all devices computers, mobiles...	
<code>print</code> printables devices	
<code>screen</code> all devices - (print + speech)	
<code>speech</code> devices that read a page	
CHEATSHEET LEGEND	
<code>html tag</code> <code>html tag w/o close tag</code> <code>obsolete</code>	
<code>attribute</code> <code>attribute w/o value</code>	
<code>value</code> <code>default value</code> <code>values set</code>	
<code>value for content</code> <code>value part</code>	

C Comment Syntax	Dev annotations
HTML COMMENT SYNTAX	
<code><!-- text without effects on webpage --></code>	
H Head tags	Header & document metadata
RELATIONS	
<code><link></code> document relation	
<code>href</code> link to related document	
<code>hreflang</code> <code>code</code> doc language en, es...	
<code>type</code> <code>mime</code> hint type for browser	
<code>title</code> set title to stylesheet set	
<code>sizes</code> hint size for favicon 64x64, 96x96	
<code>rel</code> relation type with other document	
BASIC RELATION	
<code>alternate</code> link to alternate version	
<code>author</code> link to author URL	
<code>help</code> link to help URL	
<code>icon</code> link to favicon URL (tab icon)	
<code>license</code> fetch module map	
<code>pingback</code> link to pingback server	
<code>search</code> link to search page url	
<code>stylesheet</code> imports a css style sheet	
URL STRUCTURE RELATION	
<code>canonical</code> link to preferred URL	
<code>prev</code> prev part URL of series doc	
<code>next</code> next part URL of series doc	
RESOURCE HINTS	
<code>dns-prefetch</code> resolve dns domain	
<code>preconnect</code> pre connect to domain	
<code>prefetch</code> fetch/cache link for future	
<code>preload</code> fetch/cache link for now	
<code>modulepreload</code> fetch module map	
<code>prerender</code> background render page	
<code>as</code> <code>script</code> <code>font</code> <code>image</code> <code>audio</code> <code>video</code> <code>fetch</code>	
<code>document</code> <code>embed</code> <code>object</code> <code>style</code> <code>track</code>	
<code>worker</code>	
DOCUMENT METADATA	
<code><meta></code> document metadata	
<code>charset</code> <code>enc</code> encoding utf-8, iso-8859-1...	
<code>name</code> name of metadata	
<code>application-name</code> short webapp name	
<code>author</code> name of the page's author	
<code>description</code> seo page description	
<code>generator</code> software used to build web	
<code>keywords</code> comma-separated tags	
<code>referrer</code> default page referrer policy	
<code>theme-color</code> primary theme css color	
<code>viewport</code> hint to initial size viewport	
<code>http-equiv</code> pragma directive (legacy)	
<code>content-type</code> legacy alt. to charset	
<code>default-style</code> default stylesheet set	
<code>refresh</code> html redirect 10; URL=file.html	
<code>x-ua-compatible</code> better compat IE=edge	
<code>content-security-policy</code> enforce csp	
<code>content</code> metadata value	
<code><title></code> seo document title	
<code><base></code> set a document base url	
<code>href</code> link to base url to use	
<code>target</code> <code>context</code> place to open link	

S Social metadata	For social networks
FACEBOOK OPEN GRAPH	
<code><meta></code> metadata tag for open graph	
<code>property</code> metadata type open graph	
<code>content</code> metadata value open graph	
REQUIRED METADATA PROPERTIES	
<code>og:title</code> title of your object	
<code>og:type</code> type of your object	
<code>music</code> <code>video</code> <code>article</code> <code>book</code>	
<code>profile</code> <code>website</code>	
<code>og:image</code> image url for preview	
<code>og:url</code> canonical & absolute url	
OPTIONAL METADATA PROPERTIES	
<code>og:audio</code> complementary audio url	
<code>og:description</code> 1-2 sentence descr.	
<code>og:determiner</code> word auto, the, a, an, ...	
<code>og:locale</code> language default: en_US	
<code>og:locale:alternative</code> others lang array	
<code>og:site_name</code> general site name	
<code>og:video</code> complementary video url	
TWITTER CARDS	
<code><meta></code> metadata tag for twitter cards	
<code>name</code> metadata type twitter cards	
<code>content</code> metadata value twitter cards	
BASIC METADATA PROPERTIES	
<code>twitter:title</code> title of your object	
<code>twitter:card</code> type of your object	
<code>summary</code> <code>summary_large_image</code>	
<code>app</code> <code>player</code>	
OPTIONAL METADATA PROPERTIES	
<code>twitter:site</code> account site name	
<code>twitter:creator</code> account name @manz	
<code>twitter:description</code> description	
<code>twitter:image</code> absolute image url	
APP METADATA PROPERTIES	
<code>twitter:app:country</code> country code	
<code>twitter:app:name:****</code> name of app	
<code>twitter:app:id:****</code> identifier of app	
<code>twitter:app:url:****</code> url of app store	
<code>iphone</code> <code>ipad</code> <code>googleplay</code> id for ****	
PLAYER METADATA PROPERTIES	
<code>twitter:player</code> https url to iframe player	
GOOGLE SEO RECOMMENDATIONS	
<code><title></code> first - second brand 50-60 chars	
<code><meta></code> metadata google-supported	
<code>name</code> metadata name	
<code>description</code> text snippet 50-160 chars	
<code>robots</code> <code>googlebot</code> set bots behaviour	
<code>all</code> <code>noindex</code> <code>nofollow</code> <code>none</code>	
<code>noarchive</code> <code>nosnippet</code> <code>nooodp</code>	
<code>notranslate</code> <code>noimageindex</code>	
<code>unavailable_after: date</code>	
<code>google</code> disable google features	
<code>notranslate</code> <code>nositelinkssearchbox</code>	
<code>rating</code> <code>adult</code> exclude secure search	
<code>viewport</code> optimized-mobile page	
<code>content="width=device-width, initial-scale=1.0"</code>	

**F** Forms Forms related tags

MAIN ELEMENTS

<form> form elements collection
name form name document.forms api
method GET POST dialog send method
action url to backend form submission
accept-charset **enc** force encoding utf-8
autocomplete on off autofill for all form
novalidate bypass form validation
target **context** place to put response
enctype application/x-www-form-urlencoded
 multipart/form-data text/plain encoding type
<label> associate element with caption
for reference to **id** of related element

GROUP FORMS

<fieldset> group of form elements
name element name forms.elements api
form associate fieldset with a form
disabled avoid select this group items
<legend> caption text for fieldset

I Input elements User input types

USER INPUT DATA

<input> **<textarea>** specific & large text
name element name form.elements api
autocomplete on off autofill for input
autofocus focus input when loaded
dirname submit element directionality
form associate input with a form
placeholder user visual hint

ONLY <INPUT> ELEMENT

<input> specific text input short text
type text hidden search tel url email
 number range color file password
 datetime-local date time week month
 checkbox radio submit image reset button
value current value of input element
size size of element in characters
list associate with **id** of **<datalist>**
accept hint for expected file in upload
checked enable in radio or checkbox
multiple allow multiple values

ONLY IMAGE <INPUT> ELEMENT

src url or name of image button
alt alternative text to image
width **height** image width/height size

ONLY <TEXTAREA> ELEMENT

<textarea> multiline text input large text
rows **cols** number of lines and columns
wrap wrap text

ALTER FORM SUBMISSION ONLY SUBMIT <INPUT> & <BUTTON>

formaction **formtarget** **formnovalidate**
formenctype **formmethod**
 attributes to alter main form submission

R Ruby tags Ruby Markup tags

RUBY ELEMENTS

<ruby> ruby annotation E.Asian-like chars
<rp> ruby fallback parenthesis wrapper
<rt> ruby text pronunciation, translation...

S Select data tags Interactive combo

SELECT ELEMENTS

<select> form elements collection
name form name document.forms api
form associate input with a form
size size of element in characters
autocomplete on off autofill for input
autofocus focus input when loaded
disabled avoid press button
required required field default: optional
multiple allow select multiple values
<datalist> predefined and open data list

SELECT CHILDREN ELEMENTS

<option> item from **<select>** or **<datalist>**
label user-visible text instead content
value item value for form submit
selected options selected by default
disabled avoid select this item option
<optgroup> group of **<option>**
label user-visible group text
disabled avoid select this items

B Generic Button HTML Button

HTML GENERIC <BUTTON>

<button> generic button container
name element name form.elements api
type submit reset button button type
value button value for form submission
form associate input with a form
autofocus focus button when loaded
disabled avoid press button

D Deprecatad tags Obsolete elements

DEPRECATED TAG

RECOMMENDED TAG

<applet> java widgets **<embed>** **<object>**
<acronym> abbreviation **<abbr>**
<basefont> main font use CSS instead
<big> bigger text use CSS font-size
<bgsound> background sound **<audio>**
<blink> flicker text use CSS animation
<center> center text use CSS text-align
<dir> directory list use lists instead ****
**** set font features use CSS instead
<frame> **<frameset>** frames **<iframe>**
<marquee> move text use CSS animation
<multicol> col layout use CSS columns
<noframes> frames fallback no supported
<isindex> search in page **<input>**
<keygen> keypair gen use webcrypto API
<listing> preformatted text **<pre>** **<code>**
<menuitem> context menu no supported
<nextid> auto id generated no supported
<nobr> no break use CSS instead
<noembed> no embed fallback **<object>**
<plaintext> plain text fragment **<pre>**
<rb> **<rtc>** ruby base & container **<ruby>**
<spacer> whitespace use CSS instead
<strike> strikethrough text **<s>** ****
<tt> teletype text use CSS instead
<xmp> code block use <pre> **<code>**

I Interactive tags Other elements

OTHER FORM ELEMENTS

<output> result of calculation
name element name forms.elements api
form associate input with a form
for associate result to other element
<progress> show a bar progress
value current value of bar progress
max max value of bar progress
<meter> show a known range meter
value current value of meter
low limit of low range
high limit of high range
min lower bound of range
max upper bound of range
optimum optimum value in gauge

OTHER INTERACTIVE ELEMENTS

<details> disclosure widget html accordion
open keep accordion opened
<summary> caption or title for **<details>**
<dialog> window box container dialog box
open keep dialog opened

V Validations HTML validations

USER INPUT DATA

TEXT VALIDATIONS

<INPUT> & <TEXTAREA>

minlength **maxlength** min/max length

GENERAL VALIDATIONS

<INPUT> & <TEXTAREA>

required required field default: optional
disabled avoid edit field not send
readonly avoid edit field send

NUMBER VALIDATIONS

ONLY <INPUT>

min **max** min/max value number
step granularity step between values

POWERFUL VALIDATIONS

ONLY <INPUT>

pattern **REGEXP** pattern for test validation

A ARIA Attributes Accesible elements

ACCESIBLE RICH INTERNET APPLICATIONS

role specify accessible role for element
 complementary list listitem main navigation
 region tab alert application article banner
 button cell checkbox contentinfo dialog
 document feed figure form grid gridcell
 heading img listbox row rowgroup search
 switch table tabpanel textbox timer
aria-checked true false mixed
aria-selected set current state

LABELS

aria-label specify a string as label
aria-labelledby specify **id** as label elem

RELATIONSHIPS

aria-owns set **id** element as child
aria-activedescendant set **id** as active
aria-describedby set **id** as description
aria-posinset specify position in set
aria-setsize specify size of set

**G Groups tags** Block elements

GENERAL GROUP TAGS

<div> generic division or layer block
<p> text paragraph
<hr> thematic break
<pre> preformatted text
<main> dominant contents
<blockquote> section with quote
<cite> link to url with quotation source

LISTS & TERMS

**** **** unordered & orderer list
start first value of list
reversed backwards list
type **1** **a** **A** **i** **I** kind of marker
**** item from **** or **** list
value ordinal value of item
<dl> description list container
<dt> **<dd>** description term name & value

FIGURE & CAPTIONS

<figure> figure or concept
<figcaption> caption or legend for figure

SEMANTIC TAGS

<article> entity content post, comment...
<section> thematic group of content
<nav> section with navigation links
<aside> secondary content sidebar, menu
<h1> **<h2>** ... **<h6>** heading section
<header> introductory header group
<footer> section footer group
<address> contact information group

T Tables tags Tabular data

TABLE ELEMENTS

<table> table container
<caption> title of table optional
<thead> table header includes headers
<tbody> table body includes body data
<tfoot> table footer includes summary

COLUMNS

<col> **<colgroup>** col & group of columns
span number of columns to span

ITEMS

<tr> table row horizontal container
<th> **<td>** table header & table cell data
colspan number of columns to span
rowspan number of rows to span
headers one or more **id** of **<th>** elements

ONLY FOR <TH> ELEMENT

scope **auto** **row** **col** **rowgroup** **colgroup**
abbr short abbreviated description

T Target destination

KEYWORDS & TARGET DESTINATION

target browser destination
_self current place same page
_blank new place new tab page
_parent parent place else _self
_top root parent place else _self
name custom place iframe or other

T Text tags Inline elements

TEXT SEMANTIC TAGS

**** emphasized text replace for **<i>**
**** important text replace for ****
<mark> highlight text replace for **<u>**
<i> alternate voice/mood legacy tag
**** span w/o extra purposes legacy tag
<u> non-textual data span legacy tag
<sub> **<sup>** subscript and superscript
<small> side comments small print
<var> math or programming variable
<samp> sample from computing system
<kbd> user input (keyboard shortcut)
<dfn> defining instance of a term
title full term optional
<abbr> abbreviation or acronym
title expansion of abbreviation optional
<cite> title of a work book, film, song...
<q> quoted group from another source
cite link to source url optional
**
** line break visual enter
<wbr> line break opportunity long words
<s> no longer accurate/relevant strike text
<data> associate machine-data to text
value machine-readable value
<time> associate machine-date to date
datetime machine-readable date-time
<code> fragment of computer code

H Hyperlinks Link to another resource

HYPERLINKS & AREA MAP

<a> **<area>** hyperlink / image map area
href link to url or filename
hreflang **code** doc language en, es...
download download name empty valid
rel **alternate** **author** **bookmark** **external** **help**
license **prev** **next** **search** **tag** **opener** **noreferrer**
noopenner **noreferrer**
target **context** place to open link
ping url list space-separated to ping
referrerpolicy **mode** referer behaviour

ATTRIBUTES ONLY FOR <AREA> ELEMENT

shape **rect** **circle** **poly**
coords coords list for shape
alt replacement text when no images

E Edit tags Edit elements

TEXT SEMANTIC TAGS

<ins> **** addition or removal from doc
cite link to source quotation optional
datetime date/time of change optional

S Security & Privacy Edit elementsPOLICIES ****, **<VIDEO>**, **<AUDIO>**, **<LINK>** or **<SCRIPT>**

crossorigin CORS support
anonymous **use-credentials**
referrerpolicy set how referer works
no-referrer **no-referrer-when-downgrade**
same-origin **origin** **strict-origin** **unsafe-url**
origin-when-cross-origin **strict-origin-when-cross-origin**

I Image tags Picture content

IMAGES

JPG **PNG** **SVG** **WEBP** **JPGXR** **JPG2000** **GIF** **APNG**
**** image simple or legacy fallback
src link to url image source required
alt alternative text if no image required
width **height** horizontal & vertical size
loading set lazy loading strategy
auto browser decides
lazy candidate for lazy loading
eager load right away
usemap name of image map to use
ismap image is part of server-side map
decoding **sync** **async** **auto** hint to decode
<map> image map used w/ **<a>** & **<area>**
name imagemap used in **usemap**

NEXT-GEN IMAGES

<picture> multiple image container
<source> new alternative source image
src link to url image source simple mode
type MIME type optional
media media query of resource media

PICTURE <SOURCE> & ATTRIBUTES

srcset image list candidates comma-sep
width **a1.jpg 300w, a2.jpg 600w, ...**
density **b1.jpg 1x, b2.jpg 2x, ...**
sizes final rendered width list 640w

M Multimedia tags

VIDEO OR AUDIO CONTAINER ELEMENTS

MP4 **WEBM** **HEVC** **AV1** **OGV** ← VIDEO
MP3 **AAC** **OGG** **OPUS** **FLAC** **WAV** ← AUDIO

<video> **<audio>** media container
src link to url video audio source
preload hints how much buffering needs
auto browser decides
metadata fetch metadata only
none save bandwidth and no download
autoplay autoplay only if user interact
loop restart when finished
muted silence media by default
controls show play, pause... controls

ONLY FOR <VIDEO> ELEMENT

poster cover image prior to playback
width **height** horizontal & vertical size
playsinline browser try play video inline

VIDEO OR AUDIO CHILDREN ELEMENT

<source> new alternative source media
src link to url media source
type MIME type video/mp4; codecs='...'
<track> external subtitles or tracks
src link to url subtitle resource
srclang language of the text track
label user-visible name of the text track
kind **subtitles** **captions** **descriptions**
chapters **metadata**
default set default enabled track



E Embedded tags External content

EXTERNAL CONTENT (IFRAME)

<iframe> embedded content

- src** link to url resource website, file, ...
- srcdoc** document content html syntax
- name** name context for **target** attribute
- loading** **auto** **lazy** **eager** lazy load iframe
- allowfullscreen** allow iframe fullscreen
- allowpaymentrequest** allow payments
- width** **height** horizontal & vertical sizes

<IFRAME> SECURITY, PRIVACY & POLICY ATTRIBUTES

- sandbox** **allow-forms** **allow-modals**
- allow-orientation-lock** **allow-pointer-lock**
- allow-popups-to-escape-sandbox** **allow-scripts**
- allow-same-origin** **allow-presentation**
- allow-top-navigation-by-user-activation**
- allow-top-navigation** **allow-popups**
- allow** **feature** allow access to feature
- ambient-light-sensor** **autoplay** **accelerometer**
- camera** **display-capture** **document-domain**
- encrypted-media** **fullscreen** **geolocation**
- gyroscope** **magnetometer** **microphone** **mid**
- payment** **picture-in-picture** **speaker** **sync-xhr**
- usb** **wake-lock** **webauthn** **vr**
- referrerpolicy** **mode** referer behaviour

LEGACY EMBED/OBJECT TAGS

<embed> external non-html content

- src** link to url resource
- type** type of embedded resource
- width** **height** horizontal & vertical sizes

<object> external resource multipurpose

- data** link to url resource
- type** type of embedded resource
- name** name context for **target** attribute
- usemap** name of image map to use
- form** associates element with form **id**
- width** **height** horizontal & vertical sizes

<param> external resource multipurpose

- name** **value** name & value of parameter

EXPERIMENTAL TAGS

<portal> guest embedded content ~iframe

- src** link to url resource website, file, ...
- referrerpolicy** **mode** referer behaviour

S SVG paths Scalar Vectorial Graphics

POWERFUL PATHS

<path> define a outline of a shape

- d** command/coords space-separated
- pathLength** total length of the path

PATH COMMANDS GUIDE

Command	Description	Example
M m	Move to	path begins · M10,30
Z z	Close path	path ends · Z
L l	Line to	draw line · L90,90
H h	Horiz line to	horizontal line · H40
V v	Vert line to	vertical line · V20
C c	Cubic Bézier	C30,90 25,10 50,10
S s	Smooth C. B.	S70,90 90,90
Q q	Quadratic Bézier	Q90,60 50,90
T t	Smooth Q. B.	T30,0 30,0 30,0 30,0
A a	Elliptical Arc	A20,20 0,0,1 50,30

S SVG tags Scalar Vectorial Graphics

MAIN TAGS

<svg> svg container standalone svg

- viewBox** **minx** **miny** **width** **height**
- width** **height** viewport size
- preserveAspectRatio** **align** **option**
- align** **none** **x***Y***** **Min** **Mid** **Max**
- option** **meet** **slice**

<g> related group container

SVG METADATA

<title> short text title alternative

<desc> detailed textual information

<metadata> metadata elems. container

CONTENT FOR REUSE

<defs> referenced elements container

<symbol> set reuse template no render

<use> reference another element reuse

href a url link to be cloned for rendering

<switch> reference another element

<*>** direct child of **<switch>**

systemLanguage **code**

BASIC SHAPES

<rect> define a rectangle

- x** **y** horizontal & vertical position
- width** **height** horizontal & vertical sizes
- rx** **ry** horizontal & vertical radius

<circle> define a circle

- cx** **cy** horizontal & vertical center coord
- r** radius of the circle

<ellipse> define an ellipse

- rx** **ry** horizontal & vertical radius
- cx** **cy** horizontal & vertical center coord

<line> define a line segment

- x1** **y1** start point (x,y) of line segment
- x2** **y2** end point (x,y) of line segment
- pathLength** total length of the path

<polyline> **<polygon>** line / closed shape

- points** set of coords space-separated
- pathLength** total length of the path

TEXT & IMAGE ELEMENTS

<text> **<tspan>** text layer & text container

- x** **y** start position of text
- dx** **dy** relative position of descendant
- lengthAdjust** **spacing** **spacingAndGlyphs**
- rotate** **number** rotate degrees per glyph
- textLength** **number** length per glyph

<textPath> put text on path

- path** equivalent of **d** attribute **<path>**
- href** url reference to **<path>**
- startOffset** **length** offset from start path
- method** **align** **stretch** how render glyph
- spacing** **exact** **auto** space between glyph
- side** **left** **right** side of the path to render
- lengthAdjust** **spacing** **spacingAndGlyphs**
- textLength** **number** length per glyph

<image> set reference to image

- href** a url link to image to rendering
- preserveAspectRatio** **align** **option**
- crossorigin** CORS support

S Scripting tags Javascript elements

SCRIPTING ELEMENTS

<script> include dynamic script

- src** link to script.js instead inline script
- type** associate fieldset with a form
- text/javascript** javascript file default .js
- application/json** JSON data block file .json
- module** javascript module module .mjs
- nomodule** fallback for old browsers
- defer** defer script execution
- async** exec script when available

SECURITY & PRIVACY

- referrerpolicy** **mode** referer behaviour
- crossorigin** **mode** CORS support
- integrity** verify integrity hash of **src** file

SCRIPT DOWNLOAD & PARSE MODES

● HTML PARSE ● FETCH ● EXEC

SCRIPTS

NORMAL **DEFER** **ASYNC**

MODULES

NORMAL **ASYNC**

S Other scripting tags Javascript elements

JAVASCRIPT-RELATED TAGS

<noscript> show if no scripting enabled

<template> inert html fragments to clone

<slot> create separate DOM trees

- name** name of shadow tree slot

<canvas> rendering graphs, art, etc...

- width** **height** horizontal & vertical size

<custom-elm> user custom element tag

S SVG Attrs Style SVG attributes

STYLE SVG ATTRIBUTES

FILL SHAPE

- fill** **black** **color** fills shape with a color
- fill-rule** **nonzero** **evenodd** algorithm inside
- fill-opacity** **1** **opacity** alpha channel

LINE (STROKE)

- stroke** **none** **color** set color line
- stroke-width** **1** **width** set width line
- stroke-opacity** **1** **opacity** alpha channel
- stroke-linecap** **butt** **round** **square** limit type
- stroke-linejoin** **miter** **miter-clip** **round** **bevel** **arcs**
- stroke-miterlimit** **4** **number** limit on ratio
- stroke-dasharray** **none** **number array** pattern
- stroke-dashoffset** **0** **number** array offset

OTHERS (CSS ATTRIBUTES)

- transform** **css transform** apply transform
- class** **id** **style** html attributes inherit